



NOTES:

- SEE SHEETS GI-1 AND GI-2 FOR INSTRUMENTATION SYMBOL LIST, ABBREVIATIONS, AND GENERAL NOTES.
- THIS OUTPUT SHALL BE HARDWIRED TO ANNUNCIATOR PANEL FOR FUTURE USE.
- PILOT LIGHTS MOUNTED ON CONTROL PANEL CP47. REFER TO DRAWING ID-2.
- PROVIDE INTRINSICALLY SAFE BARRIERS FOR ALL 4-20mA INPUT SIGNALS COMING FROM THOSE DEVICES THAT ARE INSTALLED IN HAZARDOUS LOCATIONS.
- CONTRACTOR TO VERIFY IF FIELD DEVICES SELECTED REQUIRE 2-WIRE OR 4-WIRE CONTROL AND CONNECT TO ANALOG INPUT MODULES ACCORDINGLY.
- ALL INTERCONNECTING WIRES/CABLES BETWEEN PANELS SHALL TERMINATE ON TERMINAL STRIPS AND SHOULD NOT BE DIRECTLY CONNECTED TO DEVICES LOCATED IN THE PANELS.

DESIGNED	DKC	REVISED	- 4-19-2012
CHECKED	KMY	REVISED	-
SCALE	DRAWN CJM	REVISED	-
DATE	03/22/2012	CHECKED	KMY
		REVISED	-

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
338/IL 59	2011-035-I	DUPAGE	181	147
			CONTRACT NO. 60P41	
ILLINOIS FED. AID PROJECT				