TRAFFIC SIGNAL LEGEND

<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R			EMERGENCY VEHICLE LIGHT DETECTOR	R ≪	∞	•	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
RAILROAD CONTROL CABINET		R	₽ ◀	CONFIRMATION BEACON	R_{o-0}	0-0	•			-/	
COMMUNICATIONS CABINET	CCR	ECC	СС	HANDHOLE	R □			COAXIAL CABLE		— <u> </u>	— <u>c</u> —
MASTER CONTROLLER		EMC	MC	HANDIGEE	В			WENDER ON F. FOR OWER		\sim	_
MASTER MASTER CONTROLLER	R	EMMC	MMC	HEAVY DUTY HANDHOLE	KH	Н	H	VENDOR CABLE FOR CAMERA			
UNINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE	r D			COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		<u></u>	<u>—6</u> —
SERVICE INSTALLATION, (P) POLE OR (G) GROUND MOUNT	- <u>_</u> R	-D-P	<u>-■</u> P	JUNCTION BOX	R		•	FIBER OPTIC CABLE		— <u>12</u> F	
TELEPHONE CONNECTION (P) POLE OR (G) GROUND MOUNT	R	P	P	GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)				NO. 62.5/125, MM12F FIBER OPTIC CABLE		—(24F)—	—(24F)—
STEEL MAST ARM ASSEMBLY AND PO	DLE R	<u> </u>	•	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	<u>R</u>			NO. 62.5/125, MM12F SM12F		<i></i>	
ALUMINUM MAST ARM ASSEMBLY AND	POLE R	0		COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		-	-
STEEL COMBINATION MAST ARM	RO-X	_ 0-¤	• ×	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS)		ŕ	
ASSEMBLY AND POLE WITH LUMINAIR	R R		_	SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		C ₁	c _{II}
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH PTZ CAN	IERA PIZA		PTZ	INTERSECTION ITEM		Ι	IP	OR (S) SERVICE		·	·
SIGNAL POST	R O	0	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
TEMPORARY WOOD POLE (CLASS 5 0	R R	\otimes	•	RELOCATE ITEM	RL			CTEEL MACE ADM DOLE AND	RMF		
BETTER) 45 FOOT (13.7m) MINIMUM GUY WIRE	R	>_	>-	ABANDON ITEM 12" (300mm) TRAFFIC SIGNAL SECTION	А		R	STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	O		
SIGNAL HEAD	R		-	12 (SOUMIN) TRAFFIC SIGNAL SECTION		(R)	K	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
GIGNAL HEAD CONSTRUCTION STAGES	—			12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE		(R) (C)					
NUMBERS INDICATE THE CONSTRUCT			→ ²	TEELOW AND ONLER THAN 10 STONAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O-X		
SIGNAL HEAD WITH BACKPLATE	+D	+1>	+▶			R	R	FOUNDATION TO BE REMOVED			
SIGNAL HEAD OPTICALLY PROGRAMM	ED	—[>"P"	→ "P"	SIGNAL FACE		G	G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
FLASHER INSTALLATION S DENOTES SOLAR POWER)	R O- : ≫''F''	0-t>"F"	◆→ "F"				G ◆Y ◆G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		IS	IS
PEDESTRIAN SIGNAL HEAD	R -	-[]	-1			R	R	SAMPLING (SYSTEM) DETECTOR		S	S
EDESTRIAN PUSHBUTTON DETECTOR	R	(6)	©	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		C	G	EXISTING INTERSECTION LOOP DETECTOR		Р	
ACCESSIBLE PEDESTRIAN PUSHBUTTO	ON DETECTOR @ APS	@APS	(a) APS				← Y ← G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	TOR		
LLUMINATED SIGN	R		<u> </u>			"P"	"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	TOR	PP	
'NO LEFT TURN''			lacksquare	12" (300mm) PEDESTRIAN SIGNAL HEAD		(5w)		PREFORMED INTERSECTION AND SAMPLING		PIS	 1
LLUMINATED SIGN	R			WALK/DON'T WALK SYMBOL		(W)		(SYSTEM) DETECTOR		6	PIS
NO RIGHT TURN"			®	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		PS	PS
ETECTOR LOOP, TYPE I											
REFORMED DETECTOR LOOP		P	P	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		<u>k</u>	*	RAILROAD	SYMBO)LS	
MICROWAVE VEHICLE SENSOR	R M1		₩	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER			₽ C			EXISTING	PROPOSED
/IDEO DETECTION CAMERA	R [V]	(V)	[V]■		ı. R	M		RAILROAD CONTROL CABINET		<u>EXISTINO</u>	<u>1 KO1 O3_D</u>
/IDEO DETECTION ZONE	L.N			RADIO INTERCONNECT	##*O	##+0			v		
ATOLO DETECTION ZONE	_			RADIO REPEATER	RERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	2	XOX X	X OX X
PAN, TILT, ZOOM CAMERA	R PTZ)	PTZ	PTZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC		_ 😭	_5_	FLASHING SIGNAL		$\times \Theta \times$	X O X
WIRELESS DETECTOR SENSOR	RW	W	W	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		$\times 0 \times >$	X - X -
WIRELESS ACCESS POINT	R		—	GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)				CROSSBUCK		*	*
											GHA #4 085
E NAME = USER N. 35.878-TR1.dwg	AME = ZACH WALLSTEN	DESIGNED - DAD/BCK DRAWN - BCK	revised Revised		OF ILLIN	OIS		DISTRICT ONE	FAU. RTE.	SECTION	COUNTY TOTAL SI
	CALE = 1" = .0833'	CHECKED - DAD	REVISED	DEPARTMENT				STANDARD TRAFFIC SIGNAL DESIGN DETAIL	S 2711	27-N-2 TS-05	LAKE 53 CONTRACT #: 60P63