

**GENERAL NOTES**

THE WORK UNDER THIS CONTRACT CONSISTS OF THE FOLLOWING:

- DATUM USED FOR SURVEY IS U.S.G.S.
- ALL STATIONING IS ALONG CENTERLINE OF ROADWAY, EXCEPT AS OTHERWISE NOTED.
- THE THICKNESS OF BITUMINOUS MIXTURES SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATION FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.
- EXCEPT AS NOTED IN THE PLANS, PAVEMENT GRADES SHOWN ARE AT THE TOP OF PAVEMENT SURFACES.
- ALL EXCAVATION UNDER PAVEMENT, SIDEWALK, AND CURB & GUTTER SHALL BE BACKFILLED AND COMPACTED WITH MATERIAL MEETING THE REQUIREMENTS OF SECTION 209. SEPARATE PAYMENT FOR TRENCH BACKFILL SHALL BE MADE ONLY WHEN SPECIFIED IN THE PLANS.
- THE ENGINEER SHALL BE THE SOLE JUDGE CONCERNING CURING TIME FOR THE VARIOUS BITUMINOUS MIXTURES.
- ONLY THOSE TREES DESIGNATED BY THE ENGINEER OR LISTED IN THE TREE REMOVAL SCHEDULE SHALL BE REMOVED. THE CONTRACTOR WILL PROTECT ALL REMAINING TREES FROM DAMAGE DUE TO HIS OPERATIONS.
- ALL SAWCUTTING OF EXISTING PAVEMENT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. THE MINIMUM SAW CUT DEPTH IN THE PAVEMENT SHALL BE 2 INCHES, UNLESS OTHERWISE SPECIFIED IN A DETAIL IN THE PLANS.
- THE CONTRACTOR SHALL PROVIDE TEMPORARY DRAINAGE.
- ALL REQUIRED SAW CUTTING SHALL BE INCIDENTAL TO THE REMOVAL PAY ITEM INVOLVED.
- FOR NEW CONSTRUCTION, PLACE SIDEWALK RAMPS FOR THE HANDICAPPED (STD 424001) AT ALL LOCATIONS WHERE PROPOSED SIDEWALK ABUTS CURB AT STREET ENTRANCES.
- THE EXISTING ROAD SIGNS THAT INTERFERE WITH CONSTRUCTION SHALL BE REMOVED OR RELOCATED AS DIRECTED BY THE ENGINEER. AFTER THE CONSTRUCTION IS COMPLETED, THE CONTRACTOR SHALL REPLACE THE SIGNS AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT AND NO COMPENSATION WILL BE ALLOWED.

- ABANDONED UNDERGROUND UTILITY ITEMS WHICH CONFLICT WITH CONSTRUCTION SHALL BE DISPOSED OUTSIDE THE LIMITS OF THE RIGHT OF WAY ACCORDING TO ARTICLE 202.03 OF THE STANDARD SPECIFICATIONS, AND AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO EARTH EXCAVATION AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- ANY REFERENCE TO A STANDARD IN THESE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION AS INDICATED BY THE SUB-NUMBER LISTED IN THE INDEX OF SHEETS, OR THE COPY OF THE STANDARD INCLUDED IN THESE PLANS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING UTILITY PROPERTY FROM CONSTRUCTION OPERATIONS AS OUTLINED IN ARTICLE 107.31 OF THE STANDARD SPECIFICATIONS. THE JULIE NUMBER IS 1-800-892-0123. A MINIMUM OF FORTY EIGHT (48) HOURS ADVANCE NOTICE IS REQUIRED.
- ALL WATER MAINS SHALL BE PROTECTED FROM CONTAMINATION. STATE CODE SECTION 653.119 EXPLAINS THE METHODS OF PROTECTION AND WHEN THEY ARE REQUIRED.
- PROTECTIVE COAT SHALL BE APPLIED TO THE SURFACES OF NEW CONCRETE ACCORDING TO ARTICLE 503.21 OF THE STANDARD SPECIFICATIONS.
- THERMOPLASTIC PAVEMENT MARKING QUANTITIES ARE APPROXIMATE ONLY. PAYMENT WILL BE MADE FOR ACTUAL QUANTITIES USED AS MEASURED IN THE FIELD.
- THE FOLLOWING UTILITY COMPANIES HAVE UTILITIES WITHIN THE LIMITS OF CONSTRUCTION. ADJUSTMENT OF UTILITY LOCATIONS WILL BE MADE BY THE OWNER, UNLESS OTHERWISE NOTED ON THE PLANS.
- THE WORK AT THE CAREER CENTER ROAD ENTRANCE TO LIBERTY SCHOOL SHALL BE COMPLETED BEFORE THE BURNS ROAD ENTRANCE IS CLOSED FOR CONSTRUCTION.
- PAVEMENT REMOVAL IS INCIDENTAL TO EARTH EXCAVATION.
- TOPSOIL STRIPPING IS INCIDENTAL TO EARTH EXCAVATION.

**LEGEND**

- IRON ROD RECOVERED
- ⊠ RIGHT-OF-WAY MARKER
- IRON PIPE RECOVERED
- ⊕ PK NAIL RECOVERED
- EXIST. MAILBOX
- EXIST. FLAG POLE
- EXIST. GUY WIRE
- EXIST. POWER POLE
- EXIST. STREET LIGHT
- EXIST. LIGHT POLE
- EXIST. TELEPHONE PEDESTAL
- EXIST. GAS VALVE
- EXIST. FIRE HYDRANT
- EXIST. WATER VALVE
- EXIST. BUFFALO BOX
- EXIST. WATER METER
- ▽ EXIST. FLARED END SECTION
- EXIST. INLET
- EXIST. MANHOLE
- ⊕ EXIST. STOP SIGN
- EXIST. SIGN
- EXIST. DITCH FLOW LINE
- GRADE
- EXIST. SWALE FLOW LINE
- ☺ TREE/BUSH
- EXIST. TREE STUMP, SIZE
- EXIST. CULVERT
- w— EXIST. WATER
- ▶— EXIST. STORM SEWER
- ┴— EXIST. SANITARY SEWER
- x—x—x— EXIST. FENCE
- EXIST. EDGE OF PAVEMENT & SIDEWALK
- EXIST. CURB & GUTTER
- RIGHT OF WAY
- ↘ (680.70) NEW SPOT ELEVATION
- NEW STREET LIGHT
- NEW FIRE HYDRANT
- NEW WATER VALVE
- NEW MANHOLE
- NEW INLET
- ▽ NEW FLARED END SECTION
- ▶— NEW STORM SEWER
- NEW EASEMENT
- ===== NEW AGGREGATE
- ===== NEW CURB & GUTTER
- ▨ SURFACE REMOVAL
- ▨ DETECTABLE WARNINGS FOR CURB RAMPS ON SIDEWALKS
- X REMOVE OBJECT

**PAVEMENT DESIGN**

**BURNS ROAD**  
STA. 0+00 to STA. 33+67

Class II, 2-lane pavement  
D.P. - 20 years  
Design Traffic  
Existing ADT: 0 1% growth  
Proposed ADT: 6600  
PV (85%): 5610 SU (10%): 660 MU (5%): 330  
73,280 pound load limit  
Critical subgrade Eri: 3ksi  
T.F. = D.P. (0.073PV+44.53SU+156.403MU) / 1,000,000

T.F. = 1.628  
Subgrade support rating: fair  
PG Binder grade for slow traffic: PG 64-22  
mixture temperature: 78.5  
Eac: 580  
design strain: 90  
**Pavement thickness required: 10.25"**

USE: 10.25"

UTILITY	STATUS OF RELOCATION		
		DATE	
<b>POWER</b> COMMONWEALTH EDISON CO. 2500 SOUTH GOVERNORS HIGHWAY UNIVERSITY PARK, IL 60466	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	
<b>TELEPHONE</b> AT&T 65 WEST WEBSTER JOLIET, IL 60431	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	
<b>CABLE TV</b> COMCAST 17700 HOFFMAN WAY HOMEWOOD, IL 60430	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	
<b>GAS</b> NORTHERN ILLINOIS GAS CO. 1844 FERRY ROAD NAPERVILLE, IL 60563	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO/ DURING CONSTRUCTION
	FINAL PLAN SET	4/13/07	
<b>WATER</b> AQUA ILLINOIS 1000 SOUTH SCHUYLER AVE. KANKAKEE, IL 60901	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	

	HMA Binder Burns Road	HMA Surface Burns Road	HMA Base Course	HMA Shoulder
PG Grade	PG64-22	PG64-22	PG64-22	PG64-22
Design Air Voids	4.0% @ N50	4.0% @ N50	4.0% @ N50	2.0% @ N30
Mixture Composition	IL 19.0	IL 9.5	IL 19.0	IL 19.06
Friction Aggregate	-	Mixture D	-	-
Density Test Method	Cores*/Correlation	Correlation	Cores*/Correlation	Cores

\* Material shall be compacted to 93.0-97.4 percent of the maximum theoretical density, except that when placed as first lift on an unimproved subgrade the minimum percent compaction shall be 92.0 percent. The maximum theoretical density shall be determined from the moving average as specified in the QC/QA Specification.

FAU. NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
*	**	KANKAKEE	36	2

CONTRACT NO. 87315  
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT  
\* BURNS ROAD WEST - FAU 6212  
\*\* 03-00058-01-FP

**TYSON ENGINEERING, INC.**  
CONSULTING CIVIL ENGINEERS  
LAND SURVEYORS  
DESIGN FIRM LICENSE #154-001136  
367 SOUTH SCHUYLER AVENUE  
KANKAKEE, ILLINOIS 60901  
PHONE (815) 932-7406

This document and the ideas and designs incorporated herein, as an instrument of professional service, is the property of Tyson Engineering Inc. and is not to be used in whole or in part, for any other project without written authorization of Tyson Engineering Inc.  
Do not scale drawings. Use dimensions only.  
Contractor shall be responsible for verifying all dimensions.  
Information herein and herein is confidential.

REVISIONS			
NO.	DATE	BY	DESCRIPTION

COVER SHEET

PROPOSED IMPROVEMENTS FOR  
**BURNS ROAD WEST**  
FROM CAREER CENTER ROAD  
TO BURNING BUSH DRIVE

SECTION 03-00058-01-FP	
DATE: 3/23/12	JOB NO. E05055
SCALE: N/A	FILE NO.
DRAWN BY: MRG	SHEET 2
CHECKED BY: SRM	36

P:\2012\030320\030320-Cover-Page.dwg, PL, 4/23/12, 9:15:02 AM