

**BEAM #1**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	110+69.50	-9.25	639.19	639.19
☉ S. Abut.	110+71.00	-9.25	639.17	639.17
a	110+81.00	-9.25	639.05	639.08
b	110+91.00	-9.25	638.96	639.02
c	111+01.00	-9.25	638.90	638.97
d	111+11.00	-9.25	638.85	638.94
e	111+21.00	-9.25	638.83	638.93
f	111+31.00	-9.25	638.83	638.93
g	111+41.00	-9.25	638.86	638.94
h	111+51.00	-9.25	638.91	638.98
i	111+61.00	-9.25	638.98	639.03
j	111+71.00	-9.25	639.07	639.09
☉ N. Abut.	111+78.00	-9.25	639.15	639.15
Bk. N. Abut.	111+79.50	-9.25	639.17	639.17

**BEAM #2**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	110+69.50	-3.08	639.28	639.28
☉ S. Abut.	110+71.00	-3.08	639.26	639.26
a	110+81.00	-3.08	639.15	639.18
b	110+91.00	-3.08	639.06	639.11
c	111+01.00	-3.08	638.99	639.07
d	111+11.00	-3.08	638.95	639.04
e	111+21.00	-3.08	638.93	639.03
f	111+31.00	-3.08	638.93	639.03
g	111+41.00	-3.08	638.95	639.04
h	111+51.00	-3.08	639.00	639.08
i	111+61.00	-3.08	639.08	639.12
j	111+71.00	-3.08	639.17	639.19
☉ N. Abut.	111+78.00	-3.08	639.25	639.25
Bk. N. Abut.	111+79.50	-3.08	639.27	639.27

**☉ ROADWAY & PROFILE GRADE LINE**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	110+69.50	0.00	639.33	639.33
☉ S. Abut.	110+71.00	0.00	639.31	639.31
a	110+81.00	0.00	639.20	639.22
b	110+91.00	0.00	639.11	639.16
c	111+01.00	0.00	639.04	639.12
d	111+11.00	0.00	639.00	639.08
e	111+21.00	0.00	638.97	639.07
f	111+31.00	0.00	638.98	639.07
g	111+41.00	0.00	639.00	639.09
h	111+51.00	0.00	639.05	639.12
i	111+61.00	0.00	639.12	639.17
j	111+71.00	0.00	639.22	639.24
☉ N. Abut.	111+78.00	0.00	639.30	639.30
Bk. N. Abut.	111+79.50	0.00	639.32	639.32

**BEAM #3**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	110+69.50	3.08	639.28	639.28
☉ S. Abut.	110+71.00	3.08	639.26	639.26
a	110+81.00	3.08	639.15	639.18
b	110+91.00	3.08	639.06	639.11
c	111+01.00	3.08	638.99	639.07
d	111+11.00	3.08	638.95	639.04
e	111+21.00	3.08	638.93	639.03
f	111+31.00	3.08	638.93	639.03
g	111+41.00	3.08	638.95	639.04
h	111+51.00	3.08	639.00	639.08
i	111+61.00	3.08	639.08	639.12
j	111+71.00	3.08	639.17	639.19
☉ N. Abut.	111+78.00	3.08	639.25	639.25
Bk. N. Abut.	111+79.50	3.08	639.27	639.27

**BEAM #4**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	110+69.50	9.25	639.19	639.19
☉ S. Abut.	110+71.00	9.25	639.17	639.17
a	110+81.00	9.25	639.05	639.08
b	110+91.00	9.25	638.96	639.02
c	111+01.00	9.25	638.90	638.97
d	111+11.00	9.25	638.85	638.94
e	111+21.00	9.25	638.83	638.93
f	111+31.00	9.25	638.83	638.93
g	111+41.00	9.25	638.86	638.94
h	111+51.00	9.25	638.91	638.98
i	111+61.00	9.25	638.98	639.03
j	111+71.00	9.25	639.07	639.09
☉ N. Abut.	111+78.00	9.25	639.15	639.15
Bk. N. Abut.	111+79.50	9.25	639.17	639.17