



Location	Concrete (Special) SQ YD	Removal Attenuator Base SQ YD	Relocate Impact Attenuator EACH
STATION 1913 + 00	108.4	108.4	2

THE CONTRACTOR AND THE ENGINEER SHALL DETERMINE THE LAYOUT FOR THE IMPACT ATTENUATORS

NOTE:
THIS DETAIL APPLIES TO:
STRUCTURE NO. 550921074R214.0

THE FIGURES WITHIN EACH CIRCLE ON THE LAYOUT DETAIL INDICATE THE AMOUNT OF SAND IN POUNDS X 100 CONTAINED IN EACH MODULE

LONGITUDINAL GRADE OF ATTENUATOR BASE SHALL MATCH THE MAINLINE PROFILE

ALL DISTURBED AREAS SHALL RECEIVE SEEDING, CLASS 2 AND FERTILIZER AT THE FOLLOWING RATES:
RATIO 1:1:1
RATE 270 lb NUTRIENTS/ACRE
(90 lb NITROGEN, 90 lb PHOSPHORUS, 90lb POTASSIUM)
SEEDING AND FERTILIZER NUTRIENTS ARE INCLUDED IN THE COST FOR INERTIAL BARRIER INSTALLATION

IMPACT ATTENUATOR DETAIL

District 5
Overhead Sign Structure
Repair and Replacement

DESIGNED	
CHECKED	
DRAWN	
CHECKED	

EXAMINED	20
PASSED	ENGINEER OF BRIDGE DESIGN
	ENGINEER OF BRIDGES AND STRUCTURES