JUNE 16, 2023 - ITEM 8A

TOTAL SHEETS: 67 UN062


CONSTRUCTION PLANS FOR WILLARD AIRPORT


UNIVERSITY OF ILLINOIS SAVOY, ILLINOIS

IL. PROJ. NO. CMI-4793 AIP PROJ. NO. 3-17-0016-XXX

MIDFIELD INTERSECTION RECONFIGURATION

APRIL 21, 2023








GROUND CONTROL RADIO FREQUENCY - 121.8 ATIS FREQUENCY - 124.85 APPROXIMATE MAXIMUM HEIGHT OF EQUIPMENT ABOVE GROUND IS 25 FT.





BEFORE EXCAVATING
1-800-892-0123

UNIVERSITY OF ILLINOIS - WILLARD AIRPORT
TOWNSHIP: T 18 N
RANGE: B 8 F

CALL J.U.L.I.E.

TAXIWAY A

COUNTY: CHAMPAIGN SECTION 2, 3, 10 AND 11

AIRPLANE DESIGN GROUP - ADG IV TAXIWAY DESIGN GROUP 5 DESIGN APPROACH CATEGORY - C

PAVEMENT STRUCTURE DESIGN DATA

GROSS WEIGHT - 361,000 LBS. DUAL WHEEL GEAR

| ITEM NO. | BASE BID QUANTITIES ITEM DESCRIPTION | UNIT | OLIANITIT |
|------------|--------------------------------------|--------|------------|
| HEWINO. | ITEM DESCRIPTION | UNIT | QUANTIT |
| Δ\Λ/107408 | L-806 WIND CONE-8' LIGHTED | EACH | 1 |
| | REMOVE WIND CONE | EACH | 2 |
| | LOCALIZER CABLE | FOOT | 1,375 |
| | PAPI CABLE | FOOT | 1,150 |
| | WINDCONE CABLE | FOOT | 2,900 |
| | 1/C #8 5KV UG CABLE | FOOT | 400 |
| | 1/C #8 5KV UG CABLE IN UD | FOOT | 4,275 |
| | 2/C #8 5KV UG CABLE IN UD | | |
| | 1/C #6 COUNTERPOISE | FOOT | 1,850 |
| | VAULT MODIFICATIONS | LSUM | 3,975 1 |
| | 4-WAY CONCRETE ENCASED DUCT | | 325 |
| | | FOOT | |
| | REMOVE DUCT | FOOT | 625 |
| | ADJUST ELECTRICAL MANHOLE | EACH | 1 |
| | ELECTRICAL HANDHOLE | EACH | 1 |
| | ELEVATED RETROREFLECTIVE MARKER | EACH | 4 |
| | MITL-BASE MOUNTED | EACH | 2 |
| | TAXI GUIDANCE SIGN, 3 CHARACTER | EACH | 4 |
| | TAXI GUIDANCE SIGN, 4 CHARACTER | EACH | 1 |
| | TAXI GUIDANCE SIGN, 5 CHARACTER | EACH | 3 |
| | SPLICE CAN | EACH | 2 |
| | REMOVE TAXI GUIDANCE SIGN | EACH | 12 |
| | REMOVE SPLICE CAN | EACH | 1 |
| | REPLACE SIGN PANEL | EACH | 84 |
| | RELOCATE BASE MOUNTED LIGHT | EACH | 81 |
| | RELOCATE TAXI GUIDANCE SIGN | EACH | 11 |
| AW150510 | ENGINEER'S FIELD OFFICE | LSUM | 1 |
| AW150520 | MOBILIZATION | LSUM | 1 |
| AW152410 | UNCLASSIFIED EXCAVATION | CU YD | 8,200 |
| AW154518 | CRUSHED CONCRETE SUBBASE 18" | SQ YD | 21,900 |
| AW156500 | TEMPORARY EROSION CONTROL | LSUM | 1 |
| AW156520 | INLET PROTECTION | EACH | 9 |
| AW201672 | CRACK CONTROL FABRIC | FOOT | 300 |
| AW209606 | CRUSHED AGG. BASE COURSE - 6" | SQ YD | 21,500 |
| AW401010 | CONTRACTOR QUALITY CONTROL PROGRAM | LSUM | 1 |
| AW401610 | BITUMINOUS SURFACE COURSE | TON | 4,850 |
| AW401630 | BITUMINOUS SURFACE TEST SECTION | EACH | 1 |
| AW401650 | BITUMINOUS PAVEMENT MILLING | SQ YD | 1,000 |
| AW403610 | BITUMINOUS BASE COURSE | TON | 7,250 |
| AW403630 | BITUMINOUS BASE TEST SECTION | EACH | 1 |
| AW501905 | REMOVE PAVEMENT | SQ YD | 22,200 |
| | PCC CRUSHING | CU YD | 11,100 |
| | BITUMINOUS PRIME COAT | GALLON | 6,200 |
| | BITUMINOUS TACK COAT | GALLON | |
| | PAVEMENT MARKING - WATERBORNE | SQFT | 9,375 |
| | TEMPORARY MARKING | SQFT | 1,000 |
| | PAVEMENT MARKING - SURFACE PAINTED | SQFT | 1,200 |
| | 24" RCP, CLASS IV | FOOT | 570 |
| | 30" RCP, CLASS IV | FOOT | 100 |
| | REMOVE PIPE | FOOT | 650 |
| | 4" PERFORATED UNDERDRAIN W/SOCK | FOOT | 3,230 |
| | 4" NON PERFORATED UNDERDRAIN | FOOT | 1,000 |
| | UNDERDRAIN COLLECTION STRUCTURE | EACH | 7 |
| | UNDERDRAIN CLEANOUT | EACH | 9 |
| | UNDERDRAIN CONNECTION | EACH | 7 |
| | | | |
| AW751410 | | EACH | 2 |
| AW751530 | | EACH | 2 |
| | REMOVE INLET | EACH | 700 |
| | 1/C # 1/0 GUARD WIRE | FOOT | 700 |
| AW901510 | | ACRE | 6.6 |
| AW904510 | | SQ YD | 1,850 |
| A1A/000E44 | LIGHT-DUTY HYDRAULIC MULCH | ACRE | 6.6 |



License No. 184-00061

NSULTANTS

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

OWNER



UNIVERSITY OF ILLINOIS
WILLARD AIRPORT
SAVOY, ILLINOIS

| MARK | DATE | DESCRIPTION |
|------|------|-------------|
| | | |


| AIP PROJ. NO. 3-17- | -0016-XXX | UN062 |
|---------------------|--------------------|-------|
| IL. PROJ. NO. CMI-4 | 793 | |
| CMT PROJECT NO: | 20005901 | |
| CAD DWG FILE: | 20005901-GI101.DWG | |
| DESIGNED BY: | HCH | |
| DRAWN BY: | DPA | |
| CHECKED BY: | MJD | |
| APPROVED BY: | CBG | |
| CORVEICHT | | |

SHEET TITL

SHEET 2

SUMMARY OF QUANTITIES & SHEET INDEX


> GI101 ₀ 67



Path: K:\ChampaignAp\z003391-00_Midheidintersech.Draw\sheets\z0005901-Gi10z.dwg Date: Friday, May 12, 2023 12:02:50 PM

неет 3

67



- THE CONTRACTOR AND ALL SUBCONTRACTORS SHALL FOLLOW THE REQUIREMENTS OF THE AIRPORT'S APPROVED CONSTRUCTION SAFETY AND PHASING PLAN (CSPP), FAA AC 150/5370-2G OR LATEST, AND ALL AIRPORT SAFETY AND SECURITY REQUIREMENTS. THE CSPP CONSISTS OF THIS SHEET AND SHEETS GC001- GC101.
- PRIOR TO THE START OF CONSTRUCTION THE CONTRACTOR SHALL SUBMIT TO THE AIRPORT FOR APPROVAL A SAFETY PLAN COMPLIANCE DOCUMENT (SPCD) IN ACCORDANCE WITH FAA AC 150/5370-2G OR LATEST. NO CONSTRUCTION ACTIVITY SHALL BEGIN UNTIL THE AIRPORT HAS APPROVED THE SPCD.
- THE CSPP COVERS OPERATIONAL SAFETY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE INDIVIDUAL SAFETY OF HIS/HER PERSONNEL AND MEETING OSHA REQUIREMENTS.
- A MINIMUM OF 10 DAYS PRIOR TO THE NOTICE TO PROCEED THE CONTRACTOR SHALL PROVIDE A LIST OF SUBCONTRACTORS AND
- PRIOR TO THE START OF CONSTRUCTION THE CONTRACTOR SHALL SIGN THE SWPPP CERTIFICATION STATEMENT
- ALL CONTRACTOR COSTS ASSOCIATED WITH THE REQUIREMENTS LISTED ON THIS SHEET SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT UNLESS A SPECIFIC PAY ITEM IS PROVIDED.

1. COORDINATION

- PRIOR TO THE START OF CONSTRUCTION THE CONTRACTOR SHALL ATTEND A PRECONSTRUCTION CONFERENCE WITH THE AIRPORT ENGINEER, AND ILLINOIS DIVISION OF AERONAUTICS (IDA), THE COST OF PREPARING FOR AND ATTENDING THE PRECONSTRUCTION CONFERENCE SHALL BE INCIDENTAL TO THE CONTRACT.
- ON OR BEFORE THE PRECONSTRUCTION CONFERENCE, THE CONTRACTOR SHALL SUBMIT A PROPOSED SCHEDULE FOR THE PROJECT. THE SCHEDULE SHALL INCLUDE A START AND COMPLETION DATE FOR EACH ITEM OF WORK. THE SCHEDULE SHALL BE UPDATED ON A WEEKLY BASIS. ALL COSTS ASSOCIATED WITH THE SCHEDULE SHALL BE INCIDENTAL TO THE CONTRACT.
- DURING CONSTRUCTION THE CONTRACTOR SHALL ATTEND A WEEKLY COORDINATION MEETING WITH THE AIRPORT STAFF, LOCAL FAA ATO AND RPR. ALL COSTS ASSOCIATED WITH ATTENDING THE WEEKLY MEETING SHALL BE INCIDENTAL TO THE CONTRACT
- THE CSPP AS WRITTEN HAS BEEN APPROVED BY THE AIRPORT AND THE FAA. PROPOSED CHANGES TO THE WORK LIMITS SHALL BE COORDINATED THROUGH THE FAA FOR AIRSPACE ANALYSIS AND WILL REQUIRE A MINIMUM OF 30 DAYS TO REVIEW.

2. PHASING

PHASING SHALL BE AS NOTED BELOW AND AS SHOWN ON THE CONSTRUCTION ACTIVITY PLAN (CAP) SHEETS.

3. CONSTRUCTION ACTIVITY AREAS

- ALL RUNWAYS, TAXIWAYS AND APRONS SHALL BE KEPT OPEN TO AIRCRAFT TRAFFIC DURING CONSTRUCTION EXCEPT AS NOTED ON THE PHASING PLAN.
- WHEN CONFLICTS ARISE BETWEEN CONSTRUCTION ACTIVITIES AND AIRCRAFT OPERATIONS AND SAFETY AIRCRAFT OPERATIONS AND SAFETY SHALL TAKE PRECEDENCE AND SHALL GOVERN. FINAL AUTHORITY IN THE APPROVAL OF CONSTRUCTION SEQUENCING LIES WITH THE AIRPORT
- ALL CONSTRUCTION TRAFFIC SHALL IMMEDIATELY YIELD TO ONCOMING

4. WORK ZONE LIGHTING FOR NIGHTWORK

- WORK PERFORMED BY THE CONTRACTOR OUTSIDE OF DAYLIGHT HOURS SHALL BE DONE UNDER SUFFICIENT ARTIFICIAL AREA LIGHTING TO ALLOW FOR PROPER CONSTRUCTION METHODS AND INSPECTION. LIGHTS SHALL CONSIST OF VEHICLE OR MOVEABLE POLE-MOUNTED FLOODLIGHTS AND/OR SPOTLIGHTS OF SUFFICIENT NUMBER TO ILLUMINATE THE WORK AREA. VEHICLE HEADLIGHTS WILL BE ALLOWED ONLY IN ADDITION TO OTHER LIGHTS MENTIONED ABOVE, LIGHTING SHALL NOT INTERFERE WITH AIR OPERATIONS OR ATCT CONTROLLER SIGHT LINES. ANY WORK BEING PERFORMED UNDER INSUFFICIENT ARTIFICIAL LIGHTING, IN THE RPR'S JUDGMENT, SHALL BE STOPPED UNTIL SUCH TIME AS ADDITIONAL LIGHTING IS PROVIDED. ALL WORK PERFORMED DURING THAT TIME WILL NOT BE ACCEPTABLE UNTIL PROPER INSPECTION & TESTING CAN BE MADE
- ARTIFICIAL LIGHTING SHALL NOT BE AIMED AT THE ATCT OR THE APPROACH ENDS OF AN ACTIVE RUNWAY.

5. CONTRACTOR ACCESS

- CONTRACTOR ACCESS SHALL BE AS NOTED BELOW AND AS SHOWN ON THE SITE PLAN AND CONSTRUCTION ACTIVITY PLAN SHEETS, ALL COSTS RELATING TO CONTRACTOR'S ACCESS AND SECURITY SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- THE CONTRACTOR IS TO ACCESS THE SITE USING THE GATES SHOWN THE CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING THE ACCESS GATE(S) CLOSED DURING WORK HOURS. THE CONTRACTOR SHALL POST A COMPETENT SECURITY GUARD TO CONTROL ACCESS AT THE GATE. THE CONTRACTOR SHALL REPLACE ANY UNSATISFACTORY SECURITY GUARDS
- CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND TEMPORARY FASEMENTS FOR THE PUBLIC ACCESS BOAD(S) SHOWN AND SHALL COMPLY WITH ALL REQUIREMENTS, LOAD RESTRICTIONS, & TRAFFIC CONTROL SIGNAGE REQUIRED BY THE VILLAGE, UNIVERSITY, COUNTY, TOWNSHIP, OR I.D.O.T.
- ALL CONTRACTOR EMPLOYEES WHO ARE DESIGNATED AS DRIVERS FOR THE CONTRACTOR WITHIN THE AIR OPERATIONS AREA (AOA) SHALL ATTEND THE APPROPRIATE DRIVERS TRAINING PROGRAM ADMINISTERED BY THE AIRPORT. ONLY THOSE INDIVIDUALS WHO RECEIVE TRAINING AND DRIVING PRIVILEGES WILL BE PERMITTED TO OPERATE VEHICLES OR EQUIPMENT ON THE AIRPORT. ALL COSTS ASSOCIATED WITH THE DRIVER TRAINING PROGRAM SHALL BE BORNE BY THE CONTRACTOR.
- DRIVERS OF TRUCKS CONTAINING MATERIAL DELIVERIES (AGGREGATE CONCRETE, ETC.) NEED NOT OBTAIN AN AIRPORT ID BADGE OR ATTAIN DRIVER'S PRIVILEGES BUT SHALL SUBMIT THEIR NAME DRIVER'S LICENSE NUMBER, TRUCK LICENSE PLATE NUMBER AND NAME OF TRUCKING COMPANY TO THE PRIME CONTRACTOR PRIOR TO ENTERING THE JOBSITE. WHILE INSIDE THE AOA, THE TRUCK DRIVERS SHALL BE ESCORTED BY THE CONTRACTOR PERSONNEL WHO IS BADGED AND HAS OBTAINED DRIVERS PRIVILEGES STATED IN #4 ABOVE, CONTRACTOR DELIVERY ESCORT PROCEDURES SHALL BE APPROVED BY THE AIRPORT PRIOR TO INITIATING ESCORT PROCEDURES.
- CONTRACTOR WORK CREWS MUST MAINTAIN RADIO CONTACT WITH THE AIR TRAFFIC CONTROL TOWER (ATCT) AT ALL TIMES WHEN INSIDE THE AIRPORT OPERATIONS AREA (AOA). THE CONTRACTOR SHALL SUPPLY ALL APPROPRIATE RADIOS NEEDED FOR COMMUNICATIONS AND ONLY HIS PERSONNEL WHO HAVE SUCCESSEULLY COMPLETED THE APPROVED CMI/FAA SAFETY COURSE MAY OPERATE THESE RADIOS.
- WHEN THE CONTRACTOR IS NOT WORKING, EQUIPMENT SHALL BE STORED AT THE STAGING AREA.
- THE CONTRACTOR WILL BE PERMITTED TO STORE EQUIPMENT AND MATERIALS ONLY AT THE LOCATIONS SHOWN. PARKED FOUIPMENT AND MATERIAL STOCKPILES SHALL NOT PENETRATE SURFACES DEFINED BY F.A.R. TITLE 14 PART 77 - OBJECTS AFFECTING NAVIGABLE AIRSPACE
- ALL CONSTRUCTION TRAFFIC OPERATING ON OR CROSSING BUNWAYS TAXIWAYS AND APRONS OPEN TO AIRCRAFT TRAFFIC SHALL BE UNDER CONTROL BY A FLAGMAN OR ESCORT IN RADIO CONTACT WITH THE ATCT. THE CONTRACTOR SHALL PROVIDE HIS OWN FLAGMEN
- THE CONTRACTOR SHALL THOROUGHLY CLEAN ALL CONSTRUCTION AREAS AND HAUL ROUTES WHICH WILL BE OPENED TO AIR TRAFFIC TO THE SATISFACTION OF AIRPORT OPERATIONS OR THE RESIDENT ENGINEER. A POWER BROOM AND OPERATOR SHALL BE ON SITE AT ALL TIMES WHEN ACTIVE PAVEMENTS ARE UTILIZED FOR CONSTRUCTION.
- ALL VEHICLE AND FOUIPMENT OPERATORS UTILIZED BY THE CONTRACTOR SHALL BE PROPERLY TRAINED BY THE CONTRACTOR.
- THE CONTRACTOR SHALL NOTIFY THE AIRCRAFT RESCUE AND FIRE FIGHTING (ARFF) FACILITY IF CONSTRUCTION ACTIVITY WILL REQUIRE THE BLOCKAGE OF EMERGENCY ACCESS TO THE AIRPORT.

6. FOD MANAGEMENT

- THE CONTRACTOR SHALL DISCARD ANY FOREIGN OBJECT DEBRIS (FOD) ON THE AIRFIELD PAVEMENTS.
- ALL PAVEMENTS DRIVES OR ANY OTHER AREAS LITTLIZED BY THE CONTRACTOR FOR HAUL ROADS OR STORAGE AREAS SHALL BE MAINTAINED AND REPAIRED TO THE SAME CONDITION OR BETTER THAN THEY WERE PRIOR TO BEGINNING CONSTRUCTION.
- THE CONTRACTOR SHALL THOROUGHLY CLEAN ALL CONSTRUCTION AREAS AND HAUL ROUTES AT THE END OF EACH WORKING DAY, REGARDLESS OF THE WORK AREA BEING OPEN OR CLOSED TO AIR

7. PROTECTION OF NAVAIDS

- THE CONTRACTOR SHALL MAINTAIN A 100' DISTANCE BETWEEN HIS OPERATIONS AND ANY FAA-OWNED NAVAID (TYPICALLY ORANGE). CONTRACTOR SHALL CONTACT ATCT PRIOR TO ENTERING AN ILS CRITICAL AREA AS SHOWN ON THE SITE PLAN.
- ANY WORK WHICH AFFECTS A NAVAID WILL BE COORDINATED WITH FAA ATO THROUGH THE AIRPORT. WORK IN A NAVAID CRITICAL AREA IS RESTRICTED AND SUBJECT TO AVAILABILITY BASED ON BUNWAY CONFIGURATION AND WEATHER CONDITIONS AND MAY BE POSTPONED BY THE AIRPORT AT ANY TIME.

8. WILDLIFE MANAGEMENT

- THE CONTRACTOR SHALL NOTIFY PUBLIC SAFETY OR THE RPR IF ANY WILDLIFF IS SEEN ENTERING THE AIRPORT
- CONTRACTOR ACCESS GATES SHALL REMAIN CLOSED AND LOCKED WHEN THE CONTRACTOR IS NOT WORKING
- THE CONTRACTOR SHALL DISPOSE OF ALL TRASH INCLUDING FOOD SCRAPS IN APPROVED CONTRACTOR PROVIDED CONTAINERS
- THE CONTRACTOR SHALL MAINTAIN THE SITE TO LIMIT STANDING WATER AND TALL GRASS TO REDUCE THEIR ATTRACTION AND DISRUPTION TO WILDLIFE HABITAT.

9. NOTIFICATION OF CONSTRUCTION ACTIVITIES

- THE CONTRACTOR SHALL PROVIDE A 24 HOUR EMERGENCY CONTACT PERSON AND PHONE NUMBER
- THE CONTRACTOR SHALL GIVE A MINIMUM OF 72 HOURS NOTICE TO AIRPORT OPERATIONS/ARFF PRIOR TO CLOSING ANY PAVEMENTS SO THAT PROPER NOTAMS MAY BE ISSUED BY THE AIRPORT
- FOR ANY EQUIPMENT USED BY THE CONTRACTOR WITH A HEIGHT GREATER THAN 25'. THE CONTRACTOR SHALL PROVIDE TO THE AIRPORT THE TYPE OF EQUIPMENT, TOTAL HEIGHT, AND LOCATION WHERE THE EQUIPMENT WILL BE USED. THE AIRPORT WILL SUBMIT FAA FORM 7460-1 TO THE FAA FOR AN AIRSPACE STUDY. NO FOUIPMENT WITH A HEIGHT GREATER THAN 25' SHALL BE USED UNTIL A DETERMINATION FROM FAA IS RECEIVED.
- IN THE EVENT OF AN EMERGENCY, THE CONTRACTOR SHALL CALL 911
- CONTACTS FOR THIS PROJECT ARE AS LISTED BELOW. PUBLIC SAFETY FIRE MARSHAL JOHN CUMBEE - DIRECTOR OF PUBLIC SAFETY OFFICE (217) 244-8764 CELL (217) 202-8213

AIRPORT OPERATIONS ANDREW SMITH - ASSISTANT DIRECTOR OF OPERATIONS AND MAINTENANCE OFFICE (217) 333-8623 CELL (217) 238-1714

CHRIS GROTH P.E. - PROJECT ENGINEER (217) 787-8050 RPR TO BE DETERMINED OFFICE (217) 787-8050

10. INSPECTION REQUIREMENTS

- THE CONTRACTOR SHALL INSPECT THE JOB SITE DAILY TO ENSURE COMPLIANCE WITH THE CSPP. THE CHECKLIST FOUND IN APPENDIX 3 OF FAA AC 150/5370-2G OR LATEST MAY BE USED TO AID IN THE
- THE CONTRACTOR SHALL REQUEST FINAL OPERATIONAL INSPECTION OF EACH PHASE WORK AREA PRIOR TO THE AREA BEING REOPENED. PUBLIC SAFETY WILL DETERMINE IF THE WORK AREA IS ALLOWED TO BE

11. UNDERGROUND UTILITIES

- IT WILL BE NECESSARY FOR THE CONTRACTOR TO MAKE HIS OWN FIELD INVESTIGATION TO DETERMINE THE EXACT LOCATION OF THE UNDERGROUND UTILITIES AT CRITICAL POINTS. THE LOCATION OF UNDERGROUND UTILITIES AS INDICATED ON THE PLANS HAS BEEN OBTAINED FROM EXISTING RECORDS NEITHER THE OWNER NOR THE ENGINEER ASSUMES ANY RESPONSIBILITY IN RESPECT TO THE ACCURACY, COMPLETENESS OR SUFFICIENCY OF THE INFORMATION. ANY UTILITY, INCLUDING AIRFIELD ELECTRICAL CABLE AND LIGHTS. DAMAGED BY THE CONTRACTOR SHALL BE REPAIRED BY HIM AT HIS OWN EXPENSE IN A MANNER WHICH IS SATISFACTORY TO THE ENGINEER AND TO THE OWNER OF THE UTILITY. ANY REPAIRS THAT MUST BE MADE BY THE OWNER OF THE UTILITY SHALL HAVE THE COST REIMBURSED TO THE UTILITY BY THE CONTRACTOR. AIREIELD LIGHTING CABLES DAMAGED BY THE CONTRACTOR SHALL BE REPAIRED BY A QUALIFIED ELECTRICIAN WITH THE COSTS TO BE BORNE BY THE CONTRACTOR.
- BEFORE INITIATING ANY DIGGING, DRILLING OR EXCAVATING ON THE AIRPORT PROPERTY, THE CONTRACTOR SHALL CALL J.U.L.I.E. AND CONTACT THE LOCAL FAA OFFICE TO ARRANGE FOR UTILITY LOCATES. SEE SECTION 70-04 & 70-05 OF THE SPECIAL PROVISIONS FOR UTILITY CONTACT INFORMATION.

12. HAZARDOUS MATERIALS MANAGAMENT

- THE CONTRACTOR SHALL DEVELOP A HAZMAT MANAGEMENT & RESPONSE PLAN AND KEEP COPIES ON THE OBSITE OF MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS HANDLED ON THE JOBSITE.
- 2. FUELING OPERATIONS SHALL NOT OCCUR IN ANY ACTIVE OBJECT FREE ARFAS

13. PENALTIES

NONCOMPLIANCE BY THE CONTRACTOR WITH AIRPORT RULES AND REGULATIONS OR FAILURE TO COMPLY WITH THE AIRPORT'S APPROVED CSPP AND THE CONTRACTOR'S APPROVED SPCD MAY RESULT IN FINES AS ALLOWED BY LAW.

14. SPECIAL CONDITIONS

ADJACENT CONSTRUCTION MAY IMPACT THE OPERATIONS OF THE CONTRACTOR, CONTRACTOR SHALL COORDINATE WITH ADJACENT CONTRACTOR(S) TO PROVIDE UNHINDERED ACCESS TO EACH WORK AREA AND ALLOW FOR THE TIMELY PROSECUTION AND PROGRESS OF ANY OTHER WORK BEING PERFORMED AT THE AIRPORT

15. RUNWAY & TAXIWAY VISUAL AIDS

- ALL RUNWAYS, TAXIWAYS, AND APRONS SHALL BE KEPT OPEN TO AIRPORT TRAFFIC DURING CONSTRUCTION EXCEPT AS NOTED IN THE CONSTRUCTION ACTIVITY PLAN.
- IF ANY RUNWAY OR TAXIWAY CLOSURES ARE REQUESTED BY THE CONTRACTOR AND APPROVED BY THE AIRPORT. THE CONTRACTOR SHALL USE MARKING, LIGHTING AND SIGNS THAT FOLLOWING THE REQUIREMENTS OF FAA AC 150/5370-2G OR LATEST EDITION

16. MARKING & SIGNS FOR ACCESS ROUTES

BARRICADES AND SIGNS SHALL BE USED ALONG THE CONTRACTOR'S ACCESS ROUTE AS DETAILED ON THIS SHEET AND THE CONSTRUCTION ACTIVITY PLAN SHEET

17. HAZARD MARKING & LIGHTING

- THE CONTRACTOR SHALL FURNISH, ERECT, AND MAINTAIN MARKINGS AND ASSOCIATED LIGHTING OF OPEN TRENCHES, EXCAVATIONS. TEMPORARY STOCKPILES, AND HIS/HER CONSTRUCTION EQUIPMENT
- ALL CONSTRUCTION EQUIPMENT SHALL BE FLAGGED AND/OR LIGHTED IN ACCORDANCE WITH FAA ADVISORY CIRCULAR 150/5370-2G AND 150/5210-5D OR LATEST EDITIONS AT ALL TIMES WHILE OPERATING ON AIRPORT PROPERTY. THE MAXIMUM EQUIPMENT HEIGHT IS 25'.
- BARRICADES SHALL BE PLACED AT THE LOCATIONS SHOWN ON THE CONSTRUCTION ACTIVITY PLAN SHEET OR AS DIRECTED BY THE
- THE CONTRACTOR SHALL INSPECT THE BARRICADES ONCE DURING FACH WORK DAY TO INSURE PROPER PLACEMENT AND PROPER OPERATION OF THE RED AND/OR YELLOW LIGHTS AND FLAG
- 5. THE AIRPORT WILL PROVIDE TWO PORTABLE CLOSED RUNWAY MARKERS FOR USE DURING THE DURATION OF WORK TO CLOSE RUNWAY 4/22. THE CONTRACTOR WILL BE RESPONSIBLE FOR MAINTENANCE OF THE RUNWAY CLOSURE MARKERS INCLUDING FUEL, OIL CHANGES AND REPLACEMENT OF THE LIGHTS.

18. PROTECTION

- ALL WORK REQUIRED INSIDE OF THE RUNWAY 4/22 SAFETY AREAS. WHICH EXTENDS 250' FROM THE RUNWAY CENTERLINE, WILL REQUIRE THE RUNWAY TO BE CLOSED. THE CONTRACTOR SHALL COORDINATE WITH THE AIRPORT A MINIMUM OF 72 HOURS PRIOR TO THE REQUESTED CLOSURE TIME.
- ALL WORK REQUIRED INSIDE OF RUNWAY 14R/32L OBJECT FREE AREA, WHICH EXTENDS 250' FROM THE RUNWAY CENTERLINE, WILL REQUIRE THE RUNWAY TO BE CLOSED. THE CONTRACTOR SHALL COORDINATE WITH THE AIRPORT A MINIMUM OF 72 HOURS PRIOR TO THE
- ALL WORK REQUIRED ON AN ACTIVE TAXIWAY OR INSIDE OF AN ACTIVE TAXIWAY OBJECT FREE AREA, WHICH EXTENDS 93' FROM THE TAXIWAY CENTERLINE OF 50' TAXIWAYS AND 130' FROM THE CENTERLINE OF 75' TAXIWAYS WILL REQUIRE THE TAXIWAY TO BE CLOSED. THE CONTRACTOR SHALL COORDINATE WITH THE AIRPORT A MINIMUM OF 72 HOURS PRIOR TO THE REQUESTED CLOSURE TIME
- ALL WORK REQUIRED ON AN ACTIVE APRON OR INSIDE OF AN ACTIVE SAFETY AREA, WHICH EXTENDS 70' FROM THE APRON'S EDGE OF PAVEMENT, WILL REQUIRE A PORTION OF THAT APRON TO BE CLOSED THE CONTRACTOR SHALL COORDINATE WITH THE AIRPORT A MINIMUM OF 72 HOURS PRIOR TO THE REQUESTED CLOSURE TIME



FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| | DESCRIPTION | DATE | MARK | | |
|------|--------------------------|---------|--------|--|--|
| | | | | | |
| UN06 | . 3-17-0016-XXX | ROJ. NO | AIP PI | | |
| | IL. PROJ. NO. CMI-4793 | | | | |
| | CMT PROJECT NO: 20005901 | | | | |

CAD DWG FILE: 20005901-GC000.DWG DESIGNED BY: HCH DRAWN BY: CHECKED BY: MJD APPROVED BY: CBG COPYRIGHT

CONSTRUCTION **ACTIVITY NOTES 1**


GC001

UN062

67


OF

_{SHEET} 6



ACTIVE RUNWAY TAXIWAY CLOSURE MARKER SEE CONSTRUCTION ACTIVITY PLAN FOR PLACEMENT **CLOSED TAXIWAY** BEAM BARRICADES WITH LIGHTS PLACED JUST BEYOND HOLDLINE

CLOSED TAXIWAY/ACTIVE RUNWAY BARRICADE DETAIL



EQUIPMENT & VEHICLE SIGNAL FLAG

SIGNAL FLAG NOTES

- ALL CONTRACTOR VEHICLES AND EQUIPMENT SHALL DISPLAY COMPANY LOGO PLACARDS AND FLAG.
- 2. WHEN WORKING PRIOR TO DAWN OR AFTER DUSK, A 360 DEGREE ROTATING AMBER BEACON IS REQUIRED ON ALL EQUIPMENT AND
- CONTRACTOR SHALL REPLACE FLAGS THAT ARE WORN AND

NOTES

BEAM BARRICADES WITH

LIGHTS PLACED AT TSA &

TOFA BOUNDARIES.

OFA BOUNDARY

- 1. CLOSURE MARKERS SHALL BE SOLID YELLOW.
- 2. MARKERS SHALL BE PLACED ON TAXIWAYS AT THE BUNWAY INTERSECTIONS INSIDE THE RUNWAY SAFETY AREA.
- 3 MARKERS SHALL BE PLACED ON RUNWAYS TO COVER THE NUMERALS
- MARKERS MAY BE CONSTRUCTED OF FABRIC, COLORED PLASTIC, PAINTED SHEETS OF PLYWOOD OR SIMILAR MATERIALS.
- MARKERS SHALL BE SECURED TO PREVENT MOVEMENT BY PROP WASH, JET BLAST OR OTHER WIND CURRENTS. METHODS OF SECURING THE MARKERS SHALL NOT PROTRUDE MORE ABOVE THE PAVEMENT.

| THAN 3" | — CENTI | ERLINE | |
|-----------------------|---------|--------|--------|
| DIMENSION SYMBOL TYPE | Α | В | С |
| CLOSED TAXIWAY | 5'-0" | 12'-6" | 30'-0" |
| CLOSED BUNWAY | 10'-0" | 25'-0" | 60'-0" |

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


UN062

FLASHER BARRICADE NOTES

FLASHERS TO BE BATTERY

6

- 2. SANDBAGS TO BE PLACED ON FACH SUPPORT BRACE AS REQUIRED TO PREVENT DISPLACEMENT BY WIND, JET OR PROP BLAST.
- MADE FOR THIS ITEM. COSTS SHALL BE CONSIDERED INCIDENTAL TO THE PROJECT.



20" x 20" ORANGE FLAGS

COPYRIGHT

DESIGNED BY:

DRAWN BY:

CHECKED BY:


PPROVED BY:

ACTIVITY DETAILS 1

67

BEAM BARRICADE NOTES

- BARRICADE SHALL BE WEIGHTED TO WITHSTAND DISPLACEMENT BY WIND, JET OR PROP BLAST
- BARRICADE MUST BE OF LOW MASS AND EASILY COLLAPSIBLE UPON CONTACT WITH AN AIRCRAFT.
- NO SEPARATE PAYMENT WILL BE MADE FOR THIS ITEM. COSTS SHALL BE CONSIDERED INCIDENTAL TO THE
- PLACE AS SHOWN IN PLANS AND AS DIRECTED BY THE
- BARRICADES SHALL BE COMPLIANT WITH FAA AC 150/5370-2 (LATEST VERSION).



LIGHTED RUNWAY CLOSURE MARKER

RUNWAY CLOSURE NOTES

- TO BE PLACED ON PAVEMENT AT THE RUNWAY NUMERALS WHEN CONSTRUCTION ACTIVITIES ALLOW 80' FROM THE ENDS OF RUNWAY 4-22 WHEN CONSTRUCTION ACTIVITIES WILL NOT ALLOW
- THE AIRPORT WILL PROVIDE TWO LIGHTED CLOSURE MARKERS FOR THE CONTRACTOR TO MAINTAIN (FUEL, OIL, LIGHT BULBS) DURING ALL PHASES DURING THE CLOSURE OF RUNWAY 4/22.
- THE CONTRACTOR WILL BE REQUIRED TO PROVIDE REPLACEMENT BULBS, FUEL, LUBRICANTS, AND DAILY/PERIODIC MAINTENANCE INSPECTIONS AS REQUIRED BY THE AIRPORT
- THE CONTRACTOR SHALL FULLY SERVICE THE LIGHTED CLOSURE MARKERS PRIOR TO RETURNING TO THE AIRPORT. AT A MINIMUM THIS SHALL INCLUDE REPLACEMENT OF ALL LIGHT BULBS AND CHANGING OIL, OIL FILTER, AIR FILTER AND SPARK PLUGS.
- THE COST OF SET-UP, FUELING, BULBS, INSPECTION, AND REMOVAL OF THE MARKERS SHALL BE INCIDENTAL TO THE CONTRACT
- CONTRACTOR SHALL OPERATE AND MAINTAIN UNITS PER AC150/5345-55A

NIGHT WORK RUNWAY CLOSURE NOTES

- WORK WITHIN THE RUNWAY SAFETY AREA MAY NOT BEGIN UNTIL THE RUNWAY HAS BEEN CLOSED, NAVAIDS DISABLED, EDGE LIGHTING, CENTERLINE LIGHTING, AND TDZ LIGHTING DISABLED IN THE VAULT AND THE LIGHTED CLOSURE MARKERS ARE IN PLACE.
- UPON COMPLETION OF WORK IN NIGHTTIME OFF-PEAK CLOSURE, NO EXCAVATIONS OR STOCKPILES SHALL EXIST IN EXCESS OF 3" AND ALL GRADES SHALL MEET FAA REQUIREMENTS. BARRICADES AND CLOSURE MARKERS SHALL BE REMOVED. AIRPORT OPERATIONS WILL INSPECT RUNWAY AT 4:30 AM.
- SEE SECTION 80 OF THE SPECIFICATIONS FOR INFORMATION REGARDING LIQUIDATED DAMAGES AND REOPENING THE RUNWAY.
- PRIOR TO REOPENING THE RUNWAY, THE CONTRACTOR SHALL SWEEP THE PAVEMENT AND REMOVE DEBRIS WITHIN THE RUNWAY SAFETY AREA.

TSA BOUNDARY -**ACTIVE TAXIWAY**

CLOSED TAXIWAY

CLOSED TAXIWAY/ACTIVE TAXIWAY BARRICADE DETAIL

FLASHER BARRICADE DETAIL - IDOT TYPE 1

SEE CONSTRUCTION

ACTIVITY PLAN FOR

PLACEMENT

OPERATED LENS TO BE BED AND

BE ABLE TO ROTATE 90 DEGREES.

NO SEPARATE PAYMENT WILL BE

4. PLACE AT 20' INTERVALS.

NON-LIGHTED CLOSURE MARKER

CONSTRUCTION

CAD DWG FILE: 20005901-GC000.DWG

HCH

MJD


CBG


MARK DATE DESCRIPTION


CMT PROJECT NO: 20005901

IL. PROJ. NO. CMI-4793


GC003










ath: K:\ChampaignAp\20005901-00 MidfieldIntersect\Draw\Sheets\20005901-GC101,










EXISTING TYPICAL SECTION TAXIWAY C TRANSITION



EXISTING TYPICAL SECTION TAXIWAY C

В

FOR BID SET JUNE 16, 2023

NCMT

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| ИARK | DATE | DES | CRIPTION | | | |
|-----------------------------------|------|-----|----------|--|--|--|
| | · · | | | | | |
| AIP PROJ. NO. 3-17-0016-XXX | | | | | | |
| IL. PROJ. NO. CMI-4793 | | | | | | |
| CMT PROJECT NO: 20005901 | | | | | | |
| OAD DING FILE ASSESSAL ODGES DING | | | | | | |


| AIF FROS. NO. 5-17- | 0010-222 | UNU62 |
|---------------------|--------------------|-------|
| IL. PROJ. NO. CMI-4 | 793 | |
| CMT PROJECT NO: | 20005901 | |
| CAD DWG FILE: | 20005901-CD200.DWG | |
| DESIGNED BY: | HCH | |
| DRAWN BY: | DPA | |
| CHECKED BY: | MJD | |
| APPROVED BY: | CBG | |
| COPYRIGHT: | | |
| | | |

EXISTING TYPICAL SECTIONS 1


CD201 67 SHEET **14**

NOTES


PAVEMENT STRUCURES SHOWN WERE TAKEN FROM RECORD DRAWINGS AND ARE CONSIDERED GENERALLY REPRESENTATIVE OF THE "AS CONSTRUCTED" PAVEMENT SECTION WITH SOME VARIABILITY FROM THE THICKNESS INDICATED TO BE EXPECTED. THERE WILL BE NO ADDITIONAL PAYMENT TO THE CONTRACTOR DUE TO VARIATIONS IN SIZE OR QUANTITY OF EXISTING







EXISTING TYPICAL SECTION TAXIWAY D





VAR. DEPTH BITUMINOUS TRANSITION (401) 8" BITUMINOUS BASE COURSE (201) 11" - 12" PCC PAVEMENT (501) 8" - 9" PCC PAVEMENT (501) 7" BITUMINOUS BASE COURSE (201)

EXISTING TYPICAL SECTION TAXIWAY B TRANSITION N.T.S

License No. 184-0006

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

OWNER



UNIVERSITY OF ILLINOIS
WILLARD AIRPORT
SAVOY, ILLINOIS

MARK DATE DESCRIPTION

AIP PROJ. NO. 3-17-0016-XXX UN062

IL. PROJ. NO. CMI-4793

CMT PROJECT NO: 20005901

CAD DWG FILE: 20005901-CD200.DWG

DESIGNED BY: HCH

DRAWN BY: DPA

CHECKED BY: MJD

APPROVED BY: CBG
COPYRIGHT:


SHEET TITLE

EXISTING TYPICAL SECTIONS 2


CD202 SHEET 15 OF 67

NOTES


1. PAVEMENT STRUCURES SHOWN WERE TAKEN FROM RECORD DRAWINGS AND ARE CONSIDERED GENERALLY REPRESENTATIVE OF THE "AS CONSTRUCTED" PAVEMENT SECTION WITH SOME VARIABILITY FROM THE THICKNESS INDICATED TO BE EXPECTED. THERE WILL BE NO ADDITIONAL PAYMENT TO THE CONTRACTOR DUE TO VARIATIONS IN SIZE OR QUANTITY OF EXISTING FEATURES.











FOR BID SET JUNE 16, 2023

NCMT

MIDFIELD INTERSECTION RECONFIGURATION

OWNER



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| MARK | DATE | DESCRIPTION | |
|------|------|-------------|--|
| | | | |

| AIP PROJ. NO. 3-17- | UN062 | |
|---------------------|--------------------|--|
| IL. PROJ. NO. CMI-4 | | |
| CMT PROJECT NO: | 20005901 | |
| CAD DWG FILE: | 20005901-CD200.DWG | |
| DESIGNED BY: | НСН | |
| DRAWN BY: | DPA | |
| CHECKED BY: | MJD | |
| APPROVED BY: | CBG | |
| COPVRIGHT: | | |


SHEET TITLE


EXISTING TYPICAL SECTIONS 3


CD203 _{SHEET} 16 of 67


NOTES


1. PAVEMENT STRUCURES SHOWN WERE TAKEN FROM RECORD DRAWINGS AND ARE CONSIDERED GENERALLY REPRESENTATIVE OF THE "AS CONSTRUCTED" PAVEMENT SECTION WITH SOME VARIABILITY FROM THE THICKNESS INDICATED TO BE EXPECTED. THERE WILL BE NO ADDITIONAL PAYMENT TO THE CONTRACTOR DUE TO VARIATIONS IN SIZE OR QUANTITY OF EXISTING FEATURES.












PROPOSED TAXIWAY A(2) TYPICAL SECTION


OP 103

N.T.S

NOTE:

SEE GRADING SHEETS FOR GRADES





MIDFIELD INTERSECTION RECONFIGURATION

OWNER




UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| MARK DATE DES | SCRIPTION | |
|---------------------|--------------------|-------|
| AIP PROJ. NO. 3-17- | 0016-XXX | UN062 |
| IL. PROJ. NO. CMI-4 | 793 | |
| CMT PROJECT NO: | 20005901 | |
| CAD DWG FILE: | 20005901-CS300.DWG | |
| DESIGNED BY: | HCH | |
| DRAWN BY: | DPA | |
| CHECKED BY: | MJD | |
| APPROVED BY: | CBG | |
| COPYRIGHT: | | |

EET TITLE

PROPOSED TYPICAL SECTIONS 2

CP302 _{SHEET} 21 of 67



MILL EXISTING HMA PAVEMENT +/- 5"

EXISTING HMA

OVERLAY

EXISTING HMA

TO REMAIN

NEW TACK COAT - P-603

SAWCUT FULL-DEPTH

MEMBRANE

DISTANCE WILL VARY AT

MILLING TAXIWAY B AND A(2)

PAVEMENT REMOVAL LIMITS

SAWCUT FULL DEPTH

HMA ABUTT REMOVAL AT EXISTING FULL

DEPTH HMA & REPLACEMENT DETAIL

THROUGH EXISTING HMA

NEW CRACK CONTROL

NEW HMA

SAWCUT FULL-DEPTH

MEMBRANE

DISTANCE WILL VARY AT

MILLING TAXIWAY B AND A(2)

PAVEMENT REMOVAL LIMITS

SAWCUT FULL DEPTH

HMA ABUTT REMOVAL AT EXISTING

HMA/PCC & REPLACEMENT DETAIL

MILL TO EXISTING PCC PAVEMENT +/- 5" HMA

EXISTING HMA

OVERLAY


TO REMAIN

NEW TACK COAT - P-603

THROUGH EXISTING HMA

NEW CRACK CONTROL

NEW HMA






MJD


CP303


SHEET 22


67


NCMT











SCMT

License No. 184-00061

CONSULTANT

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

OWNE



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

UN062

MARK DATE DESCRIPTION

AIP PROJ. NO. 3-17-0016-XXX IL. PROJ. NO. CMI-4793

CMT PROJECT NO: 20005901

CAD DWG FILE: 20005901-CG400.DWG

DESIGNED BY: HCH

DRAWN BY: DPA

CHECKED BY: MJD

APPROVED BY: CBG

COPYRIGHT:

COPYRIGHT

HEET TITLE

STORM SEWER PROFILE

CG201

67

SHEET **27**

Fant: K.:ChampaignApizouossol - Ou_Midheidintersedubrawisheetsizouossol - Co.
Date: Friday, May 12, 2023 12:05:36 PM

STRUCTURE TABLE MIDFIELD STORM SEWER STRUCTURE NAME AND TYPE STRUCTURE DETAILS RIM = N/A SUMP = N/A SS - 5 INV IN = 735.43 TAXI A(1) STA 12+83.84 OFFSET 262.12 R EXISTING PIPE - NORTH RIM = N/A TAXI A(1) STA 6+63.84 OFFSET 262.02 R SUMP = N/A SS- 1 INV OUT = 736.37 EXISTING PIPE - SOUTH RIM = 745.14 SUMP = 736.14 SS - 2 INV IN = 736.14 SS - 3 INV OUT = 736.14 TAXI A(1) STA 8+01.13 OFFSET 205.17 R INLET IN-1 - 4'X'4 SQUARE RIM = 745.28 SUMP = 735.66 SS - 3 INV IN = 735.66 SS - 4 INV OUT = 735.66 TAXI A(1) STA 11+43.19 INLET IN-2 - 4'x4' SQUARE OFFSET 205.18 R RIM = 746.66 SUMP = 736.28 S3- 1 INV IN = 736.29 SS - 2 INV OUT = 736.28 TAXI A(1) STA 7+02.51 OFFSET 226.53 R MANHOLE MH-1 - 6' ROUND RIM = 746.92 SUMP = 735.27 SS - 4 INV IN = 735.56 SS - 5 INV OUT = 735.56 TAXI A(1) STA 12+16. OFFSET 200.12 R TAXI A(1) STA 12+16.58 MANHOLE MH-2 - 6' ROUND


| PIPE SCHEDULE MIDFIELD STORM SEWER | | | | | | | |
|---------------------------------------|---------------------------|---------------------------|--------|--------|-------------|-------|---------------------|
| PIPE | UPSTREAM STRUCTURE | DOWNSTREAM STRUCTURE | INVERT | INVERT | LENGTH (FT) | SLOPE | TYPE |
| SS- 1 | EXISTING PIPE - SOUTH | MANHOLE MH-1 - 6' ROUND | 736.37 | 736.29 | 52 | 0.15% | CONCRETE PIPE - 24" |
| SS - 2 | MANHOLE MH-1 - 6' ROUND | INLET IN-1 - 4'X'4 SQUARE | 736.28 | 736.14 | 101 | 0.14% | CONCRETE PIPE - 24" |
| SS - 3 | INLET IN-1 - 4'X'4 SQUARE | INLET IN-2 - 4'X4' SQUARE | 736.14 | 735.66 | 342 | 0.14% | CONCRETE PIPE - 24" |
| SS - 4 | INLET IN-2 - 4'X4' SQUARE | MANHOLE MH-2 - 6' ROUND | 735.66 | 735.56 | 74 | 0.14% | CONCRETE PIPE - 24" |
| SS - 5 | MANHOLE MH-2 - 6' ROUND | EXISTING PIPE - NORTH | 735.56 | 735.43 | 91 | 0.14% | CONCRETE PIPE - 30" |

| STRUCTURE TABLE TAXI A - WEST UNDERDRAIN | | | | | |
|---|--|---|--|--|--|
| STRUCTURE NAME AND TYPE | STRUCTURE DETAILS | HORIZONTAL CONTROL | | | |
| RIM = 748.60 SUMP = 744.4 A - 4 INV OUT = 7 | | TAXI B STA 342+21.48 OFFSET 40.72 R | | | |
| CO - 8 | RIM = 747.97 SUMP = 741.83 A - 6 INV IN = 741.83 A - 7 INV OUT = 741.83 | TAXI A STA 622+37.11 OFFSET 41.50 R | | | |
| CS - 7 | RIM = 747.25 SUMP = 740.02 A - 7 INV IN = 740.02 A - 8 INV OUT = 740.02 | TAXI A STA 625+39.79 OFFSET 41.50 R | | | |
| INLET EIN - 2 | RIM = 746.00 SUMP = 733.78 A - 8 INV IN = 738.78 | TAXI A STA 625+96.84 OFFSET 239.92 R | | | |
| NODE A - 2 | RIM = 744.57 SUMP = N/A A - 4 INV IN = 744.24 A - 5 INV OUT = 744.24 | TAXI B STA 342+48.55 OFFSET 41.39 R | | | |
| NODE A - 3 | RIM = 743.37 SUMP = N/A A - 5 INV IN = 743.04 A - 6 INV OUT = 743.03 | TAXI B STA 343+86.41 OFFSET 74.27 R | | | |

| | PIPE SCHEDULE TAXI A - WEST UNDERDRAIN | | | | | | | | | |
|-------|---|-------------------------|--------|--------|-------------|-------|---------------|--|--|--|
| PIPE | UPSTREAM STRUCTURE | DOWNSTREAM STRUCTURE | INVERT | INVERT | LENGTH (FT) | SLOPE | TYPE | | | |
| A - 4 | CO - 7 | NODE A - 2 | 744.47 | 744.24 | 27 | 0.85% | PVC PIPE - 4" | | | |
| A - 5 | NODE A - 2 | NODE A - 3 | 744.24 | 743.04 | 142 | 0.85% | PVC PIPE - 4" | | | |
| A - 6 | NODE A - 3 | CO - 8 | 743.03 | 741.83 | 141 | 0.85% | PVC PIPE - 4" | | | |
| A - 7 | CO - 8 | CS - 7 | 741.83 | 740.02 | 303 | 0.60% | PVC PIPE - 4" | | | |
| A - 8 | CS - 7 | INLET EIN - 2 | 740.02 | 738.78 | 206 | 0.60% | PVC PIPE - 4" | | | |

| STRUCTURE TABLE TAXI A - EAST UNDERDRAIN | | | | | | | | |
|---|--|--|--|--|--|--|--|--|
| STRUCTURE NAME AND TYPE | STRUCTURE DETAILS | HORIZONTAL CONTROL | | | | | | |
| CO - 9 | RIM = 746.67 SUMP = 742.78 A - 1 INV OUT = 742.78 | TAXI A STA 623+80.91 OFFSET -143.44 L | | | | | | |
| CS - 6 | RIM = 747.25 SUMP = 741.70 A - 2 INV IN = 741.70 A - 3 INV OUT = 741.70 | TAXI A STA 625+40.68 OFFSET -41.39 L | | | | | | |
| INLET EIN - 11 | RIM = 743.45 SUMP = 739.45 A - 3 INV IN = 739.45 | TAXI A STA 625+97.39 OFFSET -98.88 L | | | | | | |
| NODE A - 1 | RIM = 742.76 SUMP = N/A A - 1 INV IN = 742.43 A - 2 INV OUT = 742.43 | TAXI A STA 623+98.32 OFFSET -75.33 L | | | | | | |

| | PIPE SCHEDULE TAXI A - EAST UNDERDRAIN | | | | | | | | |
|-------|---|-------------------------|--------|--------|-------------|-------|---------------|--|--|
| PIPE | UPSTREAM STRUCTURE | DOWNSTREAM STRUCTURE | INVERT | INVERT | LENGTH (FT) | SLOPE | TYPE | | |
| A - 1 | CO - 9 | NODE A - 1 | 742.78 | 742.43 | 70 | 0.50% | PVC PIPE - 4" | | |
| A - 2 | NODE A - 1 | CS - 6 | 742.43 | 741.70 | 146 | 0.50% | PVC PIPE - 4" | | |
| A - 3 | CS - 6 | INLET EIN - 11 | 741.70 | 739.45 | 81 | 2.78% | PVC PIPE - 4" | | |



FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| MARK | DATE | DES | SCRIPTION | | | | | |
|-----------|------------------------|---------|--------------------|--|-------|--|--|--|
| | | | | | | | | |
| AIP PI | ROJ. NO | . 3-17- | 0016-XXX | | UN062 | | | |
| IL. PR | IL. PROJ. NO. CMI-4793 | | | | | | | |
| CMT F | ROJEC | ΓNO: | 20005901 | | | | | |
| CAD | WG FILI | E: | 20005901-CG400.DWG | | | | | |
| DESIG | NED BY | : | HCH | | | | | |
| DRAWN BY: | | | DPA | | | | | |
| CHEC | KED BY: | | MJD | | | | | |
| APPR | OVED B | Y: | CBG | | | | | |

STORM SEWER &

COPYRIGHT:

CG401

67

| STRUCTURE TABLE |
|--------------------------|
| TAXI C - EAST UNDERDRAIN |

| STRUCTURE NAME AND TYPE | STRUCTURE DETAILS | HORIZONTAL CONTROL | |
|----------------------------|--|---|--|
| CO - 3 | RIM = 747.17 SUMP = 743.32 C - 1 INV OUT = 743.32 | TAXI C4 STA 2+56.62 OFFSET -22.88 L | |
| CS - 3 | RIM = 747.41 SUMP = 741.78 C - 3 INV IN = 741.78 C - 4 INV OUT = 741.78 | TAXI C STA 552+05.78 OFFSET 28.99 R | |
| INLET EIN - 6 | RIM = 743.45 SUMP = 737.85 C - 4 INV IN = 737.85 | TAXI C STA 553+37.38 OFFSET 101.38 R | |
| NODE C - 1 | RIM = 743.17 SUMP = N/A C - 1 INV IN = 742.84 C - 2 INV OUT = 742.84 | TAXI C4 STA 1+79.29 OFFSET -43.19 L | |
| NODE C - 2 | RIM = 742.69 SUMP = N/A C - 2 INV IN = 742.36 C - 3 INV OUT = 742.36 | TAXI C STA 551+09.14 OFFSET 36.96 R | |

| PIF | PE SC | HEDL | JLE | |
|----------|-------|------|--------|---|
| TAXI C - | EAST | UND | ERDRAI | N |
| | | | | |

| PIPE | UPSTREAM STRUCTURE | DOWNSTREAM STRUCTURE | INVERT | INVERT | LENGTH (FT) | SLOPE | TYPE |
|-------|-----------------------|-------------------------|--------|--------|-------------|-------|---------------|
| C - 1 | CO - 3 | NODE C - 1 | 743.32 | 742.84 | 80 | 0.60% | PVC PIPE - 4" |
| C - 2 | NODE C - 1 | NODE C - 2 | 742.84 | 742.36 | 80 | 0.60% | PVC PIPE - 4" |
| C - 3 | NODE C - 2 | CS - 3 | 742.36 | 741.78 | 97 | 0.60% | PVC PIPE - 4" |
| C - 4 | CS - 3 | INLET EIN - 6 | 741.78 | 737.85 | 150 | 2.61% | PVC PIPE - 4" |

STRUCTURE TABLE TAXI C - WEST UNDERDRAIN

| 170010 | WEST SIND | |
|----------------------------|--|---|
| STRUCTURE NAME AND TYPE | STRUCTURE DETAILS | HORIZONTAL CONTROL |
| CO - 1 | RIM = 747.92 SUMP = 742.38 C - 5 INV IN = 742.38 C - 6 INV OUT = 742.38 | TAXI C STA 549+40.64 OFFSET -38.98 L |
| CO - 2 | RIM = 747.40 SUMP = 743.57 C - 5 INV OUT = 743.57 | TAXI C STA 552+05.61 OFFSET -29.00 L |
| CS - 1 | RIM = 747.81 SUMP = 741.11 C - 8 INV IN = 741.11 C - 9 INV OUT = 741.11 | TAXI A(2) STA 812+44.66 OFFSET -41.39 L |
| INLET EIN - 5 | RIM = 735.77 SUMP = 734.77 C - 9 INV IN = 735.46 | TAXI A(2) STA 811+65.87 OFFSET -234.25 L |
| NODE C - 3 | RIM = 742.39 SUMP = N/A C - 6 INV IN = 742.06 C - 7 INV OUT = 742.06 | TAXI C STA 548+72.24 OFFSET -56.60 L |
| NODE C - 4 | RIM = 742.08 SUMP = N/A C - 7 INV IN = 741.75 C - 8 INV OUT = 741.75 | TAXI A(2) STA 813+82.28 OFFSET -74.28 L |

| PIPE SCHEDULE | | | | | | | | | |
|--------------------------|--|--|--|--|--|--|--|--|--|
| TAXI C - WEST UNDERDRAIN | | | | | | | | | |
| | | | | | | | | | |
| DOMANOTREAM | | | | | | | | | |

| PIPE | UPSTREAM STRUCTURE | DOWNSTREAM STRUCTURE | INVERT | INVERT | LENGTH (FT) | SLOPE | TYPE |
|-------|-----------------------|-------------------------|--------|--------|-------------|-------|---------------|
| C - 5 | CO - 2 | CO - 1 | 743.57 | 742.38 | 265 | 0.45% | PVC PIPE - 4" |
| C - 6 | CO - 1 | NODE C - 3 | 742.38 | 742.06 | 71 | 0.45% | PVC PIPE - 4" |
| C - 7 | NODE C - 3 | NODE C - 4 | 742.06 | 741.75 | 71 | 0.45% | PVC PIPE - 4" |
| C - 8 | NODE C - 4 | CS - 1 | 741.75 | 741.11 | 141 | 0.45% | PVC PIPE - 4" |
| C - 9 | CS - 1 | INLET EIN - 5 | 741.11 | 735.46 | 208 | 2.71% | PVC PIPE - 4" |

UNDERDRAIN SCHEDULES 1

SHEET 28

STRUCTURE TABLE TAXI A(1) - EAST UNDERDRAIN STRUCTURE NAME AND TYPE STRUCTURE DETAILS RIM = 748.26 SUMP = 744.91 A(1) - 7 INV OUT = 744.91 A(1) - 8 INV OUT = 744.91 TAXI A(1) STA 10+16.79 OFFSET 41.50 R RIM = 747.33 SUMP = 741.63 A(1) - 12 INV IN = 741.63 A(1) - 13 INV OUT = 741.63 TAXI C4 STA 3+00.21 CS - 4 OFFSET 49.09 R SUMP = 742.30 A(1) - 2 INV IN = 742.30 A(1) - 1 INV OUT = 742.30 TAXI A7 STA 702+95.53 CS - 5 OFFSET -57.24 L RIM = 746.35 SUMP = 741.76 TAXI A(1) STA 8+01.13 OFFSET 205.17 R INLET IN-1 - 4'x4' SQUARE A(1) - 1 INV IN = 741.76 RIM = 746.44 TAXI A(1) STA 11+43.19 OFFSET 205.18 R INLET IN-2 - 4'x4' SQUARE SUMP = 740.95 A(1) - 13 INV IN = 740.95 RIM = 742.99 SUMP = N/A A(1) - 3 INV IN = 742.66 A(1) - 2 INV OUT = 742.66 TAXI A7 STA 702+25.78 OFFSET -74.83 L RIM = 743.50 SUMP = N/A A(1) - 4 INV IN = 743.17 A(1) - 3 INV OUT = 743.17 TAXI A(1) STA 7+23.61 NODE A(1) - 2 OFFSET 149.28 R RIM = 743.90 SUMP = N/A A(1)- 5 INV IN = 743.57 A(1)- 4 INV OUT = 743.57 TAXI A(1) STA 7+59.81 OFFSET 94.13 R NODE A(1) - 3 RIM = 744.27 SUMP = N/A A(1) - 6 INV IN = 743.94 A(1) - 5 INV OUT = 743.94

RIM = 744.83 SUMP = N/A A(1) - 7 INV IN = 744.50 A(1) - 6 INV OUT = 744.50

RIM = 744.35 SUMP = N/A A(1) - 8 INV IN = 744.02 A(1) - 9 INV OUT = 744.02

RIM = 743.45 SUMP = N/A A(1) - 9 INV IN = 743.12 A(1) - 10 INV OUT = 743.12

SUMP = N/A A(1) - 10 INV IN = 742.62 A(1) - 11 INV OUT = 742.62

RIM = 742.31

SUMP = N/A A(1) - 11 INV IN = 741.98 A(1) - 12 INV OUT = 741.98

NODE A(1) - 4

NODE A(1) - 5

NODE A(1) - 6

NODE A(1) - 7

NODE A(1) - 8

NODE A(1) - 9

TAXI A(1) STA 8+22.68 OFFSET 55.88 R

TAXI A(1) STA 9+33.78

TAXI A(1) STA 11+27.88

TAXI A(1) STA 12+19.15 OFFSET 120.77 R

TAXI C4 STA 1+79.29

OFFSET 71.36 R

OFFSET 41.50 R

OFFSET 55.93 R

| | PIPE SCHEDULE TAXI A(1) - EAST UNDERDRAIN | | | | | | | | | | |
|-----------|--|---------------------------|--------|--------|-------------|-------|---------------|--|--|--|--|
| PIPE | UPSTREAM STRUCTURE | DOWNSTREAM STRUCTURE | INVERT | INVERT | LENGTH (FT) | SLOPE | TYPE | | | | |
| A(1)- 5 | NODE A(1) - 4 | NODE A(1) - 3 | 743.94 | 743.57 | 74 | 0.50% | PVC PIPE - 4" | | | | |
| A(1) - 1 | CS - 5 | INLET IN-1 - 4'X4' SQUARE | 742.30 | 741.76 | 108 | 0.50% | PVC PIPE - 4" | | | | |
| A(1) - 2 | NODE A(1) - 1 | CS - 5 | 742.66 | 742.30 | 72 | 0.50% | PVC PIPE - 4" | | | | |
| A(1) - 3 | NODE A(1) - 2 | NODE A(1) - 1 | 743.17 | 742.66 | 73 | 0.70% | PVC PIPE - 4" | | | | |
| A(1) - 4 | NODE A(1) - 3 | NODE A(1) - 2 | 743.57 | 743.17 | 66 | 0.60% | PVC PIPE - 4" | | | | |
| A(1) - 6 | NODE A(1) - 5 | NODE A(1) - 4 | 744.50 | 743.94 | 112 | 0.50% | PVC PIPE - 4" | | | | |
| A(1) - 7 | CO - 4 | NODE A(1) - 5 | 744.91 | 744.50 | 83 | 0.50% | PVC PIPE - 4" | | | | |
| A(1) - 8 | CO - 4 | NODE A(1) - 6 | 744.91 | 744.02 | 112 | 0.80% | PVC PIPE - 4" | | | | |
| A(1) - 9 | NODE A(1) - 6 | NODE A(1) - 7 | 744.02 | 743.12 | 112 | 0.80% | PVC PIPE - 4" | | | | |
| A(1) - 10 | NODE A(1) - 7 | NODE A(1) - 8 | 743.12 | 742.62 | 63 | 0.80% | PVC PIPE - 4" | | | | |
| A(1) - 11 | NODE A(1) - 8 | NODE A(1) - 9 | 742.62 | 741.98 | 80 | 0.80% | PVC PIPE - 4" | | | | |
| A(1) - 12 | NODE A(1) - 9 | CS - 4 | 741.98 | 741.63 | 44 | 0.80% | PVC PIPE - 4" | | | | |
| A(1) - 13 | CS - 4 | INLET IN-2 - 4'X4' SQUARE | 741.63 | 740.95 | 85 | 0.80% | PVC PIPE - 4" | | | | |

STRUCTURE TABLE TAXI A(1) - WEST UNDERDRAIN

| STRUCTURE NAME AND TYPE | STRUCTURE DETAILS | HORIZONTAL CONTROL | |
|----------------------------|--|--|--|
| CO - 5 | RIM = 748.30 SUMP = 742.30 A(1) - 17 INV IN = 742.30 A(1) - 18 INV OUT = 742.30 | TAXI A(1) STA 9+75.28 OFFSET -41.50 L | |
| CO - 6 | RIM = 748.07 SUMP = 744.05 A(1) - 14 INV OUT = 744.05 | TAXI B STA 342+49.48 OFFSET -41.50 L | |
| CS - 2 | RIM = 747.49 SUMP = 740.55 A(1) - 21 INV IN = 740.55 A(1) - 22 INV OUT = 740.55 | TAXI A(2) STA 812+45.59 OFFSET 41.50 R | |
| INLET EIN - 4 | RIM = 744.67 SUMP = 739.73 A(1) - 22 INV IN = 739.73 | TAXI A(2) STA 811+85.49 OFFSET 165.56 R | |
| NODE A(1) - 10 | RIM = 743.96 SUMP = N/A A(1) - 14 INV IN = 743.63 A(1) - 15 INV OUT = 743.63 | TAXI B STA 343+33.57 OFFSET -41.50 L | |
| NODE A(1) - 11 | RIM = 743.41 SUMP = N/A A(1) - 15 INV IN = 743.08 A(1) - 16 INV OUT = 743.07 | TAXI A(1) STA 8+21.65 OFFSET -56.04 L | |
| NODE A(1) - 12 | RIM = 742.84 SUMP = N/A A(1) - 16 INV IN = 742.51 A(1) - 17 INV OUT = 742.51 | TAXI A(1) STA 9+33.77 OFFSET -41.50 L | |
| NODE A(1) - 13 | RIM = 742.42 SUMP = N/A A(1) - 18 INV IN = 742.09 A(1) - 19 INV OUT = 742.09 | TAXI A(1) STA 10+16.79 OFFSET -41.50 L | |
| NODE A(1) - 14 | RIM = 741.86 SUMP = N/A A(1) - 19 INV IN = 741.53 A(1) - 20 INV OUT = 741.53 | TAXI A(2) STA 814+40.48 OFFSET 55.89 R | |
| NODE A(1) - 15 | RIM = 741.30 SUMP = N/A A(1) - 20 INV IN = 740.97 A(1) - 21 INV OUT = 740.97 | TAXI A(2) STA 813+29.34 OFFSET 41.50 R | |
| | | | |

| PIPE SCHEDULE TAXI A(1) - WEST UNDERDRAIN | | | | | | | | |
|--|-----------------------|-------------------------|--------|--------|-------------|-------|---------------|--|
| PIPE | UPSTREAM STRUCTURE | DOWNSTREAM STRUCTURE | INVERT | INVERT | LENGTH (FT) | SLOPE | TYPE | |
| A(1) - 14 | CO - 6 | NODE A(1) - 10 | 744.05 | 743.63 | 84 | 0.50% | PVC PIPE - 4" | |
| A(1) - 15 | NODE A(1) - 10 | NODE A(1) - 11 | 743.63 | 743.08 | 112 | 0.50% | PVC PIPE - 4" | |
| A(1) - 16 | NODE A(1) - 11 | NODE A(1) - 12 | 743.07 | 742.51 | 113 | 0.50% | PVC PIPE - 4" | |
| A(1) - 17 | NODE A(1) - 12 | CO - 5 | 742.51 | 742.30 | 42 | 0.50% | PVC PIPE - 4" | |
| A(1) - 18 | CO - 5 | NODE A(1) - 13 | 742.30 | 742.09 | 42 | 0.50% | PVC PIPE - 4" | |
| A(1) - 19 | NODE A(1) - 13 | NODE A(1) - 14 | 742.09 | 741.53 | 112 | 0.50% | PVC PIPE - 4" | |
| A(1) - 20 | NODE A(1) - 14 | NODE A(1) - 15 | 741.53 | 740.97 | 112 | 0.50% | PVC PIPE - 4" | |

740.97

INLET EIN - 4 740.55 739.73

A(1) - 22

CS - 2

740.55

84

0.50%

138 0.60% PVC PIPE - 4"



FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION




UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


| MARK | DATE | DESCRIPTION |
|------|------|-------------|
| | | |
| | | |


| AIP PROJ. NO. 3-17- | UN062 | |
|---------------------|--------------------|--|
| IL. PROJ. NO. CMI-4 | | |
| CMT PROJECT NO: | 20005901 | |
| CAD DWG FILE: | 20005901-CG400.DWG | |
| DESIGNED BY: | HCH | |
| DRAWN BY: | DPA | |
| CHECKED BY: | MJD | |
| APPROVED BY: | CBG | |
| COPYRIGHT: | | |


STORM SEWER & UNDERDRAIN SCHEDULES 2

CG402 67 SHEET 29












FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION




UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS




DRAINAGE DETAILS 1

CU502 67



SHEET 31



PLAN (Grating omitted for clar

SECTION B-B

DATE

1-1-09 Switched units to English (metric)

REVISIONS

SECTION A-A


4x3x½ (102x76x13) L frame

SAH SAN ENGINEER OF POLICY AND PROCEDURES

3'-4¼'' (1.02 m) Grating

STEEL FRAME & GRATE

DETAIL of OPTIONAL JOINT



SECTION C-C

SECTION D-D

CAST FRAME & GRATE

FLUSH INLET BOX

FOR MEDIAN

STANDARD 542546-01

JUNE 16, 2023

NCMT

MIDFIELD INTERSECTION RECONFIGURATION





UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


CAD DWG FILE: 20005901 - CU500.DWG

DRAINAGE DETAILS 2


CU503 SHEET 32 67







RUNWAY HOLD POSITION & ENHANCED TAXIWAY CENTERLINE



NON-MOVEMENT HOLDLINE

SURFACE PAINTED HOLD POSITION SIGN (SPHPS)

NOTES:

- ALL NEW WATER BORNE PAVEMENT MARKING (RED, YELLOW, WHITE)
 WILL BE PAID UNDER WATERBORNE MARKING PAY ITEM AND SHALL HAVE REFLECTIVE BEADS.
- 2. ALL NEW AIRFIELD PAVEMENT MARKING SHALL HAVE 6" BLACK BORDER UNLESS OTHERWISE NOTED. BLACK BORDER DOES NOT RECEIVE REFLECTIVE BEADS.



FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION


CHAMPAIGN URBANA

UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


MARK DATE DESCRIPTION UN062 IL. PROJ. NO. CMI-4793 CMT PROJECT NO: 20005901 CAD DWG FILE: 20005901-CM500.DWG DESIGNED BY: DRAWN BY: MJD CHECKED BY: APPROVED BY: COPYRIGHT:

MARKING DETAILS 1


CM501 SHEET 35 67



4 TAXIWAY CENTERLINE DETAIL N.T.S.



5 CLOSED TAXIWAY MARKING (YELLOW)





License No. 184-00061

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

OWNER



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

MARK DATE DESCRIPTION

AIP PROJ. NO. 3-17-0016-XXX UN062

IL. PROJ. NO. CMI-4793

CMT PROJECT NO: 20005901

CAD DWG FILE: 20005901-CM500.DWG

DESIGNED BY: HCH

DRAWN BY: DPA

CHECKED BY: MJD


APPROVED BY: CBG


COPYRIGHT:


MARKING DETAILS 2


CM502 SHEET 36 OF 67


1: K:\ChampaignAp\20005901-00_N































NOTES

- EXISTING EQUIPMENT IS SHOWN FOR INFORMATION ONLY. NEW WORK IS SHOWN IN BOLD.
- 2. ALL EXISTING CABLES AND EQUIPMENT DAMAGED DURING CONSTRUCTION SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE. THE ELECTRICAL INSTALLATION AS MINIMUM SHALL MEET NEC AND LOCAL ELECTRICAL CODES.
- PROVIDE 20A, 2-POLE, CIRCUIT BREAKER INSIDE EXISTING PANEL #1
 FOR NEW WINDCONE CIRCUIT. MATCH WITH EXISTING CIRCUIT
 BREAKERS. UPDATE CIRCUIT DIRECTORY.
- 4. RE-LABEL EXISTING CIRCUIT BREAKERS, REGULATORS, S-1 CUTOUTS, CIRCUITS INSIDE MANHOLES AND ASSOCIATED EQUIPMENT AS FOLLOWS:

TAXIWAY "A" TO "A (SE)" TAXIWAY "C" TO "A (NW)" TAXIWAY "D" TO "C"

VAULT EQUIPMENT PLAN SCALE: 1/4" = 1'-0"

NOTES

- 1. EXISTING RUNWAY 14L/32R REGULATOR (CKT. R2), L-829, 50 KW, 480V INPUT, 5-STEP 20A OUTPUT. ENGRAVED NAMEPLATE READING "RWY 14L/32R".
- 2. EXISTING "SPARE" REGULATOR #1, 50 KW, 480V INPUT, 5-STEP 20A OUTPUT. ENGRAVED NAMEPLATE READING "SPARE #1".
- 3. EXISTING RUNWAY 14R/32L REGULATOR (CKT. R4), L-829, 15 KW, 480V INPUT, 3-STEP 6.6A OUTPUT, ENGRAVED NAMEPLATE READING "RWY 14R/32L".
- 4. EXISTING "SPARE" REGULATOR #2, 15 KW, 240V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "SPARE #2"
- 5. EXISTING RUNWAY 18/36 REGULATOR (CKT. R1), L-829, 10 KW, 480V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "RWY 18/36".
- 6. EXISTING "SPARE" REGULATOR #3, 15 KW, 240V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "SPARE #3".
- 7. EXISTING RUNWAY 4/22 REGULATOR (CKT. R3), L-829, 10 KW, 480V INPUT, 5-STEP 6.6A OUTPUT
- 8. EXISTING "SPARE" REGULATOR #4, 10 KW, 240V INPUT, 5-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "SPARE #4".
- 9. EXISTING TAXIWAY B (SW) REGULATOR (CKT. T7), L-829, 20 KW, 480V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "TXY B (SW)".
- 10. EXISTING "SPARE" REGULATOR #5, 20 KW, 240V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "SPARE #5"
- 11. EXISTING TAXIWAY C (NW) REGULATOR (CKT. T2/3), L-829, 15 KW, 480V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "TXY C (NW)" (NOTE 4).
- 12. EXISTING TAXIWAY A (SE) REGULATOR (CKT. T4/5), L-829, 15 KW, 480V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "TXY A (SE)".
- 13. EXISTING CENTER TAXIWAY REGULATOR (CKT. T1), L-829, 10 KW, 480V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "CENTER TXY"

- 14. EXISTING "SPARE" REGULATOR #6, 15 KW, 240V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "SPARE #6".
- 15. EXISTING TAXIWAY D (NE) REGULATOR (CKT. T8), L-829, 10 KW, 480V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "TXY D (NE)" (NOTE 4).
- 16. EXISTING HIGH VOLTAGE AND LOW VOLTAGE 6"X6" NEMA 1 HINGED COVER WIREWAYS, TWO DOWN THE MIDDLE AND TWO ALONG EACH WALL
- 17. EXISTING IN-FLOOR CABLE TRENCH WITH REMOVABLE COVER.
- 18. EXISTING 250KW/300KVA, 277Y/480V, 3-PHASE, 4-WIRE STANDBY GENERATOR WITH 600A MAIN CIRCUIT BREAKER, IN WEATHERPROOF HOUSING, WITH 300 GALLON TANK.
- 19. EXISTING 600A, 3P, 600V UNFUSED DISCONNECT IN NEMA 3R ENCLOSURE.
- 20. EXISTING SERVICE ENTRANCE AUTOMATIC TRANSFER SWITCH, 600A, 277Y/480V, 3P, 4W IN NEMA 1 ENCLOSURE.
- 21. EXISTING LOCATION OF REGULATOR CIRCUIT INDICATING LIGHT & GROUND FAULT INDICATING LIGHT MOUNTING PANEL (NOTE 4).
- 22. EXISTING "SPARE" REGULATOR #7, 10 KW, 240V INPUT, 3-STEP 6.6A OUTPUT. ENGRAVED NAMEPLATE READING "SPARE #7".
- 23. EXISTING 600A, 480/277V, 3-PHASE, 4-WIRE POWER PANEL "PANEL #1" (SEE NOTES 3 AND 4).
- 24. EXISTING 75 KVA, 480-120/240V, 1-PHASE TRANSFORMER
- 25. EXISTING 400A, 42 CKT, 120/240V, 1-PHASE, 3-WIRE POWER PANEL "PANEL #2" (NOTE 4).
- 26. NEW 2 1/C #6 XLP-USE, 1 1/C #8 GND. IN EXISTING TROUGH AND CONDUITS TO NEW WINDCONE



License No. 184-000613 CONSULTANTS

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| MARK | DATE | DES | SCRIPTION | | | | |
|-----------------------------|---------|------|-----------------------|--|--|--|--|
| | | | | | | | |
| AIP PROJ. NO. 3-17-0016-XXX | | | | | | | |
| IL. PROJ. NO. CMI-4793 | | | | | | | |
| CMT F | ROJEC | ΓNO: | 20005901 | | | | |
| CAD | WG FILI | E: | 20005901 - EP-500.DW0 | | | | |
| | | | | | | | |

DRAWN BY: CHECKED BY: MJD APPROVED BY: COPYRIGHT

EXISTING VAULT EQUIPMENT PLAN

EP501 SHEET 46 67

FIXTURE TABLE **TAXIWAY A**

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL |
|-------------|--------------|-----------------------|
| TXY A - L1 | MITL (LED) | TAXI A STA 625+39.63 |
| TXY A - L2 | MITL (LED) | TAXI A STA 624+94.28 |
| TXY A - L3 | MITL (LED) | TAXI A STA 624+48.77 |
| TXY A - L4 | MITL (LED) | TAXI A STA 624+03.25 |
| TXY A - L5 | MITL (LED) | TAXI A STA 623+48.11 |
| TXY A - L6 | MITL (LED) | TAXI A STA 622+92.96 |
| TXY A - L7 | MITL (LED) | TAXI A STA 622+37.82 |
| TXY A - L8 | MITL (LED) | TAXI A STA 621+93.66 |
| TXY A - L9 | MITL (LED) | TAXI A STA 621+49.49 |
| TXY A - L10 | MITL (LED) | TAXI A STA 620+78.12 |
| TXY A - L11 | MITL (LED) | TAXI A STA 621+12.83 |
| TXY A - L12 | MITL (LED) | TAXI A STA 621+56.15 |
| TXY A - L13 | MITL (LED) | TAXI A STA 621+99.47 |
| TXY A - L14 | MITL (LED) | TAXI A STA 624+48.77 |
| TXY A - L15 | MITL (LED) | TAXI A STA 624+94.28 |
| TXY A - L16 | MITL (LED) | TAXI A STA 625+39.58 |

FIXTURE TABLE **TAXIWAY A7**

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL |
|-------------|--------------|-----------------------|
| TXY A7 - L1 | MITL (LED) | TAXI A7 STA 702+30.73 |
| TXY A7 - L2 | MITL (LED) | TAXI A7 STA 702+60.36 |
| TXY A7 - L3 | MITL (LED) | TAXI A7 STA 702+89.99 |
| TXY A7 - L4 | MITL (LED) | TAXI A7 STA 702+89.99 |
| TXY A7 - L5 | MITL (LED) | TAXI A7 STA 702+60.36 |
| TXY A7 - L6 | MITL (LED) | TAXI A7 STA 702+30.74 |

FIXTURE TABLE **TAXIWAY B**

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL |
|------------|--------------|-----------------------|
| TXY B - L1 | MITL (LED) | TAXI B STA 342+49.48 |
| TXY B - L2 | MITL (LED) | TAXI B STA 342+91.33 |
| TXY B - L3 | MITL (LED) | TAXI B STA 343+33.18 |
| TXY B - L4 | MITL (LED) | TAXI B STA 343+69.49 |
| TXY B - L5 | MITL (LED) | TAXI B STA 344+05.80 |
| TXY B - L6 | MITL (LED) | TAXI B STA 343+81.10 |
| TXY B - L7 | MITL (LED) | TAXI B STA 343+33.19 |
| TXY B - L8 | MITL (LED) | TAXI B STA 342+91.34 |
| TXY B - L9 | MITL (LED) | TAXI B STA 342+49.48 |

FIXTURE TABLE TAXIWAY A(2)

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL | | | |
|----------------|--------------|-------------------------|--|--|--|
| TXY A(2) - L8 | MITL (LED) | TAXI A(2) STA 812+45.59 | | | |
| TXY A(2) - L1 | MITL (LED) | TAXI A(2) STA 812+45.59 | | | |
| TXY A(2) - L2 | MITL (LED) | TAXI A(2) STA 812+87.27 | | | |
| TXY A(2) - L3 | MITL (LED) | TAXI C STA 548+01.48 | | | |
| TXY A(2) - L4 | MITL (LED) | TAXI A(2) STA 814+01.82 | | | |
| TXY A(2) - L5 | MITL (LED) | TAXI A(2) STA 813+65.39 | | | |
| TXY A(2) - L6 | MITL (LED) | TAXI A(2) STA 813+28.95 | | | |
| TXY A(2) - L7 | MITL (LED) | TAXI A(2) STA 812+87.27 | | | |
| | | | | | |

FIXTURE TABLE **TAXIWAY C4**

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL |
|-------------|--------------|-----------------------|
| TXY C4 - L1 | MITL (LED) | TAXI C4 STA 1+84.26 |
| TXY C4 - L2 | MITL (LED) | TAXI C4 STA 2+20.92 |
| TXY C4 - L3 | MITL (LED) | TAXI C4 STA 2+57.59 |
| TXY C4 - L4 | MITL (LED) | TAXI C4 STA 2+89.88 |
| TXY C4 - L5 | MITL (LED) | TAXI C4 STA 2+89.88 |
| TXY C4 - L6 | MITL (LED) | TAXI C4 STA 2+57.58 |
| TXY C4 - L7 | MITL (LED) | TAXI C4 STA 2+20.94 |
| TXY C4 - L8 | MITL (LED) | TAXI C4 STA 1+84.29 |

FIXTURE TABLE TAXIWAY C

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL |
|-------------|--------------|-----------------------|
| TXY C - L1 | MITL (LED) | TAXI C STA 548+09.15 |
| TXY C - L2 | MITL (LED) | TAXI C STA 548+53.27 |
| TXY C - L3 | MITL (LED) | TAXI C STA 548+97.39 |
| TXY C - L4 | MITL (LED) | TAXI C STA 549+41.51 |
| TXY C - L5 | MITL (LED) | TAXI C STA 549+89.08 |
| TXY C - L6 | MITL (LED) | TAXI C STA 550+36.65 |
| TXY C - L7 | MITL (LED) | TAXI C STA 550+73.40 |
| TXY C - L8 | MITL (LED) | TAXI C STA 551+10.15 |
| TXY C - L9 | MITL (LED) | TAXI C STA 551+57.81 |
| TXY C - L10 | MITL (LED) | TAXI C STA 552+05.46 |
| TXY C - L11 | MITL (LED) | TAXI C STA 552+05.46 |
| TXY C - L12 | MITL (LED) | TAXI C STA 551+57.81 |
| TXY C - L13 | MITL (LED) | TAXI C STA 551+10.15 |
| TXY C - L14 | MITL (LED) | TAXI C STA 550+73.40 |
| TXY C - L15 | MITL (LED) | TAXI C STA 548+84.06 |
| TXY C - L16 | MITL (LED) | TAXI C STA 548+55.84 |
| TXY C - L18 | MITL (LED) | TAXI C STA 547+83.50 |
| TXY D - L17 | MITL (LED) | TAXI C STA 548+19.67 |



FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

MARK DATE DESCRIPTION

IL. PROJ. NO. CMI-4793 CMT PROJECT NO: 20005901 CAD DWG FILE: 20005901-EL400.DWG DESIGNED BY: HCH DRAWN BY: CHECKED BY: MJD APPROVED BY: CBG COPYRIGHT:

LIGHTING SCHEDULE

EL401

67

SHEET **47**

FIXTURE TABLE TAXIWAY A(1)

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL |
|----------------|--------------|------------------------|
| TXY A(1) - L1 | MITL (LED) | TAXI A(1) STA 8+23.93 |
| TXY A(1) - L2 | MITL (LED) | TAXI A(1) STA 8+60.68 |
| TXY A(1) - L3 | MITL (LED) | TAXI A(1) STA 8+97.42 |
| TXY A(1) - L4 | MITL (LED) | TAXI A(1) STA 9+34.16 |
| TXY A(1) - L5 | MITL (LED) | TAXI A(1) STA 9+75.28 |
| TXY A(1) - L6 | MITL (LED) | TAXI A(1) STA 10+16.40 |
| TXY A(1) - L7 | MITL (LED) | TAXI A(1) STA 10+52.93 |
| TXY A(1) - L8 | MITL (LED) | TAXI A(1) STA 10+89.45 |
| TXY A(1) - L9 | MITL (LED) | TAXI A(1) STA 11+25.97 |
| TXY A(1) - L10 | MITL (LED) | TAXI A(1) STA 11+25.54 |
| TXY A(1) - L11 | MITL (LED) | TAXI A(1) STA 10+89.05 |
| TXY A(1) - L12 | MITL (LED) | TAXI A(1) STA 10+52.56 |
| TXY A(1) - L13 | MITL (LED) | TAXI A(1) STA 10+16.40 |
| TXY A(1) - L14 | MITL (LED) | TAXI A(1) STA 9+75.28 |
| TXY A(1) - L15 | MITL (LED) | TAXI A(1) STA 9+34.16 |
| TXY A(1) - L16 | MITL (LED) | TAXI A(1) STA 8+97.42 |
| TXY A(1) - L17 | MITL (LED) | TAXI A(1) STA 8+60.68 |
| TXY A(1) - L18 | MITL (LED) | TAXI A(1) STA 8+24.54 |
| | | |

FIXTURE TABLE TAXIWAY GUIDANCE SIGNS

| FIXTURE # | FIXTURE TYPE | HORIZONTAL CONTROL |
|-----------|-----------------------|-------------------------|
| CEN-1 | TAXIWAY GUIDANCE SIGN | TAXI C STA 551+03.96 |
| CEN-2 | TAXIWAY GUIDANCE SIGN | TAXI C4 STA 2+51.57 |
| CEN-3 | TAXIWAY GUIDANCE SIGN | TAXI C STA 548+47.53 |
| CEN-4 | TAXIWAY GUIDANCE SIGN | TAXI A(1) STA 8+84.73 |
| CEN-5 | TAXIWAY GUIDANCE SIGN | TAXI A STA 621+93.20 |
| CEN-6 | TAXIWAY GUIDANCE SIGN | TAXI A7 STA 702+79.90 |
| CEN-7 | TAXIWAY GUIDANCE SIGN | TAXI A STA 624+52.19 |
| CEN-8 | TAXIWAY GUIDANCE SIGN | TAXI A STA 621+56.88 |
| CEN-11 | TAXIWAY GUIDANCE SIGN | TAXI B STA 343+42.75 |
| CEN-12 | TAXIWAY GUIDANCE SIGN | TAXI A(1) STA 10+65.39 |
| CEN-15 | TAXIWAY GUIDANCE SIGN | TAXI A(2) STA 813+25.38 |
| CEN-16 | TAXIWAY GUIDANCE SIGN | TAXI C STA 548+60.60 |



License No. 184-000

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

OWNER




UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


MARK DATE DESCRIPTION

HEET TITLE

LIGHTING SCHEDULE

EL402 SHEET 48 OF 67





BMTL NOTES

- I. THE LIGHT FIXTURE SHALL BE BONDED TO THE LIGHT BASE INTERNAL GROUND LUG VIA A #6 AWG STRANDED COPPER WIRE BATED FOR 600 VOLTS WITH GREEN XHHW INSULATION. THE GROUND WIRE LENGTH SHALL BE SUFFICIENT TO ALLOW THE REMOVAL OF THE LIGHT FIXTURE FROM THE LIGHT BASE FOR ROUTINE MAINTENANCE, SEE THE LIGHT FIXTURE MANUFACTURER'S INSTRUCTIONS FOR PROPER METHODS OF ATTACHING THIS BONDING WIRE
- 2. LIGHT FIXTURES SHALL BE L-861T (L) WITH ARCTIC KIT AS INDICATED ON THE PLANS AND SPECIFICATIONS. LIGHTS MAY BE RELOCATED EXISTING OR NEW LIGHTS
- 3 THE TOLERANCE FOR THE HEIGHT OF RUNWAY/TAXIWAY EDGE LIGHTS MUST BE ± 1 INCH. THE TOLERANCE FOR THE LATERAL SPACING (LIGHT LANE TO RUNWAY/TAXIWAY CENTERLINE) OF RUNWAY/TAXIWAY EDGE LIGHTS MUST BE ± 1 INCH.
- 4. DIRECTION OF PRIMARY CABLES MUST BE IDENTIFIED BY COLOR CODING AS FOLLOWS: WHEN FACING LIGHT WITH BACK FACING PAVEMENT, CABLE TO THE LEFT IS CODED RED AND CABLE TO THE RIGHT IS CODED BLUE
- 5. APPLY A CORROSION INHIBITING, ANTI-SEIZE COMPOUND TO ALL SCREWS NUTS AND FRANGIBLE COUPLING THREADS. IF COATED BOLTS ARE USED PER ENGINEERING BRIEF #83, DO NOT APPLY ANTI-SEIZE COMPOLIND
- 6. ELECTRICAL INSULATING GREASE MUST BE APPLIED WITHIN THE L-830 ISOLATION TRANSFORMER SECONDARY TWO CONDUCTOR CONNECTORS TO PREVENT WATER ENTRANCE. THE CONNECTORS MUST NOT BE TAPED.
- 7. ENTRANCES IN L-867 BASES MUST BE PLUGGED FROM THE INSIDE WITH DUCT SEAL TO MAKE WATERTIGHT
- 8. EDGE LIGHTS SHALL BE LOCATED AT 10' FROM THE EXISTING PAVEMENT EDGE, IN A STRAIGHT LINE PARALLEL WITH CENTERLINE THE CONTRACTOR SHALL VERIFY LAYOUT OF LIGHTS WITH THE RPR AND TO MATCH WITH EXISTING LIGHTS PRIOR TO INSTALLATION.
- 9. ISOLATION TRANSFORMERS SHALL BE SIZED BY LED LIGHT MANUFACTURER WITH ARCTIC KIT. INSTALL NEW TRANSFORMERS FOR ALL RELOCATED LIGHTS.



nse No. 184-000613

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

MARK DATE DESCRIPTION

AIP PROJ. NO. 3-17-0016-XXX

IL. PROJ. NO. CMI-4793 CMT PROJECT NO: 20005901 CAD DWG FILE: 20005901-EL500.DWG ESIGNED BY: HCH

UN062


DRAWN BY: CHECKED BY: AMB PPROVED BY: CBG COPYRIGHT

ELECTRICAL DETAILS

67

EL501 HEET 49


BASE MOUNTED ELEVATED EDGE LIGHT NOTE: SEE COUNTERPOISE LOCATION DETAIL



COUNTERPOISE LOCATION DETAIL

COUNTERPOISE NOTES


1. #6 BARE COUNTERPOISE WITH 3/4" x 10' GROUND ROD INSTALLED AT MAX. 500' SPACING. ALSO USE GROUND BOD TO TERMINATE THE COUNTERPOISE AT BOTH ENDS OF DUCT, GROUND BODS SHALL BE CONSIDERED INCIDENTAL TO COUNTERPOISE ITEMS



LOCATION OF COUNTERPOISE (DUCT BANK)

COUNTERPOISE NOTES


- THE HEIGHT ABOVE THE CABLE AND/OR CONDUIT IS CALCULATED TO ENSURE THE CABLES AND/OR CONDUITS TO BE PROTECTED ARE WITHIN THE 45° ZONE OF PROTECTION BELOW THE COUNTERPOISE
- COUNTERPOISE WIRES MUST BE INSTALLED ABOVE MULTIPLE CONDUITS/DUCT BANKS FOR AIREFIELD LIGHTING CABLES, WITH THE INTENT BEING TO PROVIDE A COMPLETE CONE OF PROTECTION OVER THE AIRFIELD LIGHTING CABLES. WHEN MULTIPLE CONDUITS AND/OR DUCT BANKS FOR AIRFIELD CABLE ARE INSTALLED IN THE SAME TRENCH, THE NUMBER AND LOCATION OF THE COUNTERPOISE WIRES ABOVE THE CONDUITS SHALL BE ADEQUATE TO PROVIDE A COMPLETE ZONE OF PROTECTION MEASURED 22-1 /2°EACH SIDE OF VERTICAL
- REFER TO THE CURRENT VERSIONS OF FAA AC 150/5340-30 AND AC 150/5370-10 FOR MORE DETAILS ON COUNTERPOISE INSTALLATION.




LIGHT IDENTIFICATION TAG

LIGHT IDENTIFICATION NOTES

- INSTALL A NON-CORROSIVE DISC OF 2" MINIMUM DIAMETER WITH THE NUMBER PERMANENTLY STAMPED, CUT OUT, OR ENGRAVED UNDER THE HEAD OF THE BASE PLATE BOLT OR ATTACHED TO LIGHT FLANGE WITH SET SCREW.
- LEGENDS SHOWN ARE FOR ILLUSTRATIVE PURPOSES ONLY. CONTRACTOR TO COORDINATE LEGEND WITH
- THE CONTRACTOR SHALL NUMBER THE EXISTING/ PROPOSED LIGHTS AND SIGNS IN EACH CIRCUIT STARTING AT THE HOMERUN CONTINUING AROUND THE ENTIRE CIRCUIT BACK TO THE HOMERUN.
- AIRFIELD SIGNS SHALL BE TAGGED & NUMBERED







FOR BID SET JUNE 16, 2023

NCMT

MIDFIELD INTERSECTION RECONFIGURATION



- CABLES SHALL NOT BE PLACED LESS THAN 24" DEEP IN ANY ONE TRENCH UNLESS PERMITTED BY ENGINEER.
- WHERE PERMITTED, CONTRACTOR MAY INSTALL CABLE
- COUNTERPOISE NOT SHOWN FOR CLARITY



1. CONTRACTOR SHALL CUT THE #6 BARE COPPER WIRE AT EACH END OF THE NEW DUCT AND EXOTHERMICALLY

WELD THE WIRE TO A 3/4" DIA. x 10' LONG GROUND ROD. THIS COST SHALL BE INCIDENTAL TO THE SPLIT DUCT

L-853 RETROREFLECTIVE MARKER

6" x 12" HIGH

CONCRETE ANCHOR

RETROREFLECTIVE MARKER NOTES

REFLECTIVE BAND

CONNECTION TO BASE

SURFACE MOUNT BASE

PER MANUFACTURER

LOCKING PIN

REFLECTORS ARE INSTALLED 10' FROM EDGE OF MARKED PAVEMENT, IN-LINE WITH EXISTING TAXIWAY EDGE

CHAMPAIGN URBANA


> UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

MARK DATE DESCRIPTION UN062 IL. PROJ. NO. CMI-4793 CMT PROJECT NO: 20005901 CAD DWG FILE: 20005901-EL500.DWG DESIGNED BY: DRAWN BY: CHECKED BY: AMB APPROVED BY: COPYRIGHT

ELECTRICAL DETAILS

EL502 SHEET **50** 67

CABLE TRENCH NOTES





6. #4 REBAR SHALL BE INSTALLED CONTINUOUS

THE LENGTH OF THE CONCRETE ENCASEMENT



11. DEPTH AS REQUIRED TO NOT IMPACT EDGE







EL503

67

SHEET 51

NCMT

FOR BID SET

JUNE 16, 2023


MIDFIELD INTERSECTION

RECONFIGURATION

CHAMPAIGN

URBANA


CONTRACTOR MAY ELECT TO INSTALL FAA APPROVED "COMPLETE KIT" CONNECTORS IN LIEU OF HEAT SHRINK.




L-806 LED SUPPLEMENTAL WIND CONE **EXTERNALLY LIGHTED**

NOTES

- 1. L-806 SUPPLEMENTAL (8-FOOT) WIND CONE.
- 2. SUPPLEMENTAL WIND CONE SHALL BE LOCATED OUTSIDE THE RUNWAY SAFETY AREA (RSA).






L-806 WIND CONE POWER 3

WIND CONE POWER LEGEND

- (1.) 2" GALVANIZED STEEL SUPPORT POST WITH END CAPS (TYP. OF 2).
- 2. STRUT-TYPE SUPPORT, UNISTRUT 2000, OR EQUIVALENT (TYP. OF 5).
- (3.) HEAVY-DUTY 30A, 600V UNFUSED DISCONNECT IN NEMA 3R ENCLOSURE. PROVIDE GROUND LUGS. PROVIDE LABLEL READING: "CAUTION: 480 VOLTS."
- WINDCONE STEP-DOWN TRANSFORMER, 3KVA, 480-120/240V, 1-PHASE, 3-WIRE, NEMA 3R SQUARE D MODEL 3S1F, OR EQUIVALENT.
- WINDCONE PHOTOCELL, TORK MODEL #2101, OR EQUIVALENT. (NOTE: PHOTOCELL OPERATION IS AS FOLLOWS: DURING THE DAYTIME THE WINDCONE LIGHTS ARE OFF AND THE OBSTRUCTION LIGHT IS ON. AFTER DARK THE WINDCONE LIGHTS AND OBSTRUCTION LIGHT ARE ON).

LOCATE DISCONNECT/ TRANSFORMER/ PHOTOCELL INSTALLATION SUCH THAT WINDCONE LIGHT WILL NOT ADVERSELY AFFECT THE PHOTOCELL OPERATION.

- (6.) 12" DIAMETER X 4'-0" DEEP (MIN.) CONCRETE FOUNDATION. (TYP. OF TWO).
- (7.) FRANGIBLE COUPLINGS (TYP. OF 2). INSTALL FRANGIBLE COUPLING NOT MORE THAN 3" ABOVE GRADE.
- 8.) TWO #6 USE (480V). ONE #8 GROUND IN 2" CONDUCT TO VAULT.
- 9. NOT USED.
- (0) TWO #12 USE (OBSTRUCTION LIGHT 120V POWER), TWO #12 USE (WINDCONE LIGHTS 120V POWER), ONE #10 GROUND IN 2" CONDUIT TO WINDCONE.
- (11) #8 GROUND WIRE IN 1/2" PVC CONDUIT TO GROUND ROD.
- (12) 3/4" DIAMETER X 10' LONG COPPERCLAD GROUND ROD. MIN. BURIAL: 1-0". BOND GROUND WIRES TO GROUND ROD USING EXOTHERMIC WELD, CADWELD, OR EQUIVALENT. CLAMPED CONNECTIONS SHALL NOT BE ACCEPTABLE.
- (13) TWO #12 USE (SEE WINDCONE SCHEMATIC), ONE #10 GROUND IN 3/4" GRS CONDUIT.
- (4) NEMA 4 JUNCTION BOX SIZED AS REQUIRED TO HOUSE THREE 10A IN-LINE FUSES. PHOTOCELL BYPASS SELECTOR SWITCH AND WEATHERPROOF GFCI CONVENIENCE RECEPTACLE. (SEE WINDCONE SCHEMATIC.)
- (15) -1/2" GRS CONDUIT TO 1'-6" BELOW GRADE
- (6) 1" GRS CONDUIT TO 1'-6" BELOW GRADE
- (17) LIQUIDTITE FLEXIBLE CONDUIT





NOTE

- 1. CONCRETE SHALL MEET THE REQUIREMENTS OF ITEM P-610.
- 2. REBAR MEETING ASTM A-706, GRADE 60, SHALL BE INSTALLED ON 8 INCH CENTERS BOTH WAYS. REBAR SHALL BE MINIMUM #4 BARS. 3" CLEARANCE SHALL BE MAINTAINED BETWEEN THE REBAR AND THE FINISHED FACE OF THE CONCRETE.
- 3. A 6-INCH BED OF CA-7 OR CA-11 SHALL BE PLACED BENEATH THE HANDHOLE.
- 4. INSTALL GROUND ROD IN EACH HANDHOLE
- 5. ANY UNUSED DUCT OPENINGS SHALL BE FITTED WITH APPROVED PLUGS PRIOR TO BACKFILLING.
- 6. HANDHOLES SHALL HAVE A WEEP HOLE CONSTRUCTED IN THE BOTTOM OF HANDHOLE.
- HANDHOLE COVER SHALL BE LABELED "COMMUNICATION"
- 8. 4-WAY DIRECTIONAL BORE SHALL BE CONNECTED IN HANDHOLES IN MANNER THAT CREATES A SINGLE 4-WAY DUCT BANK.

MANHOLE AND HANDHOLE WIRING NOTES

- 1.) ALL WIRING IN MANHOLES AND HANDHOLES SHALL BE LABELED INSIDE MANHOLES AND HANDHOLES. LABELING MATERIALS SHALL BE SUITABLE FOR USE IN THE ENVIRONMENT AND SHALL BE WATERPROOF. LABELS SHALL IDENTIFY EACH 480V, 240V AND 120V AND MONITOR CIRCUIT PER MASTER CIRCUIT LABELING SCHEDULE DEVELOPED BY ELECTRICAL CONTRACTOR.
- 2.) WHEREVER POSSIBLE, WIRING TO INDIVIDUAL STRUCTURES AND PIECES OF EQUIPMENT SHALL BE GROUPED TOGETHER IN MANHOLES AND HANDHOLES (SEE NOTE #3, BELOW, FOR ADDITIONAL REQUIREMENTS), MULTIPLE CONDUCTORS OF INDIVIDUAL CIRCUITS SHALL BE TIE-WRAPPED TOGETHER AND LABELED.
- 3.) WHEREVER POSSIBLE, 480V WIRING, 120V/240V WIRING AND MONITOR/ALARM WIRING SHALL BE SEPARATED FROM EACH OTHER IN MANHOLES AND HANDHOLES. MONITOR WIRING SHALL BE ROUTED ABOVE 120V/240V WIRING WHICH, IN TURN, SHALL BE ROUTED ABOVE 480V WIRING
- 4.) ALL WIRING THROUGH MANHOLES SHALL BE ATTACHED TO CABLE RACKS.



FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION





UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| MARK | DATE | DES | SCRIPTION | |
|--------|---------|---------|--------------------|-------|
| AIP PI | ROJ. NO | . 3-17- | 0016-XXX | UN062 |
| IL. PR | OJ. NO. | CMI-4 | 793 | |
| CMT F | ROJECT | ΓNO: | 20005901 | |
| CAD | WG FILE | E: | 20005901-EL500.DWG | |
| DESIG | NED BY | : | HCH | |
| DRAW | N BY: | | DPA | |
| CHEC | KED BY: | | AMB | |
| APPR | OVED BY | Y: | CBG | |
| COBY | DICUT: | | | |

ELECTRICAL DETAILS

EL504 HEET 52





MIDFIELD INTERSECTION RECONFIGURATION L-823 PLUG FRANGIBLE FURNISHED WITH SIGN COUPLING FLOOR FLANGE CABLE CLAMP TOP OF 2" CONDUIT TO BE FLUSH WITH TOP SUBFACE OF

CONCRETE MOUNTING PAD

L-823 CONNECTOR

CHAMPAIGN URBANA

MARK DATE DESCRIPTION

CMT PROJECT NO: 20005901

CAD DWG FILE: 20005901-EL500.DWG

HCH

DPA

AMB

IL. PROJ. NO. CMI-4793

DESIGNED BY:

DRAWN BY:

CHECKED BY:

PPROVED BY: COPYRIGHT

UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


UN062

FOR BID SET

JUNE 16, 2023



- TRANSFORMER WATTAGE SHALL BE AS REQUIRED BY SIGN MANUFACTURER. SIGNS ON RUNWAY CIRCUITS SHALL BE STYLE 2 OR 3 DEPENDING ON REGULATOR.
- SIGN LEGEND SHALL BE AS SHOWN IN THE PLANS. SIGN SCHEDULE IS SUBJECT TO FAA APPROVAL OF THE SIGNAGE PLAN. CHANGES TO NEW LEGENDS MAY OCCUR DURING CONSTRUCTION.
- SIGN ANCHOR TETHERS AND GROUND WIRES ARE REQUIRED. SEE SPECIFICATIONS.
- SIGNS SHALL BE SIZE 2, STYLE 2, CLASS 2, AND MODE 2. SEE SIGN SCHEDULE FOR
- LIGHT I.D. TAG FOR SIGN SHALL INCLUDE SIGN DESIGNATOR SHOWN IN THE PLAN
- FOLLOWS: WHEN FACING SIGN IN BACK FACING THE RELATED RUNWAY OR TAXIWAY PAVEMENT, THE CABLE FOR THE CIRCUIT TO THE LEFT IS CODED RED AND CABLE FOR THE CIRCUIT TO THE RIGHT IS CODED BLUE.



ELECTRICAL DETAILS

EL505 SHEET **53** 67

DIRECTION OF PRIMARY CABLES MUST BE IDENTIFIED BY COLOR CODING AS

INSTALL NEW ISOLATION TRANSFORMERS FOR ALL RELOCATED SIGNS. ISOLATION TRANSFORMERS SHALL BE SIZED BY SIGN MANUFACTURER (INCIDENTAL TO SIGN

#6 BARE COPPER SIDE OF L-867 **GROUND WIRE** OR I -860 BASE CAN 1/4" ROLT

5/16" BOLT

VEGA 0919 GROUND STAMP


GROUND WIRE CLAMP

FACTORY GROUND LUG

ELECTRICAL CONNECTION (FIGURE 1)


JUMPER CARLE

TAXI GUIDANCE SIGN PCC BASE EXTENSION



KEYED NOTES

- A PRECAST CONCRETE HANDHOLE
- B PULLING IRONS MINIMUM 1" DIA. STEEL, HOT DIPPED GALVANIZED (MINIMUM 2)
- C KNOCKOUTS SHALL BE CENTERED IN THE HANDHOLE WALL AND SHALL BE SIZED AS REQUIRED FOR PROPOSED DUCT BANK
- D HATCH COVER SHALL BE CAST IN NEENAH R-3498-K2 OR APPROVED EQUAL
- E LIFTING ANCHORS (4)
- 1-1/2" DIA. GROUND ROD HOLE (1)



AIRFIELD ELECTRICAL HANDHOLE

NO SCALE

NOTE

- 1. CONCRETE SHALL MEET THE REQUIREMENTS OF ITEM P-610.
- 2. REBAR MEETING ASTM A-615, GRADE 60, SHALL BE INSTALLED ON 8 INCH CENTERS BOTH WAYS. REBAR SHALL BE MINIMUM #4 BARS. 3" CLEARANCE SHALL BE MAINTAINED BETWEEN THE REBAR AND THE FINISHED FACE OF THE CONCRETE.
- 3. A 6-INCH BED OF CA-7 OR CA-11 SHALL BE PLACED BENEATH THE HANDHOLE.
- 4. INSTALL GROUND ROD IN EACH HANDHOLE
- 5. ANY UNUSED DUCT OPENINGS SHALL BE FITTED WITH APPROVED PLUGS PRIOR TO BACKFILLING.
- 6. HANDHOLES SHALL HAVE A WEEP HOLE CONSTRUCTED IN THE BOTTOM OF HANDHOLE.
- HANDHOLE LIDS SHALL BE STAMPED AS SHOWN ON PLANS: FOR AIRFIELD LIGHTING LIGHTING AND POWER: "ELECTRIC" FOR FIBER OPTIC CABLE: "FIBER"
- 8. PRECAST HANDHOLE SHALL MEET UTILITY CONCRETE PRODUCTS ITEM #2238HH OR APPROVED EQUAL

CONDUCTOR FILL IN CONDUIT SEALS:

CONTRACTOR SHALL COMPLY WITH ARTICLE 501.15-C.6 OF THE NEC, WHICH READS:

"THE CROSS-SECTIONAL AREA OF THE CONDUCTORS PERMITTED IN A [CONDUIT] SEAL SHALL NOT EXCEED 25 PERCENT OF THE CROSS-SECTIONAL AREA OF A CONDUIT OF THE SAME TRADE SIZE UNLESS IT IS SPECIFICALLY APPROVED FOR A HIGHER PERCENTAGE OF FILL."

CONTRACTOR SHALL VERIFY COMPLIANCE WITH ARTICLE PRIOR TO INSTALLATION OF ALL CONDUIT SEALS ON THIS PROJECT.


CONDUIT SEALS INSTALLED IN VIOLATION OF THIS REQUIREMENT SHALL BE REPLACED BY THE CONTRACTOR (INCLUDING ALL CONDUCTORS IF SEALING COMPOUND HAS BEEN INSTALLED) AT THE CONTRACTOR'S EXPENSE.

NEMA 4 & NEMA 4X ENCLOSURES

TO MAINTAIN THE ENCLOSURE NEMA 4 OR NEMA 4X RATING, ALL ENCLOSURES RATED NEMA 4 OR NEMA 4X SHALL HAVE WATERTIGHT HUBS AT CONDUIT ENTRANCES WHICH ARE U.L. LISTED NEMA 4 OR NEMA 4X, AS NECESSARY, AND SUITABLE FOR USE WITH THE RESPECTIVE ENCLOSURE.

MANHOLE AND HANDHOLE WIRING NOTES

- ALL WIRING IN MANHOLES AND HANDHOLES SHALL BE LABELED INSIDE MANHOLES AND HANDHOLES. LABELING MATERIALS SHALL BE SUITABLE FOR USE IN THE ENVIRONMENT AND SHALL BE WATERPROOF. LABELS SHALL IDENTIFY EACH 480V, 240V AND 120V AND MONITOR CIRCUIT PER MASTER CIRCUIT LABELING SCHEDULE DEVELOPED BY ELECTRICAL CONTRACTOR.
- 2. WHEREVER POSSIBLE, WIRING TO INDIVIDUAL STRUCTURES AND PIECES OF EQUIPMENT SHALL BE GROUPED TOGETHER IN MANHOLES AND HANDHOLES (SEE NOTE #3, BELOW, FOR ADDITIONAL REQUIREMENTS). MULTIPLE CONDUCTORS OF INDIVIDUAL CIRCUITS SHALL BE TIE-WRAPPED TOGETHER AND LABELED.
- 3. WHEREVER POSSIBLE, 480V WIRING, 120V/240V WIRING AND MONITOR/ALARM WIRING SHALL BE SEPARATED FROM EACH OTHER IN MANHOLES AND HANDHOLES. MONITOR WIRING SHALL BE ROUTED ABOVE 120V/240V WIRING WHICH, IN TURN, SHALL BE ROUTED ABOVE 480V WIRING.
- ALL WIRING THROUGH MANHOLES SHALL BE ATTACHED TO CABLE RACKS.



TYPICAL CROSS - SECTIONS FOR CONDUCTORS IN PVC CONDUIT (FAA)

NOT TO SCALE

NOTES

1. ALL CABLES NOT IN FERROUS CONDUIT SHALL HAVE 1/0 AWG COPPER GUARD WIRE MINIMUM 10 INCHES ABOVE THE CABLES OR CONDUITS AND 8" BELOW FINISHED GRADE. GUARD WIRE SHALL BE BONDED TO THE GROUNDING SYSTEM AT EACH END AND TO GROUND RODS AT APPROXIMATELY 90 FEET INTERVALS. REFER TO FAA-STD-19F FOR DETAILS.



License No. 184-00061

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

OWNER



UNIVERSITY OF ILLINOIS
WILLARD AIRPORT
SAVOY, ILLINOIS

| MARK | DATE | DES | SCRIPTION | | |
|--------|---------|---------|--------------------|-------|---|
| AIP PI | ROJ. NO | . 3-17- | 0016-XXX | UN062 | • |
| IL. PR | OJ. NO. | CMI-4 | 793 | | |
| CMT F | ROJEC | ΓNO: | 20005901 | | |
| CAD | WG FILI | E: | 20005901-EL500.DWG | | |
| DESIG | NED BY | : | HCH | | |
| DRAW | N BY: | | DPA | | |
| CHEC | KED BY: | | AMB | | |
| APPR | OVED B | Y: | CBG | | |
| COPY | RIGHT: | | | | |
| | | | | | |


SHEET TITLE

ELECTRICAL DETAILS


EL506

67

| | | WHITE WITH BLACK | BI ACK I EGEND | VELLOW LEGEND | | | | | | | | |
|-----------------|--------------------|------------------------------|-------------------------|------------------------|-------------------------|------------------|---------------|----------------------|---------------|-------------------------|--------------|------------------|
| SIGN # SIDE | NEW SIGN LEGEND | OUTLINE ON RED BACKGROUND | ON YELLOW BACKGROUND | ON BLACK BACKGROUND | NUMBER OF CHARACTERS | POWER CIRCUIT | SIGN STYLE | CIRCUIT INTENSITY | REG OUTPUT | EXISTING MANUFACTURE | SIGN SIZE | ACTION |
| 14L-1 NE SW | A9 14L A9 | 14L | | A9 A9 | 5 | 14L-32R | 2 | HIGH | 20.0 | AGM ILUX | 2 | NEW SIGN 5 CHAR. |
| 14L-2 NE SW | A8 32R-14L A8 | 32R-14L | | A8 A8 | 9 | 14L-32R | 2 | HIGH | 20.0 | LUMACURVE | 2 | REVISE 2 LEGEND |
| 14L-6 NE SW | A4 32R-14L A4 | 32R-14L | | A4 A4 | 9 | 14L-32R | 2 | HIGH | 20.0 | AGM ILUX | 2 | REVISE 2 LEGEND |
| 14L-7 NE SW | 32R A1 A1 | 32R | | A1 A1 | 5 | 14L-32R | 3 | HIGH | 20.0 | AGM ILUX | 2 | REVISE 2 LEGEND |
| 14L-8 NE SW | A1 32R A1 | 32R | | A1 A1 | 5 | 14L-32R | 3 | HIGH | 20.0 | AGM ILUX | 2 | NEW SIGN 5 CHAR. |
| 14L-10 SW NE | D 14L-32R | 14L-32R | | D D | 8 | 14L-32R | 2 | HIGH | 20.0 | LUMACURVE | 2 | REVISE 2 LEGEND |
| 14L-18 SW NE | E 14L-32R E | 14L-32R | | E E | 8 | 14L-32R | 2 | HIGH | 20.0 | LUMACURVE | 2 | REVISE 2 LEGEND |
| 14R-1 NE SW | E 14R E | 14R | | E E | 4 | 14L-32R | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | REVISE 2 LEGEND |
| 14R-2 SE NW | E→ | | E→ | | 2 | 14R-32L | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | REVISE 1 LEGEND |
| 14R-7 NW SE | ← D | | ←D | | 2 | 14R-32L | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | REVISE 1 LEGEND |
| 14R-8 NE SW | D 32L D | 32L | | D D | 4 | 14R-32L | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | REVISE 2 LEGEND |
| 14R-9 SE NW | ←E | | ←E | | 2 | 14R-32L | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | REVISE 1 LEGEND |
| 22-1 SE NW | B1 4 B1 | 4 | | B1 B1 | 3 | 4-22 | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | NEW SIGN 3 CHAR. |
| 22-3 NE SW | B2 4-22 B2 | 4-22 | | B2 B2 | 6 | 4-22 | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 2 LEGEND |
| 22-10 SE NW | A 4-22 A | 4-22 | | A A | 5 | 4-22 | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 2 LEGEND |
| 22-12 SE NW | C1 22 C1 | 22 | | C1 C1 | 4 | 4-22 | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | NEW SIGN 4 CHAR. |
| 22-13 NW SE | A 22-4 A | 22-4 | | A A | 5 | 4-22 | 3 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 2 LEGEND |
| ANW-1 NW SE | 14L A9 → | 14L | A9 <i>→</i> | | 3 | TAXI A NW | 3 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ANW-2 NW SE | 14L↑ A A8→ XX | | A8 → | A | 4 | TAXI A NW | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ANW-3 SW NE | A8 ←A→ | | ← A → | A8 | 5 | TAXI A NW | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ANW-4 NW SE | ← A8 | | ← A8 | | 3 | TAXI A NW | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | REVISE 1 LEGEND |
| ANW-5 SE | A8 → | | A8 → | | 3 | TAXI A NW | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | REVISE 1 LEGEND |
| ANW-6 SE | ←A8 A | | ← A8 | А | 4 | TAXI A NW | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-1 NW SE | ← A6 A | | ← A6 | А | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-2 NE SW | A6 ←A→ | | ← A → | A6 | 5 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-3 NW SE | ← A5 A | | ← A5 | Α | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-4 NE SW | A5 ←A→ | | ← A → | A5 | 5 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-5 NW SE | A A4→ XX FBO → | | A4 → FBO → | Α | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-6 NW SE | ← A3 A | | ← A3 | А | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-7 NE SW | А3 ↑ | | A3 ↑ | | 3 | TAXI A SE | 3 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-8 NE SW | A3 ←A→ | | ← A → | A3 | 5 | TAXI A SE | 3 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 2 LEGEND |
| ASE-9 NW SE | ←A3 A XX FBO↑ | | ← A3 FBO ↑ | А | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-10 NE SW | A2 ↑ | | A2 ↑ | | 3 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-11 NE SW | A2 ←A→ | | ← A → | A2 | 5 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 2 LEGEND |
| ASE-12 NW SE | ← A1 | | ← A1 | | 3 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | NEW SIGN 3 CHAR. |
| ASE-13 NW SE | 32R↑ A A2→ XX | | 32R↑ A2→ | A | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-14 NW SE | A A3→ | | A3 → | A | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-15 SE NW | ←A4 A | | ← A4 | Α | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-16 SE NW | A4 → | | A4 → | | 3 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-17 NW SE | ← A4 | | ← A4 | | 3 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-18 NE SW | A4 ←A→ | | ← A → | A4 | 5 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-19 SE NW | A A5→ | | A5 → | Α | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| ASE-20 SE NW | A A6→ | | A6 → | Α | 4 | TAXI A SE | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| NW | | | | | | ., ., ., ., OL | | l | | | | |



EXISTING TAXIWAY DESIGNATIONS



NEW TAXIWAY DESIGNATIONS



License No. 184-000613

ISULTANTS

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

OWNER



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| MARK | DATE | DES | SCRIPTION | | | | |
|--------------------------|---------------------------------|-----|--------------------|--|--|--|--|
| AIP P | AIP PROJ. NO. 3-17-0016-XXX UNO | | | | | | |
| IL. PR | IL. PROJ. NO. CMI-4793 | | | | | | |
| CMT PROJECT NO: 20005901 | | | | | | | |
| CAD DWG FILE: | | | 20005901-EL500.DWG | | | | |
| DESIGNED BY: | | | HCH | | | | |
| DRAWN BY: | | | DPA | | | | |
| CHECKED BY: | | | MJD | | | | |

APPROVED BY: CBG
COPYRIGHT:

SIGN SCHEDULE 1

EL507 SHEET 55 OF

67

Path: K:\ChampaignAp\20005901-00_MidfieldIntersect\Draw\Sheets\20005901-EL500 Date: Friday, May 12, 2023 12:08:19 PM

| | | T. | _ | | T | | | | | | | | |
|--------|----------|--------------------|--|---|---|-------------------------|------------------|---------------|----------------------|---------------|-------------------------|--------------|------------------|
| SIGN # | SIDE | NEW SIGN LEGEND | WHITE WITH BLACK OUTLINE ON RED BACKGROUND | BLACK LEGEND ON YELLOW BACKGROUND | YELLOW LEGEND ON BLACK BACKGROUND | NUMBER OF CHARACTERS | POWER CIRCUIT | SIGN STYLE | CIRCUIT INTENSITY | REG OUTPUT | EXISTING MANUFACTURE | SIGN SIZE | ACTION |
| B-2 | NW SE | B2 ←B→ | | ←B → | B2 | 5 | TAXI B | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 2 LEGEND |
| B-3 | NE SW | ←B2 | | ←B2 | | 3 | TAXI B | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| B-4 | SW NE | B2 → | | B2 → | | 3 | TAXI B | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| B-5 | SW NE | ←B2 B | | ←B2 | В | 4 | TAXI B | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| B-6 | NE SW | ←B1 | | ←B1 | | 3 | TAXI B | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | NEW SIGN 3 CHAR. |
| B-7 | NE SW | B B2 → | | B2 → | В | 4 | TAXI B | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| C-1 | NE SW | C C3 → | | C3 > | С | 4 | TAXI C | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| C-2 | NE SW | C C2→ | | C2→ | С | 4 | TAXI C | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| C-3 | SW NE | C1→ | | C1 → | | 3 | TAXI C | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | NEW SIGN 3 CHAR. |
| C-4 | NE SW | ←C2 C | | ←C2 | С | 5 | TAXI C | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| C-5 | SE NW | C2 ←C→ | | ←C → | C2 | 5 | TAXI C | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| C-6 | NE SW | ←C3 C | | ←C3 | С | 4 | TAXI C | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| C-7 | SE NW | C3 ←C→ | | ←C → | С3 | 5 | TAXI C | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 2 LEGEND |
| CEN-1 | NE SW | ←C4 C | | ←C4 | С | 4 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 4 CHAR. |
| CEN-2 | SE NW | C4 ←C→ | | ←C → | C4 | 5 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 5 CHAR. |
| CEN-3 | NE SW | A7 C A→ C C4→ | | A7 A→ C4→ | C | 5 | CENTER | 2 | MEDIUM | 6.6 | | 2 | RELOCATE 5 CHAR. |
| CEN-4 | N S | A⊼ A B⊅ | | A⊼ B⊅ | А | 5 | CENTER | 2 | MEDIUM | 6.6 | | 2 | RELOCATE 5 CHAR. |
| CEN-5 | NE SW | ←A7 A | | ← A7 | А | 5 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 4 CHAR. |
| CEN-6 | NW SE | A7 ←A→ | | ←A → | A7 | 5 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 5 CHAR. |
| CEN-7 | NW SE | A A7→ A | | A7→ | A A | 4 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 4 CHAR. |
| CEN-8 | SE NW | ←B A A⊅ ←A7 A | | ←B Aオ ←A7 | A A | 5 | CENTER | 2 | MEDIUM | 6.6 | LUMACURVE | 2 | NEW SIGN 5 CHAR. |
| CEN-11 | SW NE | KA B A→ B | | ⊼A A→ | B B | 6 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 5 CHAR. |
| CEN-12 | S N | KA A CZ | | KA CZ | А | 5 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 5 CHAR. |
| CEN-13 | SW NE | A > | | A → | | 5 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| CEN-14 | NE SW | ← A | | ← A | | 8 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | REVISE 1 LEGEND |
| CEN-15 | NE SW | ←C A A⊅ | | ←C Aオ | А | 5 | CENTER | 2 | MEDIUM | 6.6 | | 2 | RELOCATE 5 CHAR. |
| CEN-16 | SW NE | C C4 → KA C A→ | | C4 → | C C | 5 | CENTER | 2 | MEDIUM | 6.6 | AGM ILUX | 2 | RELOCATE 5 CHAR. |

SIGN SCHEDULE NOTES

- 1. SIGN LEGENDS WILL REQUIRE NEW SIGN LEGENDS, NEW SIGNS AND SIGNS FROM EXISTING FIELD LOCATIONS TO BE RELOCATED WITH NEW SIGN LEGENDS.
- 2. SIGN LEGENDS TO BE REVISED WILL REQUIRE A NEW REVISED SIGN LEGEND. WHERE 2 LEGENDS ARE
 SHOWN AND ONLY 1 REVISED LEGEND, THE LEGEND
 TO BE REVISED WILL BE DENOTED WITH AN "XX".
- 3. RELOCATED SIGNS WILL REQUIRE A NEW FOUNDATION AND A NEW SIGN LEGEND SHOWN IN THE SCHEDULE.
- 4. NEW SIGNS SHOWN MAY REQUIRE A NEW OR
- EXTENSION OF THE EXISTING SIGN FOUNDATION.

 5. MANUFACTURE OF EXISTING SIGNS SHALL BE FIELD VERIFIED BY THE CONTRACTOR.



FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION



UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


| MARK | DATE | DESCRIPTION |
|------|------|-------------|


| AIP PROJ. NO. 3-17- | -0016-XXX | UNO |
|---------------------|--------------------|-----|
| IL. PROJ. NO. CMI-4 | 793 | |
| CMT PROJECT NO: | 20005901 | |
| CAD DWG FILE: | 20005901-EL500.DWG | |
| DESIGNED BY: | HCH | |
| DRAWN BY: | DPA | |
| CHECKED BY: | MJD | |
| APPROVED BY: | CBG | |


COPYRIGHT:


SIGN SCHEDULE 2


EL508 <u>SHEET</u> 56 67


























SECTION END AREA EXCAVATION EMBANKMENT

| | END AREA (S.F.) | END AREA (S.F.) |
|----------|--------------------|--------------------|
| 2+50.00 | 2.32 | 20.92 |
| 3+00.00 | 72.44 | 25.42 |
| 3+50.00 | 68.83 | 45.99 |
| 4+00.00 | 59.22 | 113.45 |
| 4+50.00 | 112.80 | 14.53 |
| 5+00.00 | 234.72 | 23.20 |
| 5+50.00 | 118.03 | 62.52 |
| 6+00.00 | 116.53 | 83.32 |
| 6+50.00 | 115.55 | 57.13 |
| 7+00.00 | 93.79 | 57.37 |
| 7+50.00 | 60.41 | 28.20 |
| 8+00.00 | 143.21 | 153.95 |
| 8+50.00 | 151.53 | 133.97 |
| 9+00.00 | 77.76 | 260.68 |
| 9+50.00 | 99.42 | 278.82 |
| 10+00.00 | 94.20 | 274.34 |
| 10+50.00 | 153.36 | 119.06 |
| 11+00.00 | 213.54 | 114.68 |
| 11+50.00 | 76.40 | 6.30 |
| 12+00.00 | 197.71 | 43.68 |
| 12+50.00 | 214.02 | 77.47 |
| 13+00.00 | 130.80 | 90.18 |
| 13+50.00 | 342.97 | 23.68 |
| 14+00.00 | 300.84 | 9.57 |
| 14+50.00 | 131.17 | 112.81 |
| 15+00.00 | 80.65 | 105.57 |
| 15+50.00 | 105.25 | 42.83 |
| 16+00.00 | 87.82 | 4.74 |
| 16+50.00 | 0.00 | 3.41 |

NCMT

License No. 184-000613 CONSULTANTS

FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

CHAMPAIGN URBANA

UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

MARK DATE DESCRIPTION

AIP PROJ. NO. 3-17-0016-XXX IL. PROJ. NO. CMI-4793

CMT PROJECT NO: 20005901 CAD DWG FILE: 20005901-CS700.DWG DESIGNED BY: DRAWN BY: CHECKED BY: MJD APPROVED BY: CBG

UN062

COPYRIGHT:


CROSS SECTIONS 1


CS701 SHEET 61

67


NOTES


EXCESS MATERIAL GENERATED FROM EMBANKMENT EXCAVATION SHALL BE HAULED OFF SITE OR TO AREAS DESIGNATED BY THE AIRPORT.







NOTES NCMT 1. EXCESS MATERIAL GENERATED FROM EMBANKMENT EXCAVATION SHALL BE HAULED OFF SITE OR TO AREAS DESIGNATED BY THE License No. 184-000613 CONSULTANTS EXISTING GROUND FOR BID SET JUNE 16, 2023 MIDFIELD INTERSECTION RECONFIGURATION SEE INDEX TO SHEETS FOR ADJACENT CROSS SECTIONS EXISTING PAVEMENT NEW PAVEMENT O/S = 0.0 ELEV = 74 NEW FINISHED GROUND LINE CHAMPAIGN URBANA UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS MARK DATE DESCRIPTION AIP PROJ. NO. 3-17-0016-XXX UN062 IL. PROJ. NO. CMI-4793 CMT PROJECT NO: 20005901 CAD DWG FILE: 20005901-CS700.DWG DESIGNED BY: DRAWN BY: CHECKED BY: MJD APPROVED BY: CBG COPYRIGHT: **CROSS SECTIONS 4** CS704 SHEET **64**







| SECTION END AREA | | | | | | |
|------------------|----------------------------------|----------------------------------|--|--|--|--|
| STATION | EXCAVATION END AREA (S.F.) | EMBANKMENT END AREA (S.F.) | | | | |
| 342+00.00 | 0.00 | 0.02 | | | | |
| 342+50.00 | 164.68 | 59.40 | | | | |
| 343+00.00 | 96.05 | 54.13 | | | | |
| 343+50.00 | 124.20 | 51.56 | | | | |
| 344+00.00 | 191.14 | 55.61 | | | | |
| | | | | | | |









FOR BID SET JUNE 16, 2023

SCMT

License No. 184-000613 CONSULTANTS

MIDFIELD INTERSECTION RECONFIGURATION

CHAMPAIGN URBANA


UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

| MARK | DATE | DES | SCRIPTION | | | |
|--------|-----------------------------------|------------|--------------------|--|--|--|
| | | | | | | |
| AIP P | AIP PROJ. NO. 3-17-0016-XXX UN062 | | | | | |
| IL. PR | OJ. NO. (| CMI-4 | 793 | | | |
| CMT F | ROJECT | NO: | 20005901 | | | |
| CAD | WG FILE | Ē: | 20005901-CS700.DWG | | | |
| DESIG | NED BY | | HCH | | | |
| DRAW | N BY: | | DPA | | | |
| CHEC | KED BY: | | MJD | | | |
| APPRO | OVED BY | ′ : | CBG | | | |
| COPY | RIGHT: | | | | | |


NOTES


1. EXCESS MATERIAL GENERATED FROM EMBANKMENT EXCAVATION SHALL BE HAULED OFF SITE OR TO AREAS DESIGNATED BY THE AIRPORT. **CROSS SECTIONS 6**


CS706 SHEET 66 67




| SECTION END AREA | | | | | |
|------------------|----------------------------------|----------------------------------|--|--|--|
| STATION | EXCAVATION END AREA (S.F.) | EMBANKMENT END AREA (S.F.) | | | |
| 812+00.00 | 0.64 | 8.08 | | | |
| 812+50.00 | 55.33 | 65.95 | | | |
| 813+00.00 | 93.46 | 59.23 | | | |
| 813+50.00 | 113.60 | 81.37 | | | |
| 814+00.00 | 209.11 | 50.02 | | | |
| | | | | | |









NOTES

EXCESS MATERIAL GENERATED FROM
 EMBANKMENT EXCAVATION SHALL BE HAULED
 OFF SITE OR TO AREAS DESIGNATED BY THE
 AIRPORT.

NCMT

License No. 184-000613 CONSULTANTS

> FOR BID SET JUNE 16, 2023

MIDFIELD INTERSECTION RECONFIGURATION

WINEH CONTROL OF THE CONTROL OF THE

UNIVERSITY OF ILLINOIS
WILLARD AIRPORT

SAVOY, ILLINOIS

CHAMPAIGN

URBANA

MARK DATE DESCRIPTION

AIP PROJ. NO. 3-17-0016-XXX UN062

IL. PROJ. NO. CMI-4793

CMT PROJECT NO: 20005901

CAD DWG FILE: 20005901-CS700.DWG

DESIGNED BY: HCH

CHECKED BY:

APPROVED BY:

COPYRIGHT:

DRAWN BY:

COPYRIGHT:

CROSS SECTIONS 7

MJD

CS707 SHEET 67 OF

67

tth: K:\ChampaignAp\20005901-00_Mix ste: Friday_May_12_2023_12-10-29_PM