



LEGEND US ROUTE 20 (LAKE STREET)

1. PROPOSED P.C.C. PAVEMENT 9 3/4" (JOINTED)
2. PROPOSED AGGREGATE SUBGRADE 12"
3. PROPOSED COMB. CONC. CURB & GUTTER, TYPE B-6.12
4. PROPOSED COMB. CONC. CURB & GUTTER, TYPE B-6.24
5. PROPOSED P.C.C. SIDEWALK 5 INCH
6. PROPOSED BRICK PAVER
7. PROPOSED TOPSOIL FURNISH AND PLACE, 24"
8. PROPOSED BOX CULVERT
9. PROPOSED LONGITUDINAL CONSTRUCTION JOINT WITH #8 TIE BARS, DEFORMED, 24" LONG, EPOXY COATED, 24" O.C. DRILL & GROUT.
10. PROPOSED LONGITUDINAL SAWED JOINT WITH #6 TIEBARS, 30" LONG, EPOXY COATED, 30" O.C.
11. PROPOSED 6" TIE BARS, 24" LONG, EPOXY COATED, DEFORMED, 24" O.C.
12. PROPOSED 1.5" BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE MIX "D"
13. PROPOSED 0.75" POLYMERIZED LEVELING BINDER COURSE (MACHINE METHOD), SUPERPAVE IL-4.75, N50
14. PROPOSED BITUMINOUS BASE COURSE, 8" SUPERPAVE
15. PROPOSED BITUMINOUS BASE COURSE, 9" SUPERPAVE
16. PROPOSED BITUMINOUS BASE COURSE, 10 1/4" SUPERPAVE
17. PROPOSED SUB-BASE GRANULAR MATERIAL, TYPE B 4"
18. PROPOSED TOP SOIL FURNISH AND PLACE, 4"
19. PROPOSED SEEDING, CLASS 2A
20. PROPOSED COMB. CONC. CURB & GUTTER, TYPE B-6.24 (SPECIAL)
21. PROPOSED CONC. MEDIAN TYPE SB-6.12

* WHEN DISTANCE BETWEEN BACK OF CURB TO SIDEWALK, > 3 FEET, SEEDING CLASS 2A IS USED OR ELSE, BRICK PAVERS ARE USED.

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
 TYPICAL CROSS SECTIONS
 US ROUTE 20 (LAKE STREET)

SCALE: NONE
 DATE: 03/01/05
 DRAWN BY: ALS
 CHECKED BY: JAR