Right-of-way markers will be erected with the back face of the marker on the right-of-way line unless the new right-of-way line has been surveyed and pinned, in which instance the right-of-way markers will be erected 300 mm (12 inches) inside the new right-of-way line.

The Contractor shall be responsible for protecting utility property during construction operations as outlined in Article 107.31 of the Standard Specifications. A minimum of 48 hours advance notice is required for non-emergency work. The JULIE number is 800-892-0123. The following listed utilities located within the project limits or immediately adjacent to the project construction limits are members of JULIE:

Mediacom Verizon Commonwealth Edison Co.

Nicor Gas Co.

McLeod USA

Following are the known utilities located within the project limits or immediately adjacent to the project construction limits which are not members of JULIE and should be notified individually by the contractor:

Mr. Dennis Schultz IDOT – District 2 819 Depot Ave. Dixon, IL 61021

CADD data will be available to Contractors and Consultants working on this project. This information will be provided upon request as MicroStation CADD files and Geopak coordinate geometry files ONLY. If data is required in other formats it will be your responsibility to make these conversions. If any discrepancy or inconsistency arises between the electronic data and the information on the hard copy, the information on the hard copy should be used. Contact the District's Project Engineer to request these files.

Salvage existing delineators within the project limits and place one at the end of each end of the new box culvert.

The Resident Engineer, prior to closing the road and after the project is finished, shall contact the corresponding Township and the JoDaviess County Engineer to video tape the following roads: From IL 78, west on Canyon Road 2 miles, northeast of Fielder Road 3.9 miles to Warren, then east on Galena Ave. 0.2 mile, then north on Bellevue Ave. for 0.2 mile to intersection with IL 78.

The Contractor shall only use state routes and marked detour routes for hauling materials and equipment. There will be no exceptions unless written permission is given from a jurisdiction, Township or County. A record of this authorization shall be given to the Resident Engineer.

The Contractor will not be allowed to set up a yard or field office on State property without written permission from the Department.

Where section or sub-section monuments are encountered, the Engineer shall be notified before such monuments are removed. The Contractor shall protect and carefully preserve all monuments or otherwise reference their location. The Contractor will be responsible for having an authorized surveyor re-establish any section or sub-section monuments destroyed by his operations.

Only those trees designated by the Engineer shall be removed.

The Contractor shall protect all remaining trees from damage due to his operations.

The following quantities have been estimated for the good neighbor policy as needed:

40600810 Bituminous Surface Course Mix C, Class 1, Type 1 N50 - 200 Tons

48101200 Aggregate Shoulders, Type B - 208 Tons

40600200 Bituminous Materials (Price Cost) - 2.62 Tons

The 24" diameter riveted drain tube located under Fiedler Road 1.2 miles north of Canyon Road shall be replaced prior to any work being done on IL 78. Removal and disposal of existing pipe and headwall, site preparation and grading, trench backfill, and 3" bituminous patch shall all be included in the price for PIPE CULVERTS, CLASS D, TYPE 1, 24". Ditches in the immediate area of the end sections shall be graded and shaped to drain, seeded, and shall be included within the above listed pay item.

Delineators shall be installed as shown in Standard 635001, except that the post shall be rotated 180° and only metal-backed delineators shall be permitted.

Delineators shall be placed at the ends of approach guardrail terminal sections, and at each headwall or end section of AR Culverts. This work will be paid for at the contract unit price each for DELINEATORS.

The following Mixture Requirements are applicable for this project:

Mixture Uses(s):		
PG:		
RAP%: (Max)		
Design Air Voids		
Mixture Composition		
(Gradation Mixture)		
Friction Aggregate		
20 Year ESAL		

Completion Date: September 1, 2005. The project shall have pavement, shoulders and striping completed prior to opening to traffic. The Contractor will be allowed 15 additional working days after September 1, 2005 to complete earthwork, rip rap, seeding, etc.

The existing culvert can not be filled, but the floor can stay in place after remainder of culvert has been removed.

Permanent Survey Marker, Type II shall be installed prior to construction beginning on the project. Markers shall be cast-in-place.

A patching detail has been included in the plans. Care shall be taken not to disturb the existing outside ten feet of the patch subgrade. If necessary, the Contractor shall make provisions to make the final saw cut immediately prior to preparing the patch. Any additional length of patch required to reach undisturbed areas shall be at the Contractor's expense.

Program #5 (Arch. Size) Enlarge 200% Enlarge 107%