

FLUSH PAVED MEDIAN: TWO-WAY LEFT TURN LANE WITH ONE-WAY LEFT TURN LANE AT SIGNALIZED INTERSECTION

TYPICAL PAVEMENT MARKING LEGEND

(Note: This is a District Standard Legend. Some elements may not apply to specific project.)

- 1 100(4) Solid (Yellow)
- 2 100(4) Solid (White)
- 3) 2-150(6) Crosswalk @ 2m (6'-6")min C.-C. (White) 2-200(8) Crosswalk @ 2m (6'-6")min C.-C. (White) (When traffic signals are present.)
- 4 150(6) Skip-Dash (White)

(See Special Note 1)

- (5) 200(8) Solid (White)
- 300(12) Diagonal (White) (IterO6 is shown on Std. 780001)
- (See Std. 780001 and Special Notes 2 & 3)
- 9 100(4) Skip-Dash (Yellow)

100(4) Double Solid (Yellow)

See Table A

- (See Special Note 1)
- 300(12) Diagonal (Yellow) (See Table A)

280(11) C.-C.

SPECIAL NOTES

- 1. Skip-Dash markings will be centered between both ends of city blocks and shall be placed in alignment transversly across the pavement.
- 2. The following shall apply to arrows located in one-way left turn lanes:
- A. A minimum of two (2) arrows is required.
- B. The maximum spacing between arrows is 24 m (80').
- C. Arrows shall be evenly spaced if three (3) or more are required.
- 3. The following shall apply to arrow pairs located in two-way left turn lanes;
 - A. A minimum of two (2) arrow pairs is required. B. The maximum spacing between arrow pairs
 - is 61 m (200'). Arrow pairs shall be evenly spaced if three (3)
 - or more are required. The spacing between Bi Directional Left Turn
 - Arrows is 10 m (33').

GENERAL NOTES

- 1. Refer to State Standard 780001 for additional Pavement Markings including letters & arrows.
- See Plans for Pavement Markings adjacent to curbed islands and medians, and through lane reductions.

All dimensions are in millimeters (inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD TYPICAL PAVEMENT MARKINGS SHEET 1 OF 2

CADD STANDARD 780001-D4 SCALE: NOT DRAWN TO SCALE

DRAWN BY CADD CHECKED BY 780001-D4 (1)