

		LT/RT	TYPE OF ENTRANCE	STREET NAME	EXIST. MATERIAL	LENGTH AT E.O.P.	WIDTH EOP TO BACK	PROP. HMA THICKNESS	HMA SURF REM, BUTT JOINT	INCIDENTAL BIT. SURF.	PREP. OF BASE	PROP. AGG. SURF. THICKNESS	AGG. SURF. COURSE, TYPE B
Location	STATION					FT	FT	INCHES	SQ YD	TON	SQ YD	INCHES	TON
	817+00	RT	SR	ALLEY	O&C	32	10	1.5	24.4	2.1			
	818+78	RT	SR	POPLAR ST	BIT	35	10	1.5	27.8	2.3			
	824+54	LT	PE		AGG	40	8	3.5		5.6	28.4	1	0.7
	824+55	RT	SR	ELM ST	O&C	48	10	1.5	42.2	3.5			1.1
	825+90	RT	PE		AGG	32	8	3.5		4.2	21.3	1	0.4
	825+42	LT	PE		AGG	32	8	3.5		4.2	21.3	1	0.4
	826+71	LT	PE		AGG	32	8	3.5		4.2	21.3	1	0.4
	827+22	RT	PE		AGG	32	8	3.5		4.2	21.3	1	0.4
	828+61	RT	PE		AGG	37	8	3.5		5.1	25.8	1	0.6
	829+17	RT	PE		AGG	32	8	3.5		4.2	21.3	1	0.4
	833+60	RT	PE		AGG	38	8	3.5		5.2	26.7	1	0.7
	830+96	RT	PE		AGG	32	8	3.5		4.2	21.3	1	0.4
	850+30	LT	SR	SECTION LINE RD	BIT	50	10	1.5	44.4	3.7			
	850+30	RT	SR	SECTION LINE RD	BIT	71	10	1.5	67.8	5.7			
	853+00	LT	SR	RANGE LINE RD	BIT	52	10	1.5	46.7	3.9			
	853+00	RT	SR	RANGE LINE RD	BIT	70	10	1.5	66.7	5.6			
	933+84	LT	SR		BIT	44	10	1.5	36.7	3.1			
	933+84	RT	SR		BIT	55	10	1.5	50.0	4.2			
	935+15	RT	PE		AGG	40	8	3.5		5.6	28.4	1	0.7
	942+00	LT	SR		BIT	100	10	1.5	100.0	8.4			
	943+19	RT	PE		AGG	37	8	3.5		5.1	25.8	1	0.6
	947+05	LT	CE		AGG	36	10	8		4.9	24.9	1	0.6
	988+26	LT	SR		BIT	52	10	1.5	46.7	3.9			
	1052+34	LT	SR		BIT	50	10	1.5	44.4	3.7			
	1052+34	RT	SR		BIT	41	10	1.5	34.4	2.9			
	1121+92	RT	PE		AGG	36	8	3.5		4.9	24.9	1	0.6
	1125+32	LT	SR	SECTION LINE RD	BIT	92	10	1.5	91.1	7.7			
	1125+32	RT	SR	SECTION LINE RD	BIT	75	10	1.5	72.2	6.1			
	1137+45	LT	SR		BIT	58	10	1.5	53.3	4.5			
	1137+45	RT	SR		BIT	55	10	1.5	50.0	4.2			
<b>Total</b>									<b>874</b>	<b>135</b>	<b>313</b>		<b>8</b>

RAISED REFLECTIVE PAVEMENT MARKER SCHEDULE					
Location	Sta to Sta		Length	REMOVE	REPLACE
			FT	EACH	EACH
IL 10	815+90	868+68	5,277.9	66	66
	865+69	964+99	9,929.6	124	124
	965+11	1171+30	20,619.0	258	258
<b>Total IL 10</b>				<b>448</b>	<b>448</b>