



SCHEDULE OF QUANTITIES			TOTAL QUANTITIES	
CODE NO	ITEM	UNIT		
81012500	CONDUIT IN TRENCH, 1 1/2" DIA., PVC	FOOT	200	200
81100500	CONDUIT ATTACHED TO STRUCTURE, 1 1/2" DIA., GALVANIZED STEEL	FOOT	65	65
81900200	TRENCH AND BACKFILL FOR ELECTRICAL WORK	FOOT	200	200
87301225	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	330	330
88040030	SIGNAL HEAD, POLYCARBONATE, LED, 1-FACE, 1-SECTION, POST MOUNTED	EACH	4	4
89502400	REMOVE EXISTING FLASHING BEACON INSTALLATION COMPLETE	EACH	4	4
X0324397	RELOCATE ELECTRIC SERVICE	EACH	1	1

ELECTRICAL GENERAL NOTES

- ALL VEHICLE SIGNAL HEADS SHALL HAVE 12" SECTIONS. MOUNTING HARDWARE SHALL BE UNPAINTED ALUMINUM. ALL BOLTS, SCREWS, NUTS AND WASHERS SHALL BE STAINLESS STEEL. ANTI-SEIZE PASTE COMPOUND SHALL BE USED ON ALL MOUNTING HARDWARE FIELD CONNECTIONS.
- ALL TRAFFIC SIGNAL CABLES SHALL BE #14 AWG STRANDED COPPER UNLESS OTHERWISE SPECIFIED. TERMINAL ENDS SHALL HAVE CRIMPED-ON RING TONGUE CONNECTORS.
- ABANDONED UNDERGROUND CONDUIT (ABI) ENDS SHALL BE REMOVED DOWN MINIMUM 12" BELOW THE PROPOSED GRADE.

