



- ELECTRICAL GENERAL NOTES**
1. ALL VEHICLE SIGNAL HEADS SHALL HAVE 12" SECTIONS. MOUNTING HARDWARE SHALL BE UNPAINTED ALUMINUM. ALL BOLTS, SCREWS, NUTS AND WASHERS SHALL BE STAINLESS STEEL. ANTI-SEIZE PASTE COMPOUND SHALL BE USED ON ALL MOUNTING HARDWARE FIELD CONNECTIONS.
  2. ALL TRAFFIC SIGNAL CABLES SHALL BE #14 AWG STRANDED COPPER UNLESS OTHERWISE SPECIFIED. TERMINAL ENDS SHALL HAVE CRIMPED-ON RING TONGUE CONNECTORS.
  3. ABANDONED UNDERGROUND CONDUIT (ABI) ENDS SHALL BE REMOVED DOWN MINIMUM 12" BELOW THE PROPOSED GRADE.



FILE NAME =	USER NAME = korlssal	DESIGNED -	REVISD -
ct:\pwork\p\1001\KARLASAL\0157010\top	n01902na.dgn	DRAWN -	REVISD -
	PLOT SCALE = 20.0000' / IN.	CHECKED -	REVISD -
	PLOT DATE = 8/18/2009	DATE -	REVISD -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**FLASHING BEACONS AT IL 158 AND MINE HAUL ROAD**

SCALE: \_\_\_\_\_ SHEET NO. \_\_\_\_ OF \_\_\_\_ SHEETS STA. \_\_\_\_\_ TO STA. \_\_\_\_\_

F.A.D. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
809	133.134BS-5, 135BS-6	ST. CLAIR	762	294B

CONTRACT NO. 7647

FED. ROAD DIST. NO. \_\_\_\_\_ ILLINOIS FED. AID PROJECT