

ROUTE		SECTION	COUNTY	SHEET	
MKD.	FAP	103 RS-3	PEORIA	TOTAL	NO.
IL 90	661			21	3

D-94-068-02
CONTRACT # 68259

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

Mixture Use(s):	POLYMERIZED SURFACE CSE	MAINLINE LEVELING BINDER	HOT-MIX ASPHALT SHOULDERS	PATCHING
AC/PG:	SBS OR SBR PG 70-22	SBS OR SBR PG 70-22	PG 64-22	PG 64-22
RAP % (Max.):**	0%	0%	30%	25%
Design Air Voids:	4.2% @ N=50	4.0% @ N=50	3.0% @ N=30	4.2% @ N=50
Mixture Composition: (Gradation Mixture)	IL-12.5 OR IL-9.5	IL 4.75	IL9.5L	IL 19.0
Friction Aggregate:	MIXTURE D	N/A	MIXTURE C	N/A

** If the RAP is selected, the asphalt cement grade may need to be adjusted; this will be determined by the Engineer

PAVING SURFACE COURSE

Continuous paving operations on the main roadway shall be maintained at all times during the construction of the bituminous surface. No interruptions for side roads, entrances, turn lanes, etc. will be allowed

COMMITMENTS

No commitments have been made for this project.

ILLINOIS DEPARTMENT OF TRANSPORTATION
**GENERAL NOTES
COMMITMENTS AND
JOB SPECIFIC
NOTES**