1	TITLE SHEET
2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
3	SUMMARY OF QUANTITIES
4-5	TYPICAL SECTIONS
6-15	ROADWAY AND PAVEMENT MARKING PLANS
16-19	DETECTOR LOOP REPLACEMENT DETAILS
20	DETAILS FOR FRAME AND LIDS ADJUSTMENT WITH MILLING (BD-8)
21	PAVEMENT PATCHING FOR HOT-MIX ASPHALT SURFACED PAVEMENT (BD-22)
22	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT (80-24)
23	BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS (BD-32)
24	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS (TC-10)
25	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT) (TC-11)
26	DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)
27	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC (TC-14)
28	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC-16)
29	ARTERIAL ROAD INFORMATION SIGN (TC-22)
30	DRIVEWAY ENTRANCE SIGNING (TC-26)
31	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING (TS-07)

INDEX OF SHEETS

STANDARDS

424001 -07 PERPENDICULAR CURB RAMPS FOR SIDEWALKS

424006 - 01	DIAGONAL CURB RAMPS FOR SIDEWALKS
424011 - 01	CORNER PARALLEL CURB RAMPS FOR SIDEWALKS
424016 - 01	MID-BLOCK CURB RAMPS FOR SIDEWALKS
424021 - 02	DEPRESSED CORMER FOR SIDEWALKS
424031 - 01	MEDIAN PEDESTRIAN CROSSINGS
442201 - 03	CLASS C AND D PATCHES
482011 - 03	HMA SHLD. STRIPS/SHLDS. WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS
604001 ~ 03	FRAME AND LIDS TYPE 1
604091 - 02	FRAME AND GRATE TYPE 24
606001 - <i>05</i>	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
635006 - 03	REFLECTOR AND TERMINAL MARKER PLACEMENT
701006 -05	OFF-RD OPERATIONS, 2L, 2W, 15' TO 24" FROM PAVEMENT EDGE
701011 - 04	OFF ROAD MOVING OPERATIONS. 2L, 2W, DAY ONLY
701301 - 04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311 - 03	LANE CLOSURE, 2L, 2W, MOVING OPERATIONS-DAY ONLY
701426 -06	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPER., FOR SPEEDS > 45 MPH
701501 - 06	URBAN, LANE CLOSURE, 2L, 2W, UNDIVIDED
701606 - 09	URBAN LANE CLOSURE, MULTILANE 2W WITH MOUNTABLE MEDIAN
701701-09	URBAN LANE CLOSURE MULTILANE INTERSECTION
701901 - <i>03</i>	TRAFFIC CONTROL DEVICES
780001-04	TYPICAL PAVEMENT MARKINGS
701306-03	
701336-06	
·	

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 1-800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGES OF ROUND LAKE, FOX LAKE, ROUND LAKE PARK, AND HAINESVILLE.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE

FOR WORK OUTSIDE THE LIMITS OF BRIDGE APPROACH PAVEMENT, ALL REFERENCES IN THE HIGHWAY STANDARDS AND STANDARD SPECIFICATIONS FOR REINFORCEMENT, DOWEL BARS, AND TIE BARS IN PAVEMENT, SHOULDERS, CURB, GUTTER, COMBINATION CURB AND GUTTER AND MEDIAN, AND CHAIR SUPPORTS FOR CRC PAVEMENT, SHALL BE EPOXY COATED, UNLESS NOTED ON THE PLAN.

WHEN THE MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED I 1/2 INCHES (40MM) WHERE THE SPEED LIMIT IS 40 MPH (80 KM/HR) OR LESS AND I INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80KM/HR), WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

UNLESS OTHER CONDITIONS WARRANT EXTENDED LANE CLOSURES AS DETERMINED AND APPROVED IN WRITING BY THE ENGINEER OR AS PROVIDED IN THE CONTRACT SPECIFICATIONS, OVERNIGHT CLOSURES SHALL NOT BE ALLOWED FOR REHABILITATION PROJE MILLING OPERATIONS AND CLASS D PATCHING.

ALL PAVEMENT MARKING AND RAISED REFLECTIVE PAVEMENT MARKERS OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS AND ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAYEMENT MARKING LINES AND RAISED REFLECTIVE PAVEMENT MARKERS IN ORDER THAT THESE LOCATIONS CAN BE REESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER

DRAINAGE ADJUSTMENT OR RECONSTRUCTION LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

LOCATION OF COMBINATION CONCRETE CURB AND GUTTER REPLACEMENT WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF

INDEX

SCALE:

THE ENGINEER SHALL CONTACT THE AREA TRAFFIC FIELD ENGINEER, WALLY CZARNY AT (847) 715-8419 DEBBIE-HANLON-AT-(847)-438-2300 A MINIMUM OF TWO (2) WEEKS PRIOR TO PLACEMENTOF PERMANENT PAVEMENT MARKINGS.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THE PROJECT.

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT)" SHOWN ON THE PLANS.

PAVEMENT MARKING TAPE, TYPE III SHALL BE USED FOR SHORT TERM PAVEMENT MARKINGS ON FINAL SURFACES. THE COST OF THE PAVEMENT MARKING TAPE, TYPE III AND ITS REMOVAL SHALL BE INCLUDED IN THE COST OF SHORT TERM PAVEMENT MARKING,

THE CONTRACTOR SHALL CAREFULLY REMOVE, STORE, AND REUSE BRICK PAVERS WHERE APPLICABLE, ANY EXTRA BRICK PAVERS ARE TO BE SALVAGED AND DELIVERED TO THE LOCAL MUNICIPALITY. THIS WORK SHALL BE INCLUDED IN THE COST OF REMOVE AND REINSTALL BRICK PAVERS.

					_
FILE NAME :	USER NAME : mrempfer	DESIGNED -	RG	REVISED -	
1:\6718\6718.85 - 3P Resurfacing Projects	Atlana 168458 1CADD/CADD Shadta 160458_Con No	· Orașin -	RG	REVISED -	
	PLOT SCALE : 188.0000 ' / In.	CHECKED -	MGR	REVISED -	
	PLOT DATE : 5/27/2014	OATE -	5/27/2014	REVISED -	_
	10.6718\6718.85 - 3P Resurfacing Frajects		1:\G718\G718\6718\65 - 3P Resurfacing Projects\Plans\68\58\CADD\CADD\Sheets\60\58.Gen Het@RAHN PLOT SCALE = 100.8880 '/ in. CHECKED	11/6718/6718.85 - 3P Resurfacing Projects/Plans/68/58/CADD/CADD Sheets/GOMS8.Com MatGRAJEN - RG PLOT SCALE : 1898.8888 '/ In. CHECKED - MGR	1/16/18/18/25 - 3P Resurfacing Projects/Plans/69/18/16/20/07/07/00 Sheets/60/58/00 Hat GRAJEN - RG REVISED - PLOT SCALE : 189/08/08 // In. CHECKED - MGR REVISED -

STATE	OF	ILLINOIS
DEPARTMENT	OF T	TRANSPORTATION

			$ \kappa$	<u>ev_</u>	
IL ROUTE 134 (MAIN STREET)	OF STATE STANDARDS, MIL. 0186 36-RS-5 LAKE 31 2 CONTRACT NO. 60N58				
INDEX OF SHEETS, LIST OF STATE STANDARDS, AND GENERAL NOTES		36-RS-5	LAKE	31	2
			CONTRACT	NO. F	50N58
SHEET NO. OF SHEETS STA. TO STA.		ILLINOIS FED. A	D PROJECT		