

DRAINAGE STRUCTURE SCHEDULE

NO.	LOCATION		TYPE	RIM ELEV	INVERT ELEVATION			
	STATION	OFFSET			(IN)	(IN)	(IN)	(OUT)
300	505+98	38.0 RT	CB TC T24F&G	924.78				921.58
301	505+98	00.0 RT	MAN TA 4 DIA T1F CL	925.85	921.42			921.42
302	507+18	38.0 RT	CB TC T24F&G	924.17				920.97
303	507+18	00.0 RT	MAN TA 4 DIA T24F&G	924.84	920.84	920.81		920.81
304	508+38	38.0 RT	CB TC T24F&G	923.56				920.36
305	508+38	00.0 RT	MAN TA 4 DIA T1F CL	924.25	920.23	920.20		920.20
306	509+58	38.0 RT	CB TC T24F&G	922.95				919.75
307	509+58	00.0 RT	MAN TA 4 DIA T1F CL	923.63	919.62	919.59		919.59
308	510+78	38.0 RT	CB TC T24F&G	922.34				918.88
309	510+78	00.0 RT	MAN TA 4 DIA T1F CL	923.53	919.01	918.72		918.72
310	511+98	38.0 RT	CB TC T24F&G	921.73				918.28
311	511+98	00.0 RT	MAN TA 4 DIA T1F CL	922.92	918.14	918.12		918.12
312	513+18	38.0 RT	CB TC T24F&G	921.12				917.92
313	513+18	00.0 RT	MAN TA 4 DIA T1F CL	922.31	917.54	917.51		917.51
314	514+38	38.0 RT	CB TC T24F&G	920.51				917.06
315	514+38	00.0 RT	MAN TA 5 DIA T1F CL	921.70	916.93	916.90		916.90
316	515+58	38.0 RT	CB TC T24F&G	919.90				916.54
317	515+58	00.0 RT	MAN TA 5 DIA T1F CL	921.09	916.36	916.37		916.36
318	516+78	38.0 RT	CB TC T24F&G	919.29				915.92
319	516+78	00.0 RT	MAN TA 5 DIA T1F CL	920.48	915.78	915.75		915.75
320	517+63.93	38.0 RT	CB TC T24F&G	918.85				915.39
321	517+63.93	00.0 RT	MAN TA 5 DIA T1F CL	919.59	915.18	915.22		915.18
322	518+70	00.0 RT	MAN TA 5 DIA T1F CL	919.25	914.77			914.74
323	518+70	73.0 RT	PRCF END S EL EQRS 18	-				914.48

DRAINAGE SEWER SCHEDULE

SEWER NO.	TYPE	SIZE (INCH)	LENGTH (FEET)	SLOPE (%)
301	STORM SEW CL A 2	12	116.0	0.50%
302	STORM SEW CL A 1	12	35.0	0.46%
303	STORM SEW CL A 1	12	116.0	0.50%
304	STORM SEW CL A 1	12	35.0	0.46%
305	STORM SEW CL A 1	12	116.0	0.50%
306	STORM SEW CL A 1	12	35.0	0.46%
307	STORM SEW CL A 2	12	116.0	0.50%
308	STORM SEW CL A 1	12	35.0	0.46%
309	STORM SEW CL A 2	15	116.0	0.50%
310	STORM SEW CL A 1	12	35.0	0.46%
311	STORM SEW CL A 2	15	116.0	0.50%
312	STORM SEW CL A 1	12	35.0	1.17%
313	STORM SEW CL A 2	15	115.5	0.50%
314	STORM SEW CL A 1	12	34.5	0.46%
315	SS CL A 2 EQRS 18	23X14	115.0	0.47%
316	STORM SEW CL A 1	12	34.5	0.50%
317	SS CL A 2 EQRS 18	23X14	115.0	0.50%
318	STORM SEW CL A 1	12	34.5	0.50%
319	SS CL A 2 EQRS 18	23X14	80.9	0.70%
320	STORM SEW CL A 1	12	34.5	0.49%
321	SS CL A 2 EQRS 18	23X14	101.1	0.40%
322	SS CL A 2 EQRS 18	23X14	64.5	0.40%