

RESURFACING SCHEDULE												
LOCATION STA TO STA			LENGTH	WIDTH	AREA	HMA SC "D" N50 1 1/2"	LEV BIND (M.M.) N50 3/4"	BIT MATLS PR CT	MIX CR JTS FLANGEWYS	HMA SURF REM 2 1/4"	LEV BIND (H.M.) N50	TEMP RAMP
			FEET	FEET	SQ YD	TON	TON	POUND	TON	SQ YD	TON	SQ YD
U.S. 24/ U.S. 45												
STATION 4+81.40 - - AT JOINT BETWEEN CONCRETE PAVEMENT AND HMA PAVEMENT EAST OF U.S. 24												
4+81.40	TO	5+55.00	73.60	38	310.8	26.1	13.1	209.8	0.1	310.8	0.2	31.7
5+55.00	TO	7+44.00	189.00	38 VAR. TO 26	672.0	56.4	28.2	453.6	0.2	672.0	0.3	
7+44.00	TO	9+29.00	185.00	26	534.4	44.9	22.4	360.8	0.2	534.4	0.3	
9+29.00	TO	10+55.00	126.00	26 VAR. TO 24	350.0	29.4	14.7	236.3	0.1	350.0	0.2	
10+55.00	TO	52+00.00	4145.00	24	11053.3	928.5	464.2	7461.0	3.3	11053.3	5.5	80.0
52+00.00	TO	53+00.00	100.00	24 VAR. TO 32	311.1	26.1	13.1	210.0	0.1	311.1	0.2	
53+00.00	TO	55+96.58	296.58	32	1054.5	88.6	44.3	711.8	0.3	1054.5	0.5	
55+96.58	TO	58+36.59	240.01	32 VAR. TO 44	1013.4	85.1	42.6	684.0	0.3	1013.4	0.5	
58+36.59	TO	58+75.10	38.51	44	188.3	15.8	7.9	127.1	0.1	188.3	0.1	86.7
OMISSION - STA. 58+75.10 TO STA. 63+49.50												
STATION EQUATION 60+72.27 BK = 60+79.68 AH												
63+49.50	TO	97+01.00	3351.50	24	8937.3	750.7	375.4	6032.7	2.7	8937.3	4.5	60.0
97+01.00	TO	99+81.00	280.00	24 VAR. TO 38	964.4	81.0	40.5	651.0	0.3	964.4	0.5	
99+81.00	TO	102+10.00	229.00	38	966.9	81.2	40.6	652.7	0.3	966.9	0.5	
102+10.00	TO	106+00.00	390.00	38 VAR. TO 24	1343.3	112.8	56.4	906.8	0.4	1343.3	0.7	
106+00.00	TO	107+68.00	168.00	24	448.0	37.6	18.8	302.4	0.1	448.0	0.2	40.0
STA. 101+31.10 (U.S. 24/U.S. 45) = 0+00 (U.S. 45 TO NORTH)												
U.S. 45 (TO NORTH)												
0+26.00	TO	1+38.00	112.00	226 VAR. TO 26.00	795.0	66.8	33.4	536.6	0.2	795.0	0.4	21.5
TOTALS					28,943	2,431	1,216	19,536	9	28,943	14	320

SIDEWALK SCHEDULE FOR NEW HANDICAP RAMPS					
LOCATION	PC CONC SIDEWALK 4"	COMB CC&G B6.24	DETECTABLE WARNINGS	SIDEWALK REM	COMB CURB GUTTER REM
	SQ FT	FOOT	SQ FT	SQ FT	FOOT
S. THOMAS ST. SW	100	20	10	80	20
TOTALS	100	20	10	80	20