TOTAL SHEETS: 83 UN053

CONSTRUCTION PLANS FOR WILLARD AIRPORT


UNIVERSITY OF ILLINOIS SAVOY, ILLINOIS

IL. PROJ. NO. CMI-4347 **AIP PROJ. NO. 3-17-0016-XX**


BASE BID - REALIGN AND WIDEN TAXIWAY C

ADDITIVE ALTERNATE - REHABILITATE T-HANGAR PAVEMENTS

JUNE 27, 2014



LOCATION MAP



SITE PLAN

CALL J.U.L.I.E. BEFORE EXCAVATING

UNIVERSITY OF ILLINOIS - WILLARD AIRPORT

RANGE: R 8 E COUNTY: CHAMPAIGN SECTION 2, 3, 10 AND 1

TAXIWAY C

DESIGN GROUP - GROUP IV WINGSPAN - UP TO BUT NOT INCLUDING 171 FT. DESIGN APPROACH CATEGORY - C TAXIWAY DESIGN GROUP 5

PAVEMENT STRUCTURE DESIGN DATA

GROSS WEIGHT - 60,000 LBS. DUAL WHEEL GEAR



GROUND CONTROL RADIO FREQUENCY - 121.8 ATIS FREQUENCY - 124.85

APPROXIMATE MAXIMUM HEIGHT OF EQUIPMENT ABOVE GROUND IS 25 FT.



CRAWFORD MURPHY & TILLY, INC. CONSULTING ENGINEERS

DATE 7-10-201

CMT JOB NUMBER: 13059-02-00

SUMMARY OF QUANTITIES			
ITEM NO.	DESCRIPTION	UNIT	QUANTIT
	BASE BID		
AR108065	RGL CABLE	LF	4,450
AR108066	REIL CABLE	LF	1,040
AR108158	1/C #8 5KV UG CABLE IN UD	LF	14,175
AR108258	2/C #8 5KV UG CABLE IN UD	LF	370
AR109210	VAULT MODIFICATIONS	EA	1
AR110504 AR110550	4-WAY CONCRETE ENCASED DUCT	LF	160
AR110550	4" DIRECTIONAL BORE	LF LF	253 2,450
AR110900	REMOVE DUCT	LF	280
AR110903	REMOVE CABLE MARKER	EA	9
AR125415	MITL - BASE MOUNTED	EA	89
AR125443	TAXI GUIDANCE SIGN, 3 CHARACTER	EA	2
AR125444	TAXI GUIDANCE SIGN, 4 CHARACTER	EΑ	6
AR125445	TAXI GUIDANCE SIGN, 5 CHARACTER	EA	4
AR125449	TAXI GUIDANCE SIGN, 9 CHARACTER	EA	1
AR125565	SPLICE CAN	EA	10
AR125740	RUNWAY GUARD LIGHT	EA	12
AR125901	REMOVE STAKE MOUNTED LIGHT	EA	87
AR125902 AR125904	REMOVE BASE MOUNTED LIGHT REMOVE TAXI GUIDANCE SIGN	EA EA	109 31
AR125904 AR125921	REPLACE STAKE MOUNTED LIGHT	EA	13
AR125921 AR125922	REPLACE BASE MOUNTED LIGHT	EA	3
AR125962	RELOCATE BASE MOUNTED LIGHT	EA	1
AR125975	RELOCATE RUNWAY GUARD LIGHT	EA	4
AR800242	REPLACE SIGN FACE	EA	10
AR150510	ENGINEER'S FIELD OFFICE	LS	1
AR152410	UNCLASSIFIED EXCAVATION	CY	12,500
AR152481	SHOULDER ADJUSTMENT	CY	2,100
AR156500	TEMPORARY EROSION CONTROL	LS	1
AR201670	CRACK CONTROL FABRIC	SY	1,520
AR209610	CRUSHED AGG. BASE COURSE - 10"	SY	19,870
AR401610	BITUMINOUS SURFACE COURSE BITUMINOUS SURFACE TEST SECTION	TON	5,400
AR401630 AR401650	BITUMINOUS SURFACE TEST SECTION BITUMINOUS PAVEMENT MILLING	EA SY	1 760
AR401921	REMOVE PAVEMENT	SY	9.800
AR403610	BITUMINOUS BASE COURSE	TON	10,970
AR403630	BITUMINOUS BASE TESTE SECTION	EA	1
AR602510	BITUMINOUS PRIME COAT	GAL	9,950
AR603510	BITUMINOUS TACK COAT	GAL	14,065
AR620520	PAVEMENT MARKING-WATERBORNE	SF	19,300
AR620525	PAVEMENT MARKING - BLACK BORDER	SF	9,200
AR620555	PREFORMED THERMOPLASTIC	SF	2,938
AR620900	PAVEMENT MARKING REMOVAL	SF	81,022
AR620910	PREFORMED THERMOPLASTIC REMOVAL	SF	1,783
AR625511	SEAL COAT	SY	19,100
AR701512 AR701521	12" RCP, CLASS IV 21" RCP, CLASS IV	LF LF	368 72
AR701900	REMOVE PIPE	LF	320
AR701900 AR705524	4" PERFORATED UNDERDRAIN W/SOCK	LF	5,730
AR705544	4" NON PERFORATED UNDERDRAIN	LF	451
AR705635	UNDERDRAIN COLLECTION STRUCTURE	EA	4
AR705640	UNDERDRAIN CLEANOUT	EA	12
AR705904	REMOVE UNDERDRAIN CLEANOUT	EA	5
AR751410	INLET	EA	3
AR751415	INLET SPECIAL	EA	1
AR751550	MANHOLE 5'	EA	2
AR751900	REMOVE INLET	EA	2
AR752421	PRECAST REINFORCED CONC. FES 21"	EA	1
AR800330	PERMANENT BARRICADES	EA	64
AR901510	SEEDING SODDING	AC SY	13 5 600
			5,600
AR904510	IMIUI (:HING		1′4
AR904510 AR908510	MULCHING KNITTED STRAW MAT	AC SY	13 5 600
AR904510	KNITTED STRAW MAT ROADWAY SIGN	AC SY EA	5,600 1

Sheet List Table		
Sheet Number	Sheet Title	
01	COVER SHEET	
02	INDEX TO SHEETS AND SUMMARY OF QUANTITIES	
03	AIRPORT SITE PLAN	
04	GENERAL NOTES	
05	CONSTRUCTION ACTIVITY PLAN NOTES & DETAILS	
06	CONSTRUCTION ACTIVITY PLAN - INDEX	
07	CONSTRUCTION ACTIVITY PLAN - PHASE 1A	
08	CONSTRUCTION ACTIVITY PLAN - PHASE 1B	
09	CONSTRUCTION ACTIVITY PLAN - PHASE 2	
10	CONSTRUCTION ACTIVITY PLAN - PHASE 3	
11	CONSTRUCTION ACTIVITY PLAN - PHASE 4A	
12	CONSTRUCTION ACTIVITY PLAN - PHASE 4B	
13	CONSTRUCTION ACTIVITY PLAN - PHASE 5	
14	CONSTRUCTION ACTIVITY PLAN - PHASE 6	
15	CONSTRUCTION ACTIVITY PLAN - PHASE 7	
16	CONSTRUCTION ACTIVITY PLAN - PHASE 8	
17	CONSTRUCTION ACTIVITY PLAN - PHASE 9	
18	CONSTRUCTION SAFETY PHASING NOTES	
19	EXISTING PAVEMENT STRUCTURES	
20	EXISTING CONDITIONS AND REMOVALS - LEGEND AND NOTES	
21	EXISTING CONDITIONS AND REMOVALS SHEET 1	
22	22 EXISTING CONDITIONS AND REMOVALS SHEET 2	
23	EXISTING CONDITIONS AND REMOVALS SHEET 3	
24	EXISTING CONDITIONS AND REMOVALS SHEET 4	
25	EXISTING CONDITIONS AND REMOVALS SHEET 5	
26	PROPOSED IMPROVEMENTS	
27	PROPOSED GEOMETRY SHEET 1	
28	PROPOSED GEOMETRY SHEET 2	
29	STAKING PLAN 1	
30	TYPICAL SECTIONS 1	
31 TYPICAL SECTIONS 2		
32	TYPICAL SECTIONS 3	
33	TYPICAL SECTIONS 4	
34	PROPOSED DRAINAGE IMPROVEMENTS SHEET 1	
35	PROPOSED DRAINAGE IMPROVEMENTS SHEET 2	
36	DRAINAGE TABLES	
37	DRAINAGE DETAILS 1	
38	DRAINAGE DETAILS 2	
39	UNDERDRAIN DETAILS	
40	PROPOSED LIGHTING LAYOUT 1	
41	PROPOSED LIGHTING LAYOUT 2	
42	PROPOSED LIGHTING LAYOUT 3	
43	PROPOSED CABLING LAYOUT 1	
44	PROPOSED CABLING LAYOUT 2	
45	PROPOSED CABLING LAYOUT 3	
46	RGL AND SIGN LOCATIONS	
47	ELECTRICAL DETAILS 1	
48	ELECTRICAL DETAILS 2	
49	ELECTRICAL DETAILS 3	
50	ELECTRICAL DETAILS 4	
51	ELECTRICAL DETAILS 5	
52	ELECTRICAL DETAILS 6	

53	ELECTRICAL VAULT PLAN
54	ALCMS GRAPHIC DISPLAY MODIFICATIONS
55	PROPOSED MARKING IMPROVEMENTS 1
56	PROPOSED MARKING IMPROVEMENTS 2
57	PROPOSED MARKING IMPROVEMENTS 3
58	PROPOSED MARKING IMPROVEMENTS 4
59	PROPOSED MARKING IMPROVEMENTS 5
60	TAXIWAY MARKING DETAILS
61	SURFACE PAINTED HOLD POSITION MARKING DETAIL
62	SURFACE PAINTED TAXIWAY MARKING
63	VORTAC CHECKPOINT DETAILS
64	TURFING PLAN AND INDEX TO CROSS SECTIONS SHEET 1
65	TURFING PLANN AND INDEX TO CROSS SECTIONS SHEET
66	TURFING PLAN AND INDEX TO CROSS SECTIONS SHEET 3
67	EROSION CONTROL DETAILS
68	ADDITIVE ALTERNATE - CONSTRUCTION ACTIVITY PLAN
69	ADDITIVE ALTERNATE - EXISTING CONDITIONS
70	ADDITIVE ALTERNATE - PROPOSED IMPROVEMENTS
71	ADDITIVE ALTERNATE - MARKING PLAN
72	ADDITIVE ALTERNATE - TYPICAL SECTIONS 1
73	CROSS SECTION PLAN 01
74	CROSS SECTION PLAN 02
75	CROSS SECTION PLAN 03
76	CROSS SECTION PLAN 04
77	CROSS SECTION PLAN 05
78	CROSS SECTION PLAN 06
79	CROSS SECTION PLAN 07
80	CROSS SECTION PLAN 08
81	CROSS SECTION PLAN 09
82	CROSS SECTION PLAN 10
83	CROSS SECTION PLAN 11

AR908525	KNITTED STRAW MAT		5,600
AR910200	ROADWAY SIGN	EA	1
AR910915	REMOVE ROADWAY SIGN	EA	1
	SUMMARY OF QUANTITIES	S	
ITEM NO.	DESCRIPTION	UNIT	QUANTITY
ADDITIVE ALTERNATE #1			
AS152511	SUBGRADE REPAIR	SY	500
AS201663	SAND MIX CRACK REPAIR	LF	200
AS209600	0 GEOTEXTILE FABRIC SY 5		500
AS209606	CRUSHED AGG. BASE COURSE - 6" SY		500
AS401610	BITUMINOUS SURFACE COURSE TON 1,010		1,010
AS401650	BITUMINOUS PAVEMENT MILLING	SY	8,730

FILE: CMI4347-1305902-GC600.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 6:58 PM

UN053

REVISIONS			
NUMBER	BY	DATE	

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS

BASE BID - REALIGN AND WIDEN TAXIWAY C INDEX TO SHEETS AND SUMMARY OF QUANTITIES

CANT
CRAWFORD, MARPHY & TILLY, NC.
CONSULTING ENGNEERS
License No. 184-000613



DESIGN BY: CBG

DRAWN BY: CMT

CHECKED BY:


APPROVED BY:

DATE: JUNE 27, 2014

JOB No: 13059-02-00

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 02 OF 83 SHEETS



GENERAL NOTES

- ALL RUNWAYS, TAXIWAYS AND APRONS SHALL BE KEPT OPEN TO AIRCRAFT TRAFFIC DURING CONSTRUCTION EXCEPT AS NOTED IN THE CONSTRUCTION ACTIVITY PLANS OR AS DIRECTED BY THE AIRPORT MANAGER.
- ALL CONSTRUCTION TRAFFIC OPERATING ON OR CROSSING ACTIVE RUNWAYS, TAXIWAYS AND APRONS SHALL BE UNDER CONTROL OF A FLAGMAN IN RADIO CONTACT WITH FAA AIR TRAFFIC CONTROL TOWER PERSONNEL AT ALL TIMES. THE CONTRACTOR SHALL PROVIDE HIS OWN RADIOS.
- 3. WHEN CONFLICTS ARISE BETWEEN CONSTRUCTION ACTIVITIES AND AIRCRAFT OPERATIONS AND SAFETY, AIRCRAFT OPERATIONS AND SAFETY SHALL TAKE PRECEDENCE AND SHALL GOVERN. FINAL AUTHORITY IN THE APPROVAL OF CLOSING AND OPENING PAVEMENTS AND CONSTRUCTION SEQUENCING LIES WITH THE AIRPORT MANAGER.
- 4. THE CONTRACTOR SHALL STORE EQUIPMENT AND MATERIALS AT THE LOCATION SHOWN FOR THE "CONTRACTOR'S STAGING, STORAGE, PARKING SITE AND FIELD OFFICE".
- 5. BROKEN OR WASTE CONCRETE AND ASPHALT SHALL BE DISPOSED OF BY THE CONTRACTOR OFF AIRPORT PROPERTY, UNLESS DIRECTED BY THE AIRPORT MANAGER.
- 6. VEHICLES AND EQUIPMENT SHALL NOT BE ALLOWED WITHIN AREAS 130' (ADG IV OFA) FROM THE CENTERLINE OF ACTIVE TAXIWAYS OR 250' FROM THE CENTERLINE OF ACTIVE RUNWAYS.
- ALL PAVEMENTS, DRIVES AND OTHER AREAS USED BY THE CONTRACTOR FOR HAUL ROADS AND STORAGE AREAS SHALL BE MAINTAINED AND REPAIRED IN KIND BY THE CONTRACTOR TO THE SATISFACTION OF AIRPORT MANAGER. NO ADDITIONAL COMPENSATION SHALL BE MADE TO THE CONTRACTOR FOR THIS WORK.
- 8. EXISTING TURF & AGRICULTURAL AREAS DISTURBED BY THE CONTRACTOR'S OPERATIONS OUTSIDE OF THE TURFING LIMITS SHALL BE COMPLETELY RESTORED BY HIM AT HIS EXPENSE TO THE SATISFACTION OF THE AIRPORT MANAGER.
- 9. THE CONTRACTOR SHALL THOROUGHLY CLEAN ALL CONSTRUCTION AREAS PRIOR TO OPENING TO AIR TRAFFIC.
- 10. REFER TO THE CONSTRUCTION ACTIVITY PLANS AND THE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS CONCERNING COORDINATION OF CONSTRUCTION ACTIVITIES.
- 11. THE ARFF VEHICLES SHALL HAVE COMPLETE ACCESS TO THE ENTIRE AIRFIELD INCLUDING THE CLOSURE AREAS.
- 12. THE CONTRACTOR IS REQUIRED TO GIVE TEN (10) FULL WORKING DAYS NOTICE TO THE AIRPORT MANAGER PRIOR TO CLOSING WORK AREAS TO AIRCRAFT.
- 13. AT THE PRECONSTRUCTION MEETING, CONTRACTOR SHALL SUPPLY THE AIRPORT MANAGER WITH PROPOSED CLOSURE AND PHASING DATES FOR HIS REVIEW AND APPROVAL. THE RESIDENT ENGINEER SHALL KEEP THE AIRPORT MANAGER ADVISED OF ANY PROPOSED CHANGES IN CLOSURE AND PHASING DATES.
- 14. ALL CONTRACTOR'S VEHICLES AND EQUIPMENT SHALL DISPLAY AN ORANGE AND WHITE CHECKED AVIATION SIGNAL FLAG, EXCEPT HAUL VEHICLES.
- 15. ANY VEHICLE OPERATING WITHIN A MOVEMENT AREA DURING THE HOURS OF DARKNESS SHOULD BE EQUIPPED WITH AN AMBER REVOLVING OR FLASHING DOME-TYPE LIGHT AS SPECIFIED IN THE SPECIAL PROVISIONS.
- 16. IF, DURING CONSTRUCTION, AN EMERGENCY IS DECLARED BY THE AIRPORT, THE CONTRACTOR SHALL IMMEDIATELY CLEAR THE PAVEMENT OF ALL VEHICLES, PERSONNEL AND EQUIPMENT.


CONTRACTOR'S RESPONSIBILITY FOR UTILITY SERVICE

THE LOCATION OF UNDERGROUND UTILITIES AS INDICATED ON THE PLANS HAS BEEN OBTAINED FROM EXISTING RECORDS. NEITHER THE OWNER NOR THE ENGINEER ASSUMES ANY RESPONSIBILITY WHATEVER IN RESPECT TO THE ACCURACY, COMPLETENESS, OR SUFFICIENCY OF THE INFORMATION. THERE IS NO GUARANTEE, EITHER EXPRESSED OR IMPLIED, THAT THE LOCATIONS, SIZE AND TYPE OF MATERIAL OF EXISTING UNDERGROUND UTILITIES INDICATED ARE REPRESENTATIVE OF THOSE TO BE ENCOUNTERED IN THE CONSTRUCTION.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE ACTUAL LOCATION OF ALL SUCH FACILITIES, INCLUDING SERVICE CONNECTIONS TO UNDER- GROUND UTILITIES, PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE UTILITY COMPANY OF HIS OPERATIONAL PLANS. THE CONTRACTOR SHALL MAKE ARRANGEMENTS FOR DETAILED INFORMATION AND ASSISTANCE IN LOCATING UTILITIES. IN THE EVENT AN UNEXPECTED UTILITY INTERFERENCE IS ENCOUNTERED DURING CONSTRUCTION, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE UTILITY COMPANY, THE OWNER AND THE ENGINEER. ANY SUCH MAINS AND/OR SERVICES DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED IMMEDIATELY AT HIS EXPENSE TO THE SATISFACTION OF THE OWNER AND THE ENGINEER.

CONTRACTOR'S ACCESS

- 1. CONTRACTOR'S ACCESS SHALL BE AS FOLLOWS:
- A. THE CONTRACTORS ACCESS TO THE WORK SHALL BE AS SHOWN ON THE SITE PLAN AND CONSTRUCTION ACTIVITY PLANS.
- B. DURING ADVERSE WEATHER, THE CONTRACTOR SHALL MAKE PROVISIONS FOR ACCESS TO THE WORK SITE AT NO ADDITIONAL COST TO THE CONTRACT. NO EXTENSION OF CONTRACT TIME WILL BE CONSIDERED FOR DELAYS DUE TO LACK OF ADEQUATE ACCESS TO THE WORK
- C. THE CONTRACTOR SHALL INSTALL AND MAINTAIN A HEAVY-DUTY PADLOCK ON THE ACCESS GATE. HE SHALL PROVIDE KEYS FOR THIS PADLOCK TO THE RESIDENT ENGINEER, AIRPORT SECURITY AND MAINTENANCE SUPERVISOR. NO ADDITIONAL KEYS ARE TO BE DISTRIBUTED UNLESS AUTHORIZED BY THE AIRPORT MANAGER.
- D. THE CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING ALL CONSTRUCTION ACCESS GATES CLOSED & SECURED AT ALL TIMES INCLUDING WORK HOURS. IF THE CONTRACTOR CHOOSES TO LEAVE THE GATE OPEN, HE SHALL POST A COMPETENT, FULL TIME SECURITY GUARD TO PREVENT UNAUTHORIZED ENTRIES. THE CONTRACTOR SHALL REPLACE ANY UNSATISFACTORY SECURITY GUARDS IF SO DIRECTED BY THE AIRPORT MANAGER OR ENGINEER.
- E. THE CONTRACTOR SHALL CLOSE AND LOCK THE ACCESS GATES UPON LEAVING THE SITE.
- F. THROUGHOUT THE DURATION OF THE CONTRACT, ANY DAMAGE TO THE ACCESS GATES OR FENCING ADJACENT TO THE PROJECT SHALL BE REPAIRED BY THE CONTRACTOR TO THE SATISFACTION OF THE AIRPORT MANAGER.
- G. ALL COSTS RELATING TO CONTRACTOR'S ACCESS AND SECURITY SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- H. THE CONTRACTOR SHALL STORE EQUIPMENT AND MATERIALS IN SUCH A WAY AS TO NOT DISTURB AGRICULTURAL AREAS OR VIOLATE THE PART 77 APPROACH AND PRIMARY SURFACES.
- I. EMPLOYEE PERSONAL VEHICLES SHALL NOT BE ALLOWED BEYOND THE CONTRACTOR'S PARKING AREA. CONTRACTOR PERSONNEL SHALL PARK IN THE CONTRACTOR'S STORAGE AREA. PERSONNEL SHALL BE TRANSPORTED TO THE WORK SITE BY COMPANY OWNED VEHICLES.
- J. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL ACCESS ROADS WITH THE APPROPRIATE AGENCY RESPONSIBLE FOR THE ROADWAY.
- K. THE CONTRACTOR SHALL HAVE A VACUUM TYPE SWEEPER AVAILABLE AT ALL TIMES
- 2. AN AREA WILL BE PROVIDED BY THE AIRPORT TO THE CONTRACTOR AS THE STAGING, STORAGE AND EMPLOYEE PARKING SITE, AT THE LOCATION SHOWN.
- 3. A LIST OF AUTHORIZED PERSONNEL PERMITTED TO USE THE GATE SHALL BE PROVIDED BY THE CONTRACTOR TO THE RESIDENT ENGINEER.
- 4. THE CONTRACTOR SHALL PROVIDE A SIGN AT THE ACCESS GATE SAYING "AUTHORIZED PERSONNEL & CONSTRUCTION ACCESS ONLY".
- 5. SUPERINTENDENT, SUPERVISING FOREMEN, ESCORT PERSONNEL AND SECURITY GUARDS ON THE AIRFIELD WILL BE REQUIRED TO SUBMIT A TEN YEAR BACKGROUND CHECK TO AIRPORT SECURITY AND WILL BE REQUIRED TO BE TRAINED BY THE AIRPORT TO GAIN ACCESS PER SECTION 80-13 OF THE SPECIFICATIONS. CONTRACTOR SHALL COORDINATE THE BADGING PROCESS A MINIMUM OF 10 DAYS PRIOR TO REQUESTING ACCESS TO THE FIELD.



VEHICLE SIGNAL FLAG (ORANGE / WHITE) N.T.S.

GROUND CONTROL FREQUENCY 121.8 MHZ

MAXIMUM EQUIPMENT HEIGHT 25 FEET

K:\ChampaignAp\1305902\Draw\Sheets FILE: CMI4347-1305902-GC001.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 6:59 PM

UN053

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

WIDEN TAXIWA

BID - REALIGN AND WIDI

Ш

BASI

NOTE!

ENERAL

Ō

CMT, Inc.	
© Copyright CMT, Inc. PHY & TILLY, INC. NEERS	
© CODYIGH CMT. INC. CRAWFORD MARPHY & TLLY, NC. CONSULTING ENGNEERS LICENSE No. 184-000613	
CRAWFORD, CONSULTING LICENSE NO. 1	

DESIGN BY: CBG

DRAWN BY: CMT

CHECKED BY: CET

APPROVED BY: CET

DATE: JUNE 27, 2014

JOB No: 13059-02-00

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 04 OF 83 SHEETS

SEQUENCE OF CONSTRUCTION NOTES

THE GENERAL PROGRESSION OF THE WORK SHALL BE AS FOLLOWS


- A. SUBMIT EQUIPMENT AND BUILDING SHOP, PLAN AND WORKING DRAWINGS FOR REVIEW. INCLUDE WITH THE SUBMITTALS ALL BUY AMERICAN CERTIFICATIONS FOR ALL MATERIALS.
- B. SUBMIT NOTICE OF OBSTRUCTION EVALUATION- AIRPORT AIRSPACE ANALYSIS (OE/AAA) INFORMATION FOR ANTICIPATED EQUIPMENT HEIGHTS IF IN EXCESS OF 25'. NOTE THAT THIS PROCESS MAY REQUIRE UP TO 90 DAYS FOR FAA APPROVAL. EQUIPMENT ABOVE 25' HEIGHT SHALL NOT BE UTILIZED UNTIL FAA APPROVAL HAS BEEN PROVIDED.
- SUBMIT PROJECT SCHEDULE SHOWING RELATIONSHIP BETWEEN CONSTRUCTION DURATION FOR PAY ITEMS IN RELATION TO THE PHASES OF WORK WHERE THEY ARE BEING PERFORMED.
 CLEARLY IDENTIFY DATES OF RUNWAY CLOSURES AND WHAT PHASES WILL BE WORKED IN DURING THAT CLOSURE.
- SUBMIT PRELIMINARY MATERIALS CERTIFICATIONS INCLUDING BUY AMERICAN CERTIFICATIONS AND WAIVER REQUEST FOR MATERIALS THAT DO NOT MEET THE CONTRACT REQUIREMENTS.
- E. INITIATE CONSTRUCTION OF TAXIWAY REALIGNMENT AND WIDENING. INSTALL BARRICADES AS OUTLINED ON THE CONSTRUCTION ACTIVITY PLANS. FIELD VERIFY LOCATION OF EXISTING CIRCUITS, PERFORM TESTING ON EXISTING AIRFIELD CIRCUITS TO VERIFY CONDITION OF CIRCUIT CABLES. THE RESIDENT ENGINEER SHALL BE PRESENT AT THE TIME OF TESTING AND SHALL BE GIVEN A COPY OF THE TEST RESULTS.
- INITIATE CONSTRUCTION WITHIN THE VARIOUS PHASES OF THE PROJECT. TAXIWAY C REALIGNMENT AND WIDENING PHASES SHALL BE CONSIDERED THE PRIMARY WORK AREAS. WORK IN THESE AREAS SHALL INCLUDE REMOVAL OF PAVEMENT/ELECTRICAL EQUIPMENT/DRAINAGE STRUCTURES. EARTH EMBANKMENT EXCAVATION, PAVEMENT CONSTRUCTION, DRAINAGE IMPROVEMENTS, ELECTRICAL IMPROVEMENTS, PAVEMENT MARKING AND TURFING
- UPON COMPLETION OF ALL PHASES, THE CONTRACTOR SHALL REQUESTE A FINAL INSPECTION OF THE PROJECT.

RUNWAY SAFETY AREAS

- 1. WORK IN THE RUNWAY 14L/32R SAFETY AREA SHALL BE LIMITED TO THAT WORK NECESSARY TO CONSTRUCT THE CONNECTING TAXIWAY C PAVEMENTS AND CONSTRUCT DIRECTIONAL BORES UNDER RUNWAY 14L/32R FOR RGL CIRCUITS. NO PAVEMENT IMPROVEMENTS WILL BE MADE TO THE SURFACE OF RUNWAY
- WORK IN THE RUNWAY 4/22 SAFETY AREA SHALL BE LIMITED TO THAT WORK NECESSARY TO CONSTRUCT THE PARALLEL TAXIWAY C PAVEMENTS AND CONSTRUCT DIRECTIONAL BORES UNDER RUNWAY 4/22 FOR TAXIWAY C HOME RUN CIRCUITS. PAVEMENT IMPROVEMENTS OF TAXIWAY C WILL BE AT THE INTERSECTION OF TAXIWAY C AND THE RUNWAY 4/22 PAVEMENT
- RUNWAY 4/22 AND RUNWAY 14L/32R SHALL NOT BE CLOSED AT THE SAME TIME.
- EQUIPMENT OR PERSONNEL SHALL REMAIN CLEAR OF THE RUNWAY PAVEMENTS AT ALL TIMES.
- NO EQUIPMENT, STOCKPILES OR EXCAVATIONS SHALL REMAIN INSIDE THE RUNWAY SAFETY AREAS AFTER WORKING HOURS.

APRON / TAXIWAY OBJECT FREE AREAS


- WORK IN THE TAXIWAY OBJECT FREE AREAS SHALL REQUIRE THAT TAXIWAY TO BE CLOSED. WORK WITHIN THE TAXIWAY OBJECT FREE AREAS BUT NOT ON THE HARD SUBFACE OF THE TAXIWAY SHALL INCLUDE, TAXIWAY GUIDANCE SIGN INSTALLATION, TRENCHING CABLE, RUNWAY GUARD LIGHT INSTALLATION AND DIRECTIONAL BORES. WORK WITHIN THE TAXIWAY OBJECT FREE AREAS ON THE HARD SURFACE WILL INCLUDE PAVEMENT MARKING AND PAVEMENT
- 2. NO EQUIPMENT, OPEN TRENCHES OR EXCAVATIONS SHALL REMAIN INSIDE THE TAXIWAY OBJECT FREE AREAS AFTER WORKING HOURS
- THE TAXIWAYS OR EDGES OF APRONS SHALL BE CLOSED WITH BARRICADES AT 15' MAXIMUM SPACING PRIOR TO WORKING IN THE CRITICAL WORK AREAS.



BARRICADE NOTES:

- 1. FLASHERS SHALL BE BATTERY OPERATED. LENS SHALL BE RED AND BE ABLE TO ROTATE 90°.
- 2. FACING OF BARRICADE SHALL BE COVERED WITH REFLECTIVE
- BARRICADES TO BE PLACED WITH A MAXIMUM OF 15' SPACING BETWEEN ENDS OF BARRICADES ALONG OPERATIONAL PAVEMENT ADJACENT TO CONSTRUCTION OR AS DIRECTED BY THE RESIDENT ENGINEER. ALTERNATE FLASHER LENSES SO THAT EVERY OTHER LENS IS ROTATED 90°
- 4. FLASHERS SHALL BE SECURED TO THE BARRICADES, AS APPROVED BY THE RESIDENT ENGINEER.
- BARRICADES SHALL BE OF LOW MASS, EASILY COLLAPSIBLE UPON CONTACT WITH AN AIRCRAFT OR ANY OF IT COMPONENTS, AND WEIGHTED OR STURDILY ATTACHED TO THE SURFACE. IF AFFIXED TO THE SURFACE, THE BARRICADE MUST BE FRANGIBLE AT GRADE LEVEL OR LOW AS POSSIBLE, BUT NOT TO EXCEED 3 INCHES ABOVE THE GROUND.


LOW PROFILE LIGHTED BARRICADE



CLOSED RUNWAY MARKER DETAIL

NOTES


- 1. MARKERS SHALL BE SOLID YELLOW.
- MARKERS SHALL BE SELF CONTAINED MOBILE MARKERS PROVIDED BY THE CONTRACTOR THROUGH THE CONTRACT.
- 3. CONTRACTOR SHALL MAINTAIN MARKERS.
- 4. COST OF INSTALLING, MAINTAINING, RELOCATING AND REMOVING MARKERS SHALL BE INCIDENTAL
- 5. MARKERS SHALL BE PLACED OVER EXISTING RUNWAY NUMERALS.



BARRICADES SHALL BE PLACED AS SHOWN ON THE CONSTRUCTION ACTIVITY PLANS 15' ON CENTER AT DESIGNATED LOCATIONS. BARRICADE SHALL BE WEIGHTED WITH A MINIMUM OF 6 SAND BAGS TO PREVENT THEM FROM BEING BLOWN OVER

IDOT TYPE 1 BARRICADE DETAIL

WHERE NOT SPECIFIED, THE CONTRACTOR SHALL HAVE THE OPTION AS TO WHICH TYPE OF BARRICADE IS USED.




CLOSED RUNWAY/ TAXIWAY MARKER DETAIL N.T.S.

SYMBOL TYPE DIMENSION	Α	В	С
CLOSED RUNWAY	10'-0"	25'-0"	60'-0"
CLOSED TAXIWAY	5'-0"	12'-6"	30'-0"

NOTES


- 1. CLOSURE MARKERS SHALL BE SOLID YELLOW.
- 2. MARKERS SHALL BE PLACED ON TAXIWAYS AT THE RUNWAY INTERSECTIONS INSIDE THE RUNWAY SAFETY AREA.
- 3. MARKERS SHALL BE PAINTED ON THE TAXIWAY USING TEMPORARY PAINT OR CONSTRUCTED OF FABRIC, COLORED PLASTIC, PAINTED SHEETS OF PLYWOOD OR SIMILAR MATERIALS.
- 4. NON PAINTED MARKERS SHALL BE SECURED TO PREVENT MOVEMENT BY PROP WASH, JET BLAST OR OTHER WIND CURRENTS. METHODS OF SECURING THE MARKERS SHALL NOT PROTRUDE MORE THAN 3" ABOVE THE PAVEMENT STRUCTURE



LIGHTED RUNWAY CLOSURE MARKER

NOTES

- 1. TO BE PLACED ON PAVEMENT AT THE RUNWAY NUMERALS.
- PAIR OF LIGHTED 'X'S TO BE PROVIDED BY THE AIRPORT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE (FUEL, OIL, LIGHT BULBS) WHEN USED DURING CONSTRUCTION CLOSURES.



ILE: CMI4347-1305902-GC003.dwa JPDATE BY: Chris Groth PLOT DATE: 7/10/2014 6:59 PM

UN053

REVISIONS			
NUMBER	BY	DATE	
0	1	2	

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

Š

ETAIL

ပေ ဟ - REALIGN AND WIDEN TAXIWAY (CTION ACTIVITY PLAN NOTE)
DETAILS OF ILLINOIS
AIRPORT
ILLINOIS

UNIVERSITY (WILLARD A SAVOY, II Αď CONSTRUCTION **BASE BID**


9


CBG DESIGN BY: DRAWN BY CMT CET CHECKED BY CET APPROVED BY: JUNE 27, 2014


JOB No: 13059-02-00 IL. PROJ. NO. CMI-4347


AIP PROJ. NO. 3-17-0016-XX


SHEET 05 OF 83 SHEETS


























REVISIONS				
NUMBER	BY	DATE		







GENERAL

- THE CONTRACTOR AND ALL SUBCONTRACTORS SHALL FOLLOW THE REQUIREMENTS OF THE AIRPORT'S APPROVED CONSTRUCTION SAFETY AND PHASING PLAN (CSPP), FAA AC 150/5370-2F, AND ALL AIRPORT SAFETY AND SECURITY
- PRIOR TO THE START OF CONSTRUCTION THE CONTRACTOR SHALL SUBMIT TO THE AIRPORT FOR APPROVAL A SAFETY PLAN COMPLIANCE DOCUMENT (SPCD) IN ACCORDANCE WITH FAA AC 150/5370-2F. NO CONSTRUCTION ACTIVITY SHALL BEGIN UNTIL THE AIRPORT HAS APPROVED THE SPCD.
- THE CSPP COVERS OPERATIONAL SAFETY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE INDIVIDUAL SAFETY OF HIS/HER PERSONNEL AND MEETING OSHA REQUIREMENTS.
- A MINIMUM OF 10 DAYS PRIOR TO THE NOTICE TO PROCEED THE CONTRACTOR SHALL PROVIDE A LIST OF SUBCONTRACTORS AND
- PRIOR TO THE START OF CONSTRUCTION THE CONTRACTOR SHALL SIGN THE SWPPP CERTIFICATION STATEMENT.
- ALL CONTRACTOR COSTS ASSOCIATED WITH THE REQUIREMENTS. LISTED ON THIS SHEET SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT UNLESS A SPECIFIC PAY ITEM IS PROVIDED.

1. COORDINATION

- PRIOR TO THE START OF CONSTRUCTION THE CONTRACTOR SHALL ATTEND A PRECONSTRUCTION CONFERENCE WITH THE AIRPORT, ENGINEER, AND ILLINOIS DIVISION OF AERONAUTICS (IDA). THE COST OF PREPARING FOR AND ATTENDING THE PRECONSTRUCTION CONFERENCE SHALL BE INCIDENTAL TO THE
- ON OR BEFORE THE PRECONSTRUCTION CONFERENCE. THE CONTRACTOR SHALL SUBMIT A PROPOSED SCHEDULE FOR THE PROJECT. THE SCHEDULE SHALL INCLUDE A START AND COMPLETION DATE FOR EACH ITEM OF WORK. THE SCHEDULE SHALL BE UPDATED ON A WEEKLY BASIS. ALL COSTS ASSOCIATED WITH THE SCHEDULE SHALL BE INCIDENTAL TO THE CONTRACT.
- DUBING CONSTRUCTION THE CONTRACTOR SHALL ATTEND A WEEKLY COORDINATION MEETING WITH THE AIRPORT STAFF AND RESIDENT ENGINEER. ALL COSTS ASSOCIATED WITH ATTENDING THE WEEKLY MEETING SHALL BE INCIDENTAL TO THE CONTRACT.

2. PHASING

- TOTAL CONTRACT TIME SHALL BE 122 CALENDAR DAYS.
- PHASING SHALL BE AS NOTED BELOW AND AS SHOWN ON THE CONSTRUCTION ACTIVITY PLAN (CAP) SHEET.

3. AREAS AND OPERATIONS AFFECTED BY THE CONSTRUCTION ACTIVITY

- ALL RUNWAYS, TAXIWAYS AND APRONS SHALL BE KEPT OPEN TO AIRCRAFT TRAFFIC DURING CONSTRUCTION EXCEPT AS NOTED ON THE PHASING PLAN.
- WHEN CONFLICTS ARISE BETWEEN CONSTRUCTION ACTIVITIES AND AIRCRAFT OPERATIONS AND SAFETY, AIRCRAFT OPERATIONS AND SAFETY SHALL TAKE PRECEDENCE AND SHALL GOVERN. FINAL AUTHORITY IN THE APPROVAL OF CONSTRUCTION SEQUENCING LIES WITH THE AIRPORT
- ALL CONSTRUCTION TRAFFIC SHALL IMMEDIATELY YIELD TO ONCOMING AIRCRAFT AT ALL TIMES.

5. CONTRACTOR ACCESS

- CONTRACTOR ACCESS SHALL BE AS NOTED BELOW AND AS SHOWN ON THE SITE PLAN AND CONSTRUCTION ACTIVITY PLAN SHEETS. ALL COSTS RELATING TO CONTRACTOR'S ACCESS AND SECURITY SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- THE CONTRACTOR IS TO ACCESS THE SITE USING THE GATES SHOWN. THE CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING THE ACCESS GATE(S) CLOSED DURING WORK HOURS. THE CONTRACTOR SHALL POST A COMPETENT SECURITY GUARD TO CONTROL ACCESS AT THE GATE. THE CONTRACTOR SHALL REPLACE ANY UNSATISFACTORY SECURITY GUARDS AS DIRECTED.
- CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND TEMPORARY EASEMENTS FOR THE PUBLIC ACCESS ROAD(S) SHOWN AND SHALL COMPLY WITH ALL REQUIREMENTS, LOAD RESTRICTIONS, & TRAFFIC CONTROL SIGNAGE REQUIRED BY THE VILLAGE, UNIVERSITY, COUNTY, TOWNSHIP, OR I.D.O.T.
- A MINIMUM OF THREE (3) CONTRACTOR EMPLOYEES SHALL OBTAIN AN AIRPORT IDENTIFICATION BADGE. THIS CONSISTS OF FILLING OUT ALL NECESSARY PAPERWORK FINGERPRINTING ATTENDING AND PASSING A TRAINING CLASS CONCERNING SAFETY AND SECURITY AT THE AIRPORT. CONTRACTOR EMPLOYEES MUST MEET CERTAIN BACKGROUND CHECK CRITERIA AND THE CONTRACTOR MUST MAKE CERTAIN CERTIFICATION ABOUT EACH EMPLOYEE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FINGERPRINTING COSTS. ALL COSTS ASSOCIATED WITH OBTAINING THE IDENTIFICATION BADGE SHALL BE BORNE BY THE CONTRACTOR.
- ALL CONTRACTOR EMPLOYEES WHO ARE DESIGNATED AS DRIVERS FOR THE CONTRACTOR WITHIN THE AIRFIELD OPERATIONS AREA (AOA) SHALL ALSO ATTEND AND PASS THE AIRPORT DRIVERS TRAINING PROGRAM. ONLY THOSE INDIVIDUALS WHO RECEIVE THIS DESIGNATION WILL BE PERMITTED TO OPERATE VEHICLES OR EQUIPMENT ON THE AIRPORT. ALL COSTS ASSOCIATED WITH THE DRIVER TRAINING PROGRAM SHALL BE BORNE BY THE CONTRACTOR.
- CONTRACTOR'S VEHICLES AND EQUIPMENT SHALL BE MARKED AND FLAGGED PER SECTION 70-10 OF THE STANDARD SPECIFICATIONS. MAXIMUM HEIGHT OF CONTRACTOR'S
- DRIVERS OF TRUCKS CONTAINING MATERIAL DELIVERIES (AGGREGATE, CONCRETE, ETC.) NEED NOT OBTAIN AN AIRPORT ID BADGE BUT SHALL BE REQUIRED TO SUBMIT THEIR NAME, DRIVER'S LICENSE NUMBER, TRUCK LICENSE PLATE NUMBER AND NAME OF TRUCKING COMPANY TO THE PRIME CONTRACTOR PRIOR TO ENTERING THE JOBSITE. WHILE INSIDE THE AOA, THE TRUCK DRIVERS SHALL BE ESCORTED BY THE CONTRACTOR PERSONNEL THAT HAS OBTAINED PROPER DRIVING PRIVELAGES.
- CONTRACTOR WORK CREWS MUST MAINTAIN RADIO CONTACT WITH THE AIR TRAFFIC CONTROL TOWER (ATCT) AT ALL TIMES WHEN INSIDE THE AIRPORT OPERATIONS AREA (AOA). THE CONTRACTOR SHALL SUPPLY ALL APPROPRIATE RADIOS NEEDED FOR COMMUNICATIONS AND ONLY HIS PERSONNEL WHO HAVE SUCCESSFULLY COMPLETED THE APPROVED CMI/FAA SAFETY COURSE MAY OPERATE THESE RADIOS.
- THE CONTRACTORS STORAGE AND STAGING AREA WILL BE AS
- THE CONTRACTOR SHALL KEEP A RECORD OF THE NAMES OF ALL EMPLOYEES ENTERING THE JOB SITE ON A DAILY BASIS. A RECORD OF EACH SUBCONTRACTOR ENTERING THE JOB SITE SHALL ALSO BE KEPT BY THE CONTRACTOR.
- WHEN THE CONTRACTOR IS NOT WORKING, EQUIPMENT SHALL BE STORED AT THE STAGING AREA.
- 12. DURING ADVERSE WEATHER THE CONTRACTOR SHALL MAINTAIN ACCESS TO THE WORK AT NO ADDITIONAL COST TO THE CONTRACT. NO EXTENSION OF THE CONTRACT TIME WILL BE CONSIDERED FOR DELAYS DUE TO LACK OF ADEQUATE ACCESS TO THE WORK SITE
- 13. THE CONTRACTOR WILL BE PERMITTED TO STORE EQUIPMENT AND MATERIALS ONLY AT THE LOCATIONS SHOWN PARKED EQUIPMENT AND MATERIAL STOCKPILES SHALL NOT PENETRATE SURFACES DEFINED BY F.A.R. TITLE 14 PART 77 - OBJECTS AFFECTINGNAVIGABLE AIRSPACE. EXISTING TURF AREAS DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED BY HIM AT HIS EXPENSE TO THE SATISFACTION OF THE RESIDENT ENGINEER AND THE AIRPORT.
- 14. ALL CONSTRUCTION TRAFFIC OPERATING ON, OR CROSSING RUNWAYS, TAXIWAYS AND APRONS OPEN TO AIRCRAFT TRAFFIC SHALL BE UNDER CONTROL BY A FLAGMAN OR ESCORT IN RADIO CONTACT WITH THE ATCT. THE CONTRACTOR SHALL PROVIDE HIS OWN FLAGMEN
- 15. THE CONTRACTOR SHALL THOROUGHLY CLEAN ALL CONSTRUCTION AREAS AND HAUL ROUTES WHICH WILL BE OPENED TO AIR TRAFFIC TO THE SATISFACTION OF AIRPORT OPERATIONS OR THE RESIDENT ENGINEER. A POWER BROOM AND OPERATOR SHALL BE ON SITE AT ALL TIMES WHEN ACTIVE PAVEMENTS ARE UTILIZED FOR CONSTRUCTION TRAFFIC.

5. CONTRACTOR ACCESS (CONTINUED)

- 16. ALL PAVEMENTS, DRIVES OR ANY OTHER AREAS UTILIZED BY THE CONTRACTOR FOR HAUL ROADS OR STORAGE AREAS SHALL BE MAINTAINED AND REPAIRED TO THE SAME CONDITION OR BETTER THAN THEY WERE PRIOR TO BEGINNING CONSTRUCTION. NO ADDITIONAL COMPENSATION WILL BE MADE TO THE CONTRACTOR
- 17. ALL VEHICLE AND EQUIPMENT OPERATORS USED BY THE CONTRACTOR SHALL BE PROPERLY TRAINED BY THE
- THE CONTRACTOR SHALL NOTIFY THE AIRCRAFT RESCUE AND FIRE FIGHTING (ARFF) FACILITY IF CONSTRUCTION ACTIVITY WILL REQUIRE THE BLOCKAGE OF EMERGENCY ACCESS TO THE

6. WILDLIFE MANAGEMENT

- THE CONTRACTOR SHALL NOTIFY PUBLIC SAFETY OR THE ENGINEER IF ANY WILDLIFE IS SEEN ENTERING THE AIRPORT.
- CONTRACTOR ACCESS GATES SHALL REMAIN CLOSED WHEN THE CONTRACTOR IS NOT WORKING
- THE CONTRACTOR SHALL DISPOSE OF ALL TRASH INCLUDING FOOD SCRAPS IN APPROVED CONTRACTOR PROVIDED

7. NOTIFICATION OF CONSTRUCTION ACTIVITIES

- THE CONTRACTOR SHALL PROVIDE A 24 HOUR EMERGENCY CONTACT
- THE CONTRACTOR SHALL GIVE A MINIMUM OF 72 HOURS NOTICE TO AIRPORT OPERATIONS PRIOR TO CLOSING ANY PAVEMENTS SO THAT PROPER NOTAMS MAY BE ISSUED BY THE AIRPORT.
- FOR ANY EQUIPMENT USED BY THE CONTRACTOR WITH A HEIGHT GREATER THAN 25', THE CONTRACTOR SHALL PROVIDE TO THE AIRPORT THE TYPE OF EQUIPMENT, TOTAL HEIGHT, AND LOCATION WHERE THE EQUIPMENT WILL BE USED. THE AIRPORT WILL SUBMIT FAA FORM 7460-1 TO THE FAA FOR AN AIRSPACE STUDY NO EQUIPMENT WITH A HEIGHT GREATER THAN 40' SHALL BE USED UNTIL A DETERMINATION FROM FAA IS RECEIVED.
- IN THE EVENT OF AN EMERGENCY, THE CONTRACTOR SHALL CALL 911.
- CONTACTS FOR THIS PROJECT ARE AS LISTED BELOW. CHIEF JOHN RIEGEL - PUBLIC SAFETY OFFICE (217) 244-8764 CELL (217) 202-8213

AIRPORT MAINTENANCE RON DECKARD - MAINTENANCE CONTACT OFFICE (217) 369-0099 CELL (217) 714-4600

CHRIS GROTH P.E. - PROJECT ENGINEER (217) 787-8050 RESIDENT ENGINEER TO BE DETERMINED OFFICE (217) 787-8050

8. INSPECTION REQUIREMENTS

- THE CONTRACTOR SHALL INSPECT THE JOBISTE DAILY TO ENSURE COMPLIANCE WITH THE CSPP. THE CHECKLIST FOUND IN APPENDIX 3 OF FAA AC 150/5370-2F MAY BE USED TO AID IN THE INSPECTIONS.
- THE CONTRACTOR SHALL REQUEST OPERATIONAL INSPECTION OF EACH PHASE WORK AREA PRIOR THE AREA BEING REOPENED. PUBLIC SAFETY WILL DETERMINE IF THE WORK AREA IS ALLOWED TO

9. UNDERGROUND UTILITIES

- IT WILL BE NECESSARY FOR THE CONTRACTOR TO MAKE HIS OWN FIELD INVESTIGATION TO DETERMINE THE EXACT LOCATION OF THE UNDERGROUND UTILITIES AT CRITICAL POINTS. THE LOCATION OF UNDERGROUND UTILITIES AS INDICATED ON THE PLANS HAS BEEN OBTAINED FROM EXISTING RECORDS. NEITHER THE OWNER NOR THE ENGINEER ASSUMES ANY RESPONSIBILITY IN RESPECT TO THE ACCURACY, COMPLETENESS OR SUFFICIENCY OF THE INFORMATION. ANY UTILITY, INCLUDING AIRFIELD ELECTRICAL CABLE AND LIGHTS, DAMAGED BY THE CONTRACTOR SHALL BE REPAIRED BY HIM AT HIS OWN EXPENSE IN A MANNER WHICH IS SATISFACTORY TO THE ENGINEER AND TO THE OWNER OF THE UTILITY. ANY REPAIRS THAT MUST BE MADE BY THE OWNER OF THE UTILITY SHALL HAVE THE COST REIMBURSED TO THE UTILITY BY THE CONTRACTOR. AIRFIELD LIGHTING CABLES DAMAGED BY THE CONTRACTOR SHALL BE REPAIRED BY A QUALIFIED ELECTRICIAN WITH THE COSTS TO BE BORNE BY THE
- BEFORE INITIATING ANY DIGGING, DRILLING OR EXCAVATING ON THE AIRPORT PROPERTY, THE CONTRACTOR SHALL CALL J.U.L.I.E AND CONTACT THE LOCAL FAA OFFICE TO ARRANGE FOR UTILITY LOCATES. SEE SECTION 50-17 OF THE SPECIAL PROVISIONS FOR UTILITY CONTACT INFORMATION.

10. PENALTIES

NONCOMPLIANCE BY THE CONTRACTOR WITH AIRPORT RULES AND REGULATIONS OR FAILURE TO COMPLY WITH THE AIRPORT'S APPROVED CSPP AND THE CONTRACTOR'S APPROVED SPCD MAY RESULT IN FINES AS ALLOWED

11. SPECIAL CONDITIONS

ADJACENT CONSTRUCTION MAY IMPACT THE OPERATIONS OF THE CONTRACTOR. SEE THE COORDINATION NOTES FOR ADDITIONAL INFORMATION.

12. RUNWAY AND TAXIWAY VISUAL AIDS

- ALL RUNWAYS, TAXIWAYS, AND APRONS SHALL BE KEPT OPEN TO AIRPORT TRAFFIC DURING CONSTRUCTION EXCEPT AS NOTED IN THE CONSTRUCTION
- IF ANY RUNWAY OR TAXIWAY CLOSURES ARE REQUESTED BY THE CONTRACTOR AND APPROVED BY THE AIRPORT, THE CONTRACTOR SHALL USE MARKING, LIGHTING AND SIGNS THAT FOLLOWING THE REQUIREMENTS OF FAA AC

13. MARKING AND SIGNS FOR ACCESS ROUTES

BARRICADES AND SIGNS SHALL BE USED ALONG THE CONTRACTOR'S ACCESS ROUTE AS DETAILED ON THIS SHEET AND THE CONSTRUCTION ACTIVITY PLAN

14. HAZARD MARKING AND LIGHTING

- THE CONTRACTOR SHALL FURNISH, ERECT, AND MAINTAIN MARKINGS AND ASSOCIATED LIGHTING OF OPEN TRENCHES, EXCAVATIONS, TEMPORARY STOCKPILES, AND HIS/HER CONSTRUCTION EQUIPMENT
- ALL CONSTRUCTION EQUIPMENT SHALL BE FLAGGED AND/OR LIGHTED IN ACCORDANCE WITH FAA ADVISORY CIRCULAR 150/5370-2F AND 150/5210-5C AT ALL TIMES WHILE OPERATING ON AIRPORT PROPERTY. THE MAXIMUM EQUIPMENT HEIGHT IS 25'.
- BARRICADES SHALL BE PLACED AT THE LOCATIONS SHOWN ON THE CONSTRUCTION ACTIVITY PLAN SHEET OR AS DIRECTED BY THE ENGINEER.
- THE CONTRACTOR SHALL INSPECT THE BARRICADES ONCE DURING EACH WORK DAY TO INSURE PROPER PLACEMENT AND PROPER OPERATION OF THE RED LIGHTS AND FLAG PLACEMENT.
- THE AIRPORT WILL PROVIDE TWO PORTABLE CLOSED RUNWAY MARKERS FOR USE DURING THE PROJECT. THE CONTRACTOR WILL BE RESPONSIBLE FOR MAINTENANCE OF THE RUNWAY CLOSURE MARKERS INCLUDING FUEL, OIL CHANGES AND REPLACEMENT OF THE LIGHTS. UPON COMPLETION OF THE PROJECT, THE PORTABLE CLOSED RUNWAY MARKERS SHALL BE TURNED OVER TO THE AIRPORT

15. PROTECTION

- ALL WORK REQUIRED INSIDE OF THE BUNWAY 4-22 OR 14L/32B SAFETY AREAS WHICH EXTENDS 250' FROM THE RUNWAY CENTERLINE, WILL REQUIRE THE RUNWAY TO BE CLOSED. THE CONTRACTOR SHALL COORDINATE WITH THE AIRPORT A MINIMUM OF 72 HOURS PRIOR TO THE REQUESTED CLOSURE TIME
- ALL WORK REQUIRED ON AN ACTIVE TAXIWAY OR INSIDE OF AN ACTIVE TAXIWAY OBJECT FREE AREA, WHICH EXTENDS 93' FROM THE TAXIWAY CENTERLINE OF 50' TAXIWAYS AND 130' FROM THE CENTERLINE OF 75' TAXIWAYS, WILL REQUIRE THE TAXIWAY TO BE CLOSED. THE CONTRACTOR SHALL COORDINATE WITH THE AIRPORT A MINIMUM OF 72 HOURS PRIOR TO THE REQUESTED CLOSURE TIME.
- ALL WORK REQUIRED ON AN ACTIVE APRON OR INSIDE OF AN ACTIVE SAFETY AREA. WHICH EXTENDS 70' FROM THE APRON'S EDGE OF PAVEMENT. WILL REQUIRE A PORTION OF THAT APRON TO BE CLOSED. THE CONTRACTOR SHALL COORDINATE WITH THE AIRPORT A MINIMUM OF 72 HOURS PRIOR TO THE REQUESTED CLOSURE TIME.

16. OTHER LIMITATIONS ON CONSTRUCTION

- IF, DURING CONSTRUCTION, AN EMERGENCY IS DECLARED BY THE AIRPORT, THE CONTRACTOR SHALL IMMEDIATELY CLEAR THE PAVEMENT OF ALL VEHICLES PERSONNEL AND FOLIPMENT
- BROKEN CONCRETE, BROKEN ASPHALT, RUBBISH FROM DEMO, AND OTHER MISCELLANEOUS DEBRIS SHALL BE DISPOSED OF OFF AIRPORT PROPERTY. UNLESS OTHERWISE SPECIFIED.
- THE CONTRACTOR WILL BE RESPONSIBLE FOR COORDINATING THE AIRSPACE FOR THE CONSTRUCTION EQUIPMENT THAT IS TALLER THAN THAT SPECIFIED ON THE PLANS WITH THE FAA. THIS PROCESS MAY TAKE UP TO 12 WEEKS TO
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR MEGGAR TESTING ALL EXISTING CIRCUITS PRIOR TO CONSTRUCTION AND FOLLOWING CONSTRUCTION AS SPECIFIED IN THE CONTRACT DOCUMENTS.

ILE: CMI4347-1305902-GC002.dwc PDATE BY: Chris Groth LOT DATE: 7/10/2014 7:03 PM

UN053

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS FOLIAL TO ' AT FULL SCALE (34X22).

NOTE TAXIWAY **PHASING** WIDEN SAFETY - REALIGN AND CONSTRUCTION

BD

BASE

OF ILLINOIS
AIRPORT
ILLINOIS

UNIVERSITY (WILLARD A SAVOY, II

ပ


9 CRAWFO

DESIGN BY:	CBG
DRAWN BY:	ADD
CHECKED BY:	CET
APPROVED BY:	CET
DATE:	JUNE 27, 2014

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 18 OF 83 SHEETS

13059-02-00



JPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:04 PM **UN053** NUMBER LEGEND **LEGEND** 0 EXISTING BASE MOUNTED TAXIWAY LIGHT —> — UD—> — UD— EXISTING UNDERDRAIN \circ EXISTING STAKE MOUNTED TAXIWAY LIGHT — ss ——— EXISTING STORM SEWER \Box EXISTING STAKE MOUNTED RUNWAY LIGHT -- ASR -----EXISTING VGSI CABLE 7 OF ILLINOIS DAIRPORT ILLINOIS EXISTING TAXIWAY GUIDANCE SIGN —LOC —— EXISTING LOCALIZER CABLE 00 EXISTING RUNWAY GUARD LIGHT EXISTING TAXIWAY C CIRCUIT СМ EXISTING DUCT MARKER — RGL ——— RGL —— EXISTING RUNWAY GUARD LIGHT CABLE 0 EXISTING MANHOLE EXISTING RUNWAY 18--36 CIRCUIT СВ EXISTING CATCH BASIN EXISTING RUNWAY 14L-32R CIRCUIT EXISTING HANDHOLE EXISTING RUNWAY 4-22 CIRCUIT Φ EXISTING BASE MOUNTED THRESHOLD LIGHT --> --- UD----> --- UD---EXISTING UNDER DRAIN \ominus EXISTING STAKE MOUNTED THRESHOLD LIGHT RUNWAY SAFETY AREA (NON UTILITY) -RSA----- OFA-----TAXIWAY OBJECT FREE AREA (NON UTILITY) R REMOVE ITEM EXISTING CLEANOUT EXISTING DUCT \triangle CONTROL POINTS _ _ _ _ _ NEW PAVEMENT EXISTING VASI

UNIVERSITY (WILLARD / SAVOY, II

2 CRAWFORD, CONSULTING

CONTRACTOR'S RESPONSIBILITY FOR UTILITY SERVICE

THE LOCATION OF UNDERGROUND UTILITIES AS INDICATED ON THE PLANS HAS BEEN OBTAINED FROM EXISTING RECORDS. NEITHER THE OWNER NOR THE ENGINEER ASSUMES ANY RESPONSIBILITY WHATEVER IN RESPECT TO THE ACCURACY, COMPLETENESS, OR SUFFICIENCY OF THE INFORMATION. THERE IS NO GUARANTEE, EITHER EXPRESSED OR IMPLIED, THAT THE LOCATIONS, SIZE AND TYPE OF MATERIAL OF EXISTING UNDERGROUND UTILITIES INDICATED ARE REPRESENTATIVE OF THOSE TO BE ENCOUNTERED IN THE CONSTRUCTION.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE ACTUAL LOCATION OF ALL SUCH FACILITIES, INCLUDING SERVICE CONNECTIONS TO UNDER-GROUND UTILITIES. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE UTILITY COMPANY OF HIS OPERATIONAL PLANS. THE CONTRACTOR SHALL MAKE ARRANGEMENTS FOR DETAILED INFORMATION AND ASSISTANCE IN LOCATING UTILITIES. IN THE EVENT AN UNEXPECTED UTILITY INTERFERENCE IS ENCOUNTERED DURING CONSTRUCTION, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE UTILITY COMPANY THE OWNER AND THE ENGINEER. ANY SUCH MAINS AND/OR SERVICES DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED IMMEDIATELY AT HIS EXPENSE TO THE SATISFACTION OF THE OWNER AND THE ENGINEER.



DESIGN BY: CBG DRAWN BY: ADD CHECKED BY: CET CET APPROVED BY: DATE: JUNE 27, 2014 JOB No: 13059-02-00

FILE: CMI4347-1305902-CD100.dwg

REVISIONS

BY

THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22).

DATE


-REALIGN AND WIDEN TAXIWAY C CONDITIONS AND REMOVALS LEGEND AND NOTES


BD


BASE BID EXISTING


IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX


SHEET 20 OF 83 SHEETS




































TIE IN AT PARALLEL TAXIWAY C

- NOTES:

 1. SEE INDIVIDUAL CROSS SECTIONS FOR MORE INFORMATION.
 CUT SECTION NOT SHOWN FOR WIDENING BUT MAY BE
- 2. SEE PROPOSED IMPROVEMENTS SHEET FOR APPROXIMATE LOCATION OF TYPICAL SECTIONS.

FILE: CMI4347-1305902-CP305.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:10 PM **UN053** REVISIONS BY NUMBER DATE THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22). TAXIWAY UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS - REALIGN AND WIDEN SECTIONS **TYPICAL** BASE BID TILLY, INC. CRAWFORD, I CONSULTING License No. 18 CBG DESIGN BY: DRAWN BY: ADD CHECKED BY: CET CET APPROVED BY: JUNE 27, 2014 JOB No: 13059-02-00 IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX SHEET 32 OF 83 SHEETS




EDGE MILLING DETAIL "B"


NEW TOPSOIL PLACEMENT,
SPREAD STOCKPILED TOPSOIL EVENLY
OVER ALL DISTURBED AREAS TO PROMOTE
TURF GROWTH - COST INCIDENTAL TO
THE PROJECT

NEW 6" AVG. TOPSOIL STRIPPING AT ALL
EXCAVATION & EMBANKMENT AREAS TO BE
DISTURBED - COST INCIDENTAL TO THE PROJECT

TOPSOIL STRIPPING DETAIL

N.T.





EXISTING PAVEMENT DETAIL "C" EXCAVATION AND MILLING
N.T.S.

NOTES

- SAW CUT MAY BE REQUIRED IF MILL DOES NOT PROVIDE CLEAN VERTICAL FACE TO ABUTMENT -SAWING SHALL BE INCIDENTAL TO MILLING IF REQUIRED BY RESIDENT ENGINEER.
- 2. CONTRACTOR SHALL TAKE PRECAUTIONS TO PRESERVE THE EXISTING P.C.C. EDGE FROM DAMAGE DURING EXCAVATION. CONTRACTOR SHALL NOT OVER EXCAVATE ADJACENT TO THE EXISTING PAVEMENT AND CAUSE UNDERMINING AT THE EXISTING PAVEMENT.

FILE: CMI4347-1305902-CP302.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:10 PM

UN053

REVISIONS							
NUMBER	BY	DATE					

THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22).

SAVOY, ILLINOIS - REALIGN AND WIDEN TAXIWAY TYPICAL SECTIONS 4

BASE BID

CMT RILY, INC. CONSULTING ENGNETRS License No. 184-000613

DESIGN BY: CBG

DRAWN BY: ADD

CHECKED BY: CET


APPROVED BY: CET


DATE: JUNE 27, 2014

JOB No: 13059-02-00

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 33 OF 83 SHEETS





STRUCTURE	RIM	INVERT	STATION	OFFSET	PIPE IN	PIPE OUT	NOTES
CO-1	753.35	750.35	183+81.92	-40		UD-1	AR705640
CO-2	753.12	750.12	184+01.14	-164		UD-2	AR705640
CO-3	749.95	746.95	179+87.16	40	UD-1	UD-3	AR705640
CO-4	749.61	746.61	179+87.16	-49	UD-2	UD-4	AR705640
CO-5	750.5	746.5	172+00	-40	UD-9	UD-7	AR705640
CO-6	750.24	747.24	172+00	39	UD-10	UD-8	AR705640
CO-7	750.88	747.88	167+30.08	-39		UD-9	AR705640
CO-8	751.22	748.22	168+86.21	-39		UD-10/UD-11	AR705640
CO-9	749.13	746.13	158+00	-39		UD-12/UD-14	AR705640
CO-10	746.2	743.28	151.53.55	-53		UD-15	AR705640
CO-11	746.08	742.75	145+75.54	-40	UD-18	UD-17	AR705640
CO-12	747.17	743.75	141+63.16	-79		UD-18	AR705640
CS-1	749.47	744.7	176+00	-39	UD-3/UD-7	UD-5	AR705635
CS-2	748.98	744.3	176+00	-53	UD-5	UD-6	AR705635
CS-3	749.58	745	162+85.14	-39	UD-11/UD-12	UD-13	AR705635
CS-4	746.34	741.5	149+75.69	-39	UD-15/UD-17	UD-14	AR705635
DC-1	746.25	743.25	152+85.14	-61	UD-14	EXIST	INCIDENTAL

STRUCTURE	RIM	INVERT	STATION	OFFSET	PIPE IN	PIPE OUT	NOTES
IN-1	747.7	743.7	181+02	-106		SS-1	AR751410
IN-2	747.125	744.42	176+36.56	-119		SS-2/UD-6	AR751410
IN-3	747.75	743.7	173+98.11	-95	SS-2	EXIST	AR751415
IN-4	743.51	741.01	149+49.35	-95	UD-16	SS-4	AR751410
MH-1	749.07	743.53	181+20.61	-76	SS-1	Exist	AR751550
MH-2	744.39	740.5	150+71.34	-98	SS-4	EXIST	AR751550
FES-1	744	744	174+00	-115		SS-3	AR752421
EIN-3	746.67	743.62	174+00	-45	SS-3	EXIST	EXISTING STRUCTURE
EIN-5		744.5	164+50.64	-192	UD-13		EXISTING STRUCTURE

PIPE	MATERIAL	UP STR	DOWN STR	UP INV	DOWNINV	LENGTH	SLOPE	NOTES
UD-1	4" Perforated	CO-1	CO-3	750.35	746.95	400	0.85%	AR705524
UD-2	4" Perforated	CO-2	CO-4	750.12	746.61	455	0.77%	AR705524
UD-3	4" Perforated	CO-3	CS-1	746.95	744.7	440	0.51%	AR705524
UD-4	4" Perforated	CO-4	CS-2	746.61	744.3	258	0.90%	AR705524
UD-5	4" PVC	CS-1	CS-2	744.7	744.3	108	0.37%	AR705544
UD-6	4" PVC	CS-2	IN-2	744.3	743.7	66	0.91%	AR705544
UD-7	4" Perforated	CO-5	CS-1	746.5	744.7	400	0.45%	AR705524
UD-8	4" Perforated	CO-6	CS-2	747.24	744.3	401	0.73%	AR705524
UD-9	4" Perforated	CO-7	CO-5	747.88	746.5	470	0.29%	AR705524
UD-10	4" Perforated	CO-8	CO-6	748.22	747.24	314	0.31%	AR705524
UD-11	4" Perforated	CO-8	CS-3	748.22	745	601	0.54%	AR705524
UD-12	4" Perforated	CO-9	CS-3	746.13	745	485	0.23%	AR705524
UD-13	4" PVC	CS-3	EIN-5	745	744.5	222	0.23%	AR705544
UD-14	4" Perforated	CO-9	EXIST	746.13	743.25	516	0.56%	AR705524
UD-15	4" Perforated	CO-10	CS-4	743.28	741.5	175	1.02%	AR705524
UD-16	4" PVC	CS-4	IN-4	741.5	741.01	55	0.89%	AR705544
UD-17	4" Perforated	CO-11	CS-4	742.75	741.5	400	0.31%	AR705524
UD-18	4" Perforated	CO-12	CO-11	743.75	742.75	415	0.24%	AR705524

PIPE	MATERIAL	UP STR	DOWN STR	UP INV	DOWN INV	LENGTH	SLOPE	NOTES
SS-1	12" RCP	IN-1	MH-1	743.7	743.53	32	0.53%	AR701512
SS-2	12" RCP	IN-2	IN-3	744.42	743.7	240	0.30%	AR701512
SS-3	21" RCP	FES-1	EIN-3	744	743.62	72	0.53%	AR701521
SS-4	12" RCP	IN-4	MH-2	741.01	740.5	96	0.53%	AR701512

FILE: CMI4347-1305902-CU104.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:12 PM

UN053

REVISIONS							
NUMBER	DATE						

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

AT FULL SCALE (34A22)

UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS BASE BID - REALIGN AND WIDEN TAXIWAY

DRAINAGE TABLES

© Copyright CMT, Inc.

CRAWFORD, MJRPHY & TILY, INC.
CONSULTING ENGNEERS
Locence No. 184-000613



DESIGN BY: CBG

DRAWN BY: ADD

CHECKED BY: CET


APPROVED BY: CET

DATE: JUNE 27, 2014

JOB No: 13059-02-00

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX


SHEET 36 OF 83 SHEETS



	DIMENSIONS - TABLE 1									
PIPE DIA.	APPROX WT.(lbs.)	WALL	А	В	С	D	Е	G	R	SLOPE
12"	530	2"	4"	2'-0"	4'-0 7/8"	6'-0 7/8"	2'-0"	2"	9"	3:1
15"	740	2 1/4"	6"	2'-3"	3'-10"	6'-1"	2'-6"	2 1/4"	11"	3:1
18"	990	2 1/2"	9"	2'-3"	3'-10"	6'-1"	3'-0"	2 1/2"	12"	3:1
21"	1280	2 3/4"	9"	2'-11"	3'-2"	6'-1"	3'-6"	2 3/4"	13"	3:1
24"	1520	3"	9 1/2"	3'-7 1/2"	2'-6"	6'-1 1/2"	4'-0"	3"	14"	3:1
27"	1930	3 1/4"	10 1/2"	4'-0"	2'-1 1/2"	6'-1 1/2"	4'-6"	3 1/4"	14 1/2"	3:1
30"	2190	3 1/2"	1'-0"	4'-6"	1'-7 3/4"	6'-1 3/4"	5'-0"	3 1/2"	15"	3:1
33"	3200	3 3/4"	1-1 1/2"	4'-10 1/2"	3'-3 1/4"	8'-1 3/4"	5'-6"	3 3/4"	17 1/2"	3:1
36"	4100	4"	1'-3"	5'-3"	2'-10 3/4"	8'-1 3/4"	6'-0"	4"	20"	3:1
42"	5380	4 1/2"	1'-9"	5'-3"	2'-11"	8'-2"	6'-6"	4 1/2"	22"	3:1
48"	6550	5"	2'-0"	6'-0"	2'-2"	8'-2"	7'-0"	5"	22"	3:1
54"	8240	5 1/2"	2'-3"	5'-5"	2'-11"	8'-4"	7'-6"	5 1/2"	24"	2.4:1
60"	8730	6"	2'-11"	5'-0"	3'-3"	8'-3"	8'-0"	5"	*	2:1
66"	10710	6 1/2"	2'-6"	6'-0"	2'-3"	8'-3"	8'-6"	5 1/2"	*	2:1
72"	12520	7"	3'-0"	6'-6"	1'-9"	8'-3"	9'-0"	6"	*	1.86:1
78"	14770	7 1/2"	3'-0"	7'-6"	1'-9"	9'-3"	9'-6"	6 1/2"	*	1.82:1
84"	18160	8"	3'-0"	7'-6 1/2"	1'-9"	9'-3 1/2"	10'-0"	6 1/2"	*	1.5:1
	* RADIUS AS FURNISHED BY MANUFACTURER.									

NOTES

- PRECAST CONCRETE FLARED END SECTIONS SHALL CONFORM TO THE APPLICABLE REQUIREMENTS OF AASHTO M-170 CLASS III, WALL B REINFORCED CONCRETE PIPE.
- 2. PRECAST CONCRETE FLARED END SECTION FOR PIPE DIAMETER REQUIRED SHALL BE AS INDICATED ON DETAIL PLAN FOR EACH INDIVIDUAL INSTALLATION.
- THE END BLOCK SHALL BE PLACED PRIOR TO THE INSTALLATION OF THE FLARED END SECTION. THE END BLOCK SHALL BE BACKFILLED IN ACCORDANCE WITH ITEM 701.



(I.D.O.T. STD. NO. 542301)

N.T.S.

FILE: CMI4347-1305902-CU501.dwg JPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:12 PM **UN053** REVISIONS NUMBER BY DATE THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22). C **TAXIWAY** WIDEN . UNIVERSITY OF ILLINOI WILLARD AIRPORT SAVOY, ILLINOIS DETAIL - REALIGN AND **DRAINAGE** В BASE

CRAWFORD, MAPPHY & TILLY, INC.
CONSULTING ENGINEERS
License No. 184-000613

DESIGN BY: CBG

DRAWN BY: ADD

CHECKED BY: CET

APPROVED BY: CET

DATE: JUNE 27, 2014


JOB No: 13059-02-00


IL. PROJ. NO. CMI-4347


AIP PROJ. NO. 3-17-0016-XX

SHEET 37 OF 83 SHEETS

:\ChampaignAp\1305902\Dra









1'-6" FINISHED GROUND 10" (PAVEMENT OR TURF) ITEM P-610 P.C.C. NON-PERFORATED P.V.C. PIPE (2)-#4 BARS TOP & BOTTOM CONNECTION TO 4" UNDERDRAIN SIDE VIEW

UNDERDRAIN CLEAN-OUT DETAIL - TYPE 2





UNDERDRAIN DIRECT TOP CONNECTION DETAIL

1'-10"

1'-8 1/2"

1'-11"

2'-4"

FRAME &

LID

OR APPROVED EQUAL)

NEW 4"

GROUT BASE TO PROVIDE

SMOOTH FLOW LINE AND

SLOPE FROM PERIMETER

PROVIDE WATERTIGHT

CONNECTIONS WITH

WATER SEALING GROUT

SEAL AT PIPE

GROUT UNDER

THICKNESS PER

NEW CLASS IV

CASING

STANDARD

R.C.P. OR EQUIVALENT

4" (MIN.)

THICKNESS

CONC.BASE

6" SAND

CUSHION

UNDERDRAIN COLLECTION STRUCTURE DETAIL

WITH WATER SEALING GROUT

UNDERDRAIN


PLAN

2'-0"


SIDE VIEW

- FINISHED GROUND SURFACE

NEENAH R-1690-A HEAVY DUTY MANHOLE FRAME WITH SOLID LID (OR APPROVED EQUAL)




TYPICAL UNDERDRAIN DETAIL - PAVEMENT EDGE



UNDERDRAIN CLEAN-OUT DETAILS

N.T.S.



TYPICAL UNDERDRAIN DETAIL - BELOW PAVEMENT

DURING UNDERDRAIN CONSTRUCTION, CARE SHALL BE TAKEN TO ENSURE GOOD DRAINAGE BETWEEN THE SUB-BASE AND THE POROUS BACKFILL MATERIAL WHICH WILL AFFECT DRAINAGE TO

- REALIGN AND WIDEN TAXIWAY **DETAILS** 7 OF ILLINOIS DAIRPORT ILLINOIS UNDERDRAIN UNIVERSITY (WILLARD / SAVOY, II BD BASE 2 CRAWFORD, CONSULTING CBG DESIGN BY: DRAWN BY ADD

CET

CET

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 39 OF 83 SHEETS

JUNE 27, 2014

13059-02-00

CHECKED BY


APPROVED BY:

JOB No:

REVISIONS


BY


DATE





NOTES


THE UNDERDRAIN SHALL BE REMOVED PRIOR TO THE PLACEMENT OF PROPOSED POROUS BACKFILL. ALL COST FOR THIS WORK SHALL BE CONSIDERED INCIDENTAL.























NOTES:

- CONNECT SIGN TO EXISTING LIGHT BASE. SPLICE INTO EXISTING CIRCUIT AT EXISTING LIGHT AR108258 2/C #8 CABLE.
- 2. SEE RGL DETAIL FOR MORE INFORMATION ON INSTALLING RGL UNITS.
- SEE AIRFIELD SIGNAGE DETAIL FOR SIGN LEGEND AND INSTALLATION DETAILS.
- 4. SEE PROPOSED LIGHT AND CABLING SHEET FOR CONTINUATION OF RGL
- 5. RELOCATE BASE MOUNTED LIGHT FROM PREVIOUSLY REMOVED EDGE LIGHT
- 6. CONNECT TO EXISTING EDGE LIGHT.
- 7. SIGNS 8, 9. AND 16 MAY BE CONSTRUCTED BY EXTENSION OF EXISTING PCC FOUNDATION AND INSTALLING SIGN ON LARGER FOUNDATION.
- 8. EXISTING SIGNS ARE LUMACURVE AND AGM ILUX. CONTRACTOR SHALL VERIFY PROPER SIGN MANUFACTURE DURING THE SHOP DRAWING SUBMITTALS. SIGNS MAY REQUIRE FULL OR PARTIAL REPLACEMENT ON FACES INDICATED IN LEGEND.

	THIS KEY MAP
┰	
l	
l	

FILE: CMI4347-1305902-EP401.dwg
UPDATE BY: Chris Groth
PLOT DATE: 7/10/2014 7:18 PM

CMI-V-AERL
CMI 1305902-V-AF2D

CMI-V-AERL CMI 1305902-V-AF2D CMI 1305902-C-SPAL UTILITY_CMI KEYMAP CMI 1305902-E-AL


UN053

REVISIONS					
NUMBER	BY	DATE			

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

ပ

SIGNAGE SCHEDULE							
SIGN NO.	SIDE	NEW LEGEND	WHITE ON BLACK	BLACK ON YELLOW	YELLOW ON BLACK	CHARACTERS	NOTES
7	N	←D C EÎ A Z B→		←D E↑A≯B→	С		REPLACE SIGN FACE
	s	С			С	8	AR800242
8	NE	∿D1 D		∖D1 D	D	4	NEW SIGN -
	sw	D			D	4	AR12544X
9	N	D 1			D 1	5	NEW SIGN -
	s	D1 ∠ D.7		∠ D.7	D 1	5	AR12544X
10	N	←EDA↑B↗C↘		←E A↑B⊅C↘	D	9	REPLACE SIGN FACE
	s	D			D	9	AR800242
11	E	∠A ^K BE CZ D ⅓		∠A NB CZ DN	E		NEW SIGN -
	w	E			E	9	AR12544X
12	NE	В			В	9	REPLACE SIGN FACE
	sw	←CND B EZAN		←CND EZAN	В	9	AR800242
13	E	∠ANBE CZ D ⅓		∠A NB CZ DN	Е	9	REPLACE SIGN FACE
	w	E			E	9	AR800242
14	N	A			Α	9	REPLACE SIGN FACE
	s	←B A C Z D Z E S		← B CZDZES	Α	9	AR800242
15	E	A 2 ←A→		← A →	A 2	-	NEW SIGN -
	w	A 2			A 2	5	AR12544X
16	N	А			Α	4	NEW SIGN -
	s	A A2→		A 2→	Α	4	AR12544X
17	NW SE	A5 →		A5 →		3	NEW SIGN - AR12544X
18		7.0		7.0 7			REMOVE SIGN




BASE BID - REALIGN AND WIDEN TAXIWAY RGL AND SIGN LOCATIONS



DESIGN BY:	CBG			
DRAWN BY:	ADD			
CHECKED BY:	CET			
APPROVED BY:	CET			
DATE:	JUNE 27, 2014			
JOB No:	13059-02-00			
II PROJ NO CMI-4347				

AIP PROJ. NO. 3-17-0016-XX

SHEET 46 OF 83 SHEETS




NOTES

1. THE LIGHT FIXTURE SHALL BE BONDED TO THE LIGHT BASE INTERNAL GROUND LUG VIA A #6 AWG STRANDED COPPER WIRE RATED FOR 600 VOLTS WITH GREEN XHHW INSULATION. THE GROUND WIRE LENGTH SHALL BE SUFFICIENT TO ALLOW THE REMOVAL OF THE LIGHT FIXTURE FROM THE LIGHT BASE FOR ROUTINE MAINTENANCE. SEE THE LIGHT FIXTURE MANUFACTURER'S INSTRUCTIONS FOR PROPER METHODS OF ATTACHING THIS BONDING WIRE.

- 2 LIGHT FIXTURES SHALL BE LED, TYPE L-861T (L), WITH HEATER.
- 3. LED EDGE LIGHTS WITH HEATERS SHALL BE L-830-17, 20/25 WATT OR L-830-1, 30/45 WATT, AS RECOMMENDED BY LIGHT FIXTURE MANUFACTURER.
- 4 ENTRANCES INTO L-867 BASES MUST BE PLUGGED FROM THE INSIDE WITH DUCT SEAL
- 5 THE TOLERANCE FOR THE HEIGHT OF RUNWAY/TAXIWAY EDGE LIGHTS MUST BE ± 1 INCH. THE TOLERANCE FOR THE LATERAL SPACING (LIGHT LANE TO RUNWAY/TAXIWAY CENTERLINE) OF RUNWAY/TAXIWAY EDGE LIGHTS MUST BE ± 1 INCH.
- 6 DIRECTION OF PRIMARY CABLES MUST BE IDENTIFIED BY COLOR CODING AS FOLLOWS: WHEN FACING LIGHT WITH BACK FACING PAVEMENT, CABLE TO THE LEFT IS CODED RED AND CABLE TO THE RIGHT IS CODED BLUE.
- 7 APPLY A CORROSION INHIBITING, ANTI-SEIZE COMPOUND TO ALL SCREWS, NUTS AND FRANGIBLE COUPLING THREADS. IF COATED BOLTS ARE USED PER ENGINEERING BRIEF #83, DO NOT APPLY ANTI-SEIZE COMPOUND.
- 8 ELECTRICAL INSULATING GREASE MUST BE APPLIED WITHIN THE L-830 ISOLATION TRANSFORMER SECONDARY TWO CONDUCTOR CONNECTORS TO PREVENT WATER ENTRANCE. THE CONNECTORS MUST NOT BE TAPED.

BASE MOUNTED EDGE LIGHT

N.T.S



FILE: CMI4347-1305902-EL501.dwg
UPDATE BY: Chris Groth
PLOT DATE: 7/10/2014 7:18 PM

UN053

REVISIONS

NUMBER BY DATE

0 1 2

THIS BAR IS EQUAL TO 2"
AT FULL SCALE (34X22).

CMT
WILLARD AIRPORT
SAVOY, ILLINOIS
License No. 184-000613

BASE BID - REALIGN AND WIDEN

ELECTRICAL DETAIL

Coccupied to the company of ILLINOIS

CONSULTIVE SYMPHY & TILY. NC.

BASE BID - REALIGN AND WIDEN

ELECTRICAL DETAIL

S

DESIGN BY: CBG

DRAWN BY: ADD

CHECKED BY: CET


APPROVED BY: CET

DATE: JUNE 27, 2014

JOB No: 13059-02-00

IL. PROJ. NO. CMI-4347
AIP PROJ. NO. 3-17-0016-XX

SHEET 47 OF 83 SHEETS




AND CONCRETE ENCASED DUCT LOCATIONS. THE INSTALLATION OF THE DUCT MARKERS SHALL BE INCIDENTAL TO THE DUCT BEING INSTALLED. TYPE, NUMBER OF DUCTS AND DUCT SIZE PRESTAMPED OR CHISELED ON THE JOB ELÉC. 4-3" <u>PLAN</u> TOP OF PAVEMENT - 1/16" TURF PAVEMENT ELECTRICAL DUCT NEW DUCT MARKER SHALL BE INSTALLED AT ALL DUCT NON CORROSIVE METAL DISK LOCATIONS PROPOSED AND (BRASS) œ CABLING AND DUCT PLAN MARKER PLACEMENT 15' DUCT MARKERS SHALL BE RECESSED

NEW DUCT MARKERS SHALL BE INSTALLED AT BOTH EDGES OF PAVEMENT AT ALL NEW DIRECTIONAL BORE, SPLIT DUCT,

$\underline{\text{IN PAVEMENT DUCT MARKER DETAIL}}_{\text{NTS}}$

SECTION


AND GROUTED INTO THE PAVEMENTS.



CONTRACTOR SHALL CUT THE #6 BARE COPPER WIRE AT EACH END OF THE NEW DUCT AND EXOTHERMICALLY WELD THE WIRE TO A 3/4" DIA. X 10" LONG GROUND ROD. THIS COST SHALL BE INCIDENTAL TO THE SPLIT DUCT INSTALLATION.

SPLIT DUCT DETAIL

N.T.S.




NOTES:

- CABLES SHALL NOT BE PLACED LESS THAN 24" DEEP IN ANY ONE TRENCH UNLESS PERMITTED BY ENGINEER.
- 2. WHERE PERMITTED, CONTRACTOR MAY INSTALL CABLE IN UNIT DUCT BY PLOWING METHOD.

CABLE TRENCH DETAIL


N.T.S.



N.T.S.

NOTES

- 1. DIMENSIONS SHOWN ARE MINIMUM.
- 2. TOP OF CONCRETE ENCASEMENT SHALL BE NOT LESS THAN 24" BELOW FINISHED SUBGRADE BELOW PAVEMENTS AND NOT LESS THAN 24" BELOW FINISHED GRADE IN UNPAVED AREAS, EXCEPT WHERE DIRECTED OTHERWISE BY ENGINEER. AVOID ALL CONFLICTS WITH OTHER UTILITIES (UNDERDRAINS, WATER LINES, SEWER LINES, TELEPHONE, ELECTRICAL) OR OTHER OBSTACLES, ADJUSTING DEPTH AS NECESSARY.
- 3. CONCRETE SHALL BE ITEM 610.
- 4. CONDUIT FOR CONCRETE ENCASEMENT SHALL BE SCHEDULE 40 PVC, 4" NOMINAL DIAMETER, OR AS INDICATED ON THE PLANS.
- 5. CONCRETE ENCASEMENT SHALL EXTEND A MINIMUM OF 5'-0" BEYOND EDGES OF PAVEMENT, OR AS SHOWN ON THE PLANS OR DIRECTED BY THE RESIDENT ENGINEER.
- 6. #4 REBAR SHALL BE INSTALLED CONTINUOUS THE LENGTH OF THE CONCRETE FNCASEMENT
- 7. DUCT BANK SHALL BE STACKED NO MORE THAN THREE CONDUITS HIGH UNLESS DIRECTED OTHERWISE BY THE RESIDENT ENGINEER.
- 8. AT ENDS OF DUCT BANKS, INSTALL A PVC COUPLING FLUSH WITH END OF CONCRETE FOR CONNECTING FUTURE CONDUIT. INSTALL POLYETHELENE PULL STRING, GREENLEE, OR EQUIVALENT. PLUG THE ENDS OF UNUSED SPARE CONDUITS WITH WOODEN PLUGS.
- 9. HIGH VOLTAGE WIRING, RUNWAY & TAXIWAY SERIES CIRCUIT WIRING, ETC., AND POWER WIRING OVER 480V SHALL BE INSTALLED IN SEPARATE CONDUITS FROM LOW VOLTAGE WIRING, 480V OR LESS.
- 10. IF POSSIBLE, INSTALL FIBER OPTIC CABLES AND COMMUNICATION CABLES (FAA, ETC.) IN THEIR OWN CONDUITS; OTHERWISE, INSTALL THEM IN THE CONDUITS WITH LOW VOLTAGE WIRING.



4-WAY DUCT BANK DETAIL

FILE: CMI4347-1305902-EL502.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:18 PM

UN053

911000						
REVISIONS						
NUMBER BY DAT						
0	1	2				

THIS BAR IS EQUAL TO 2"
AT FULL SCALE (34X22).

C

UNIVERSITY OF ILLINOIS
WILLARD AIRPORT
SAVOY, ILLINOIS
BASE BID - REALIGN AND WIDEN TAXIWAY
ELECTRICAL DETAILS 2

CAWFORD, MARPHY & TILLY, NC.
CONSULTING ENGNEERS
License No. 184-000613

DESIGN BY: CBG

DRAWN BY: ADD

CHECKED BY: CET


APPROVED BY: CET

DATE: JUNE 27, 2014

JOB No: 13059-02-00


IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 48 OF 83 SHEETS





INSTALLATION INSTRUCTIONS TO SUPPLEMENT THE MANUFACTURER'S INSTRUCTIONS

- 1. CLEAN THE CABLE THOROUGHLY 9" MIN. FROM THE END.
- 2. REMOVE INSULATION PER MANUFACTURER'S INSTRUCTIONS. DO NOT NICK THE CONDUCTOR. DO NOT PENCIL INSULATION ON L-824 TYPE C CABLE.
- 3. INSTALL PIN AND/OR RECEPTICAL WITH CRIMPING TOOL WHICH MUST BE COMPLETELY CLOSED BEFORE THE TOOL MAY BE REMOVED.
- 4. BE SURE CABLE AND CONDUCTOR FITTINGS ARE CLEAN. COAT THE CABLE INSULATION WITH INSULATION JELLY FROM THE CONNECTOR.
- 5. CAREFULLY INSERT CABLE INTO CONNECTOR TO THE PROPER DEPTH.
- 6. SLIP 14 INCH LENGTH OF HEAT SHRINK TUBING ON TRANSFORMER LEAD RAYCHEM TCS-13-14-U OR APPROVED EQUAL.
- 7. COMPLETE CONNECTION BY MATING THE PLUG AND RECEPTICAL. **CAUTION** BE SURE THE CABLE DOES NOT SLIP WHEN THE CONNECTION IS MADE.
- 8. APPLY RUBBER TAPE AND PLASTIC TAPE, ONE HALF LAPPED 1-1/2" ON EACH SIDE OF JOINT.
- 9. ANY CONNECTOR WHICH IS CONTAMINATED BY DIRT OR OTHER DELETERIOUS MATERIAL SHALL BE REMOVED NOT REINSTALLED.
- 10. CLEAN CONNECTOR AND CABLE INSULATION WITH WAX OR GREASE SOLVENT TO REMOVE SURFACE SILICONE JELLY.
- 11. WRAP SEALANT SECURELY AROUND THE CABLE. INSULATION TO EXTEND 1-1/2" BEYOND BOTH ENDS OF CONNECTORS. SEALANT SHALL BE RAYCHEM S-1052 (STRIPS) OR APPROVED EQUAL.
- 12. CENTER HEAT SHRINK OVER THE CONNECTOR. APPLY HEAT EVENLY BEGINNING AT THE CENTER AND WORKING AROUND CABLE TO ENDS. THERMOCHROMIC PAINT SHALL SHOW PROPER HEAT HAS BEEN USED. *** DO NOT OVER HEAT ***.
- 13. THE HEAT SOURCE SHALL BE AN ELECTRIC HEAT GUN OR A PROPANE WITH FLAME




FOR SPLICES IN HOMERUNS AND FOR EXTENSIONS TO EXISTING CABLES ONLY





TYPE C
FOR SPLICES AT RUNWAY LIGHTS,
TAXIWAY LIGHT AND SIGNS




TYPE D FOR SPLICES AT RUNWAY LIGHTS, TAXIWAY LIGHT AND SIGNS

NOTES:


- MATCH THE OUTSIDE DIAMETER OF CABLE INSIDE DIAMETER OF CONNECTOR SHALL PROPERLY
- WRAP WITH AT LEAST ONE LAYER OF RUBBER OR TAPE, ONE-HALF LAPPED, EXTENDING AT LEAST 1-1/2 INCHES ON EACH SIDE OF JOINT.

UN053 REVISIONS NUMBER BY DATE THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22). က OF ILLINOIS
AIRPORT
ILLINOIS S WIDEN ETAIL AND ECTRICAL UNIVERSITY (WILLARD A SAVOY, II REALIGN ᇳ \Box $\overline{\mathbf{a}}$ BASE CRAWFORD. CBG DESIGN BY: DRAWN BY ADD CET CHECKED BY: CET APPROVED BY: JOB No: 13059-02-00 IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX SHEET 49 OF 83 SHEETS

FILE: CMI4347—1305902—EL503.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:19 PM




ELEVATION VIEW



SECTION VIEW

NOTES:

 NO NEW HANDHOLES WILL BE INSTALLED AS PART OF THIS PROJECT. HANDHOLE DETAIL FOR INFORMATION ONLY.



DETAIL A

EXISTING ELECTRICAL HANDHOLE DETAILS

FILE: CMI4347-1305902-EL504.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:19 PM **UN053** REVISIONS BY DATE NUMBER THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22). ပ BASE BID - REALIGN AND WIDEN TAXIWAY UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS **ELECTRICAL DETAILS** TILLY, INC. CRAWFORD, I CONSULTING License No. 18 CBG DESIGN BY: ADD DRAWN BY: CHECKED BY: CET

CET

IL. PROJ. NO. CMI-4347

AIP PROJ. NO. 3-17-0016-XX

SHEET 50 OF 83 SHEETS


JUNE 27, 2014

13059-02-00

APPROVED BY:

DATE:

JOB No:



NEW RUNWAY GUARD LIGHT INSTALLATION (VOLTAGE POWERED)

NOTES:

- 1) L-804 RUNWAY GUARD LIGHT (RGL), MODE 2 (240V) WITH PHOTOCELL, NOT MONITORED, 100W/6.6A INCANDESCENT LAMPS, TRAFFIC SIGNAL YELLOW.
- 2) SPECIAL BASE PLATE, SUPPLIED WITH RUNWAY GUARD LIGHT.
- 3 L-867B LIGHT BASE.
- (4) CONCRETE.
- (5) CONNECTOR AND PIGTAIL, SUPPLIED WITH RUNWAY GUARD LIGHT
- 6 WATERPROOF TAPED SPLIT BOLT SPLICE (TYP. OF TWO).
- LIGHT BASE GROUND TERMINAL. CONNECT ALL GROUND WIRES TO HERE.
- 8 TWO #2 OR TWO #4 USE (240V), ONE #8 GROUND IN 1" UNIT DUCT. TO VAULT OR TO NEXT PAIR OF RUNWAY GUARD LIGHTS. SEE SITE PLAN FOR ADDITIONAL INFORMATION.
- TWO #12 USE (240V), ONE #12 GROUND. TO RUNWAY GUARD LIGHT ON OPPOSITE SIDE OF TAXIWAY, INCIDENTAL TO INSTALLATION OF RUNWAY GUARD LIGHTS.
- (10) PLUG ENTRANCES FROM INSIDE WITH DUCT SEAL.

L-804 RGL LIGHT FIXTURE (LED) TRAFFIC SIGNAL YELLOW EXISTING GROUND

L-804 RUNWAY GUARD LIGHT HORIZONTAL AIMING DETAIL

NOTE


CONTRACTOR SHALL AIM THE RGL UNITS 5 DEGREES UPWARD PER MANUFACTURER'S INSTRUCTIONS.

L-804 RUNWAY GUARD LIGHT INSTALLATION DETAILS BASE MOUNTED, 6.6 AMP SERIES CIRCUIT

RUNWAY GUARD LIGHT AIMING SCHEDULE					
PAIR NUMBER	L 4	A R	∡B		
1	23.3°	16.7°	5°		
2	18.2°	18.2°	5°		
3	14.4°	14.4°	5°		
4	10.5°	10.5°	5°		
5	10.5°	10.5°	5°		
6	16.7°	16.7°	5°		
7	10.5°	10.5°	5°		
8	10.5°	10.5°	5°		

NOTES:

- A A IS ANGLE UNIT SHOULD BE AIMED TOWARD TAXIWAY
 CENTERLINE AND IS SYMMETRICAL ABOUT THE TAXIWAY
 CENTERLINE.
- 4. B IS ANGLE UNIT SHOULD BE AIMED UPWARD FROM THE HORIZONTAL AND IS THE SAME FOR EACH UNIT IN EVERY PAIR OF RUNWAY GUARD LIGHTS.
- 3. LEFT (L) AND RIGHT (R) ARE DESIGNATED BY LOOKING TOWARD THE RUNWAY FROM THE HOLD SIDE OF THE HOLD LINE.
- 4. PAIR NUMBER IS DESIGNATED ON PROPOSED LIGHTING LAYOUT AND RGL AND SIGN LOCATIONS SHEETS.




FILE: CMI434 UPDATE BY: PLOT DATE: UN053	Chris Groth 7/10/2014	h 1-7:19 PM
O THIS B	1	2 AL TO 2"
UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS	RASE BID.	
CAMFORD MARPHY & TILLY, NC.	CONSULTING ENGINEERS License No. 184-000613	
DESIGN BY: DRAWN BY: CHECKED B	CBG ADD)

IL. PROJ. NO. CMI-4347

AIP PROJ. NO. 3-17-0016-XX

SHEET 51 OF 83 SHEETS



EXISTING VAULT PLAN N.T.S. EXISTING VAULT PLAN NOTES (1) EXISTING RUNWAY 18/36 REGULATOR, L-829, 10 KW, 480V INPUT, 3-STEP 6.6A OUTPUT. REMOVE EXISTING NAMEPLATE AND REPLACE WITH ENGRAVED NAMEPLATE MATCHING EXISTING, WHICH READS "SPARE #7".

② EXISTING DISTRIBUTION PANEL #1, SECTION #1. TURN OFF CIRCUIT BREAKER FOR RUNWAY 18/36. REVISE ALL PANELBOARD SCHEDULES AND LEGEND PLATES TO READ "SPARE #7".

<u>NOTES</u>

A. EXISTING POWER AND CONTROL WIRING TO EXISTING RUNWAY 18/36 REGULATOR SHALL REMAIN.

FILE: ELECTRICAL VAULT PLAN.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:19 PM

Base_Vault

UN053

)					
NUMBER	BY	DATE				
_						

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

AT FULL SCALE (34X22).

SAVOY, ILLINOIS BASE BID - REALIGN AND WIDEN TAXIWAY ELECTRICAL VAULT PLAN

© COPYIGN CMT. Inc.

CRAWFORD, MAPPHY & TLLY, INC.
CONSULTING ENGREERS
LICERS NO. 184-000613



DESIGN BY: CBG

DRAWN BY: ADD

CHECKED BY: CET


APPROVED BY: CET

DATE: JUNE 27, 2014

JOB No: 13059-02-00

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 53 OF 83 SHEETS




EXISTING BASE DISPLAY N.T.S.

- VISIBILITY-

NIGHT > 5

RWY / TXY



- BUNWAY SELECTOR

END 04

END 22

END 18


END 36

END 14R


END 32L

END 14L

END 32R



PROPOSED BASE DISPLAY N.T.S.



PROPOSED DROP DOWN DISPLAY

N.T.S.

ALCMS GRAPHIC DISPLAY NOTES

THE FOLLOWING GRAPHIC ELEMENTS SHALL BE REMOVED AND/OR MODIFIED ON THE TOUCH SCREEN GRAPHIC DISPLAY:

- AIRFIELD GRAPHIC DISPLAY

 A. REMOVE RUNWAY 18/36 AND CONNECTING TAXIWAYS
- B. REMOVE PAPI 18 C. REMOVE VASI 36

- RUNWAY SELECTOR DISPLAY A. REMOVE "END 18" BUTTON
- B. REMOVE "END 36" BUTTON
 C. CONSOLIDATE THE REMAINING BUTTONS ON THE DISPLAY AS SHOWN, TO PROVIDE ROOM FOR REVISED "TAXIWAY C"

- RWY/TXY DROP DOWN GRAPHIC DISPLAY

 A. REMOVE "RWY 18/36" BUTTON AND ASSOCIATED RUNWAY BRIGHTNESS BUTTONS "1", "2" AND "3".
 - B. REMOVE "PAPI 18" AND "VASI 36" BUTTONS.
 - C. CONSOLIDATE THE REMAINING BUTTONS ON THE "DROP DOWN" DISPLAY AS SHOWN.
- D. RELOCATE THE "RWY/TXY" MENU BUTTON ON THE DISPLAY AS SHOWN, TO PROVIDE ROOM FOR REVISED "TAXIWAY C"
- THE LEGENDS ON ALL THE BUTTONS SHALL BE MODIFIED AS NEEDED TO MATCH THE LEGENDS SHOWN IN THESE DISPLAYS.

ALCMS NOTES

—ALARM —

SILIENCE

GEN

BEACON

WIND

THE ALCMS SHALL OPERATE AS DESCRIBED IN THE SPECIFICATIONS. WHILE THE CONTROL WIRING FROM THE ALCMS PLC TO EXISTING RUNWAY 18/36 REGULATOR, NOW "SPARE #7" REGULATOR, SHALL REMAIN IN PLACE, AT NO TIME DURING THE OPERATION OF THE ALCMS SHALL THIS WIRING BECOME "ENERGIZED", FOR SAFETY REASONS.
THAT IS, WHILE THE PLC LOGIC FOR CONTROL OF THIS REGULATOR MAY
REMAIN IN PLACE, IT SHALL BE DISABLED OR BYPASSED.

FILE: ALCMS GRAPHIC DISPLAY MODIFICAT JPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:19 PM

UN053

REVISIONS					
NUMBER	BY	DATE			

THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22).

DISPLAY MODIFICATIONS ပ - REALIGN AND WIDEN TAXIWAY UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS **ALCMS GRAPHIC**

BASE BID


2 CRAWFORD, I





JOB No:


CBG DESIGN BY: DRAWN BY: ADD CHECKED BY: CET CET APPROVED BY: DATE: JUNE 27, 2014 13059-02-00


IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX



















NOTES:

- 1. THE DASH USED WITH 12' TALL NUMBERS AND LETTERS SHALL BE 2.1' TALL AND 1.8' WIDE.
- 2. THE NUMBERS AND LETTERS USED SHALL CONFORM IN STYLE AND APPEARANCE TO THOSE USED IN APPENDIX 1 OF THE FAA AIRPORT ADVISORY CIRCULAR 150/5340-1L.
- 3. ON A CURVED TAXIWAY, THE MARKING SHALL REMAIN PARALLEL TO THE HOLD LINE MARKING.
- 4. THE SURFACE PAINTED HOLDING POSITION MARKING SHALL BE 3' TO 10' FROM THE CENTER OF THE CENTERLINE AND AT LEAST 2' FROM THE EDGE OF THE TAXIMAY. THESE SHALL BE MEASURED TO THE CLOSEST CORNER OF THE SURFACE PAINTED HOLDING POSITION MARKING.





SURFACE PAINTED HOLDING POSITION SIGNS

FILE: CMI4347-1305902-CM501.dwg UPDATE BY: Chris Groth
PLOT DATE: 7/10/2014 7:23 PM

UN053

REVISIONS						
NUMBER	BY	DATE				

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).


BASE BID - REALIGN AND WIDEN TAXIWAY C SURFACE PAINTED HOLD POSITION MARKING DETAIL UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS


© CORVIGIN CONT. Inc. CRAWFORD, MURPHY & TLLY, INC. CONSULTING ENGINEERS License No. 184-000613	
	I


DESIGN BY:	CBG
DRAWN BY:	ADD
CHECKED BY:	CET
APPROVED BY:	CET
DATE:	JUNE 27, 2014
JOB No:	13059-02-00

IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX

SHEET 61 OF 83 SHEETS








VOR RECEIVER CHECK POINT SIGN

N.T.S.

NOTES:

- SIGN LEGEND WILL DEPEND ON THE EXACT LOCATION OF CHECKPOINT MARKING.
- CONTRACTOR SHALL VERIFY MARKING LAYOUT LOCATION AND SIGN LEGEND PRIOR TO CONSTRUCTING SIGN.



VOR RECEIVER CHECK POINT MARKER

N.T.S

NOTES:

- 1. ARROW IS TO BE ALIGNED TOWARD THE VORTAC.
- CIRCLE MAY BE BORDERED ON INSIDE AND OUTSIDE WITH A 6 INCHES BLACK BAND IF NECESSARY FOR CONTRAST.
- 3. REFER TO AC150/5340-18.

FILE: CMI4347-1305902-CM505.dwg
UPDATE BY: Chris Groth
PLOT DATE: 7/10/2014 7:24 PM
CMI-V-AERL
CMI 1305902-C-SPAL
CMI 1305902-C-MPSP

UN053

REVISIONS			
NUMBER	BY	DATE	
0	1	2	

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

ပ

WILLARD AIRPORT SAVOY, ILLINOIS BASE BID - REALIGN AND WIDEN TAXIWAY VORTAC CHECKPOINT DETAILS

CANT CRAWFORD. MARPHY & TILLY, INC. CONSULTING ENGNERS.
License No. 184-000613

DESIGN BY: CBG

DRAWN BY: ADD

CHECKED BY: CET


APPROVED BY: CET


DATE: JUNE 27, 2014


JOB No: 13059-02-00


IL. PROJ. NO. CMI-4347 AIP PROJ. NO. 3-17-0016-XX


SHEET 63 OF 83 SHEETS












SECTION


MANUFACTURERS:

- . NORTH AMERICAN GREEN
- WESTERN EXCELSIOR
- 3. APPROVED EQUAL




ELEVATION

<u>SILT FILTER FENCE AS A</u> PERIMETER EROSION BARRIER



SLICE METHOD



STRAW WATTLES

N.T.S.

FILE: CMI4347-1305902-CG501.dwg UPDATE BY: Chris Groth PLOT DATE: 7/10/2014 7:26 PM **UN053** REVISIONS BY NUMBER DATE THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22). ပ BASE BID - REALIGN AND WIDEN TAXIWAY **EROSION CONTROL DETAILS** UNIVERSITY OF ILLINOIS WILLARD AIRPORT SAVOY, ILLINOIS TILLY, INC. CRAWFORD, I CONSULTING License No. 18 CBG DESIGN BY: ADD DRAWN BY: CHECKED BY: CET CET APPROVED BY: JUNE 27, 2014 JOB No: 13059-02-00 IL. PROJ. NO. CMI-4347

AIP PROJ. NO. 3-17-0016-XX

SHEET 67 OF 83 SHEETS

