

INDEX OF SHEETS

| SHEET NO. | DESCRIPTION |
|-----------|--|
| 1 | COVER SHEET |
| 2 | INDEX OF SHEETS |
| 2 | LIST OF STANDARDS |
| 2 | GENERAL NOTES |
| 3 | LOCATION MAPS |
| 4 | SUMMARY OF QUANTITIES |
| 5-6 | EXISTING TYPICAL CROSS SECTIONS |
| 7 | SCHEDULE OF QUANTITIES |
| 8 | PLAN DETAIL FOR F.A.P. 804 / (PROSPECT AVE.) |
| 9 | PCC PARTIAL DEPTH HOT-MIX ASPHALT PATCHING |

LIST OF STANDARDS

| STANDARD NO. | NAME OF STANDARD |
|--------------|--|
| 000001-06 | STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS |
| 001001-02 | AREAS OF REINFORCEMENT BARS |
| 001006 | DECIMAL OF AN INCH AND OF A FOOT |
| 420001-07 | PAVEMENT JOINTS |
| 420701-02 | PAVEMENT FABRIC |
| 442101-07 | CLASS B PATCHES |
| 701501-06 | URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED |
| 701701-08 | URBAN LANE CLOSURE, MULTILANE INTERSECTION |
| 701901-02 | TRAFFIC CONTROL DEVICES |

GENERAL NOTES

G.N. -100
ENGLISH UNITS OF MEASUREMENT SHALL GOVERN OVER AND SUPERSEDE ANY METRIC UNITS SHOWN IN THIS CONTRACT. WHERE INCLUDED, METRIC UNITS ARE FOR INFORMATION ONLY.

G.N. -100A
ELECTRONIC FILES AND/OR ELECTRONIC SURVEY INFORMATION INCLUDING CADD FILES WILL NOT BE AVAILABLE TO THE CONTRACTOR.

G.N. -406H
Mixture Requirements

| Location | Prospect Ave. | Prospect Ave. |
|---------------------|-------------------------------------|--------------------------------------|
| Mixture Use | Partial Depth Patch (top 1 1/2") | * Partial Depth Patch (bottom 4") |
| AC/PG | SBS PG 70-22 | SBS PG 70-22 |
| RAP % (Max) | See RAP-RAS S.P. | See RAP-RAS S.P. |
| Design Air Voids | 4.0% @ Ndes=90 | 4.0% @ Ndes=90 |
| Mix Comp(Gradation) | IL 9.5 | IL 19.0 FG |
| Friction Aggregate | Mix D | N.A. |

* Polymer Mix D N90 may be used for the entire thickness of the partial depth patch at the contractor's option. If surface mix is used for the total thickness the maximum allowed lift will be 2".

G.N.-442B --PATCHING SCHEDULES
THE PATCHING SCHEDULES INCLUDED IN THE PLANES REPRESENT THE BEST INFORMATION AVAILABLE AT THE TIME OF COMPLETION OF THE PLANS FOR LETTING. VARIATIONS IN LOCATION AND SIZES OF BOTH FULL-DEPTH AND PARTIAL-DEPTH PATCHES MAY OCCUR.

G.N. 1004.01
COARSE AGGREGATE GRADATION CA-10 MAY BE USED WHENEVER COARSE AGGREGATE CA-6 IS SPECIFIED IN THE STANDARD SPECIFICATIONS.

NO COMMITMENTS

• F.A.P. 719 & F.A.P. 804

| | | | | | | | | | | | |
|---------------------------------------|-----------------------------|------------|-----------|---|---|---------------------------|--------------------|-----------|--------------|-----------|--|
| FILE NAME : | USER NAME : bakercr | DESIGNED - | REVISED - | STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION | INDEX OF SHEETS /LIST OF STANDARDS GENERAL NOTES | F.A.P. | SECTION | COUNTY | TOTAL SHEETS | SHEET NO. | |
| c:\pwork\pwidet\bakercr\10345555\0576 | 37-shs-gennote.dgn | DRAWN - | REVISED - | | | * | 05 PATCHING 2014-3 | CHAMPAIGN | 9 | 2 | |
| #MODELNAME# | PLOT SCALE = 40,0000' / in. | CHECKED - | REVISED - | | | CONTRACT NO. 70A37 | | | | | |
| | PLOT DATE = 5/22/2013 | DATE - | REVISED - | | | ILLINOIS FED. AID PROJECT | | | | | |
| | | | | | SCALE: | SHEET 1 OF 1 SHEETS | | STA. | TO STA. | | |