

**INDEX**

- 1 COVER SHEET
- 2 INDEX/STANDARDS/SIGNATURES/MIXTURE REQUIREMENTS
- 3 LOCATION MAP
- 4 SUMMARY & SCHEDULE OF QUANTITIES
- 5 PLAN VIEW - SUB-SURFACE DRAINS
- 6-7 TYPICAL SECTIONS
- 8 BUTT JOINT DETAIL

**STANDARDS**

- 442201-03 CLASS C & D PATCHES
- 601001-04 SUB-SURFACE DRAINS
- 701001-02 OFF-RD OPERATIONS, 2L, 2W, MORE THAN 15' (4.5 m) AWAY
- 701006-04 OFF-RD OPERATIONS, 2L, 2W, 15' (4.5 m) TO 24" (600 mm) FROM PAVEMENT EDGE
- 701201-04 LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS > 45 MPH
- 701301-04 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
- 701306-03 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS > 45 MPH
- 701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS DAY ONLY
- 701326-04 LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS >45 MPH
- 701901-02 TRAFFIC CONTROL DEVICES
- 780001-03 TYPICAL PAVEMENT MARKINGS
- 781001-03 TYPICAL APPLICATIONS, RAISED REFLECTIVE PAVEMENT MARKERS

<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS DISTRICT 6</b>	
EXAMINED <u>4/4</u> 20 <u>13</u>	
<u>Belmont</u> ENGINEER OF OPERATIONS	
EXAMINED <u>APRIL 3</u> 20 <u>13</u>	
<u>Jimmy F. [Signature]</u> ENGINEER OF PROJECT IMPLEMENTATION	
EXAMINED <u>April 3</u> 20 <u>13</u>	
<u>Laura A. Macnisk</u> ENGINEER OF PROGRAM DEVELOPMENT	

<b>MIXTURE REQUIREMENTS</b>			
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT			
MIXTURE USES (S):	SURFACE	PAVEMENT PATCHING	H.M.A SHOULDER
AC/PG:	PG 64-22	PG 64-22	PG 64-22
DESIGN AIR VOIDS:	4.0% @ N70	4.0% @ N70	4.0% @ N50
MIXTURE COMPOSITION:	IL 9.5	IL 19.0	IL 9.5
FRICTION AGGREGATE:	MIX C	N/A	MIX C