

ENTRANCE AND SIDEROAD SCHEDULE					
STATION	TYPE	PREP OF BASE	INCIDENTAL BIT SURF	AGG. TY B	SECTION
LT 707+08	BIT. F.E.	5.0 SQ YD	1.1 TON		B-B
LT 720+95	AGG. P.E.	7.0 SQ YD	1.6 TON		A-A
LT 724+75	WILLOW LANE OIL & CHIP S.R.	20.0 SQ YD	6.7 TON		B-B
RT 728+90	BIT. F.E.	6.3 SQ YD	1.4 TON		B-B
RT 738+09	OIL & CHIP S.R.	25.6 SQ YD	8.6 TON		B-B
LT 752+74	BIT. P.E.	5.0 SQ YD	1.1 TON		B-B
TOTAL		68.9 SQ YD	20.5 TON		

NOTES:

1. ENTRANCES AND SIDEROADS SHALL BE CONSTRUCTED ACCORDING TO THE SECTION INDICATED AND AS SHOWN ON SHEET 9.
2. MAILBOX TURNOUTS TO BE TREATED IN KIND.
3. STATIONS ARE APPROXIMATE.

PAVEMENT MARKING SCHEDULE				
STATION	TYPE	PAINT PVT MK LINE 5"		PAINT PVT MK LINE 6"
		WHITE	YELLOW	WHITE
LT & RT 697+21 TO 791+53	EDGE LINE	18,864 FT		
697+21 TO 791+53	SKIP DASH		2,358 FT	
DEDUCT FOR SIDEROADS	EDGE LINE	(402 FT)		
777+80	CROSSWALK			48 FT
TOTALS		18,462 FT	2,358 FT	48 FT

MIXTURE REQUIREMENTS			
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT			
MIXTURE USE(S):	BC BC SUPER IL-19.0 N50	BC SC SUPER "C" N50	INC BIT SURF SUPER N50
AC/PG	PG 64-22	PG 64-22	PG 64-22
RAP %: (MAX)	20%	15%	15%
DESIGN AIR VOIDS:	3.0% @ N DESIGN = 50	4.0% @ N DESIGN = 50	4.0% @ N DESIGN = 50
MIXTURE COMPOSITION:	IL-19.0	IL-9.5 OR 12.5	IL-9.5 OR 12.5
FRICTION AGGREGATE	N/A	MIX "C"	MIX "C"

SCHEDULES & QC/OA TABLES  
FAS 723 (NOKOMIS BLACKTOP)  
SECTION (17R)RS-5  
MONTGOMERY COUNTY