

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
70	*	FAYETTE	5	2
STA.		TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		
• 07 BIT RESURF 2007-1				

GENERAL NOTES

THIS SECTION SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE PLANS; THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" ADOPTED JANUARY 1, 2002; THE "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS" INDICATED ON THE CHECK SHEET, AND "THE SPECIAL PROVISIONS" INCLUDED IN THIS PROPOSAL.

THE WORK INCLUDED IN THIS SECTION CONSISTS OF THE REMOVAL OF THE EXISTING BITUMINOUS SURFACE AND THE PLACEMENT OF BITUMINOUS BINDER AND SURFACE COURSES ON THE WEIGH STATION RAMPS AT INTERSTATE 70 NEAR BROWNSTOWN AND ANY OTHER WORK NECESSARY TO COMPLETE THIS SECTION.

THE MATERIAL THAT IS REMOVED BITUMINOUS SURFACE REMOVAL WILL BECOME THE PROPERTY OF THE DEPARTMENT AND SHALL BE TRANSPORTED AND STOCKPILED AT THE VANDALIA YARD, NORTH OF VANDALIA OFF US ROUTE 51. THE CONTRACTOR SHALL CONTACT THE IDOT BUREAU OF OPERATIONS TO COORDINATE THE DELIVERY OF THIS MATERIAL.

THE CONTRACTOR WILL PROVIDE INTERNET ACCESSIBILITY TO THE BITUMINOUS PLANT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK SHALL BE INCLUDED IN THE COST OF ALL BITUMINOUS ITEMS.

THE CONTRACTOR WILL BE REQUIRED TO USE EITHER RC-70 OR SS-1HP AS THE BITUMINOUS MATERIALS PRIME COAT.

THE TOTAL QUANTITY OF THERMOPLASTIC PAVEMENT MARKING, LINE 4" CONSISTS OF 1463 FT. OF YELLOW AND 3815 FT. OF WHITE AND THE TOTAL QUANTITY OF THERMOPLASTIC PAVEMENT MRKING, LINE 8" CONSISTS OF 360 FT. OF WHITE.

THE FOLLOWING BITUMINOUS CONCRETE BINDER CSE., SUPERPAVE, IL-19.0, N105 MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

MIXTURE USE(S):	BINDER COURSE
PG GRADE:	SBS PG 76-22
RAP%:	0%
DESIGN AIR VOIDS:	4.0% @ NDESIGN = 105
MIXTURE COMPOSITION:	IL-19.0
FRICTION AGGREGATE:	N/A

THE FOLLOWING POLYMERIZED BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIXTURE D, N90 MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

MIXTURE USE(S):	SURFACE COURSE
AC/PG:	SBS PG 76-22
RAP%: (MAX)	0%
DESIGN AIR VOIDS:	4.0% @ NDESIGN = 105
MIXTURE COMPOSITION:	IL-9.5
(GRADATION MIXTURE)	
FRICTION AGGREGATE:	MIXTURE D

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	GENERAL NOTES & INDEX OF SHEETS
3	SUMMARY OF QUANTITIES
4	TYPICAL SECTIONS
5	PLAN SHEET

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED AFTER SHEET NUMBER 38

STD. NO.	DESCRIPTION
000001-04	STANDARD SYMBOLS, ABBREVIATIONS, PATTERNS
001006	DECIMAL OF AN INCH AND OF A FOOT
701400-02	APPROACH TO LANE CLOUSER, FREEWAY/EXPRESSWAY
701401-03	LANE CLOSURE, FREEWAY/EXPRESSWAY
701426-02	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPERATIONS
702001-06	TRAFFIC CONTRL DEVICES

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

INDEX OF SHEETS AND GENERAL NOTES

SCALE: VERT. DATE HORIZ.

DRAWN BY CHECKED BY