




CONTRACT NO. 97256








ANCHOR STUD DETAIL



VANE GRATE DETAIL



SECTION B-B

## Notes:

All cast iron parts shall be gray iron conforming to the requirements of AASHTO M 105, Class 35B.

Bolts, anchor studs, washers and nuts shall conform to the requirements of ASTM A 307 and shall be galvanized according to AASHTO M 232.

The grate, frame and downspout shall be galvanized according to AASHTO M 111 and ASTM A 385.
As an alternate, bolts, anchor studs, washers and nuts may be

As an alternate, bolts, anchor studs, washers and nuts may be stainless steel according to Article 1006.29(d) of the Standard Specifications.

Structural steel weldments of equal sections and of the same configuration may be substituted for cast iron. Fillet or full penetration welds shall be used for the weldments. Details shall be submitted to the Engineer for approval.

The Contractor shall take appropriate measures to assure that Protective Coat is not applied to the scupper.

Cost of the Grate, Frame, Downspout, Anchor Studs, Bolts, Washers and Nuts including complete installation of the scupper shall be paid for at the contract unit price each for Drainage Scupper, DS-11.

## BILL OF MATERIAL

ITEM	UNIT	QUANTIT
Drainage Scupper, DS-11	Each	8

DRAINAGE SCUPPER, DS-11
POWDER MILL ROAD OVER
EAST FORK OF WOOD RIVER
SECTION 03-00044-00-BR
VILLAGE OF EAST ALTON
STA. 13+10
STRUCTURE NO. 060-6400

*B* **4**₁

 $B \blacktriangleleft 1$ 

PLAN

1'-5'8"

1'-4"

1'-2"

1'-0"

34"

95<sub>8</sub>"

6"

7/2"

SECTION A-A

See sheet 9 of 17 for scupper location relative to parapet.

Drill and tap  $\frac{l_2}{2}$  -13 $x\frac{3}{4}$  DP. for  $\frac{l_2}{2}$   $\phi$  Anchor Studs

34"

4 locations

Ħ

**♣** 

Drill and tap scupper for 4  $I_2$ "  $\phi$  stainless steel hexagon

head bolts with lock washers