

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	SIGNATURE SHEET
3	INDEX OF SHEETS, HIGHWAY STANDARDS, & MIXTURE REQUIREMENTS
4	GENERAL NOTES AND MTD CROSSING RESTRICTIONS TABLE
5-6	SUMMARY OF QUANTITIES
7-8	TYPICAL SECTIONS
9-11	RESURFACING SCHEDULE
12-13	PAVEMENT MARKING SCHEDULE
14	STANDARD DETAIL: TEMPORARY HOT-MIX ASPHALT TRANSITIONS
15	STANDARD DETAIL: UNEVEN LANES SIGN
16	STANDARD DETAIL: ROUGH GROOVED SURFACE SIGN

HIGHWAY STANDARDS

000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001006	DECIMAL OF AN INCH AND OF A FOOT
442201-03	CLASS C and D PATCHES
701001-02	OFF-RD OPERATIONS, 2L, 2W, MORE THAN 15' (4.5 m) AWAY
701006-05	OFF-RD OPERATIONS, 2L, 2W, 15' (4.5 m) TO 24' (600 mm) FROM PAVEMENT EDGE
701011-04	OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701301-04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701306-03	LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS • 45 MPH
701311-03	LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY
701336-06	LANE CLOSURE, 2L, 2W, WORK AREAS IN SERIES, FOR SPEEDS • 45 MPH
701901-03	TRAFFIC CONTROL DEVICES
780001-04	TYPICAL PAVEMENT MARKINGS
781001-03	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

MIXTURE REQUIREMENTS SHALL BE PREPARED AS DIRECTED BELOW:

LOCATIONS	HOT-MIX ASPHALT SURFACE COURSE
MIXTURE USE(S):	HOT-MIX ASPHALT SURFACE COURSE, MIX C, N90
AC/PG:	PG64-22
ABR % (MAX):	SEE SPECIAL PROVISION
DESIGN AIR VOIDS:	4.0% , 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-9.5 MM
FRICITION AGGREGATE:	C SURFACE
QUALITY MANAGEMENT PROGRAM:	OCP

LOCATIONS	HOT-MIX ASPHALT LEVELING BINDER COURSE
MIXTURE USE(S):	HOT-MIX ASPHALT LEVELING BINDER, N90, IL-9.5MM FINE GRADE
AC/PG:	PG64-22
ABR % (MAX):	SEE SPECIAL PROVISION
DESIGN AIR VOIDS:	4.0% , 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-9.5MM FINE GRADE
FRICITION AGGREGATE:	NONE
QUALITY MANAGEMENT PROGRAM:	OCP

LOCATIONS	PAVEMENT PATCHING
MIXTURE USE(S):	HOT-MIX ASPHALT BINDER COURSE, N90, IL-19.0MM FINE GRADE
AC/PG:	PG64-22
ABR % (MAX):	SEE SPECIAL PROVISION
DESIGN AIR VOIDS:	4.0% , 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-19.0MM FINE GRADE
FRICITION AGGREGATE:	NONE
QUALITY MANAGEMENT PROGRAM:	OC/OA

FILE NAME *	USER NAME * #USER#	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	INDEX OF SHEETS, HIGHWAY STANDARDS, & MIXTURE REQUIREMENTS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
c:\pwork\p1dot\brandon\1033567417	040-sh1a-cvr_seq_index.dgn	DRAWN -	REVISED -			881	*	JOHNSON	16	3	
PLOT SCALE * 100.0000 1/1 in.	CHECKED -	REVISED -				CONTRACT NO. 78348					
MODELNAME#	PLOT DATE * 6/13/2014	DATE -	REVISED -			ILLINOIS FED. AID PROJECT					