

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	SIGNATURE SHEET
3	INDEX OF SHEETS, HIGHWAY STANDARDS, & MIXTURE REQUIREMENTS
4	GENERAL NOTES, COMMITMENTS, AND MTD CROSSING RESTRICTIONS TABLE
5-7	SUMMARY OF QUANTITIES
8-16	TYPICAL SECTIONS
17	PATCHING SCHEDULE
18	RESURFACING SCHEDULE
19	CURB RAMP SCHEDULE
20	PAVEMENT MARKING SCHEDULE
21	LEFT TURN LANE STRIPING DETAIL
22	STANDARD DETAIL: TEMPORARY HOT-MIX ASPHALT TRANSITIONS
23	STANDARD DETAIL: UNEVEN LANES SIGN
24	STANDARD DETAIL: ROUGH GROOVED SURFACE SIGN

HIGHWAY STANDARDS

- 000001-06 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
- 001006 DECIMAL OF AN INCH AND OF A FOOT
- 424001-07 PERPENDICULAR CURB RAMPS
- 424006-01 DIAGONAL CURB RAMPS
- 424011-01 CORNER PARALLEL CURB RAMPS
- 442201-03 CLASS C and D PATCHES
- 606001-05 CONC CURB TYPE B AND COMB CONC CURB AND GUTTER
- 701001-02 OFF-RD OPERATIONS, 2L, 2W, MORE THAN 15* (4.5 m) AWAY
- 701006-05 OFF-RD OPERATIONS, 2L, 2W, 15* (4.5 m) TO 24' (600 mm) FROM PAVEMENT EDGE
- 701011-04 OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY
- 701301-04 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
- 701306-03 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS \leq 45 MPH
- 701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY
- 701336-06 LANE CLOSURE, 2L, 2W, WORK AREAS IN SERIES, FOR SPEEDS \leq 45 MPH
- 701901-03 TRAFFIC CONTROL DEVICES
- 780001-04 TYPICAL PAVEMENT MARKINGS
- 781001-03 TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

MIXTURE REQUIREMENTS SHALL BE PREPARED AS DIRECTED BELOW:

LOCATIONS	HOT-MIX ASPHALT SURFACE COURSE
MIXTURE USE(S):	HOT-MIX ASPHALT SURFACE COURSE, MIX D, N90
AC/PG:	PG64-22
ABR % (MAX):	SEE SPECIAL PROVISION
DESIGN AIR VOIDS:	4.0 %, 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-9.5 MM
FRICTION AGGREGATE:	D SURFACE
QUALITY MANAGEMENT PROGRAM:	QCP

LOCATIONS	HOT-MIX ASPHALT LEVELING BINDER COURSE
MIXTURE USE(S):	HOT-MIX ASPHALT LEVELING BINDER, N90, IL-9.5MM FINE GRADE
AC/PG:	PG64-22
ABR % (MAX):	SEE SPECIAL PROVISION
DESIGN AIR VOIDS:	4.0 %, 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-9.5MM FINE GRADE
FRICTION AGGREGATE:	NONE
QUALITY MANAGEMENT PROGRAM:	QCP

LOCATIONS	PAVEMENT PATCHING
MIXTURE USE(S):	HOT-MIX ASPHALT BINDER COURSE, N90, IL-19.0MM FINE GRADE
AC/PG:	PG64-22
ABR % (MAX):	SEE SPECIAL PROVISION
DESIGN AIR VOIDS:	4.0 %, 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-19.0MM FINE GRADE
FRICTION AGGREGATE:	NONE
QUALITY MANAGEMENT PROGRAM:	QC/QA

LOCATIONS	HOT-MIX ASPHALT SHOULDERS
MIXTURE USE(S):	HOT-MIX ASPHALT SURFACE COURSE, MIX D, N90
AC/PG:	PG64-22
ABR % (MAX):	SEE SPECIAL PROVISION
DESIGN AIR VOIDS:	4.0 %, 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-9.5MM
FRICTION AGGREGATE:	C SURFACE
QUALITY MANAGEMENT PROGRAM:	QC/QA

FILE NAME *	USER NAME = #USER#	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	INDEX OF SHEETS, HIGHWAY STANDARDS, & MIXTURE REQUIREMENTS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
01\pwwork\pwwidot\stover\pg\04482025\2011-11-15\sta-evr_sog_index.dgn		DRAWN -	REVISED -			726	119(RS-1), 126(RS-1)	FRANKLIN	24	3
PLOT SCALE = 100.0000 * / in.		CHECKED -	REVISED -			CONTRACT NO. 78181				
PLOT DATE = 7/9/2014		DATE -	REVISED -			ILLINOIS FED. AID PROJECT				
#MODELNAME#				SCALE:	SHEET OF SHEETS	STA. TO STA.				