

PAVEMENT MARKING SCHEDULE

LOCATION STATION TO STATION	LENGTH	THERMOPLASTIC PAVEMENT MARKING				REMARKS
		LINE 4"				
		YELLOW			WHITE	
		DBL SOLID	SOLID	SKIP DASH	SOLID	
		FOOT	FOOT	FOOT	FOOT	
U. S. 45 (FAP 332)						
1094+61.6 AH TO 1095+52	90			23	180	
1095+52 TO 1101+90	638		638	160	1276	
1101+90 TO 1113+85	1195			299	2390	
1113+85. TO 1117+85	400		400	100	800	
1117+85 TO 1123+55	570	1140			1140	
1123+55 TO 1133+37	982		982	246	1964	
1133+37 TO 1139+82 BK	645			161	1290	
719+40 AH TO 783+60 BK	6420			1605	12840	
1204+20 AH TO 1208+27	407			102	814	
1208+27 TO 1217+23	896		896	224	1792	
1217+23 TO 1247+17 BK	2994	5988			5988	
881+99 TO 876+27	572	1143			1143	
876+27 TO 867+35	892		892	223	1784	
867+35 TO 859+75	760			190	1520	
859+75 TO 852+45	730		730	183	1460	
SUBTOTALS	18191	8271	4538	3514	36381	
TOTALS			52704			