



EXISTING LEGEND

- (A) HOT-MIX-ASPHALT PAVEMENT
- (B) COMBINATION CONCRETE CURB & GUTTER
- (C) PCC SIDEWALK

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

MIXTURE TYPE	AIR VOIDS
DRIVEWAYS	
HOT MIX ASPHALT SURFACE COURSE, MIX "D", N50(IL-9.5mm); 2"	4% @ 50 Gyr.
HOT MIX ASPHALT BASE COURSE, (HMA BINDER IL-19.0mm); 8" (3 LIFTS)	4% @ 50 Gyr.

NOTE:
THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURE QUANTITIES IS 112 LBS/SY/IN.

THE "AC-TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA, THE "AC-TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS. FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.

PREPARED BY:



FILE NAME = 06R26_02-TYPX-01 - IDO: TYPX 01

USER NAME =	DESIGNED -- DWS	REVISED --
	CHECKED -- PAP	REVISED --
PLOT SCALE =	DRAWN -- ACAD	REVISED --
PLOT DATE = 06/27/12	CHECKED -- ACAD	REVISED --

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PULASKI ROAD STREET LIGHTING TYPICAL CROSS SECTIONS	
SCALE:	SHEET NO. 3 OF 17 SHEETS STA. TO STA.

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
377B	06-00082-01-LT	COOK	17	3
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT HPP M-9003(774)			CONTRACT NO. 63726	