



TYPICAL DETOUR SIGN ASSEMBLY

SIGN NO. 14
SIGN NO. 12
SIGN NO. 6 TO 10

- LEGEND**
- SIGNALIZED INTERSECTION
 - W20-1 48 IN. x 48 IN. CONSTRUCTION WARNING SIGN, WITH AMBER FLASHING LIGHT. NUMBER DENOTES TYPE
 - M4-9 SERIES DETOUR SIGN WITH ROAD NAME AND DIRECTION PLATES. NUMBER DENOTES TYPE
 - OTHER DETOUR SIGNS NUMBER DENOTES TYPE
 - 2 TYPE III BARRICADES WITH AMBER FLASHING LIGHTS SEE SHEET 6
 - DETOUR ROUTE
 - CONSTRUCTION ZONE
 - NORTHBOUND WAGNER ROAD CLOSED BEGINNING MONTH __, 20__ PROVIDE ADVANCE NOTICE SIGN MINIMUM 72 HOURS PRIOR TO CLOSURE

TRAFFIC CONTROL NOTES

1. TRAFFIC CONTROL SHALL BE PERFORMED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, SECTION 900; APPLICABLE GUIDELINES IN THE FEDERAL MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS; AND THE APPLICABLE HIGHWAY STANDARDS FOR TRAFFIC CONTROL, UNLESS HEREIN REVISED.
2. EXISTING TRAFFIC CONTROL SIGNS AND DEVICES IN CONFLICT WITH TEMPORARY SIGNS WILL BE RELOCATED OR COVERED BY THE CONTRACTOR. AFTER THE TRAFFIC CONTROL REQUIREMENTS ARE MET OR AS AUTHORIZED BY THE ENGINEER RELOCATED SIGNS SHALL BE REINSTALLED AND COVERS REMOVED AS REQUIRED. ANY SIGNS OR DEVICES LEFT IN PLACE ARE TO BE PROTECTED FROM DAMAGE AND MAINTAINED BY THE CONTRACTOR.
3. TYPE I OR TYPE II BARRICADES WITH TWO WAY FLASHING LIGHTS SHALL BE REQUIRED AT ALL OPEN TRENCHES, EXCAVATIONS, OPEN OR EXPOSED SEWER STRUCTURES, TRANSVERSE PAVEMENT JOINTS, MATERIALS, OR EQUIPMENT WITHIN THE RIGHT OF WAY (NUMBER AND SPACING DEPENDS ON THE CONDITIONS); AND AT LOCATIONS DESIGNATED BY THE ENGINEER OR LOCAL LAW ENFORCEMENT AGENCIES.
4. THE CONTRACTOR SHALL PROVIDE ACCESS WITHIN THE RIGHT OF WAY FOR EMERGENCY VEHICLES ENTERING CONSTRUCTION AREAS AT ALL TIMES.
5. PEDESTRIAN ACCESS SHALL BE MAINTAINED AT ALL TIMES AND SEPARATED FROM CONSTRUCTION AREAS BY TEMPORARY CONSTRUCTION FENCE AS SHOWN ON THE PLANS OR APPROVED BY THE ENGINEER.
6. THE AVERAGE DAILY TRAFFIC THROUGH THE AREA POSTED FOR LOCAL ACCESS ONLY IS EXPECTED TO BE LESS THAN 100 VEHICLES. FLAGMEN ARE THEREFORE NOT REQUIRED UNLESS DIRECTED BY THE ENGINEER.

SCHEDULE OF QUANTITIES			SIGN NO.	SIGN TYPE	QUANTITY
1	DETOUR AHEAD	W20-2 (0) 48	1	4	
2	ROAD CLOSED AHEAD	W20-3 (0) 48	2	1	
3	ROAD CLOSED 500 FT	W20-3 (0) 48	3	1	
4	ROAD CLOSED	R11-1 6030	4	1	
5	ROAD CLOSED 700 FT AHEAD LOCAL TRAFFIC ONLY	R11-3 6030	5	2	
6	DETOUR	M4-9 (0) 3021	6	6	
7	DETOUR	M4-9R (0) 3021	7	2	
8	DETOUR	M4-9R (0) 3021	8	2	
9	DETOUR	M4-9L (0) 3021	9	2	
10	DETOUR	M4-9L (0) 3021	10	2	
11	END DETOUR	M4-8a (0) 2418	11	1	
12	WAGNER RD	SPECIAL (0)9 VARIABLE	12	20	
13	NORTHBOUND WAGNER ROAD CLOSED TO THRU TRAFFIC USE WILLOW RD	SPECIAL (0) 6030 5" BLACK LETTERS ON ORANGE BACKGROUND	13	4	
14	NORTH	M3-3 (0) 2412	14	15	
15	ROAD CONSTRUCTION AHEAD	W20-2 (0) 48	15	1	
16	SPEED LIMIT 20	R2-1 (0) 3648	16	1	
17	NO LEFT TURN	R3-1 (0) 2424	17	1	
18	ONE WAY	R6-1 (0) 3612	18	2	
19	DETOUR	R4-10 (0) 4818	19	2	
20	ROAD CLOSED	R5-1 (0) 3030	20	1	