TRAFFIC SIGNAL LEGEND

<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
ONTROLLER CABINET	\bowtie R		\blacksquare	EMERGENCY VEHICLE LIGHT DETECTOR	R ✓	≪	•	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
ILROAD CONTROL CABINET		R R	R B	CONFIRMATION BEACON	$R_{\circ - 0}$	o-()		COAVIAL CARLE		es es	
DMMUNICATIONS CABINET	C C	E C C	CC	HANDHOLE	R 🖂			COAXIAL CABLE			
ASTER CONTROLLER		EMC	MC	·	R	Processor of the Control of the Cont		VENDOR CABLE FOR CAMERA		(v)	<u> </u>
ASTER MASTER CONTROLLER	R	ЕММС	ММС	HEAVY DUTY HANDHOLE		H	H	COPPER INTERCONNECT CABLE.		/-	
NINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE	R SS			NO. 18 3 PAIR TWISTED, SHIELDED		-6-	-6-
ERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT	- <u>R</u>	- <u></u> -	- ■	JUNCTION BOX GALVANIZED STEEL CONDUIT	R 🕡	<u> </u>	0	FIBER OPTIC CABLE NO. 62.5/125, MM12F		—(12F)—	
ELEPHONE CONNECTION P) POLE OR (G) GROUND MOUNT	R	P	Ē	TEMPORARY SPAN WIRE, TETHER WIRE,	R			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		(24F)	—24F—
TEEL MAST ARM ASSEMBLY AND POLE	R O	O	•	AND CABLE				FIBER OPTIC CABLE NO. 62.5/125,		,	
LUMINUM MAST ARM ASSEMBLY AND POLE	R			COMMON TRENCH			СТ	(NUMBER OF FIBERS & TYPE TO BE NOTED ON PLANS)		1-5-	-
STEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH LUMINAIRE	RO-X	One Commencement	•	COILABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		S	ENC S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		c √∥—∘	^C ∥ ├ •
STEEL COMBINATION MAST ARM	R PTZ 1	Q	PIZM	INTERSECTION ITEM		I	ΙP	OR (S) SERVICE		11	4
ASSEMBLY AND POLE WITH PTZ CAMERA SIGNAL POST	R	O	•	REMOVE ITEM	R			CONTROLLER CABINET AND	RCF		
EMPORARY WOOD POLE (CLASS 5 OR	°O R_	⊗	⊗	RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED			
BETTER) 45 FOOT (13.7m) MINIMUM	$\overset{\mathbb{R}}{\otimes}$	V	•	ABANDON ITEM	А			STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
SUY WIRE	>R	>	\rightarrow	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	ALUMINUM MAST ARM POLE AND	RMF		
IGNAL HEAD	R -		-	12" (300mm) RED WITH 8" (200mm)		(R)		FOUNDATION TO BE REMOVED	O		
IGNAL HEAD CONSTRUCTION STAGES NUMBERS INDICATE THE CONSTRUCTION STAGE)			2	YELLOW AND GREEN TRAFFIC SIGNAL FACE			panamana	STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O-X		
SIGNAL HEAD WITH BACKPLATE	+CR	+->	+-	,		R	R	FOUNDATION TO BE REMOVED			
SIGNAL HEAD OPTICALLY PROGRAMMED			— > "P"	SIGNAL FACE			G +Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
FLASHER INSTALLATION S DENOTES SOLAR POWER)	R ○>''F''	O-⊳"F"	• → ″F″				 G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR			IS
PEDESTRIAN SIGNAL HEAD	R -	-0	-1			R	R	SAMPLING (SYSTEM) DETECTOR		[5]	S
PEDESTRIAN PUSHBUTTON DETECTOR	R (6)	©	•	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		G	Y G	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTION	OR	[P]	
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	· @APS	APS			4 6	◆ Y → G				
ILLUMINATED SIGN	R					"P"	"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR	TOR	ÎPPÎ	
"NO LEFT TURN"	S		•	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		ÓW W		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
ELLUMINATED SIGN 'NO RIGHT TURN''	8			12" (300mm) PEDESTRIAN SIGNAL HEAD				PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
DETECTOR LOOP, TYPE I				INTERNATIONAL SYMBOL, OUTLINED						<u>↓</u>	J
PREFORMED DETECTOR LOOP		ÎP Î	Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		(*	RAILROAD SYMBOLS			
MICROWAVE VEHICLE SENSOR	R M	(M)	∭ M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		● C 3 D	C * D			<u>EXISTING</u>	PROPOSED
/IDEO DETECTION CAMERA	R [V]J	[Ûþ	\bigcirc	RADIO INTERCONNECT	₩ ^R	##+0	 	RAILROAD CONTROL CABINET		R ≥R	B ∕ E
VIDEO DETECTION ZONE						1.		RAILROAD CANTILEVER MAST ARM	Σ	XOX X X	XeX X
	R			RADIO REPEATER	RERR	ERR	RR	FLASHING SIGNAL		XO X	X⊕X
PAN, TILT, ZOOM CAMERA	PTZ)1	PTZ)	1	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,						XOX	
WIRELESS DETECTOR SENSOR	RW	W	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED		/-	-	CROSSING GATE			X-X-
WIRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)	(1)	CROSSBUCK		>≥≤	*
USER NAME = kanthaphixa bw_work\PWIDOT\KANTHAPHIXAYBC\d0!126[4\traffic_legend_v7.dgn		DESIGNED - DAG/BCK DRAWN - BCK	REVISED -	CTATE	OF ILLINOI	s		DISTRICT 1	F.A. RTE.	SECTION	COUNTY TO
PLOT SCALE = 20.0000 '/		CHECKED - DAD	REVISED			TRANSPORTATION		STANDARD TRAFFIC SIGNAL DESIGN DETAILS SCALE: NONE		CONTRACT NO.	