

LEGEND

- BURIED CIRCUIT CONDUCTORS IN HDPE UNIT DUCT CONDUIT
- DIRECTIONAL BORE MINIMUM 48" BENEATH PAVED SURFACE
- PEDESTRIAN LIGHT, 15' HT. ** = CIRCUIT AND FIXTURE NUMBER
- STREET LIGHT, 30' HT. ** = CIRCUIT AND FIXTURE NUMBER
- GULFBOX, CAST IRON
- GULFBOX, COMPOSITE CONCRETE
- POWER PEDESTAL * = IDENTIFIER

NOTES


1. EXTEND DIRECTIONAL BORE BEYOND PAVEMENT EDGES BY 10' MIN.
2. PLACE COMPOSITE GULFBOX NEAR EXISTING GAZEBO FOR PUBLIC ADDRESS WIRING. EXACT LOCATION TO BE DETERMINED BY ENGINEER.

PEDESTRIAN LIGHT SCHEDULE

CIRCUIT & FIXTURE NO.	STATION	OFFSET
U.S. ROUTE 24		
A1	3+73.53	47.08' RT
A2	4+38.74	47.08' RT
LIBERTY STREET		
B5	12+73.77	58.58' LT
B6	13+38.83	58.58' LT
LAFAYETTE STREET		
B1	20+96.75	58.58' LT
B2	21+65.36	58.58' LT
B3	22+33.98	58.58' LT
B4	23+02.59	58.58' LT
WASHINGTON STREET		
A3	30+97.54	58.59' RT
A4	31+66.37	58.59' RT
A5	32+35.19	58.59' RT
A6	33+04.02	58.59' RT

STREET LIGHT SCHEDULE

CIRCUIT & FIXTURE NO.	STATION	OFFSET
U.S. ROUTE 24		
D2	6+02.30	23.58' RT
E1	2+12.27	24.46' LT
F1	3+09.37	35.58' RT
F3	4+06.13	30.08' LT
F4	5+15.08	27.08' LT
LIBERTY STREET		
A7	14+00.89	37.12' LT
C2	11+97.71	18.10' RT
C3	13+00.11	30.08' RT
D5	15+01.70	24.08' RT
E4	11+10.47	24.12' LT
LAFAYETTE STREET		
C1	22+99.59	37.12' LT
E2	20+85.73	20.11' RT
E3	22+00.87	30.09' RT
E5	24+00.84	24.59' RT
F2	20+11.29	22.15' LT
WASHINGTON STREET		
C4	34+02.06	28.13' RT
D1	31+03.46	15.06' LT
D3	32+12.64	30.09' LT
D4	33+15.02	18.10' LT
F5	30+12.25	22.00' LT



EXPIRES: 11/30/2011

Thomas Memminger
 THOMAS MEMMINGER
 ELECTRICAL ENGINEER
 8/11/2010
 DATE

FILE NAME =	USER NAME = #USER#	DESIGNED - TM	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	LIGHTING PLAN LAYOUT			F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
#FILEA#		DRAWN - RAH	REVISED -		N/A	05-00017-00-FP	SCHUYLER	49	28			
		CHECKED - TM	REVISED -		SCALE: 1" = 30' SHEET NO. 28 OF 49 SHEETS STA. TO STA.			CONTRACT NO. 93541				
		DATE -	REVISED -		FED. ROAD DIST. NO. [ILLINOIS] FED. AID PROJECT							