



- * Slab information not shown for clarity. See sheet 3 and sheet 4 of 13 for slab information.
- ** Epoxy grout #5 v(E) bars in 7/8" ϕ drilled holes. See Art. 584 Std. Specs. Cost included with Reinforcement Bars, Epoxy Coated.
- *** Secure bars such that they remain centered and level during pouring of the concrete.

SOUTH ABUTMENT ELEVATION (SHOWING CONCRETE PLACEMENT)
NORTH ABUTMENT SIMILAR

MIN. BAR LAP
 #6 bar = 3'-4"

Notes:

- Reinforcement bars are billed with superstructure on sheet 6 of 13.
- Concrete is included with Concrete Superstructure on sheet 6 of 13.
- For details of bars s(E) see sheet 6 of 13.
- The s(E) bars shall be placed parallel to the beams. Spacing for these bars shall be at right angles to the beams.
- For Bar Splicer Details, See sheet 13 of 13
- Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction.
- Bars indicated thus 4x2 #6 etc. indicate 4 lines of bars with 2 lengths per line.
- For Section B-B & C-C see sheet 5 of 13

DESIGNED <i>RAD</i>	EXAMINED _____	DATE - _____	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	IL RTE 83 AT SALT CREEK ABUTMENT PLACEMENT ELEVATION (S.N. 022-0045)	F.A.P. RTE. 344	SECTION 543-X-B-1-2	COUNTY DUPAGE	TOTAL SHEETS 31	SHEET NO. 11	
CHECKED <i>RB</i>	ENGINEER OF STRUCTURAL SERVICES	REVISOR _____			CONTRACT NO. 60T76					
DRAWN <i>RAD</i>	PASSED _____	REVISOR _____			SHEET NO. 8 OF 13 SHEETS					
CHECKED <i>JAM</i>	ENGINEER OF BRIDGES AND STRUCTURES	REVISOR _____			ILLINOIS FED. AID PROJECT					