ROADWAY SCHEDULE

LOCATION	STATION	TO	STATION	TREE TRUNK PROTECTION	TREE ROOT PRUNING	TREE PRUNING (1 TO 10 INCH DIAMETER)	TREE PRUNING (OVER 10 INCH DIAMETER)	GEOTECHNICAL FABRIC FOR GROUND STABILIZATION	AGGREGATE SUBGRADE IMPROVEMENT	SUBBASE GRANULAR MATERIAL, TYPE B, 4"	SUBBASE GRANULAR MATERIAL, TYPE B, 6"	PORTLAND CEMENT CONCRETE BASE COURSE 9"	HIGH-EARLY-STRENGTH PORTLAND CEMENT CONCRETE BASE COURSE 9"	BITUMINOUS MATERIALS (PRIME COAT)	AGGREGATE (PRIME COAT)	HOT-MIX ASPHALT BINDER COURSE, IL-19.0 N70	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70	PAVEMENT FABRIC	PROTECTIVE COAT	BRIDGE APPROACH PAVEMENT CONNECTOR (FLEXIBLE)	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 8 INCH	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	PORTLAND CEMENT CONCRETE SIDEWALK 8 INCH	CONCRETE CURB, TYPE B (SPECIAL) (CDOT)	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24	CONCRETE MEDIAN SURFACE, 4 INCH	IMPACT ATTENUATORS (FULLY REDIRECTIVE, NARROW), TEST LEVEL 3
				EACH	EACH	EACH	EACH	SQ YD	CU YD	SQ YD	SQ YD	SQ YD	SQ YD	TON	TON	TON	TON	SQ YD	SQ YD	SQ YD	SQ YD	SQ FT	SQ FT	FOOT	FOOT	SQ FT	EACH
HALSTED STREET	3830+15.00	TO	3839+05.00	-	-	-	-	3639	145	-	3291	3048	-	1.3	7	384	314	3048	731	71	23	5871.0	1832.5	-	-	-	-
HARRISON STREET	7807+25.00	TO	7811+33.00	-	-	-	-	137	30	-	314	248	-	0.2	1	32	25	248	308	39	118	1279.2	-	85.9	-	-	-
I-290 WESTBOUND				-	-	-	-	-	-	437	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
I-290 EASTBOUND				-	-	-	-	-	-	605	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
I-90/94 SOUTHBOUND				-	-	-	-	-	-	143	-	-	-	-	-	-	-	-	241	-	-	-	-	-	-	-	-
RAMP ES	105+51.22	TO	110+50.00	6	6	2	4	-	-	1195	-	-	-	-	-	-	-	-	-	-	-	-	-	-	273	-	1
RAMP ES	110+50.00	TO	112+95.78	-	-	-	-	-	-	329	-	-	-	-	-	-	-	-	547	-	-	-	-	-	-	-	-
RAMP SW				5	5	3	2	-	-	303	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	770	-
RAMP NW				-	-	-	-	-	-	134	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
RAMP EN				-	-	-	-	-	-	62	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1
HIGH-EARLY-STRENGTH PCC BASE CSE 9" (ASSUME 10% OF HALSTED ST PCC BASE CSE 9")				-	-	-	-	-	-	-	-	-305	305	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ROUNDED TOTAL				11	11	5	6	3777	175	3208	3605	2991	305	1.5	8	416	339	3296	1827	110	141	7150.5	1832.5	86	273	770	2

LOCATION	STATION	TO	STATION	CHAIN LINK FENCE, 6'	CHAIN LINK FENCE, 8'	CHAIN LINK GATES, 6' X 8' DOUBLE	CHAIN LINK GATES, 8' X 10' DOUBLE	SAND CUSHION, 4 INCH, (CDOT)	DETECTABLE WARNINGS (SPECIAL)	ORNAMENTAL FENCE, WROUGHT IRON	SELECT GRANULAR BACKFILL, SPECIAL	COMBINATION CURB AND GUTTER TYPE B V.12 (CDOT)	CONCRETE MEDIAN (SPECIAL)	TEMPORARY PAVEMENT	CONCRETE BARRIER, SINGLE FACE, 42 INCH HEIGHT	CONCRETE BARRIER TRANSITION	CONCRETE BARRIER BASE	CONCRETE BARRIER BASE (SPECIAL)	CONCRETE BARRIER WALL (SPECIAL)	CONCRETE BARRIER TRANSITION (SPECIAL)	BARRIER WALL MARKERS, TYPE C	TEMPORARY CONCRETE BARRIER (TO REMAIN PERMANENTLY)	CONSTRUCTION ACCESS	TEMPORARY CHAIN LINK FENCE
				FOOT	EACH	EACH	EACH	SQ FT	SQ FT	FOOT	CU YD	FOOT	SQ YD	SQ YD	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	EACH	FOOT	EACH	FOOT
HALSTED STREET	3830+15.00	TO	3839+05.00	-	-	-	-	7704	160	118	-	761	252	-	-	-	-	-	-	-	-	-	-	-
HARRISON STREET	7807+25.00	TO	7811+33.00	-	14	-	1	1280	-	-	-	95	-	85	-	-	-	-	-	-	-	-	1	310
I-290 WESTBOUND				-	-	-	-	-	-	-	-	-	-	416	72	24	96	-	-	-	2	-	-	-
I-290 EASTBOUND				-	-	-	-	-	-	-	-	-	-	553	72	37	109	70	40	30	4	-	-	-
I-90/94 SOUTHBOUND				-	-	-	-	-	-	-	-	-	-	137	78	30	108	-	-	-	3	-	-	-
RAMP ES	105+51.22	TO	110+50.00	-	-	-	-	-	-	-	-	-	-	1149	106	77	183	12	12	-	10	87.5	-	-
RAMP ES	110+50.00	TO	112+95.78	117	-	1	-	-	-	-	-	-	-	308	202	42	244	-	-	-	5	-	-	-
RAMP SW				-	-	-	-	-	-	-	120	-	-	176	-	-	-	317	272	45	6	-	-	-
RAMP NW				-	-	-	-	-	-	-	-	-	-	134	-	-	-	-	-	-	-	-	-	-
RAMP EN				-	-	-	-	-	-	-	-	-	-	-	-	-	-	154	124	30	9	87.5	-	-
HIGH-EARLY-STRENGTH PCC BASE CSE 9" (ASSUME 10% OF HALSTED ST PCC BASE CSE 9")				-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ROUNDED TOTAL				117	14	1	1	8984	160	118	120	856.5	252	2958	530	210	740	553	448	105	39	175	1	310

FILE PATH = j:\388837\portal\aecomonline\local\PWECOMDN\Documents\01 Americas\Transportation\60296938 Circle Phase II\000 CAD\026 Roadway\Sheets\D168w26-sht-Schedule-02