



**CAMBER DIAGRAM**

**\*TOP OF GIRDER WEB ELEVATIONS (E.B.)**

Location	℄ Brg. W. Abut.	℄ Splice 1	℄ Splice 2	℄ Brg. Pier	℄ Splice 3	℄ Splice 4	℄ Brg. E. Abut.
Girder 1	710.10	710.16	710.71	710.94	711.17	711.88	712.20
Girder 2	710.24	710.30	710.85	711.08	711.31	712.02	712.34
Girder 3	710.36	710.42	710.97	711.20	711.43	712.14	712.46
Girder 4	710.26	710.33	710.88	711.11	711.34	712.04	712.37
Girder 5	710.13	710.20	710.74	710.97	711.20	711.91	712.24
Girder 6	709.97	710.04	710.58	710.81	711.04	711.75	712.08

\*For fabrication use only.

**\*TOP OF GIRDER WEB ELEVATIONS (W.B.)**

Location	℄ Brg. W. Abut.	℄ Splice 1	℄ Splice 2	℄ Brg. Pier	℄ Splice 3	℄ Splice 4	℄ Brg. E. Abut.
Girder 7	709.97	710.04	710.58	710.81	711.04	711.75	712.08
Girder 8	710.13	710.20	710.74	710.97	711.20	711.91	712.24
Girder 9	710.26	710.33	710.88	711.11	711.34	712.04	712.37
Girder 10	710.36	710.42	710.97	711.20	711.43	712.14	712.46
Girder 11	710.24	710.30	710.85	711.08	711.31	712.02	712.34
Girder 12	710.10	710.16	710.71	710.94	711.17	711.88	712.20

\*For fabrication use only.

		0.4 Sp. 1 or 0.6 Sp. 2	Pier
$I_s$	(in <sup>4</sup> )	184991	264204
$I_c(n)$	(in <sup>4</sup> )	309073	404536
$I_c(3n)$	(in <sup>4</sup> )	239549	323073
$I_c(cr)$	(in <sup>4</sup> )	—	282916
$S_s$	(in <sup>3</sup> )	4204	5871
$S_c(n)$	(in <sup>3</sup> )	5006	6701
$S_c(3n)$	(in <sup>3</sup> )	4624	6279
$S_c(cr)$	(in <sup>3</sup> )	—	6656
DC1	(k/')	1.366	1.529
M <sub>DC1</sub>	(k)	4189.2	8340.7
DC2	(k/')	0.173	0.173
M <sub>DC2</sub>	(k)	541.7	1044.9
DW	(k/')	0.383	0.383
M <sub>DW</sub>	(k)	1199.2	2313.2
$M\ell + IM$	(k)	3902.3	4210.0
$M_u$ (Strength I)	(k)	14541.5	22569.2
$\phi_r M_n$	(k)	24475.9	26246.9
$f_s$ DC1	(ksi)	12.0	17.0
$f_s$ DC2	(ksi)	1.4	1.9
$f_s$ DW	(ksi)	3.1	4.2
$f_s$ ( $\ell + IM$ )	(ksi)	9.4	7.6
$f_s$ (Service II)	(ksi)	28.6	33.0
$0.95R_n F_y f$	(ksi)	47.5	47.5
$f_s$ (Total)(Strength I)	(ksi)	—	43.2
$\phi_r F_n$	(ksi)	—	50.0
$V_r$	(k)	68.4	65.5

	Abutments	Pier
$R_{DC1}$	(k) 103.7	375.1
$R_{DC2}$	(k) 13.7	46.9
$R_{DW}$	(k) 30.4	103.9
$R\ell + IM$	(k) 118.9	253.9
$R_{Total}$	(k) 266.7	779.8

$I_s, S_s$ : Non-composite moment of inertia and section modulus of the steel section used for computing  $f_s$  (Total-Strength I, and Service II) due to non-composite dead loads (in<sup>4</sup> and in<sup>3</sup>).

$I_c(n), S_c(n)$ : Composite moment of inertia and section modulus of the steel and deck based upon the modular ratio, "n", used for computing  $f_s$  (Total-Strength I, and Service II) in uncracked sections due to short-term composite live loads (in<sup>4</sup> and in<sup>3</sup>).

$I_c(3n), S_c(3n)$ : Composite moment of inertia and section modulus of the steel and deck based upon 3 times the modular ratio, "3n", used for computing  $f_s$  (Total-Strength I, and Service II) in uncracked sections, due to long-term composite (superimposed) dead loads (in<sup>4</sup> and in<sup>3</sup>).

$I_c(cr), S_c(cr)$ : Composite moment of inertia and section modulus of the steel and longitudinal deck reinforcement, used for computing  $f_s$  (Total-Strength I and Service II) in cracked sections, due to both short-term composite live loads and long-term composite (superimposed) dead loads (in<sup>4</sup> and in<sup>3</sup>).

DC1: Un-factored non-composite dead load (kips/ft.).  
M<sub>DC1</sub>: Un-factored moment due to non-composite dead load (kip-ft.).  
DC2: Un-factored long-term composite (superimposed excluding future wearing surface) dead load (kips/ft.).  
M<sub>DC2</sub>: Un-factored moment due to long-term composite (superimposed excluding future wearing surface) dead load (kip-ft.).  
DW: Un-factored long-term composite (superimposed future wearing surface only) dead load (kips/ft.).  
M<sub>DW</sub>: Un-factored moment due to long-term composite (superimposed future wearing surface only) dead load (kip-ft.).  
 $M\ell + IM$ : Un-factored live load moment plus dynamic load allowance (impact) (kip-ft.).  
 $M_u$  (Strength I): Factored design moment (kip-ft.).  
 $1.25 (M_{DC1} + M_{DC2}) + 1.5 M_{DW} + 1.75 M\ell + IM$   
 $\phi_r M_n$ : Compact composite positive moment capacity computed according to Article 6.10.7.1 or non-slender negative moment capacity according to Article A6.1.1 or A6.1.2 (kip-ft.).  
 $f_s$  DC1: Un-factored stress at edge of flange for controlling steel flange due to vertical non-composite dead loads as calculated below (ksi).  
 $M_{DC1} / S_{nc}$   
 $f_s$  DC2: Un-factored stress at edge of flange for controlling steel flange due to vertical composite dead loads as calculated below (ksi).  
 $M_{DC2} / S_c(3n)$  or  $M_{DC2} / S_c(cr)$  as applicable.  
 $f_s$  DW: Un-factored stress at edge of flange for controlling steel flange due to vertical composite future wearing surface loads as calculated below (ksi).  
 $M_{DW} / S_c(3n)$  or  $M_{DW} / S_c(cr)$  as applicable.  
 $f_s$  ( $\ell + IM$ ): Un-factored stress at edge of flange for controlling steel flange due to vertical composite live load plus impact loads as calculated below (ksi).  
 $M\ell + IM / S_c(n)$  or  $M_{DW} / S_c(cr)$  as applicable.  
 $f_s$  (Service II): Sum of stresses as computed below (ksi).  
 $f_{sDC1} + f_{sDC2} + f_{sDW} + 1.3 f_s (\ell + IM)$   
 $0.95R_n F_y f$ : Composite stress capacity for Service II loading according to Article 6.10.4.2 (ksi).  
 $f_s$  (Total)(Strength I): Sum of stresses as computed below on non-compact section (ksi).  
 $1.25 (f_{sDC1} + f_{sDC2}) + 1.5 f_{sDW} + 1.75 f_s (\ell + IM)$   
 $\phi_r F_n$ : Non-Compact composite positive or negative stress capacity for Strength I loading according to Article 6.10.7 or 6.10.8 (ksi).  
 $V_r$ : Maximum factored shear range in span computed according to Article 6.10.10.

PRE-FINAL