



# Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

October 30, 2019

SUBJECT: PARK ROAD  
Section LAKE AQUA NA 2018  
Stephenson County  
Contract No. 46906  
Item No. 60, November 8, 2019 Letting  
Addendum A

## NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised the Schedule of Prices.
2. Revised page 6 of the Special Provisions.
3. Revised sheets 3 and 12 of the Plans.

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read 'Jack A. Elston'.

Jack A. Elston, P.E.  
Bureau Chief, Design and Environment

### **ABANDON AND FILL EXISTING SANITARY SEWER**

This work shall consist of the abandonment and filling of the existing sanitary sewers at the locations shown in the plans with a controlled low strength material. Prior to filling the sanitary sewers, the Contractor shall plug each end of the sanitary sewers to the satisfaction of the Engineer.

The material used to fill the sanitary sewers shall conform to Section 1019 of the Standard Specifications. The intent of this mixture is to create a material with a plastic or fluid like consistency that is workable enough to take the shape of all the dimensions of the sanitary sewers. The yield strength of the material is unimportant.

The mixture shall be pumped or chuted into the sanitary sewers from the upstream end with the seals sequenced to provide the flow and release of air as the sanitary sewers are filled. The controlled low strength material shall be injected into the sanitary sewers until it completely fills the sanitary sewers.

Equipment and methods used to perform this work shall meet the approval of the Engineer.

This work shall be paid for at the contract unit price Each for ABANDON AND FILL EXISTING SANITARY SEWER which price shall include all labor, equipment and materials necessary to complete the work as herein specified.

### **AGGREGATE SURFACE COURSE, TYPE B SPECIAL**

This item shall consist of the installation of aggregate surface course materials in accordance with the details shown in the plans and Sections 351 and 402 of the Standard Specifications. The material used for the bottom surface course shall be CA6 in accordance with Article 1004.01 of the Standard Specifications. The material used for the top surface course shall consist of limestone screenings. The gradation of the material shall be FA20 or FA21 in accordance with Article 1003.01 of the Standard Specifications.

This work shall consist of blending the surface of the existing aggregate camp site pads to a depth of 2 inches with the additional bottom aggregate surface course materials prior to the placement and compaction of the top aggregate surface course materials in accordance with Section 351 of the Standard Specifications and this special provision. The blending shall be accomplished by disking, or other methods approved by the Engineer, to sufficiently break down oversized clods, mix the different materials, secure a uniform moisture content, and ensure uniform density and compaction. After placement of the aggregate surface course materials, the aggregate materials shall be compacted in accordance with Article 351.05 (b) of the Standard Specifications.

This work will be paid for at the contract unit price per Sq. Yd. for AGGREGATE SURFACE COURSE, TYPE B SPECIAL which price shall include all labor, materials, and equipment needed to complete the work as specified above.