



- GENERAL NOTES:**
1. Installation shall conform to IDOT Highway Standard 781001-02 (or latest) for marker placement.
 2. IDOT Standard 781001-02 shall be modified to reflect recessed pavement markers instead of raised pavement markers.

RECESSED REFLECTIVE PAVEMENT MARKERS

- INSTALLATION NOTES:**
1. Saw cut to dimensions shown.
 2. Sawcut areas to be dry and free of material that adversely affects the adhesive bond.
 3. Install the reflector with an approved two-component epoxy adhesive. Epoxy should not obscure or block the lens.
 4. Install top of reflector +/- 3/8 inch below the pavement surface.
 5. Reflector shall be 3M Series 190 or approved equivalent.

TYPICAL
RECESSED REFLECTIVE
PAVEMENT MARKERS

STANDARD KC781001-03

COMPANY NAME: HRGreen
 PROJECT CONTACT: HRGreen.com
 DATE PLOTTED: 6/26/2012 10:50:06 PM
 FILE NAME: 8610019614-01-13.dgn
 PLOT DRIVER: pdf.plt
 PEN TABLE: standard-trans.tbl



USER NAME = spenal	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE =	CHECKED -	REVISED -
PLOT DATE = 6/26/2012	DATE - 6/26/12	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**KANE COUNTY DIVISION OF TRANSPORTATION
RECESSED REFLECTIVE PAVEMENT MARKER DETAIL**

SCALE: SHEET NO. 1 OF 1 SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
3887	AR-N-2	KANE	85	74
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT			CONTRACT NO. 60P65	