
**GEOTECHNICAL REPORT
JANE BYRNE INTERCHANGE RECONSTRUCTION
CONTRACT 60X79 DRAINAGE WORK
IDOT D-91-227-13/ PTB 163-001
COOK COUNTY, ILLINOIS**

**For
AECOM
303 East Wacker Drive
Chicago, IL 60601
(312) 938-0300**

**Submitted by
Wang Engineering, Inc.
1145 North Main Street
Lombard, IL 60148
(630) 953-9928**

**Original: May 17, 2018
Revised: August 7, 2018**

Technical Report Documentation Page

1. Title and Subtitle Geotechnical Report Circle Interchange Reconstruction Contract 60X79 Drainage Work		2. Report Date Original: May 17, 2018 Revised: August 7, 2018	
4. Route / Section / County FAI 90/94//290/2014-005R&B/ Cook		3. Report Type <input checked="" type="checkbox"/> SGR <input type="checkbox"/> RGR <input type="checkbox"/> Draft <input checked="" type="checkbox"/> Final <input type="checkbox"/> Revised	
6. PTB / Item No. 163/001		7. Existing Structure Number(s) NA	5. IDOT Job No./Contract D-91-259-12/60X79
9. Prepared by Wang Engineering, Inc. 1145 N Main Street Lombard, IL 60148		Contributor(s) Author: Mohammed Kothawala, P.E., D.GE. QC/QA: Corina T. Farez, P.E., P.G. PIC: Corina T. Farez, P.E., P.G.	8. Proposed Structure Number(s) NA
10. Prepared for AECOM 303 East Wacker Drive Chicago, IL 60601		Design Engineer Jesse L. Vuorenmaa PE TranSystems Corporation	Author Phone Number/Email Address (630) 953-9928 Ext 1036 mkothawala@wangeng.com
11. Abstract		Contact Phone Number (847) 407-5352	
<p>Construction Contract 60X79 includes various drainage works. This report provides geotechnical recommendations for the proposed drainage work.</p> <p>Beneath the pavement or topsoil, the general subsurface soils consists of up to 13 feet of fill materials, up to 5 feet medium stiff to very stiff clay crust, up to 42 feet of very soft to medium stiff silty clay, 30 feet of stiff to hard clay loam, and up to 23 feet of very dense silt to silty loam and sand extending to the boring termination depths or weathered bedrock. Sound bedrock was encountered at elevations of about 479 to 490 feet. Groundwater was encountered within the fill layer at elevations of 570 to 589 feet. Under pressure water-bearing layers are expected at deeper levels.</p> <p>The installation of most of the drainage pipes, junction chambers and manholes, and jacking/receiving pits will be expected to encounter soft clay at the bearing elevations. We recommend that a provision be made for the removal of some base clay and replacing with the stabilization material. Before placing stabilization material, a geotextile fabric for ground stabilization should be provided.</p> <p>The open cuts for drainage pipes greater than 5 feet bgs, junction chambers, manhole, and jacking/receiving pits will require a Temporary Soil Retention System (TSRS) for excavations and installations. Geotechnical parameters for design of TSRS are presented in this report. We strongly recommend that the TSRS designers review the included boring logs and apply their judgement on assessing soil parameters for the type of analyses required for the design of their specific TSRS.</p> <p>We estimate factor of safety (FOS) of 1.7 to 2.3 against basal heave instability at the jacking/receiving pits and junction chambers for excavation depths. The minimum required FOS is 1.5. Our estimated FOS satisfies the minimum required. However, the contractor should check the base stability based on the construction sequence and actual excavation depth required.</p> <p>Recommendations for the backfill material and its placement for trenches, junction chamber, and jacking/receiving pits established in existing/ future open spaces and pavements are provided.</p>			
12. Path to archived file			
S:\Netprojects\11000401\Reports\Other Reports\Contract 60X79 Drainage\RPT_Wang_NSB_11000401Contract60X79Drainage_V04_20180807.doc			

TABLE OF CONTENTS

1.0	INTRODUCTION	1
1.1	PROJECT DESCRIPTION	1
1.2	PROPOSED DRAINAGE WORK.....	2
2.0	SITE CONDITIONS AND GEOLOGICAL SETTING	2
2.1	PHYSIOGRAPHY	2
2.2	SURFICIAL COVER	3
2.3	BEDROCK	3
3.0	METHODS OF INVESTIGATION	4
3.1	SUBSURFACE INVESTIGATION	4
3.2	VANE SHEAR TESTS	5
3.3	LABORATORY TESTING	6
4.0	RESULTS OF FIELD AND LABORATORY INVESTIGATIONS	6
4.1	SOIL AND GROUNDWATER CONDITIONS	6
4.1.1	Area 1.....	6
4.1.2	Area 2.....	7
4.1.3	Area 3.....	7
4.1.4	Area 4.....	8
4.1.5	Area 5.....	9
4.1.6	Area 6.....	9
5.0	ANALYSIS AND RECOMMENDATIONS	10
5.1	OPEN CUT INSTALLATIONS	11
5.2	JACKING PIPES.....	11
5.3	JUNCTION CHAMBERS/MANHOLE	12
5.4	JACKING/RECEIVING PIPES.....	12
5.5	TEMPORARY SOIL RETENTION SYSTEMS	13
5.6	EXCAVATION BASE STABILITY IN JACKING/RECEIVING PITS AND JUNCTION CHAMBERS	20
6.0	CONSTRUCTION CONSIDERATIONS	21
6.1	FILLING AND BACKFILLING.....	21
6.2	ADJACENT FACILITIES PROTECTION	22

6.3	EARTHWORK OPERATIONS.....	22
7.0	QUALIFICATIONS.....	23
	REFERENCES	24
	EXHIBITS	
	1. Site Location Map	
	2. Site and Regional Geology	
	3. Boring Location Plan	
	4. Subsurface Soil Data Profile	
	APPENDIX A	
	Boring Logs	
	APPENDIX B	
	Laboratory Test Results	
	APPENDIX C	
	Proposed Drainage Plan and Profiles	

LIST OF TABLES

Table 1:	Summary of Drainage Work and Reference Borings	4
Table 2:	Summary of Drainage Areas and Proposed Installation Methods	10
Table 3:	TSRS Design Soil Parameters for Area 1.....	14
Table 4:	TSRS Design Soil Parameters for Area 2.....	15
Table 5:	TSRS Design Soil Parameters for Area 3.....	16
Table 6:	TSRS Design Soil Parameters for Area 4.....	17
Table 7:	TSRS Design Soil Parameters for Area 5.....	18
Table 8:	TSRS Design Soil Parameters for Area 5.....	19
Table 9:	TSRS Design Soil Parameters for Area 6.....	20

GEOTECHNICAL REPORT
JANE BYRNE INTERCHANGE RECONSTRUCTION
CONTRACT 60X79 DRAINAGE WORK
IDOT D-91-227-13/PTB 163-001
COOK COUNTY, ILLINOIS
FOR
AECOM

1.0 INTRODUCTION

This report presents the results of Wang Engineering, Inc. (Wang) subsurface investigation, laboratory testing, geotechnical engineering evaluations and recommendations for Contract 60X79 drainage work in connection with the Jane Byrne Interchange Reconstruction project in the City of Chicago, Cook County, Illinois. A *Site Location Map* is presented as Exhibit 1.

The purpose of Wang's investigation was to characterize the site soil and groundwater conditions, perform geotechnical engineering analyses, and provide recommendations for the drainage work within Contract 60X79.

1.1 Project Description

The Circle Interchange is over 50 years old and has significant congestion and safety problems. The project is aiming to improve safety and mobility as well as upgrade the mainline and interchange facilities. The project will also improve other modes of transportation such as transit, pedestrians and bicyclists within the same corridor.

The Circle Interchange Reconstruction project is along Interstate 90/94 (I-90/94) from south of Roosevelt Road to north of Lake Street, along Interstate 290 (I-290) from Loomis Street to the Circle Interchange; and along Congress Parkway from the Circle Interchange to Canal Street/Old Post Office. The routes typically have three lanes of traffic in each direction with mostly one lane ramp at interchanges. Locally, the north leg is known as the Kennedy Expressway, the south leg as the Dan Ryan Expressway and the west leg as the Eisenhower Expressway. Within the project area, there are several cross street bridges over I-90/94 and I-290 considered for reconstruction. Along I-90/94, from south to north, the cross street overpasses include Taylor Street, Van Buren Street, Jackson

Boulevard, and Adams Street. Along I-290, from west to east, the cross street overpasses include Morgan Street, Peoria Street, and Halsted Street.

The proposed improvements include additional through lanes in each direction on I-90/94. The horizontal alignment and vertical profiles throughout the interchange will be improved. A new two-lane flyover, Ramp NW (Flyover) will be constructed for I-90/94 northbound to I-290 westbound traffic. Cross street bridges, Morgan Street, Harrison Street, Halsted Street, Peoria Street, Taylor Street, Adams Street, Jackson Boulevard, and Van Buren Street will be reconstructed. Various existing ramps will be reconstructed and up to fifty one new retaining walls will be constructed.

1.2 Proposed Drainage Work

Based on the proposed drainage and utilities plans and profiles (Appendix C) provided by TranSystems Corporation (TranSystems), Wang understands several drainage/sewer pipes, junction chambers, a 10-foot diameter manhole will be installed in Contract 60X79. The sewer pipes will be installed using open cut and pipe jacking methods. In addition, there are five jacking/receiving pit locations identified along pipe jacking alignments.

2.0 SITE CONDITIONS AND GEOLOGICAL SETTING

The site is located within the City of Chicago at the I-90/94 and I-290 Circle Interchange. On the USGS *Chicago Loop 7.5 Minute Series* map, the drainage work is located in the NW¹/₄ of Section 16, Tier 39 N, Range 14 E of the Third Principal Meridian.

The following review of published geologic data, with emphasis on factors that might influence the design and construction of the proposed engineering works, is meant to place the project area within a geological framework and confirm the dependability and consistency of the present subsurface investigation results. For the study of the regional geologic framework, Wang considered northeastern Illinois in general and Cook County in particular. Exhibit 2 illustrates the *Site and Regional Geology*.

2.1 Physiography

The site is situated within the Chicago Lake Plain Physiographic Subsection. The area is characterized by a flat surface that slopes gently toward the lake, largely made of groundmoraine till covered by thin and discontinuous lacustrine silt and clay.

2.2 Surficial Cover

The project area was shaped during the Wisconsin-age glaciation, and more than 75-foot thick drift covers the bedrock (Leetaru et al. 2004). The glacial cover is made up of clay and silt of the Equality Formation of the Mason Group and diamictons of the Wadsworth and Lemont Formations of the Wedron Group (Hansel and Johnson 1996). The Equality Formation is made up of bedded silt and clay, locally laminated, with lenses and/or thin beds of sand and gravel. The Wadsworth Formation consists of relatively homogenous, massive, gray till with clay to silty clay matrix, with dolostone and shale clasts and occasional lenses of sorted and stratified silt. The Wadsworth Formation is underlain by the pebbly silty clay loam to silty loam diamicton of the Yorkville Member of the Lemont Formation, known informally as the Chicago “hardpan.”

From a geotechnical viewpoint, the Equality Formation is characterized by low strength, medium to high plasticity, and medium to high moisture content, whereas the Wadsworth Formation is characterized by low plasticity, medium to low moisture content, medium to very stiff consistency, poor permeability, and low compressibility. The Yorkville Member (hardpan) is characterized by low plasticity, high blow counts, and low moisture content (Bauer et al. 1991; Peck and Reed 1954).

2.3 Bedrock

In the project area, the glacial deposits unconformably rest over approximately 350-foot thick Silurian-age dolostone (Leetaru et al 2004). The top of bedrock may be encountered at 475 to 500 feet elevation or 75 to 100 feet below ground surface (bgs) or more. The Silurian dolostone dips gently eastward at a pace of 15 feet per mile. Only inactive faults are known in the area, and the seismic risk is minimal (Leetaru et al. 2004; Willman 1971). There are no records of mining activity in the area, but deep tunnel excavations are known to exist.

Our subsurface investigation results fit into the local geologic context. The borings drilled in the project area revealed the native sediments consist of clay to silty clay diamicton of the Wadsworth Formation resting on top of more competent silty clay loam diamicton (hardpan) of the Lemont Formation, which in turn is underlain by bedrock. Sound dolostone bedrock was encountered at depths of 88 to 106 feet bgs, corresponding to 479 to 490 feet elevations, within the range predicted based on published geological data.

3.0 METHODS OF INVESTIGATION

The following sections outline the subsurface and laboratory investigations. All elevations in this report are based on NAVD 1988.

3.1 Subsurface Investigation

No specific borings were performed along the proposed drainage alignments or at the proposed jacking/receiving pits; therefore, nearby borings completed for other structures were used on our analyses and recommendations. The borings considered for our analyses and recommendations are listed in Table 1. The as-drilled boring locations were surveyed by Dynasty Group, Inc. and station and offset information for each boring were provided by AECOM. Boring location data are presented in the *Boring Logs* (Appendix A). The as-drilled boring locations are shown in the *Boring Location Plan* (Exhibit 3).

Table 1: Summary of Drainage Work and Reference Borings

Area	Approximate Location	Reference Borings
Area 1 (Exhibit 3-1)	Ramp EN near Station 1604+50	18-RWB-03 and 1715-B-05
	Ramps EN and WS near Station 1606+50	1715-B-05, 18-RWB-02, 18-RWB-03, and 19-RWB-01
Area 2 (Exhibit 3-2)	Ramp EN near Stations 1608+00, 1610+00, and 1611+00	1712-B-01, 1712-B-02, and 20-RWB-01
	Ramp EN near Station 1611+00	20-RWB-01, 21-RWB-01 to 21-RWB-03
	Near Wall 22A (SN016-1813)	22-RWB-01
Area 3 (Exhibit 3-3)	Ramp EN near Station 1616+00	1703-B-04, 1703-PZ-01, 1706-B-02, 1712-B-03, 22-RWB-03, 22-RWB-04, and VST-06
Area 4 (Exhibit 3-4)	NB C-D Road	1712-B-03, 23-RWB-01 to 23-RWB-04, and 23-RWB-05HA
	NB C-D Road	23-RWB-01, 23-RWB-03, and 23-RWB-05
Area 5 (Exhibit 3-5)	I-90/I-94 and Ramps WS and WN	1706-B-02, 1715-B-03, 1712-B-03, and COMM-HUT-CCTV
Area 6 (Exhibit 3-6)	Ramp WS	1715-B-03, 2055-B-03, and 2055-B-04

We also considered the Piezometer 1703-PZ-01 located in this Contract area. The piezometer was installed in accordance with ASTM D5092, “*Standard Practice for Design and Installation of Groundwater Monitoring Wells in Aquifers.*”

A truck-mounted drilling rig equipped with hollow stem augers, was used to advance and maintain an open borehole to 10 feet depths after that mud rotary was used to boring termination depths. Soil sampling was performed according to AASHTO T 206, “*Penetration Test and Split Barrel Sampling of Soils.*” The soil was sampled at 2.5-foot intervals to 30 feet bgs and at 5-foot intervals to boring termination depths. Soil samples collected from each sampling interval were placed in sealed jars and transported to Wang Geotechnical Laboratory in Lombard, Illinois for further examination and laboratory testing.

Field boring logs, prepared and maintained by a Wang engineer or geologist, include lithological descriptions, visual-manual soil/rock classifications, results of Rimac and pocket penetrometer unconfined compressive strength tests, results of Standard Penetration Tests (SPT) recorded as blows per 6 inches of penetration. The SPT-N value, shown on the soil profile, is the sum of the second and third blows per 6 inches. The soils were described and classified according to Illinois Division of Highways (IDH) Textural Classification system. The field logs were finalized by an experienced engineering geologist after verifying the field visual classifications and laboratory test results.

Groundwater observations were made during drilling to depths of 10 feet before using mud rotary method. Due to safety considerations, boreholes were backfilled with grout immediately upon completion. Groundwater levels in the piezometer were recorded autonomously at defined intervals by digital pressure loggers suspended within the water column. Barometric affects were compensated by a second in-air pressure logger installed in the riser pipe. Data retrieved from loggers periodically were downloaded to a computer for analysis.

3.2 Vane Shear Tests

Wang previously performed vane shear tests in Boring VST-06 within the Area 3 as delineated in this report. Vane shear tests were performed using calibrated RocTest vane shear equipment in undisturbed and remolded conditions. The sensitivity shown on the boring logs is the ratio of shear strength in undisturbed and remolded conditions. In general, the vane shear strength values for soft clays were significantly higher than the corresponding values from unconfined compressive strength tests using the RIMAC apparatus. Vane shear test results were used in our analyses.

3.3 Laboratory Testing

The soil samples were tested in the laboratory for moisture content (AASHTO T265). Atterberg limits (AASHTO T 89/T 90) and particle size analyses (AASHTO T 88) tests were performed on selected soil samples representing the main soil layers encountered during the investigation. Field visual descriptions of the soil samples were verified in the laboratory. Laboratory test results are shown in the *Boring Logs* (Appendix A), in the *Soil Profile* (Exhibit 4), and in the *Laboratory Test Results* (Appendix B).

4.0 RESULTS OF FIELD AND LABORATORY INVESTIGATIONS

Detailed descriptions of the soil conditions encountered during our subsurface investigation are presented in the attached *Boring Logs* (Appendix A) and in the *Soil Profile* (Exhibit 4). Please note that strata contact lines represent approximate boundaries between soil types. The actual transition between soil types in the field may be gradual in horizontal and vertical directions.

4.1 Soil and Groundwater Conditions

In descending order, the general lithologic succession encountered beneath the pavement structure or topsoil includes: 1) man-made ground (fill); 2) medium stiff to very stiff silty clay to silty loam; 3) very soft to medium stiff clay to silty clay; 4) stiff to hard silty clay to silty clay loam; 5) medium dense to very dense silt to silty loam and sand to gravelly sand; and 6) weathered to sound dolostone. A specific soil profile along each area is presented in the following sections.

4.1.1 Area 1

Area 1 borings encountered 4 to 12 inches of topsoil or 3 to 4 inches of asphalt over 8 to 9 inches of concrete pavement at the surface. Beneath the pavement or topsoil, the borings revealed 2 to 5 feet of fill materials. The fill consists of medium dense to dense silty loam to sandy gravel with N values of 16 to 46 blows per foot and stiff to hard silty clay loam with unconfined compressive strength (Q_u) values of 1.0 to 4.5 tsf. Below the granular fill, some borings encountered 2 to 5 feet of soft to stiff silty clay loam. At elevations of 568 to 583 (5 to 8 feet bgs), the borings advanced through 26 to 41 feet of very soft to medium stiff clay to silty clay. Below the very soft to medium stiff clay to silty clay, at elevations 539 to 546 feet (32 to 47 feet bgs), the borings encountered up to 30 feet of stiff to hard clay to silty clay loam followed by medium dense to very dense silt to sand. The borings encountered weathered bedrock at elevations of 491 to 495 feet (87 to 94 feet bgs) and cored dolostone bedrock at elevation of 490 feet (88 feet bgs).

Perched groundwater was encountered in granular fill layer at an elevation of 570.4 feet or 3.5 feet bgs. Granular soils below clay are expected to be saturated and groundwater in granular soils above the bedrock is expected to be under hydrostatic pressure.

4.1.2 Area 2

Below the pavement or topsoil, Area 2 borings encountered 2 to 13 feet of fill materials. The fill consists of primarily medium stiff to hard silty clay to silty clay loam and clay loam with Q_u values of 1.0 to greater than 4.5 tsf and medium dense to dense gravelly sand to gravelly loam fill layers with N values of 15 to greater than 50 blows per foot. Below the fill, some borings encountered 2 to 5 feet of stiff silty clay. At elevations of 574 to 582 (3 to 15 feet bgs), the borings advanced through 33 to 42 feet of very soft to medium stiff clay to silty clay. Beneath the very soft to medium stiff clay to silty clay, at elevations of 539 to 542 feet (37 to 57 feet bgs), the borings encountered up to 25 feet of stiff to hard silty clay to silty clay loam followed by medium dense to very dense silt to gravelly sand. The borings revealed weathered bedrock at elevations of 490 to 492 feet (87 to 104 feet bgs) and sound bedrock at elevations of 484 to 490 feet (91 to 105 feet bgs).

The groundwater observed while drilling in granular soils at an elevation of 521 feet or 56 to 57 feet bgs and measured at drilling completion at an elevation of 496 feet or 82 feet bgs. Granular soils below clay are expected to be saturated and groundwater in granular soils above the bedrock is expected to be under hydrostatic pressure.

4.1.3 Area 3

Below the pavement or topsoil, the borings in Area 3 encountered 3 to 6 feet of fill materials. The fill consists of very stiff to hard silty clay loam and clay loam with Q_u values of 2.3 to 4.5 tsf. Below the fill, some borings encountered 2 to 5 feet of stiff to very stiff silty clay to silty clay loam with Q_u values of 1.6 to 2.9 tsf. At elevations of 578 to 580 (5 to 8 feet bgs), the borings advanced through 35 to 41 feet of very soft to medium stiff clay to silty clay. In-situ undisturbed vane shear strengths obtained in Boring VST-06 between elevations 575 and 542 feet in the very soft to medium stiff clay to silty clay layers ranged from 580 to 980 psf. Beneath the very soft to medium stiff clay to silty clay, the borings encountered up to 5 to 15 feet of stiff to hard silty clay to silty clay loam followed by medium dense to very dense silt to gravelly sand. The boring revealed the weathered bedrock at elevation of 488 feet (100 feet bgs) and cored dolostone bedrock at an elevation of 479 feet (106 feet).

The groundwater was observed while drilling in granular soils between elevations of 505 and 526 feet or 62 to 78 feet bgs and measured at completion of drilling at an elevation of 494 feet or 91 feet bgs. A Piezometer 1703-PZ-01 was installed on November 12, 2014. The screen was placed with the top and bottom elevations at 507.2 and 487.2 feet (75 to 95 feet bgs), respectively within soil on top of bedrock. A summary of the monitoring data between November 2014 and March 2017 is shown in Figure 1.




Figure 1: Summary of Groundwater Monitoring Data

The data shows groundwater that is under hydrostatic pressure head. The average hydrostatic elevation within the aquifer is about 553 feet.

4.1.4 Area 4

Beneath the pavement, the borings encountered primarily 3 to 6 feet of fill materials. The fill includes stiff to very stiff silty clay loam with Q_u values of 1.5 to 2.0 tsf and loose to medium dense gravelly sandy loam to sand with N values of 6 to 10 blows per foot. Below the fill, some borings encountered 2 to 5 feet of medium stiff to very stiff silty clay loam with Q_u values of 0.7 to 2.5 tsf. At elevations of 567 to 584 feet (3 to 8 feet bgs), the borings advanced through 24 to 39 feet of very soft to medium stiff clay to silty clay. Beneath the clay to silty clay, at elevations of 538 to 546 feet (32 to 48 feet bgs), the borings revealed 10 to 22 feet of stiff to hard silty clay to silty clay loam followed by medium dense to very dense silty loam to sand. Boring 1712-B-03 revealed the possible weathered bedrock at an elevation of 485 feet (100 feet bgs).

Perched groundwater was encountered while drilling in granular fill layer at an elevation of 586.8 feet or 3.5 feet bgs. Granular soils below clay are expected to be saturated and groundwater in granular soils above the bedrock is expected to be under hydrostatic pressure.

4.1.5 Area 5

Below the pavement, the borings encountered 5 to 13 feet of fill materials. The fill includes stiff silty clay loam with Q_u values of 1.5 to 1.6 tsf and very loose to medium dense gravelly sand N values of to 10 blows per foot. At elevations of 576 to 581 feet (3 to 13 feet bgs), the borings advanced through 24 to 39 feet of very soft to medium stiff clay to silty clay. Beneath the clay to silty clay, at elevations of 537 to 553 feet (32 to 57 feet) the borings revealed 10 to 15 feet of stiff to hard silty clay to silty clay loam followed by medium dense to very dense silt to sandy gravel. The borings revealed weathered bedrock at elevations of 485 to 488 feet (91 to 100 feet) and cored dolostone bedrock at an elevation of 482 feet (92 feet bgs).

Perched groundwater was encountered while drilling in granular fill layer at elevations of 575.0 to 588.9 feet or 3 to 5.5 feet bgs. In Boring 175-B-02, a 24-hour groundwater level was measured at an elevation of 507 feet or 72 feet bgs. Granular soils below clay are expected to be saturated and groundwater in granular soils above the bedrock is expected to be under hydrostatic pressure.

4.1.6 Area 6

Beneath the pavement, the borings encountered 8 feet of fill materials. The fill materials include very stiff to hard silty clay loam with Q_u values of 2.5 to 4.5 tsf. At elevations of 570 to 572 feet (3 to 8 feet bgs), the borings advanced through 22 to 34 feet of very soft to medium stiff clay to silty clay. Beneath the clay to silty clay, at elevations of 538 to 542 feet (35 to 37 feet), the borings revealed 10 to 20 feet of stiff to hard silty clay to silty clay loam followed by silt to sandy gravel. The borings encountered weathered bedrock at elevations of 483 to 485 feet (92 to 94 feet bgs) and cored dolostone bedrock at an elevation of 479 feet (97 feet bgs).

Perched groundwater was encountered while drilling in granular fill layer at an elevation of 572 feet or 2.5 feet bgs. The groundwater was measured at completion of drilling at an elevation of 512 feet or 62 feet bgs. Granular soils below clay are expected to be saturated and groundwater in granular soils above the bedrock is expected to be under hydrostatic pressure.

5.0 ANALYSIS AND RECOMMENDATIONS

Our analyses were based on the drainage work plans and profiles shown in Appendix C provided by TranSystems. We understand the sewer pipes will be installed by open cuts or jacking methods. Proposed locations, installation methods, approximate excavation depths, and Exhibit of the soil profile associated with each pipe alignment are summarized in Table 2. Since there were no specific borings performed for the Contract 60X79 drainage work, our analyses and recommendations are based on generalized soil conditions and groundwater conditions described in Section 4.1 and as shown in *Subsurface Data Profile* (Exhibit 4).

Table 2: Summary of Drainage Areas and Proposed Installation Methods

Area	Approximate Location	Subsurface Data Profile Exhibit	Proposed Installation Methods / Approximate Excavation Depth (feet)
Area 1 (Exhibit 3-1)	Ramp EN near Station 1604+50	Exhibit 4-1	Open Cut/ 5 to 7 feet
	Ramps EN and WS near Station 1606+50	Exhibits 4-2 and 4-3	Open Cut /5 to 17 feet
Area 2 (Exhibit 3-2)	Ramp EN near Station 1610+00	Exhibits 4-4 and 4-5	Open Cut / 3 to 5 feet
	Ramp EN near Station 1611+00	Exhibits 4-6 to 4-9	Open Cut /2 to 23 feet
	Near Wall 22A (SN016-1813)	Exhibit 4-9	Open Cut / 22 feet
Area 3 (Exhibit 3-3)	Ramp EN near Station 1616+00	Exhibits 4-10 to 4-22	Open Cut /10 to 25 feet
Area 4 (Exhibit 3-4)	NB C-D Road	Exhibit 4-23	Open Cut / 25 feet
			Jacking/ 25 feet
Area 5 (Exhibit 3-5)	I-90/I-94 and Ramps WS and WN	Exhibit 4-25	Jacking/25 feet
			Open Cut /15 to 25 feet
Area 6 (Exhibit 3-6)	Ramp WS	Exhibit 4-26	Jacking / 25 feet

5.1 Open Cut Installations

Based on the information provided by TranSystems, almost all the drainage pipes will be installed by utilizing open cut excavations. The pipes proposed to be installed by open cut method are shown on the Boring Location Plan (Exhibit 3) in green highlighter. The open cut excavations will be extended to depths ranging from 3 to 25 feet bgs. We recommend temporary open cut excavations up to a depth of 5 feet below ground surface should have a slope of 1:2 (V:H) for cohesive soils and 1:2.5 (V:H) for granular soils. Based on the encountered soil conditions, adjacent utilities, structures, and roadways, the temporary open cut excavations greater than 5 feet bgs will require a Temporary Soil Retention System (TSRS) consisting of sheeting, shoring or bracing systems as discussed in Section 5.5.

Depending on the depth of excavation, very soft to soft clay to silty clay may be encountered at the base of the excavations and the base may not remain stable during construction. The determination as to whether undercuts are needed in these areas should be made by a qualified soils inspector at the time of construction. We recommend that a provisional quantity be included for removal and replacement in the contract to account for soft clay subgrade treatment. The provisional quantity should be assuming 12 inches of thickness for the full width of the trench. The undercut should be limited to 2 feet. The actual removal and replacement thickness should be determined in the field based on the contractor's method and equipment to be used. The replacement material should be in accordance with the IDOT District One Special Provision *Aggregate Subgrade Improvement (D-1)*. Before placing stabilization material, a geotextile fabric for ground stabilization meeting the requirements of IDOT SSRBC Sections 210 and 1080.02 should be provided. The contractor should review the subsurface soil conditions and judge their efforts on means, methods, and progress of work.

5.2 Jacking Pipes

Jacking pipe locations are shown on the Boring Location Plan (Exhibit 3) in purple highlights. Pipe should be jacked in accordance with IDOT Standard Specifications Section 552, Storm sewer jacked in place. Frictional resistance to the jacking force can be estimated from the product of shear strength of soil and the surface area of pipe in contact with the soil. The subsurface soil conditions within the jacking depths, as revealed by borings, generally consist of very soft to soft clay to silty clay. The contractor should review the subsurface soil conditions and judge their effects on means, methods, and progress of work. The jacking operation, once started, should be continued until completed. If continuous jacking cannot be maintained, the contractor should take the necessary precautions for not

allowing the jacked pipes to freeze or set in the ground. There may be intermediate pits necessary to allow for pipe jacking through changing alignments. The contractor should be required to submit details of his means and methods for constructing pipelines by jacking.

5.3 Junction Chambers/Manhole

One junction chamber and a manhole will be installed at the following locations:

- Junction Chamber #1, Station 6332+00 (NB C-D Road);
- Junction Chamber #2, Station 1610+50 (Ramp EN);and
- Ten feet diameter manhole, Station 1106+50 (Ramp WN)

As proposed junction chambers and ten feet diameter manhole locations are shown on the Boring Location Plan (Exhibit 3). Junction Chamber #1 will be located adjacent to the Wall 22 B (SN 049-1839) and was addressed in the Structure Geotechnical Report (SGR) dated April 25, 2018. The construction of Junction Chamber #1 will require about 40 feet of temporary excavation to reach the chamber bearing elevation of about 553 feet. The proposed excavation will generally consists of an open cut with 1:2 (V:H) back-slope to about elevation 573 feet, then a braced TSRS to reach the chamber bearing elevation. The TSRS is discussed in Section 5.5.

Ten feet diameter manhole will be installed via open cut and will require excavation up to 20 feet bgs. A TSRS will be required and is discussed in Section 5.5.

Very soft to soft clay to silty clay will be encountered at the base of junction chambers and manhole. We recommend that a provision be made for the removal of some base clay and replacing with the stabilization material. Before placing stabilization material, a geotextile fabric for ground stabilization meeting the requirements of IDOT SSRBC Sections 210 and 1080.02 should be provided. For contract estimate purposes, we recommend considering a 2-foot thick layer of stabilization material. The removal and replacement thickness should be determined in the field based on the contractor's method and equipment to be used.

5.4 Jacking/Receiving Pits

Based on the information drawings provided by TranSystems, the proposed five jacking/receiving pits are located at:

- Pit #1, Station 20+25;
- Pit #2, Station 16+25;
- Pit #3, Station 102+50;
- Pit #4, Station 6333+00; and
- Pit #5, Station 6334+00.

Pit locations are shown on the Boring Location Plan (Exhibit 3). Excavations depths or the proposed depths of excavations for jacking/ receiving pits will be approximately 25 feet below ground surface.

The jacking/receiving pit size should be large enough to provide a safe and adequate working area. Pit size will depend on the contractor's equipment and space constraint. The jacking pit walls should be supported in accordance with OSHA construction requirements to insure a solid, stable base for boring machine and pit sides. Jacking load can be transferred to the soil behind the jacking pit through a thrust block constructed at the back of the pit. The resistance which the soil can provide to the jacking loads may be estimated from the allowable passive pressures. A factor of safety of 2 should be considered. If enough resistance is not available, additional ground improvement measure may be required to provide additional lateral resistance to withstand the jacking loads.

Very soft to soft clay to silty clay will be encountered at the base of the pits. We recommend that a provision be made for the removal of some base clay and replacing with the stabilization material. Before placing stabilization material, a geotextile fabric for ground stabilization meeting the requirements of IDOT SSRBC Sections 210 and 1080.02 should be provided. For contract estimate purposes, we recommend considering a 2-foot thick layer of stabilization material. The removal and replacement thickness should be determined in the field based on the contractor's method and equipment to be used.

Groundwater was observed in the granular fill near the proposed pits. It is recommended that that the design groundwater level be placed at elevations of 569 to 573 feet. Provisions should be made to collect and remove groundwater seepage that may accumulate in the pits. Groundwater was also encountered in the gravel and sand layers at elevations of 494 to 512 feet.

5.5 Temporary Soil Retention Systems

Temporary excavations up to 25 feet deep below the existing grade will be required for the drainage pipe installations and jacking/receiving pits. The TSRS consisting of sheeting, shoring or bracing systems can be used to create vertical excavation walls. A temporary vertical excavation support

system may also be required due to space limitations and where existing buildings, roadways, and other structures and utilities are to be protected. Therefore, it is our opinion that a temporary enclosed braced system will be necessary.

It is recommended that the design groundwater levels for a short-term condition be assumed to be at elevations 569 to 573 feet. In addition, lateral pressure from adjacent foundations and other surcharge loads such as construction equipment should also be considered in the design of the bracing system. The soil parameters shown in Tables 3 through 9 can be used for the design of TSRS system. We recommend that the TSRS designer review the included boring logs and apply their judgement on assessing soil parameters for the type of analyses required for the design of their specific temporary support system. The TSRS designer should consider nearest boring (s) for the excavation support design.

Table 3: TSRS Design Soil Parameters for Area 1
 Reference Borings 19-RWB-01 and VST-06

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle ϕ (degree)
Existing Grade to 585	Silty Loam Fill	120	0	33
585 to 577	Stiff Clay to Silty Clay	120	1000	0
577 to 565	Soft to Medium stiff Clay to Silty Clay	110	550	0
565 to 555	Soft to Medium stiff Clay to Silty Clay	110	650	0
555 to 542	Soft to Medium stiff Clay to Silty Clay	115	800	0
542 to 539	Stiff Clay to Silty Clay	120	1400	0
539 to 522	Very Stiff to Hard Silty Clay Loam to Silty Loam	120	4500	0
522 to 515	Dense Sand	63 ⁽¹⁾	0	35

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle \emptyset (degree)
515 to 511	Hard Silty Clay Loam	63 ⁽¹⁾	7000	0
511 to 495	Very Dense Silt to Silty Loam	63 ⁽¹⁾	0	35

⁽¹⁾Submerged unit weight

Table 4: TSRS Design Soil Parameters for Area 2
 Reference Borings 1705-B-05, 21-RWB-02, 22-RWB-01, and VST-06

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle \emptyset (degree)
Existing Grade to 592	Clay Loam Fill	120	2000	0
592 to 582	Medium stiff to Stiff Silty Clay Fill	120	1000	0
582 to 560	Soft to Medium stiff Clay to Silty Clay	110	550	0
560 to 555	Soft to Medium stiff Clay to Silty Clay	110	650	0
555 to 545	Soft to Medium stiff Clay to Silty Clay	115	800	0
545 to 540	Stiff Clay to Silty Clay	120	1400	0
540 to 515	Very Stiff to Hard Silty Clay Loam to Silty Loam	125	4000	0
515 to 490	Very Dense Silt to Silty Loam	125	0	37

⁽¹⁾Submerged unit weight

Table 5: TSRS Design Soil Parameters for Area 3
 Reference Borings 1712-B-03, 22-RWB-05, and VST-06

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle ϕ (degree)
573 ⁽¹⁾ to 571	M Stiff Clay to Silty Clay	115	700	0
571 to 569	Stiff Silty Clay	120	1000	0
569 to 566	Soft Clay to Silty Clay	110	550	0
566 to 556	Medium stiff Clay to Silty Clay	110	680	0
556 to 550	Medium stiff Clay to Silty Clay	115	750	0
550 to 538	Medium Stiff Clay to Silty Clay	115	950	0
538 to 533	Stiff Clay to Silty Clay	120	1500	0
533 to 524	Very Stiff to Hard Silty Clay	125	3000	0
524 to 518	Medium Dense Silty Loam to Sand	120	0	30
518 to 494	Very Dense Silty Loam	63 ⁽²⁾	0	36
494 to 485	Very Dense Sand	63 ⁽²⁾	0	35
485 to 474.8	Very Dense Weathered Bedrock	73 ⁽²⁾	0	37

⁽¹⁾ After initial open cut excavation with 1:2 (V:H) side slope for Wall 22B (SN 016-1839); ⁽²⁾ Submerged unit weight

Table 6: TSRS Design Soil Parameters for Area 4
 Reference Borings 23-RWB-01 and VST-06

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle ϕ (degree)
Existing Grade to 570	Granular Fill	120	0	30
570 to 567	Stiff Silty Clay Loam	120	1100	0
567 to 556	Soft to Medium stiff Clay to Silty Clay	110	600	0
556 to 542	Soft to Medium stiff Clay to Silty Clay	115	750	0
542 to 538	Soft to Medium stiff Clay to Silty Clay	115	900	0
538 to 533	Stiff Silty Clay	120	1600	0
533 to 524	Very Stiff Silty Clay	120	2400	0
524 to 519	Medium Stiff Clay	115	870	0
519 to 514	Dense Sandy Loam	125	0	35
514 to 510	Hard Silt Clay Loam	125	7400	0

Table 7: TSRS Design Soil Parameters for Area 5
 Reference Borings 1715-B-03 and VST-06

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle ϕ (degree)
Existing Grade to 571	Granular Fill	120	0	30
571 to 565	Soft to Medium Stiff Clay to Silty Clay	115	900	0
565 to 555	Soft to Medium Stiff Clay to Silty Clay	110	600	0
555 to 543	Soft to Medium Stiff Clay to Silty Clay	115	800	0
543 to 538	Medium Stiff Clay to Silty Clay	120	1200	0
538 to 523	Very Stiff to Hard Silty Clay	120	3000	0
523 to 518	Medium Stiff Clay	115	800	0
518 to 513	Hard Silty Clay Loam	120	9400	0
513 ⁽¹⁾ to 510	Dense Silt	58 ⁽¹⁾	0	35
510 to 508	Hard Silty Clay Loam	63 ⁽¹⁾	4500	0
508 to 498	Very Dense Silty Loam	63 ⁽¹⁾	0	35
498 to 491	Hard Silty Clay Loam	63 ⁽¹⁾	7300	0
491 to 483	Very Dense Silt to Silty Loam	63 ⁽¹⁾	0	36

⁽¹⁾Submerged unit weight

Table 8: TSRS Design Soil Parameters for Area 5
 Reference Borings 1706-B-02 and VST-06

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle ϕ (degree)
Existing Grade to 570	Granular Fill	120	0	30
570 to 568	Stiff to very Stiff Silty Clay Loam	120	1600	0
568 to 556	Soft to Medium Stiff Clay to Silty Clay	110	600	0
556 to 542	Soft to Medium Stiff Clay to Silty Clay	115	800	0
542 to 538	Stiff Silt Clay	120	1200	0
538 to 524	Very Stiff to Hard Silt Clay	120	2800	0
524 to 517	Medium Dense Silt	120	0	30
517 to 502	Hard Silty Clay Loam to Silty Loam	125	7000	0
502 to 492	Very Dense Gravelly Sandy Loam	130	0	37
492 to 484	Very Dense Silt	125	0	33
484 to 482	Very Dense Gravelly Sand	68 ⁽¹⁾	0	37

⁽¹⁾Submerged unit weight

Table 9: TSRS Design Soil Parameters for Area 6
 Reference Borings 2055-B-03, 38-RWB-02, and VST-06

Approximate Elevation Range (feet)	Soil Type (Layer)	Unit Weight (pcf)	Cohesion C_u (psf)	Friction Angle ϕ (degree)
Existing Grade to 573	Silty Clay to Silty Clay Loam Fill	120	2800	0
573 to 565	Soft to Medium stiff Clay to Silty Clay	115	800	0
565 to 555	Soft to Medium stiff Clay to Silty Clay	110	600	0
555 to 542	Soft to Medium stiff Clay to Silty Clay	115	800	0
542 to 539	Stiff Clay to Silty Clay	120	1200	0
539 to 522	Stiff to Very Stiff Silty Clay to Silty Clay Loam	120	2400	0
522 to 517	Medium Dense Silt	120	0	30
517 to 507	Hard Silty Clay Loam	125	7000	0
507 to 492	Very Dense Silt to Silty Loam	125	0	35
492 to 487	Hard Silty Clay Loam	125	8200	0
487 to 485	Very Dense Sandy Gravel	68 ⁽¹⁾	0	35

⁽¹⁾Submerged unit weight

5.6 Excavation Base Stability at Jacking/Receiving Pits and Junction Chambers

Wang performed preliminary analyses for bottom heave stability of the jacking/receiving pits and junction chambers. The in-situ vane shear testing results were used to better assess the shear strength of the soft clay at the pits. The shear strength values used on the evaluation of base stability are shown in Tables 4 through 9. Wang estimates factor of safety (FOS) of 1.7 to 2.3 against basal heave instability at the jacking/receiving pits and junction chambers for excavation depths ranging from 19

to 25 feet. In general, the minimum required FOS is 1.5. Our estimated FOS satisfies the minimum required. However, the contractor should check the base stability based on the construction sequence and actual excavation depth required.

6.0 CONSTRUCTION CONSIDERATIONS

6.1 Filling and Backfilling

All fill and backfill materials shall be as per IDOT *Standard Specification for Road and Bridge Construction* (IDOT 2016), Sections 550 and 551. We recommend using Method 1 of Article 550.07.

Existing /Future Open Space Areas

The backfill material should consist of suitable excavated material or trench backfill. Suitable excavated material or trench backfill should be placed in uniform lifts not exceeding 12 inches in depth, loose measurement, and compacted to 85 percent of standard lab density. In lieu of suitable excavated material or trench backfill, the Contractor may, at no additional cost to the Department, backfill the entire excavation with controlled low-strength material according to IDOT Standard Specification Section 593 or Light Weight Cellular Concrete Fill (LCCF) Class II as per IDOT District One Special Provision.

Existing/Future Pavement Areas

For the trenches, junction chamber, and jacking/receiving pits established at least two feet above top of soft clay, the backfill material should consist of suitable excavated material or trench backfill. Suitable excavated material or trench backfill should be placed in uniform lifts not exceeding 8 inches in depth, loose measurement, and compacted to 95 percent of standard lab density. In lieu of suitable excavated material or trench backfill, the Contractor may, at no additional cost to the Department, backfill the entire excavation with controlled low-strength material according to IDOT Standard Specification Section 593 or Light Weight Cellular Concrete Fill (LCCF) Class II as per IDOT District One Special Provision. This requirement should also be applicable where the inner edge of the excavation is within 2 feet of the proposed edge of pavement, curb, gutter, curb and gutter and side walk.

For the trenches, junction chamber, manhole, and jacking/receiving pits established in soft clay, suitable excavated material should be used and capped with geotextile fabric for ground stabilization and 2 feet of CA-6 crushed stone below the proposed pavement subgrade. Suitable excavated material

should be placed in uniform lifts not exceeding 8 in in depth, loose measurement, and compacted to 95 percent of standard lab density. In lieu of suitable excavated material, the Contractor may, at no additional cost to the Department, backfill the entire excavation with controlled low-strength material according to IDOT Standard Specification Section 593 or Light Weight Cellular Concrete Fill Class II (LCCF) as per IDOT District One Special Provision. This requirement should also be applicable where the inner edge of the excavation is within 2 feet of the proposed edge of pavement, curb, gutter, curb and gutter and side walk.

6.2 Adjacent Facilities Protection

Given the proximity of building, structures, roads, and utilities, Wang recommends special precautions should be taken during the construction not undermine the existing foundations, pavements, and utilities. In addition, the TSRS discussed in Section 5.5 should have deflection control to prevent movement of adjacent structures, utilities, and roadways. Ground movements nearby existing roadways, utilities, and foundations should be evaluated by the Contractor. Ground movements as well as wall deflections should be monitored during construction. We recommend including Special Provisions for vibration and displacement monitoring in the contract documents.

6.3 Earthwork Operations

The required earthwork can be accomplished with conventional construction equipment. Moisture and traffic will cause deterioration of exposed subgrade soils. Precautions should be taken by the contractor to prevent water erosion of the exposed subgrade. We recommend backfilling trench excavations, both sloped and wall supported, as soon as possible after construction.

Earth moving operations should be scheduled to not coincide with excessive cold or wet weather (early spring, late fall or winter). Any soil allowed to freeze or soften due to the standing water should be removed and replaced with additional compacted aggregate. Wet weather can cause problems with subgrade compaction.

It is recommended that an experienced geotechnical engineer be retained to inspect the exposed subgrade, monitor earthwork operations, and provide material inspection services during the construction phase of this project.

7.0 QUALIFICATIONS

The analysis and recommendations submitted in this report are based upon the data obtained from the borings drilled at the locations shown on the boring logs and in Exhibit 3. This report does not reflect any variations that may occur between the borings or elsewhere on the site, variations whose nature and extent may not become evident until the course of construction. In the event that any changes in the design and/or location of the improvements are planned, we should be timely informed so that our recommendations can be adjusted accordingly.

It has been a pleasure to assist AECOM and the Illinois Department of Transportation on this project. Please call if there are any questions, or if we can be of further service.

Respectfully Submitted,

WANG ENGINEERING, INC.

Mohammed Kothawala, P.E., D.GE
Senior Geotechnical Engineer


Corina T. Farez, P.E., P.G.
Vice President

Nesam S. Balakumaran
Project Geotechnical Engineer

REFERENCES



- BAUER, R.A., CURRY, B.B., GRAESE, A.M., VAIDEN, R.C., SU, W.J., and HASEK, M.J., 1991, *Geotechnical Properties of Selected Pleistocene, Silurian, and Ordovician Deposits of Northeastern Illinois*: Environmental Geology 139, Illinois State Geological Survey, 69 p.
- HANSEL, A.K., and JOHNSON, W.H. (1996) *Wedron and Mason Groups: Lithostratigraphic Reclassification of the Wisconsin Episode, Lake Michigan Lobe Area: ISGS Bulletin 104*. Illinois State Geological Survey, Champaign, IL. 116 p.
- LEETARU, H.E., SARGENT, M.L., AND KOLATA, D.R., 2004, *Geologic Atlas of Cook County for Planning Purposes*, ISGS, Champaign, IL
- ILLINOIS DEPARTMENT OF TRANSPORTATION (2015) *Geotechnical Manual*. IDOT Bureau of Materials and Physical Research, Springfield, IL.
- ILLINOIS DEPARTMENT OF TRANSPORTATION (2016) *Standard Specifications for Road and Bridge Construction*. IDOT Division of Highways, Springfield, IL.
- WILLMAN, H.B., 1971, *Summary of the Geology of the Chicago Area*, ISGS Circular C460: Urbana, Illinois State Geological Survey, p. 77.
- PECK, R.B., and REED, W.C., 1954, *Engineering Properties of Chicago Subsoils*: University of Illinois Engineering Experiment Station Bulletin No. 423: Urbana, University of Illinois, 62 p.

EXHIBITS



CONTRACT 60X79 DRIANAGE WORK
 NW1/4 Sec. 16, T 39N, R 14E of 3rd PM

Cook County




SITE LOCATION MAP: CIRCLE INTERCHANGE RECONSTRUCTION,
 CONTRACT 60X79 DRAINAGE WORK, CHICAGO, IL

SCALE: GRAPHICAL | EXHIBIT 1 | DRAWN BY: NSB
 CHECKED BY: MAK



1145 N. Main Street
 Lombard, IL 60148
 www.wangeng.com

FOR AECOM | 1100-04-01



CONTRACT 60X79 DRAINAGE WORK
NW 1/4 Sec. 16, T 39N, R 14E of 3rd PM


I-90/I-94

I-90/I-94

Qls

Modified after Bretz (1926)

REGIONAL GEOLOGY



- Wedron Group**
- Wadsworth Formation
 - Lemont Formation
 - Tiskilwa Formation

Modified after Hansel and Johnson (1996)


Legend

- Qls
Glacial lake bottom
(Covered by lacustrine deposits)

DRIFT THICKNESS

BEDROCK TOPOGRAPHY

BEDROCK THICKNESS



Modified after Leetaru et al. (2004)

SITE AND REGIONAL GEOLOGY: CIRCLE INTERCHANGE RECONSTRUCTION,
CONTRACT 60X79 DRAINAGE WORK, CHICAGO, IL

SCALE: GRAPHICAL **EXHIBIT 2** DRAWN BY: NSB
CHECKED BY: MAK

Wang
Engineering

1145 N. Main Street
Lombard, IL 60148
www.wangeng.com


FOR AECOM 1100-04-01

LEGEND

- ⊙ EXISTING MANHOLE
- EXISTING CATCH BASIN
- EXISTING INLET
- ▬ BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
- ⊙ MANHOLE TO BE INSTALLED BY OTHERS
- CATCH BASIN TO BE INSTALLED BY OTHERS
- ▬ INLET TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
- PROPOSED STORM SEWER
- ⊕ BORING LOCATIONS
- ⊙ PROPOSED MANHOLE
- PROPOSED CATCH BASIN
- ▬ PROPOSED INLET



LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE



AREA-1
 BORING LOCATION MAP : CIRCLE INTERCHANGE RECONSTRUCTION, SEWER PIPE AND JACKING/RECEIVING , CONTRACT 60X79, COOK COUNTY, ILLINOIS

SCALE: GRAPHICAL	EXHIBIT 3-1	DRAWN BY: RKC CHECKED BY: NSB
		1145 N. Main Street Lombard, IL 60148 www.wangeng.com
FOR AECOM		1100-04-01



D:\61779-SHT-Drain-02.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION



PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 2 OF 10 SHEETS STA. 1602+00 TO STA. 1607+50

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 263
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

FILE PATH = p:\61779-SHT-Drain-02.dgn

FILE PATH = p:\617479-P\INT\aecon\line\local\aecon\DS02_MW\Documents\01_Americas\Transportation\60X79_Circle\Phase_11\000_CAD\006_Roadway\Sheets\60X79_Contract\016879-SHT-Drain-03.dgn



LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

LEGEND

- EXISTING MANHOLE
- EXISTING CATCH BASIN
- EXISTING INLET
- BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
- MANHOLE TO BE INSTALLED BY OTHERS
- CATCH BASIN TO BE INSTALLED BY OTHERS
- INLET TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
- PROPOSED STORM SEWER
- BORING LOCATIONS
- PROPOSED MANHOLE
- PROPOSED CATCH BASIN
- PROPOSED INLET


AREA-2

BORING LOCATION MAP : CIRCLE INTERCHANGE RECONSTRUCTION, SEWER PIPE AND JACKING/RECEIVING, CONTRACT 60X79, COOK COUNTY, ILLINOIS

SCALE: GRAPHICAL **EXHIBIT 3-2** DRAWN BY: RKC
CHECKED BY: NSB

Wang Engineering 1145 N. Main Street
Lombard, IL 60148
www.wangeng.com

FOR AECOM 1100-04-01




D:\60X79-SHT-Drain-03.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -

STATE OF ILLINOIS	DEPARTMENT OF TRANSPORTATION
-------------------	------------------------------

PROPOSED DRAINAGE AND UTILITIES PLAN	
SCALE: 1"=20'	SHEET 3 OF 10 SHEETS
STA. 1607+50 TO STA. 1613+00	

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 264
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

FILE PATH = p:\1617479-P\INT\document\1617479-Drain-04.dgn



FOR MAIN DRAIN INFORMATION UNDER I-90/94 SEE SHEET NO.268

BEGIN INTERIM RAMP W/ STA 2105+76.20
 STATION EQUATION
 2105+76.20
 RAMP W/ STA 1105+76.20
 INTERIM RAMP W/ STA 2105+76.20

JUNCTION CHAMBER NO. 1
 SEE DRAINAGE DETAILS

SEE SHEET NO.271 FOR PUMP STATION NO. 5 PARKING LOT DRAINAGE PLAN.

LEGEND

	EXISTING MANHOLE		PROPOSED MANHOLE
	EXISTING CATCH BASIN		PROPOSED CATCH BASIN
	EXISTING INLET		PROPOSED INLET
	BRIDGE SCUPPER (SEE STRUCTURAL PLANS)		
	MANHOLE TO BE INSTALLED BY OTHERS		
	CATCH BASIN TO BE INSTALLED BY OTHERS		
	INLET TO BE INSTALLED BY OTHERS		
	STORM SEWER TO BE INSTALLED BY OTHERS		
	STORM SEWER TO BE INSTALLED BY OTHERS (60X93)		
	PROPOSED STORM SEWER		
	BORING LOCATIONS		

LEGEND


	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
	STORM SEWER TO BE JACKED IN PLACE
	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

AREA-3
 BORING LOCATION MAP : CIRCLE INTERCHANGE RECONSTRUCTION, SEWER PIPE AND JACKING/RECEIVING, CONTRACT 60X79, COOK COUNTY, ILLINOIS

SCALE: GRAPHICAL	EXHIBIT 3-3	DRAWN BY: RKC
		CHECKED BY: NSB

Wang Engineering
 1145 N. Main Street
 Lombard, IL 60148
 www.wangeng.com

FOR AECOM 1100-04-01



D160X79-SHT-Drain-04.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0017' / 1"	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 4 OF 10 SHEETS STA. 1613+00 TO STA. 1618+50

F.A.I. R.T.E. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 265
ILLINOIS FED. AID PROJECT			CONTRACT NO. 60X79	

LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE




LEGEND


- EXISTING MANHOLE
- EXISTING CATCH BASIN
- EXISTING INLET
- BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
- MANHOLE TO BE INSTALLED BY OTHERS
- CATCH BASIN TO BE INSTALLED BY OTHERS
- INLET TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
- PROPOSED STORM SEWER
- BORING LOCATIONS
- PROPOSED MANHOLE
- PROPOSED CATCH BASIN
- PROPOSED INLET

BILL OF MATERIAL		
ITEM	UNIT	QUANTITY
DUCTILE IRON FITTING, TYPE 2 WYE 8" PIPE - 6" BRANCH	EACH	1
DUCTILE IRON FITTING 8" 90 DEGREE ELBOW	EACH	1
PIPE CLEANOUT, 8"	EACH	1
STORM SEWERS, TYPE 4, DUCTILE IRON PIPE 8"	FOOT	50
DRAINAGE STRUCTURE	EACH	1
SUBBASE GRANULAR MATERIAL, TYPE B 6"	SQ YD	1
MISCELLANEOUS CONCRETE	CU YD	4.5

NOTE: ALL ITEMS INCLUDED IN THE COST OF DRAINAGE SYSTEM (SPECIAL)



PR 42" STORM SEWER TO BE INSTALLED BY FUTURE CONTRACTOR
23-RWB-05, 592.27



AREA-4

BORING LOCATION MAP : CIRCLE INTERCHANGE RECONSTRUCTION, SEWER PIPE AND JACKING/RECEIVING, CONTRACT 60X79, COOK COUNTY, ILLINOIS

SCALE: GRAPHICAL **EXHIBIT 3-4** DRAWN BY: RKC CHECKED BY: NSB

Wang Engineering 1145 N. Main Street Lombard, IL 60148 www.wangeng.com

FOR AECOM 1100-04-01

KEY PLAN



D:\617479-P\INT\recomon\line\local\p\60X79-SHT-Drain-05.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 5 OF 10 SHEETS STA. 1618+50 TO STA. 1624+00

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 266
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

FILE PATH = p:\61779-P\INT\ascomon\line\local\IAC\CDM_D502_NA\Documents\01_Americas\Transportation\60X79_SHT-Drain-07.dgn



LEGEND	
	EXISTING MANHOLE
	PROPOSED MANHOLE
	EXISTING CATCH BASIN
	PROPOSED CATCH BASIN
	EXISTING INLET
	PROPOSED INLET
	BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
	MANHOLE TO BE INSTALLED BY OTHERS
	CATCH BASIN TO BE INSTALLED BY OTHERS
	INLET TO BE INSTALLED BY OTHERS
	STORM SEWER TO BE INSTALLED BY OTHERS
	STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
	PROPOSED STORM SEWER BORING LOCATIONS

LEGEND	
	ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
	YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
	GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
	PURPLE - STORM SEWER TO BE JACKED IN PLACE
	PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
	BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE


AREA-5

BORING LOCATION MAP : CIRCLE INTERCHANGE RECONSTRUCTION, SEWER PIPE AND JACKING/RECEIVING, CONTRACT 60X79, COOK COUNTY, ILLINOIS

SCALE: GRAPHICAL EXHIBIT 3-5 DRAWN BY: RKC CHECKED BY: NSB



FOR AECOM 1100-04-01



D160X79-SHT-Drain-07.dgn
 USER NAME = mkwilson
 PLOT SCALE = 40.0000' / in.
 PLOT DATE = 7/30/2018

DESIGNED - MRC	REVISED -
DRAWN - MRC	REVISED -
CHECKED - JMG	REVISED -
DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

PROPOSED DRAINAGE AND UTILITIES PLAN


SCALE: 1"=20' SHEET 7 OF 10 SHEETS STA. 100+00 TO STA. 104+00

F.A.I. R.T.E.: 90/94/290	SECTION: 2014-005R&B	COUNTY: COOK	TOTAL SHEETS: 888	SHEET NO.: 268
ILLINOIS FED. AID PROJECT				

FILE PATH = p:\61779-P\INT\secomon\line\local\IAC\CDM_D502_NA\Documents\01_Americas\Transportation\60X79_Contract\Phase_1\1000_CAD\006_Roadway\Sheets\60X79_Contract\0168779-SHT-Drain-08.dgn



FOR MAIN DRAIN INFORMATION UNDER I-90/94 SEE SHEET NO.268




LEGEND	
	EXISTING MANHOLE
	PROPOSED MANHOLE
	EXISTING CATCH BASIN
	PROPOSED CATCH BASIN
	EXISTING INLET
	PROPOSED INLET
	BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
	MANHOLE TO BE INSTALLED BY OTHERS
	CATCH BASIN TO BE INSTALLED BY OTHERS
	INLET TO BE INSTALLED BY OTHERS
	STORM SEWER TO BE INSTALLED BY OTHERS
	STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
	PROPOSED STORM SEWER
	BORING LOCATIONS

LEGEND	
	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
	STORM SEWER TO BE JACKED IN PLACE
	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

AREA-6

BORING LOCATION MAP : CIRCLE INTERCHANGE RECONSTRUCTION, SEWER PIPE AND JACKING/RECEIVING, CONTRACT 60X79, COOK COUNTY, ILLINOIS

SCALE: GRAPHICAL	EXHIBIT 3-6	DRAWN BY: RKC CHECKED BY: NSB
		1145 N. Main Street Lombard, IL 60148 www.wangeng.com
FOR AECOM		1100-04-01





D:\61779-P\INT\secomon\line\local\IAC\CDM_D502_NA\Documents\01_Americas\Transportation\60X79_Contract\Phase_1\1000_CAD\006_Roadway\Sheets\60X79_Contract\0168779-SHT-Drain-08.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


PROPOSED DRAINAGE AND UTILITIES PLAN			
SCALE: 1"=20'	SHEET 8 OF 10 SHEETS	STA. 16+00 TO STA. 21+50	

F.A.I. R.T.E.: 90/94/290	SECTION: 2014-005R&B	COUNTY: COOK	TOTAL SHEETS: 888	SHEET NO.: 269
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				




Site Map Scale 1 inch equals 110 feet


Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 1.5x






Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 1 : Drainage P2-01**




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-1




Site Map Scale 1 inch equals 145 feet

Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 2x

Lithology Graphics

- Topsoil
- Weathered bedrock
- Gravelly sand, sandy gravel
- IDH Silty Clay, Silty Clay Loam
- Dolomite or Dolomitic Limestone
- IDH Clay
- Pavement
- IDH Silt, Silty Loam
- Concrete




Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile Area 1: Drainage P2-02, P2-03, and P2-06




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-2




Site Map Scale 1 inch equals 50 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 1.5x

Lithology Graphics

- | | | | |
|-------------------|----------|-----------------------------|---------------------------------|
| Pavement | Concrete | Gravelly sand, sandy gravel | IDH Silty Clay, Silty Clay Loam |
| IDH Clay | Topsoil | IDH Silt, Silty Loam | Coarse sand |
| Weathered bedrock | | | |


Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile Area 1: Drainage P2-05












Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-3



DISTANCE ALONG PROFILE (feet)


Lithology Graphics



- | | | | |
|---|---|---|---|
|  Pavement |  Concrete |  Crushed stone |  IDH Silty Clay, Silty Clay Loam |
|  IDH Clay |  IDH Silt, Silty Loam |  Coarse sand |  Weathered bedrock |
|  Dolomite or Dolomitic Limestone | | | |




Site Map Scale 1 inch equals 0 feet

Explanation:



-  Water Level Reading at time of drilling.
-  Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0x


Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile
Area 2 : Bridge Drainage at Sta. 1608+00.00




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM


JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-4



Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0x

Lithology Graphics

- | | | | |
|---------------------------------|----------------------|----------------------|-------------|
| Concrete | Pavement | Crushed stone | IDH Clay |
| IDH Silty Clay, Silty Clay Loam | IDH Sand, Sandy Loam | IDH Silt, Silty Loam | Coarse sand |
| Dolomite or Dolomitic Limestone | | | |



Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 2 : Drainage P3-06 and P3-07**



Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM


JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-5




20-RWB-01

Site Map Scale 1 inch equals 0 feet

Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0x

Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148




Subsurface Data Profile
Area 2 : Bridge Drainage at Sta. 1611+00.00



Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM


JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-6

WEI 11X17 11000401.GPJ_WANGENG.GDT 5/2/18




Site Map Scale 1 inch equals 60 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling.



Vertical Exaggeration: 1x

	Concrete		Pavement		Crushed stone		IDH Clay
	IDH Silty Clay, Silty Clay Loam		IDH Silt, Silty Loam		Coarse sand		Gravelly sand, sandy gravel
	Topsoil		IDH Clay Loam		Weathered bedrock		Dolomite or Dolomitic Limestone


Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile Area 2: Drainage P3-01, P3-12, and P3-08



Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-7



DISTANCE ALONG PROFILE (feet)

Lithology Graphics

- Topsoil
- IDH Clay Loam
- IDH Silty Clay, Silty Clay Loam
- IDH Clay
- IDH Silt, Silty Loam

Site Map Scale 1 inch equals 0 feet

Explanation:

21-RWB-02
1611+67.44

Borehole Lithology

N-N-value, (blw/12 in)
Cu-UC Strength, (lbf)
MC-Moisture Content, (%)

Borehole Number Station

Water Level Reading at time of drilling.

Water Level Reading 24-hr after drilling or at end of drilling

Horizontal Scale (feet)

Vertical Exaggeration: 0x


Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile
Area 2: Drainage P3-05



Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-8



DISTANCE ALONG PROFILE (feet)

Lithology Graphics

- | | | | |
|----------------------|---------------------------------|-------------------|---------------------------------|
| Crushed stone | IDH Silty Clay, Silty Clay Loam | IDH Loam | IDH Clay |
| IDH Silt, Silty Loam | Gravelly sand, sandy gravel | Weathered bedrock | Dolomite or Dolomitic Limestone |

Site Map Scale 1 inch equals 0 feet

Explanation:

22-RWB-01
1703+67.42 — Borehole Number Station

Borehole Lithology

N—N-value, (blw/12 in)
Qu—UC Strength, (tsf)
MC—Moisture Content, (%)

▽ Water Level Reading at time of drilling.
▼ Water Level Reading 24-hr after drilling or at end of drilling

Horizontal Scale (feet)

Vertical Exaggeration: 0x



Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 2: Drainage P3-03 and P3-04**




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM


JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-9



Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0x

Lithology Graphics

- | | | | |
|----------------------|---------------------------------|-------------------|---------------------------------|
| Crushed stone | IDH Silty Clay, Silty Clay Loam | IDH Loam | IDH Clay |
| IDH Silt, Silty Loam | Gravelly sand, sandy gravel | Weathered bedrock | Dolomite or Dolomitic Limestone |



Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 2: Drainage P3-03 and P3-04**




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-10



Site Map Scale 1 inch equals 20 feet

Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0.5x

Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148








Subsurface Data Profile
Area 3: Drainage P4-02 and P4-07






Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-11

Lithology Graphics


-  Crushed stone
-  IDH Silty Clay, Silty Clay Loam
-  IDH Clay
-  IDH Sand, Sandy Loam
-  IDH Silt, Silty Loam
-  Gravelly sand, sandy gravel
-  Dolomite or Dolomitic Limestone

WEI 11X17 11000401.GPJ_WANGENG.GDT 5/2/18




Site Map Scale 1 inch equals 35 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0.5x

- Lithology Graphics**
- Crushed stone
 - IDH Silty Clay, Silty Clay Loam
 - IDH Clay
 - IDH Sand, Sandy Loam
 - IDH Silt, Silty Loam
 - Gravelly sand, sandy gravel
 - Dolomite or Dolomitic Limestone


Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 3 : Drainage P4-03**




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-12




Lithology Graphics

- Topsoil
- IDH Sand, Sandy Loam
- IDH Clay Loam
- IDH Silt, Silty Loam
- IDH Silty Clay, Silty Clay Loam
- Gravelly sand, sandy gravel
- IDH Clay
- Weathered bedrock




Site Map Scale 1 inch equals 45 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 1x



Wang Engineering, Inc.
 1145 N Main Street
 Lombard, IL 60148

Subsurface Data Profile
Area 3 : Drainage P4-04 and P4-05




Circle Interchange Reconstruction
 Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-13




Site Map Scale 1 inch equals 80 feet


Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 2x






Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile
Area 3 : Drainage P4-08, P4-09




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-14




Site Map Scale 1 inch equals 80 feet

Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 3x

Lithology Graphics

- Topsoil
- IDH Silty Clay, Silty Clay Loam
- IDH Clay
- IDH Silt, Silty Loam
- IDH Sand, Sandy Loam



Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 3 : Drainage P4-10**




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-15



Site Map Scale 1 inch equals 0 feet

Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0x

Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148







**Subsurface Data Profile
Area 3: Drainage P4-01**



Jane Byrne Interchange
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-16

Lithology Graphics


-  Gravelly sand, sandy gravel
-  IDH Silt, Silty Loam
-  IDH Silty Clay, Silty Clay Loam
-  IDH Clay
-  Weathered bedrock
-  Dolomite or Dolomitic Limestone



N



1712-B-03



DISTANCE ALONG PROFILE (feet)

Lithology Graphics



Pavement



Gravelly sand, sandy gravel



IDH Silty Clay, Silty Clay Loam



IDH Clay



IDH Silt, Silty Loam




IDH Sand, Sandy Loam



Weathered bedrock

Site Map Scale 1 inch equals 0 feet

Explanation:



- ▽ Water Level Reading at time of drilling.
- ▼ Water Level Reading 24-hr after drilling or at end of drilling



Horizontal Scale (feet)

Vertical Exaggeration: 0x

Wang Engineering, Inc.
 1145 N Main Street
 Lombard, IL 60148



Subsurface Data Profile
Area 3: Drainage P4-11



Jane Byrne Interchange
 Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-17

WEI 11X17 11000401.GPJ_WANGENG.GDT 7/7/18



Site Map Scale 1 inch equals 0 feet

Explanation:

1712-B-03
1618+05.95

Borehole Number Station

Borehole Lithology

N--N-value, (blw/12 in)
Cu--UC Strength, (tsf)
MC--Moisture Content, (%)

▽ Water Level Reading at time of drilling.

▼ Water Level Reading 24-hr after drilling or at end of drilling

0 0

Horizontal Scale (feet)

Vertical Exaggeration: 0x


Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 3: Drainage P4-12**

 SINCE 1982	Jane Byrne Interchange Section 17, T39N, R14E of 3rd PM	
	JOB NUMBER	PLATE NUMBER
	1100-04-01	EXHIBIT 4-18




1712-B-03




Site Map Scale 1 inch equals 0 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0x

Wang Engineering, Inc.
 1145 N Main Street
 Lombard, IL 60148

Subsurface Data Profile Area 3: Drainage P4-13






Jane Byrne Interchange
 Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-19


WEI 11X17 11000401.GPJ_WANGENG.GDT 7/7/18

WEI 11X17 11000401.GPJ_WANGENG.GDT 7/7/18




Site Map Scale 1 inch equals 0 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0x

Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 3: Drainage P4-14**



Jane Byrne Interchange
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-20




N



L=83', D=12"

A

A'



DISTANCE ALONG PROFILE (feet)

Lithology Graphics



Pavement



Gravelly sand, sandy gravel



IDH Silty Clay, Silty Clay Loam



IDH Clay



IDH Silt, Silty Loam




IDH Sand, Sandy Loam



Weathered bedrock

Site Map Scale 1 inch equals 0 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Horizontal Scale (feet)

Vertical Exaggeration: 0x

Wang Engineering, Inc.


1145 N Main Street
Lombard, IL 60148

**Subsurface Data Profile
Area 3: Drainage P4-15**



Jane Byrne Interchange
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-21



U/S P4-16
Invert El. 566.89

D/S P4-16
Invert El. 566.60


L=58', D=24"

DISTANCE ALONG PROFILE (feet)

ELEVATION (feet)


Lithology Graphics

- Topsoil
- IDH Sand, Sandy Loam
- IDH Clay Loam
- IDH Silt, Silty Loam
- IDH Silty Clay, Silty Clay Loam
- Gravelly sand, sandy gravel
- IDH Clay
- Weathered bedrock




Site Map Scale 1 inch equals 45 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 0.5x


Wang Engineering, Inc.
1145 North Main Street
Lombard, IL 60148

**Soil Profile
Area 3: Pipe P4-16**




Jane Byrne Interchange
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-21




Site Map Scale 1 inch equals 185 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 2.5x

Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148



Subsurface Data Profile Area 4: Drainage, P5-01, P5-03, and P5-05

WEI SINCE 1982	Circle Interchange Reconstruction Section 17, T39N, R14E of 3rd PM	
	JOB NUMBER 1100-04-01	PLATE NUMBER EXHIBIT 4-23

Lithology Graphics


- | | | | |
|----------------------|-----------------------------|---------------------------------|---------------|
| Pavement | Gravelly sand, sandy gravel | IDH Silty Clay, Silty Clay Loam | IDH Clay |
| IDH Silt, Silty Loam | IDH Sand, Sandy Loam | Weathered bedrock | Crushed stone |
| Concrete | Coarse sand | Topsoil | |

WEI 11X17 11000401.GPJ_WANGENG.GDT 5/2/18




Site Map Scale 1 inch equals 130 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 2.5x



Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile
Area 4: Drainage P5-02, P5-04, P5-07 to P5-09




Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-24



Site Map Scale 1 inch equals 185 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 2.5x

Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile Area 5: Drainage P7-01, P7-02, and P4-13



Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM



JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-25

Lithology Graphics

- | | | | |
|----------------------|-----------------------------|---------------------------------|----------------------|
| Pavement | Crushed stone | IDH Silty Clay, Silty Clay Loam | IDH Clay |
| IDH Silt, Silty Loam | Gravelly sand, sandy gravel | Dolomite or Dolomitic Limestone | IDH Sand, Sandy Loam |
| Weathered bedrock | Topsoil | IDH Clay Loam | |


WEI 11X17 11000401.GPJ_WANGENG.GDT 5/2/18

WEI 11X17 11000401.GPJ_WANGENG.GDT 5/2/18




Site Map Scale 1 inch equals 75 feet

Explanation:



- Water Level Reading at time of drilling.
- Water Level Reading 24-hr after drilling or at end of drilling



Vertical Exaggeration: 1x

Wang Engineering, Inc.
1145 N Main Street
Lombard, IL 60148

Subsurface Data Profile Area 6 : Drainage P8-01



Circle Interchange Reconstruction
Section 17, T39N, R14E of 3rd PM

JOB NUMBER	PLATE NUMBER
1100-04-01	EXHIBIT 4-26

Lithology Graphics

- | | | | |
|---------------------------------|---------------------------------|-----------------------------|----------|
| Pavement | Crushed stone | Gravelly sand, sandy gravel | IDH Clay |
| IDH Silty Clay, Silty Clay Loam | IDH Silt, Silty Loam | Weathered bedrock | Topsoil |
| IDH Sand, Sandy Loam | Dolomite or Dolomitic Limestone | | |

APPENDIX A



BORING LOG 1703-B-04

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 584.72 ft
 North: 1898071.44 ft
 East: 1171813.94 ft
 Station: 1104+42.63
 Offset: 42.6570 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	584.53	4'-4" 53-inch thick CRUSHED STONE --FILL--															
		Very stiff, dark brown and gray SILTY CLAY LOAM, trace gravel, brick and glass fragments --FILL--			1	5 11 15	2.25 P	26						9	0 1 2	0.25 B	26
					2	3 7 9	2.75 P	16				25		10	0 0 2	0.25 B	26
	579.2	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			3	2 3 4	0.66 B	19						11	0 0 1	0.25 B	27
		--L _L (%)=29, P _L (%)=16-- --%Gravel=3.8-- --%Sand=16.9-- --%Silt=54.2-- --%Clay=25.1-- --A-6(8)--			4	2 2 3	0.57 B	21				30		12	0 0 2	0.33 B	26
					5	0 1 3	0.49 B	24									
					6	0 2 2	0.44 B	23				35		13	0 2 2	0.16 B	25
					7	0 2 2	0.41 B	25									
					8	0 0 0	0.41 B	25				40		14	0 1 2	0.33 B	28
											--L _L (%)=36, P _L (%)=18-- --%Gravel=1.8-- --%Sand=10.7--						

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-10-2013** Complete Drilling **10-17-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&R** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **74.00 ft**
 At Completion of Drilling **91.25 ft**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1703-B-04

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 584.72 ft
 North: 1898071.44 ft
 East: 1171813.94 ft
 Station: 1104+42.63
 Offset: 42.6570 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--%Silt=50.0-- --%Clay=37.5-- --A-6(15)--															
			45		15	3 4 4	0.66 B	20									
	538.0	Very stiff, gray SILTY CLAY, trace gravel															
		--L _L (%)=27, P _L (%)=16-- --%Gravel=6.1-- --%Sand=20.1-- --%Silt=50.9-- --%Clay=22.9-- --A-6(6)--	50		16	4 7 11	3.53 B	23									
	533.0	Dense, gray SANDY LOAM, trace gravel															
			55		17	11 14 26	NP	12									
	530.5	Hard, gray SILTY LOAM, trace gravel															
			75		21	18 36 50/5											
	510.7	Very dense, gray SILTY LOAM, trace gravel --Saturated--															
	508.0	Hard, gray SILTY CLAY LOAM to SILTY LOAM, trace gravel															
			80		22	34 50/6											

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-10-2013** Complete Drilling **10-17-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&R** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **74.00 ft**
 At Completion of Drilling **91.25 ft**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



BORING LOG 1703-B-04

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 584.72 ft
 North: 1898071.44 ft
 East: 1171813.94 ft
 Station: 1104+42.63
 Offset: 42.6570 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--HARD DRILLING-- --Possible Cobbles--	85	X	23	50/6	4.50 P					105	X	27	21 50/3	NP	14
		--HARD DRILLING-- --Possible Cobbles--	90	X	24	28 50/5	3.69 S	17				110		1			
	493.5	Very dense, gray GRAVELLY SAND --Saturated--								478.7	Strong, light gray, poor to excellent rock mass quality, bedded fresh DOLOSTONE, up to 30-inch beds, 17-inch spaced joints, horizontal joints with less than 0.2-inch infilling, hard joint wall, with stylolitic surfaces, and moderately vuggy porosity.						
			95	X	25	50/3	NP	10			--Run 1 - RECOVERY=88%-- --RQD=26%-- 109.5ft-Qu=10990 psi ---> --Run 2 - RECOVERY=99%-- --RQD=92%--	115		2			
			100	X	26	19 50/2	NP	10		466.7	113.0ft-Qu=9060 psi --->	120					
											Boring terminated at 118.00 ft						

GENERAL NOTES

Begin Drilling **10-10-2013** Complete Drilling **10-17-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&R** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **74.00 ft**
 At Completion of Drilling **91.25 ft**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1703-PZ-01

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 582.49 ft
 North: 1898127.96 ft
 East: 1171807.47 ft
 Station: 1104+74.81
 Offset: 3.30157 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	
		--Drilled without sampling--	5								Piezometer Data: --Installed in Nov. 12, 2014 --Bentonite Seal 70 to 72 feet --Top of Sand Pack at 72 feet --Top of Screen at 75.3 feet --Screen Length 20 feet --Bottom of Screen at 95.3 feet	25						
			10								--piezometer stabilized water level reading -- --reading during well development (11/20/2014) = 32.00 feet bgs-- --reading date: 12/05/2014 = 31.10 feet bgs--	30						
			15									35						
			20									40						

GENERAL NOTES

Begin Drilling **11-10-2014** Complete Drilling **11-12-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **4.25" HSA, monitoring water well**

WATER LEVEL DATA

While Drilling ▽ **78.00 ft**
 At Completion of Drilling ▾ **NA**
 Time After Drilling **NA**
 Depth to Water ▽ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1703-PZ-01

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 582.49 ft
 North: 1898127.96 ft
 East: 1171807.47 ft
 Station: 1104+74.81
 Offset: 3.30157 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
			45									65					
			50									70					
			55									75					
			60									80					

Piezometer Data:
 --Installed in Nov. 12, 2014
 --Bentonite Seal 70 to 72 feet
 --Top of Sand Pack at 72 feet
 --Top of Screen at 75.3 feet
 --Screen Length 20 feet
 --Bottom of Screen at 95.3 feet

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **11-10-2014** Complete Drilling **11-12-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **4.25" HSA, monitoring water well**

While Drilling ▽ **78.00 ft**
 At Completion of Drilling ▼ **NA**
 Time After Drilling **NA**
 Depth to Water ▼ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1703-PZ-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 582.49 ft
 North: 1898127.96 ft
 East: 1171807.47 ft
 Station: 1104+74.81
 Offset: 3.30157 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	482.5		85														
		Very dense, gray SILTY LOAM, trace gravel	90		1	40 42 18/3	NP	13									
		--Dry--															
			95		2	10 23 50/3	NP	20									
		--Dolostone fragments--															
			100		3	15 30/2	NP	14									
		Boring terminated at 100.00 ft															

GENERAL NOTES

Begin Drilling **11-10-2014** Complete Drilling **11-12-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **4.25" HSA, monitoring water well**

WATER LEVEL DATA

While Drilling ∇ **78.00 ft**
 At Completion of Drilling ∇ **NA**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



BORING LOG 1706-B-02

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 573.51 ft
 North: 1898279.12 ft
 East: 1171636.73 ft
 Station: 1214+88.11
 Offset: 8.0782 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	572.2	16-inch thick ASPHALT --PAVEMENT--									--%Silt=49.0-- --%Clay=31.3-- --A-6 (12)--						
	570.3	Medium dense, white and gray CRUSHED STONE --BASE COURSE--	1		1	6 12 13	NP					9		9	0 0 1	0.49 B	25
	568.0	Very stiff, gray SILTY CLAY LOAM, trace gravel	5		2	2 4 4	3.28 B	19				25		10	0 1 2	< 0.25 P	27
		Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			3	1 1 1	0.41 B	16						11	1 2 3	< 0.25 P	24
			10		4	0 0 2	0.41 B	27				30		12	2 2 3	0.82 B	25
					5	0 1 1	0.41 B	27		541.8	Stiff to hard, gray SILTY CLAY, trace gravel						
			15		6	0 1 1	0.25 B	26				35		13	7 6 7	1.23 B	18
					7	0 1 1	0.41 B	25									
		--L _L (%)=34, P _L (%)=17-- --%Gravel=4.2-- --%Sand=15.6--	20		8	0 0 1	0.41 B	24				40		14	4 7 8	3.03 B	20

GENERAL NOTES

Begin Drilling **03-27-2014** Complete Drilling **03-31-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **M. de los Reyes** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1706-B-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 573.51 ft
 North: 1898279.12 ft
 East: 1171636.73 ft
 Station: 1214+88.11
 Offset: 8.0782 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	524.0	Medium dense, gray SILT	45	X	15	4 6 18	2.87 B	18				65	X	19	15 20 27	9.02 S	16
	501.8	--Wet-- Hard, gray SILTY CLAY LOAM to SILTY LOAM, trace gravel	50	X	16	5 15 13	4.10 B	16		501.8	--HARD DRILLING-- --Possible Cobbles-- Very dense, gray GRAVELLY SANDY LOAM	70	X	20	16 26 50/2	4.74 B	13
	516.8		55	X	17	7 7 8	NP	23				75	o	21	50/2	NP	
			60	X	18	15 20 27	6.97 S	13				80	X	22	50/3	NP	13

GENERAL NOTES

Begin Drilling **03-27-2014** Complete Drilling **03-31-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **M. de los Reyes** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1706-B-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 573.51 ft
 North: 1898279.12 ft
 East: 1171636.73 ft
 Station: 1214+88.11
 Offset: 8.0782 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	491.8	--HARD DRILLING-- --Possible Cobbles--								471.5							
		Very dense, gray SILT, trace CLAY lamination									Boring terminated at 102.00 ft						
		--DRY--	85		23	20 33 28	NP	20				105					
	484.3	Very dense, gray GRAVELLY SAND	90		24	17 50 43	NP	16				110					
	481.5	Strong, light gray, good rock mass quality, bedded fresh DOLOSTONE, up to 12-inch beds, 9-inch joints spacing, horizontal and vertical joints with none to more than 0.2-inch infilling, up to 2-inch greenish gray argillaceous partings, hard joint wall, with stylolitic surfaces, and moderately vuggy porosity.	95		1							115					
		--Run 1 - RECOVERY=100%-- --RQD=83%--															
		--Run 2 - RECOVERY=97%-- --RQD=92%--	100		2							120					

GENERAL NOTES

Begin Drilling **03-27-2014** Complete Drilling **03-31-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **M. de los Reyes** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



BORING LOG 1712-B-02

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 578.30 ft
 North: 1897649.82 ft
 East: 1171680.84 ft
 Station: 1610+06.78
 Offset: 3.2187 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		13.5-inch thick CONCRETE --PAVEMENT--															
	577.2																
	576.8	4-inch thick ASPHALT --PAVEMENT--															
		Medium dense, brown SANDY GRAVEL --BASE COURSE--			1	12 11 4	NP	9						9	0 0 0	0.16 B	22
	574.8				2	1 2 2	0.25 B	29						10	0 0 1	0.16 B	27
			5		3	0 0 0	0.16 B	21						11	0 0 2	0.33 B	23
					4	0 1 3	0.33 B	17						12	1 2 2	0.25 B	26
					5	1 1 2	0.57 B	22									
					6	0 0 1	0.16 B	25						13	1 2 1	0.41 B	28
			15		7	0 0 1	0.08 B	26		541.6	Very stiff, gray SILTY CLAY, trace gravel						
					8	0 0 0	0.16 B	26		538.8	Gray SANDY LOAM			14	5 13 18	2.62 B	16
			20														

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-15-2013** Complete Drilling **10-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&R** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **57.00 ft**
 At Completion of Drilling **82.00 ft**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



BORING LOG 1712-B-02

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 578.30 ft
 North: 1897649.82 ft
 East: 1171680.84 ft
 Station: 1610+06.78
 Offset: 3.2187 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	536.6	--Moist--								536.6							
		Hard, gray SILTY LOAM to SILTY CLAY LOAM, trace gravel			15	9 22 26	6.23 B	15			Gray, coarse SAND, some gravel			19	20 20 18		
		--L _L (%)=27, P _L (%)=16-- --%Gravel=8.1-- --%Sand=26.9-- --%Silt=51.7-- --%Clay=13.3-- --A-6(5)--	45							513.8	Very dense, gray SILTY LOAM, trace gravel	65					
					16	12 17 23	4.50 P	15			--L _L (%)=19, P _L (%)=14-- --%Gravel=7.4-- --%Sand=21.3-- --%Silt=59.7-- --%Clay=11.7-- --A-4(1)--	70		20	32 50/5		
	526.6	Very stiff, gray CLAY			17	4 7 9	2.62 B	25						21	24 44 50/3	9.59 S	
		--L _L (%)=36, P _L (%)=19-- --%Gravel=0.1-- --%Sand=2.0-- --%Silt=49.4-- --%Clay=48.5-- --A-6(17)--	55														
	521.6	Medium dense, gray SANDY LOAM, trace gravel			18	4 6 9	NP	20						22	50/3		
		--Saturated--															
			60														

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-15-2013** Complete Drilling **10-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&R** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **57.00 ft**
 At Completion of Drilling **82.00 ft**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1712-B-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 578.30 ft
 North: 1897649.82 ft
 East: 1171680.84 ft
 Station: 1610+06.78
 Offset: 3.2187 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	496.6	Very dense, gray SILT --Saturated--								477.3	Boring terminated at 101.00 ft						
		--%Gravel=0.0-- --%Sand=1.7-- --%Silt=91.5-- --%Clay=6.8-- --A-4(0)--	85		23	20 34 50	NP	19				105					
		--HARD DRILLING-- --Possible Cobbles--															
		--HARD DRILLING-- --Possible Cobbles--	90		24	30 50/5	NP	16				110					
	487.3	Strong, light gray, fair rock mass quality, thin bedded, fresh DOLOSTONE, 2- to 44-inch beds, 2- to 44-inch spaced joints, horizontal and vertical joints with less than 0.2-inch infilling, hard joint wall, with stylolitic surfaces, and moderately vuggy porosity, <0.5 inch vugs.															
		--Run 1 - RECOVERY=100%-- --RQD=71%--	95		1							115					
			100									120					

GENERAL NOTES

Begin Drilling **10-15-2013** Complete Drilling **10-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&R** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling ∇ **57.00 ft**
 At Completion of Drilling ∇ **82.00 ft**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



BORING LOG 1712-B-03

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 584.78 ft
 North: 1898322.61 ft
 East: 1171738.21 ft
 Station: 1618+05.95
 Offset: 4.7838 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	583.8	3-inch thick, ASPHALT over 9-inch thick, CONCRETE --PAVEMENT--															
	582.5	Medium dense, grayish white SANDY GRAVEL --DRY-- --BASE COURSE--			1	12 11 9	NP	5						9	0 0 2	0.41 B	25
		Stiff, brown to gray SILTY CLAY LOAM, trace gravel --FILL--			2	2 4 5	1.50 N/6	8				25		10	0 0 1	0.49 B	25
					3	1 3 3	1.64 B	17						11	0 0 1	0.25 B	25
	576.8	Soft to stiff, gray CLAY to SILTY CLAY, trace gravel			4	1 3 3	0.82 B	18						12	0 0 1	0.25 B	26
					5	0 0 2	0.57 B	23									
					6	0 1 2	0.57 B	22						13	0 1 1	0.41 B	25
					7	0 0 1	0.49 B	24									
					8	0 1 2	0.41 B	24						14	0 2 3	0.66 B	26

GENERAL NOTES

Begin Drilling **07-28-2014** Complete Drilling **08-20-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1712-B-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 584.78 ft
 North: 1898322.61 ft
 East: 1171738.21 ft
 Station: 1618+05.95
 Offset: 4.7838 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	538.0	Stiff to very stiff, gray SILTY CLAY, trace gravel	45	X	15	0 0 2	0.33 B	20		523.0	Medium dense, gray fine SAND, trace gravel	65	X	19	10 8 13	NP	13
	518.0	Dense, gray SILTY LOAM, trace gravel	50	X	16	3 6 9	1.00 P	21		518.0	Dense, gray SILTY LOAM, trace gravel	70	X	20	13 15 28	NP	13
			55	X	17	2 5 10	2.87 B	17				75	X	21	14 17 26	NP	13
	528.0	Medium dense, gray SILTY LOAM, trace gravel	60	X	18	5 8 13	NP	21				80	X	22	18 27 50/4	NP	23

GENERAL NOTES

Begin Drilling **07-28-2014** Complete Drilling **08-20-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1712-B-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 584.78 ft
 North: 1898322.61 ft
 East: 1171738.21 ft
 Station: 1618+05.95
 Offset: 4.7838 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)			
	493.6	Very dense, gray, very fine to fine SAND --possible water bearing--		⊗	23	80/6	NP	13	[Patterned Soil Profile]	474.8	Very dense, greenish gray, shaly DOLOSTONE; moist to wet	105	⊗	27	100/4	NP	21			
				○	24	80/4	NR							110	○	28	100/3	NR		
					⊗	25	90/6	NP		10					115					
	484.8				○	26	100/5	NR							120					
										Boring terminated at 111.00 ft										

GENERAL NOTES

Begin Drilling **07-28-2014** Complete Drilling **08-20-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling ▽ **Rotary wash**
 At Completion of Drilling ▾ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ▾ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



BORING LOG 1715-B-02

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 578.98 ft
 North: 1898224.57 ft
 East: 1171745.64 ft
 Station: 1105+89.73
 Offset: 39.7965 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	578.82	82-inch thick ASPHALT --PAVEMENT--															
	578.0	10-inch thick CONCRETE --PAVEMENT--															
		Loose, light brown CRUSHED STONE --BASE COURSE--			1	4 5 4	NP	10						9	0 1 2	0.25 B	27
	576.0	Soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			2	0 1 2	0.82 B	23				25		10	1 1 2	0.50 N/6	
					3	2 2 3	0.41 B	19						11	0 2 2	0.41 B	26
					4	2 2 3	0.49 B	22						12	1 1 2	0.57 B	26
					5	1 2 2	0.74 B	20									
					6	0 1 2	0.33 B	23						13	2 2 2	0.33 B	28
					7	1 1 2	0.33 B	26									
					8	1 1 2	0.25 B	26						14	4 6 9	0.67 B	18

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **02-23-2014** Complete Drilling **03-23-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **3.00 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **24 hours**
 Depth to Water **72.00 ft**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1715-B-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 578.98 ft
 North: 1898224.57 ft
 East: 1171745.64 ft
 Station: 1105+89.73
 Offset: 39.7965 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	537.2	Very stiff, gray SILTY CLAY LOAM, trace gravel															
			45	X	15	7 7 7	3.36 B	22				65	X	19	20 31 42	4.59 S	14
			50	X	16	6 10 12	2.54 B	16				70	X	20	20 50/4	5.74 S	13
	527.2	Dense, gray SILT									Very dense, gray SILTY LOAM, trace to some gravel						
		--Wet--	55	X	17	14 16 18	NP	16				75	X	21	30 50/4	NP	10
	522.2	Hard, gray SILTY CLAY LOAM to SILTY LOAM, trace gravel									--HARD DRILLING-- --Possible Cobbles--						
			60	X	18	18 24 27	8.19 S	12				80	X	22	50/5	NP	12

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **02-23-2014** Complete Drilling **03-23-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **3.00 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **24 hours**
 Depth to Water **72.00 ft**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1715-B-02

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 578.98 ft
 North: 1898224.57 ft
 East: 1171745.64 ft
 Station: 1105+89.73
 Offset: 39.7965 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--HARD DRILLING-- --Possible Cobbles--	85	○	23	50/3	NP										
		--HARD DRILLING-- --Possible Cobbles--		⊗	24	50/3	NP	10									
	486.0	--VERY HARD, STEADY DRILLING-- --WEATHERED BEDROCK-- --ROLLER BIT REFUSAL--															
	486.0	Boring terminated at 93.00 ft															
			95														
			100														

GENERAL NOTES

Begin Drilling **02-23-2014** Complete Drilling **03-23-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling ∇ **3.00 ft**
 At Completion of Drilling ▼ **mud in the borehole**
 Time After Drilling **24 hours**
 Depth to Water ▼ **72.00 ft**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



BORING LOG 1715-B-03

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 574.74 ft
 North: 1898289.14 ft
 East: 1171492.75 ft
 Station: 1216+42.65
 Offset: 33.3447 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		14-inch thick ASPHALT --PAVEMENT--															
	573.5																
	573.24	24-inch thick CRUSHED STONE --BASE COURSE--			1	5 6 6	NP							9	1 1 2	0.16 B	27
		Medium dense, brown SANDY GRAVEL --FILL--															
	571.5				2	4 2 3	0.25 P	26						10	0 0 1	0.16 B	25
		Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel															
					3	2 1 3	0.25 B	24						11	0 0 0	0.16 B	26
					4	1 1 2	0.41 B	25						12	1 2 3	0.49 B	27
					5	0 0 2	0.25 B	25									
					6	1 2 1	0.49 B	25						13	1 3 4	0.74 B	19
					7	1 1 1	0.33 B	27		538.0	Very stiff to hard, gray SILTY CLAY, trace gravel						
					8	0 0 0	0.25 B	26						14	6 8 10	5.41 B	15

GENERAL NOTES

Begin Drilling **03-19-2014** Complete Drilling **03-19-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **2.50 ft**
 At Completion of Drilling **62.00 ft**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1715-B-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 574.74 ft
 North: 1898289.14 ft
 East: 1171492.75 ft
 Station: 1216+42.65
 Offset: 33.3447 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	513.0	Gray SILT, trace gravel								513.0	Gray SILT, trace gravel						
			45	X	15	4 8 14	3.69 B	19				65	X	19	16 20 21	NP	20
										510.0	Hard (>4.5P), gray SILTY CLAY LOAM, trace gravel						
			50	X	16	5 9 10	2.87 B	24		508.0	Very dense, gray SILTY LOAM, little to some gravel			20	50/5	NP	9
	523.0	Medium stiff, gray CLAY, trace gravel									--HARD DRILLING-- --Possible Cobbles--						
			55	X	17	4 5 6	0.75 P	27						21	50/5	NP	13
	518.0	Hard, gray SILTY CLAY LOAM, trace gravel								498.0	Hard, gray SILTY CLAY LOAM, trace gravel						
			60	X	18	10 12 16	9.35 S	15						22	33 50/4	7.30 S	10

--L_L(%)=36, P_L(%)=18--
 --%Gravel=0.5--
 --%Sand=3.1--
 --%Silt=59.8--
 --%Clay=36.7--
 --A-6 (18)--

GENERAL NOTES

Begin Drilling **03-19-2014** Complete Drilling **03-19-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling ▽ **2.50 ft**
 At Completion of Drilling ▼ **62.00 ft**
 Time After Drilling **NA**
 Depth to Water ▼ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1715-B-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 574.74 ft
 North: 1898289.14 ft
 East: 1171492.75 ft
 Station: 1216+42.65
 Offset: 33.3447 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	
	490.7	Very dense, gray SILTY LOAM to SILT, trace gravel --Wet-- --L _L (%)=NP, P _L (%)=NP-- --%Gravel=0.1-- --%Sand=1.1-- --%Silt=92.6-- --%Clay=6.3-- --A-4 (0)--	85	✓	23	13 19 28	NP	22										
			90	✓	24	50/2	NP	19										
	483.2	--DIFFICULT DRILLING-- --WEATHERED BEDROCK--																
	480.7	--ROLLER BIT REFUSAL-- Boring terminated at 94.00 ft																

GENERAL NOTES

Begin Drilling **03-19-2014** Complete Drilling **03-19-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&P** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling ▽ **2.50 ft**
 At Completion of Drilling ▼ **62.00 ft**
 Time After Drilling **NA**
 Depth to Water ▼ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1715-B-05

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 577.87 ft
 North: 1897826.42 ft
 East: 1171228.58 ft
 Station: 1223+01.29
 Offset: 21.767 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	576.9	Dark brown SILTY LOAM, trace gravel															
		--TOPSOIL--															
		Stiff to hard, brown and gray SILTY CLAY LOAM, trace gravel and roots			1	6 8 7	4.50 P	14						9	1 2 3	0.25 B	27
		--FILL--															
					2	1 3 2	1.00 P	28				25		10	2 2 3	0.33 B	26
	572.4	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			3	1 2 3	0.25 B	20						11	3 3 4	0.49 B	26
					4	1 2 2	0.25 B	25				30		12	2 2 3	0.57 B	27
					5	1 1 2	0.25 B	28		546.1	Stiff to hard, gray SILTY CLAY LOAM, trace gravel						
					6	1 2 1	0.16 B	28				35		13	4 5 8	2.17 N/6	21
					7	1 2 2	0.25 B	27									
					8	1 2 2	0.16 B	27				40		14	4 5 10	1.75 P	24

GENERAL NOTES

Begin Drilling **04-14-2014** Complete Drilling **04-17-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **N&J** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1715-B-05

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 577.87 ft
 North: 1897826.42 ft
 East: 1171228.58 ft
 Station: 1223+01.29
 Offset: 21.767 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	516.1	Loose, gray SILT	45	X	15	8 10 14	4.10 B	15		516.1	Loose, gray SILT	65	X	19	4 4 4	NP	29
	511.1	Hard, gray SILTY CLAY LOAM, trace gravel	50	X	16	10 12 16	4.67 B	14		511.1	Hard, gray SILTY CLAY LOAM, trace gravel	70	X	20	10 16 22	6.07 B	20
	506.1	Very dense, gray SILTY LOAM, some gravel	55	X	17	8 9 14	2.95 B	21		506.1	Very dense, gray SILTY LOAM, some gravel	75	X	21	7 36 50/5	NA	
	521.1	Medium stiff, gray CLAY, trace gravel	60	X	18	4 3 5	0.66 B	38				80	X	22	50/5	NP	13

--HARD DRILLING--
 --Possible Cobbles--

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **04-14-2014** Complete Drilling **04-17-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **N&J** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**
 The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 1715-B-05

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 577.87 ft
 North: 1897826.42 ft
 East: 1171228.58 ft
 Station: 1223+01.29
 Offset: 21.767 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--HARD DRILLING-- --Possible Cobbles--	85		23	50/0											
	491.1	--DIFFICULT DRILLING-- --WEATHERED BEDROCK--															
	489.9	Strong, light gray, fair rock quality, bedded DOLOSTONE, beds up to 10 inch, 6 inch joint spacing, joints with more than 0.2 inch or no infilling, vuggy, and with stylolitic surfaces.	90						C O R E								
		--Run 1 -RECOVERY= 91%-- --RQD= 66%--															
					1												
			95														
	479.9	Boring terminated at 98.00 ft															
			100														

GENERAL NOTES

Begin Drilling **04-14-2014** Complete Drilling **04-17-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **N&J** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 18-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 585.35 ft
 North: 1897627.64 ft
 East: 1171433.33 ft
 Station: 1607+57.15
 Offset: 14.1384 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	585.04	1-inch thick, black SILTY LOAM --TOPSOIL-- Very stiff to hard, brown and gray SILTY CLAY LOAM, trace gravel --FILL--			1	13 11 12	4.50 P	17						9	1 2 3	0.41 B	24
			5		2	6 6 8	3.44 B	17				25		10	1 2 2	0.33 B	26
	579.8	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			3	2 2 3	0.41 B	20						11	1 1 2	0.25 B	27
			10		4	2 2 3	0.49 B	20				30		12	1 1 2	0.16 B	25
					5	0 1 2	0.25 B	25									
			15		6	2 3 4	0.66 B	21				35		13	2 2 4	0.66 B	24
					7	2 3 4	0.57 B	22									
			20		8	1 3 3	0.49 B	25				40		14	2 3 4	0.49 B	26

GENERAL NOTES

Begin Drilling **10-16-2013** Complete Drilling **10-17-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling ∇ **52.00 ft**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 18-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 585.35 ft
 North: 1897627.64 ft
 East: 1171433.33 ft
 Station: 1607+57.15
 Offset: 14.1384 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)							
	543.6	Very stiff to hard, gray SILTY CLAY LOAM, trace gravel	45	X	15	5 6 14	3.12 B	14		523.6	Dense to very dense, gray GRAVELLY SAND --Wet--	65	X	19	17 19 17	NP	13							
	533.6					16				9 14 18				4.76 B	14				70		20	26 26 21	NP	12
	531.3				Gray, medium to coarse SAND, trace gravel --Wet--																--HARD DRILLING-- --Possible Cobbles--			
	510.3	Very stiff to hard, gray SILTY CLAY, trace gravel	55	X	17	13 22 32	5.00 B	18		510.3	Boring terminated at 75.00 ft	75	O	21	22 50/3	NR								
	60					18				11 11 23				3.85 B	22				80					

GENERAL NOTES

Begin Drilling **10-16-2013** Complete Drilling **10-17-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **52.00 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 18-RWB-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 575.58 ft
 North: 1897703.15 ft
 East: 1171280.67 ft
 Station: 1224+34.52
 Offset: 9.451 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	575.33	33-inch thick ASPHALT --PAVEMENT--															
	574.6	9-inch thick CONCRETE --PAVEMENT--															
	572.6	Medium dense, brown SANDY GRAVEL --FILL--			1	11 10 6	NP	14						9	0 0 0	0.16 B	27
		Soft to medium stiff, gray SILTY CLAY LOAM, trace gravel			2	2 2 3	0.83 N/6					25		10	0 0 2	0.33 B	25
		--L _L (%)=30, P _L (%)=14-- --%Gravel=3.5-- --%Sand=15.1-- --%Silt=56.3-- --%Clay=25.2-- --A-6 (10)--			3	1 1 2	0.25 B	23						11	0 2 2	0.33 B	25
	567.6	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			4	1 1 2	0.25 B	26				30		12	0 0 1	0.33 B	27
					5	0 0 2	0.03 B	28									
					6	0 1 1	0.25 B	26				35		13	1 2 3	0.49 B	19
					7	0 1 2	0.25 B	26									
					8	0 0 0	0.16 B	27				40		14	4 9 10	3.12 B	17
										538.8	Very stiff, gray SILTY CLAY, trace gravel						

GENERAL NOTES

Begin Drilling **10-14-2013** Complete Drilling **10-14-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 18-RWB-02

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 575.58 ft
 North: 1897703.15 ft
 East: 1171280.67 ft
 Station: 1224+34.52
 Offset: 9.451 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	525.6																
		--L _L (%)=35, P _L (%)=17-- --%Gravel=2.2-- --%Sand=9.4-- --%Silt=51.7-- --%Clay=36.7-- --A-6 (15)-	45	X	15	4 8 10	2.95 B	19									
			50	X	16	6 17 14	3.20 B	17									
		Boring terminated at 50.00 ft															
			55														
			60														

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-14-2013** Complete Drilling **10-14-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA, boring backfilled upon completion**

While Drilling ▽ **Rotary wash**
 At Completion of Drilling ▽ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ▽ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 18-RWB-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 573.93 ft
 North: 1897759.34 ft
 East: 1171203.61 ft
 Station: 1604+97.68
 Offset: 33.9208 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	573.64	1/4-inch thick ASPHALT --PAVEMENT--															
	572.9	8-inch thick CONCRETE --PAVEMENT--															
		Medium dense, brown SANDY GRAVEL and CRUSHED STONE --FILL--			1	12 14 12	NP	7						9	0 0 2	0.25 B	26
					2	4 5 6	NP	11				25		10	0 1 2	0.33 B	25
	568.4	Very soft to soft, gray CLAY to SILTY CLAY, trace gravel			3	2 1 1	0.25 B	22						11	0 1 2	0.33 B	25
					4	0 1 1	0.33 B	26						12	0 0 0	0.25 B	29
					5	0 0 0	0.16 B	27		542.2	Stiff to hard, gray SILTY CLAY LOAM to SILTY LOAM, trace gravel						
		--L _L (%)=33, P _L (%)=19-- --%Gravel=2.2-- --%Sand=9.4-- --%Silt=51.7-- --%Clay=36.7-- --A-6 (10)--			6	0 0 0	0.16 B	27						13	3 5 10	3.85 B	15
					7	0 0 0	0.16 B	24									
					8	0 1 1	0.25 B	27			--L _L (%)=24, P _L (%)=15-- --%Gravel=8.4-- --%Sand=24.5--			14	8 12 14	4.35 B	14

GENERAL NOTES

Begin Drilling **10-14-2013** Complete Drilling **10-14-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **3.50 ft**
 At Completion of Drilling **40.00 ft**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 18-RWB-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 573.93 ft
 North: 1897759.34 ft
 East: 1171203.61 ft
 Station: 1604+97.68
 Offset: 33.9208 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--%Silt=49.1-- --%Clay=18.1-- --A-4 (3)--															
			45		15	5 8 12	3.03 B	22									
			50		16	5 8 10	1.97 B	23									
	523.9	Boring terminated at 50.00 ft															
			55														
			60														

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-14-2013** Complete Drilling **10-14-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **D. Kolpacki** Checked by **C. Marin**
 Drilling Method **3.25" HSA, boring backfilled upon completion**

While Drilling ▽ **3.50 ft**
 At Completion of Drilling ▼ **40.00 ft**
 Time After Drilling **NA**
 Depth to Water ▼ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 19-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 588.28 ft
 North: 1897670.99 ft
 East: 1171413.08 ft
 Station: 1607+21.55
 Offset: 18.1192 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	588.04	inch thick, dark brown SILTY LOAM --TOPSOIL-- Dense, dark brown SILTY LOAM, trace gravel --FILL--			1	6 23 22	NP	16		566.5	--%Silt=57.5-- --%Clay=11.8-- --A-4 (2)-- Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel		9	4 6 5	NA		
	585.3	Stiff, brown and gray SILTY CLAY LOAM, trace gravel	5		2	3 6 7	1.97 B	17				25	10	1 1 2	0.16 B		27
	582.8	Very soft to stiff, gray CLAY to SILTY CLAY, trace gravel --L _L (%)=31, P _L (%)=17-- --%Gravel=2.2-- --%Sand=18.3-- --%Silt=47.1-- --%Clay=32.3-- --A-6 (10)--	10		3	3 3 4	1.15 B	21				30	11	1 1 2	0.25 B		27
			15		4	1 2 3	0.33 B	24				35	12	1 1 2	0.33 B		27
					5	1 1 1	0.08 B	25					13	0 2 2	0.25 B		27
		--L _L (%)=31, P _L (%)=18-- --%Gravel=4.1-- --%Sand=13.3-- --%Silt=51.6-- --%Clay=31.0-- --A-6 (9)--			6	1 1 2	0.25 B	29				40	14	2 2 3	0.66 B		26
	571.5	Soft, gray SILTY LOAM, trace gravel --L _L (%)=23, P _L (%)=16-- --%Gravel=6.9-- --%Sand=23.7--	20		7	1 4 10	NA										
					8	4 3 4	0.49 B	17									

GENERAL NOTES

Begin Drilling **10-14-2013** Complete Drilling **10-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **67.00 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **48 hours**
 Depth to Water **15.00 ft**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 19-RWB-01

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 588.28 ft
 North: 1897670.99 ft
 East: 1171413.08 ft
 Station: 1607+21.55
 Offset: 18.1192 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--HARD DRILLING-- --Possible Cobbles--															
	501.5	Very dense, gray SILT	85		23	29 34 40	NP	11									
			90		24	15 50/5	NP	18									
	494.6	DOLOSTONE fragments --DIFFICULT DRILLING--															
	493.3	--WEATHERED BEDROCK--	95		25	50/4	NP	17									
		Boring terminated at 95.00 ft															

GENERAL NOTES

Begin Drilling **10-14-2013** Complete Drilling **10-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling ▽ **67.00 ft**
 At Completion of Drilling ▽ **mud in the borehole**
 Time After Drilling **48 hours**
 Depth to Water ▽ **15.00 ft**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



BORING LOG 2055-B-03

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 579.03 ft
 North: 1898462.94 ft
 East: 1171413.63 ft
 Station: 8149+26.26
 Offset: 58.3388 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	
	578.5	6-inch thick, black SILTY CLAY LOAM --TOPSOIL-- Very stiff to hard, brown and gray SILTY CLAY LOAM, trace gravel and brick --FILL--			1	7 9 9	4.50 P	14										
			5		2	3 4 4	2.46 B	14				25		10	1 1 1	0.49 B	27	
					3	4 5 5	2.50 P	16						11	0 2 1	0.49 B	27	
	571.0	Soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			4	1 2 2	0.49 B	24				30		12	0 2 1	0.49 B	27	
					5	0 2 1	0.41 B	25										
			15		6	0 2 2	0.57 B	26				35		13	1 1 2	0.49 B	26	
					7	0 1 2	0.49 B	26										
					8	0 1 2	0.41 B	26						14	2 2 4	0.74 B	20	
										542.3	Medium stiff to very stiff, gray SILTY CLAY to CLAY, trace gravel							

GENERAL NOTES

Begin Drilling **05-15-2013** Complete Drilling **05-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling ∇ **Rotary wash**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 2055-B-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 579.03 ft
 North: 1898462.94 ft
 East: 1171413.63 ft
 Station: 8149+26.26
 Offset: 58.3388 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	522.3	Medium dense, gray SILT															
			45	X	15	3 7 9	2.30 B	16		517.3	Hard, gray SILTY CLAY LOAM, trace gravel	65	X	19	13 18 30	4.50 P	16
			50	X	16	4 8 11	2.46 B	18				70	X	20	13 23 32	10.25 B	15
			55	X	17	3 7 8	2.30 B	24		507.3	Very dense, gray SILT to SILTY LOAM, trace gravel	75	X	21	32 50/5"	NP	10
			60	X	18	2 4 6	NP	23				80	X	22	40 50/2"	NP	9

GENERAL NOTES

Begin Drilling **05-15-2013** Complete Drilling **05-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig _____
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 2055-B-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 579.03 ft
 North: 1898462.94 ft
 East: 1171413.63 ft
 Station: 8149+26.26
 Offset: 58.3388 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
			85		23	26 38 44	NP	19									
	492.3	Hard, gray SILTY CLAY LOAM															
			90		24	18 21 35	8.20 B	14									
	487.3	Very dense, gray SANDY GRAVEL with dolostone clasts															
	485.0	Probably weathered DOLOSTONE			25	48	NP	13									
	484.0	--AUGER REFUSAL-- Boring terminated at 95.00 ft	95			50 1"											

GENERAL NOTES

Begin Drilling **05-15-2013** Complete Drilling **05-16-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 2055-B-04

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 575.69 ft
 North: 1898363.22 ft
 East: 1171499.16 ft
 Station: 8150+09.25
 Offset: 43.5063 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	574.7	5-inch thick ASPHALT over 7-inch thick CONCRETE --PAVEMENT--															
		Medium dense, brown SANDY GRAVEL --BASE COURSE--			1	5 9 9	NP	4						9	0 2 2	0.57 B	26
	572.7	Stiff, gray SILTY CLAY			2	3 2 3	1.07 B	20				25		10	0 1 2	0.49 B	25
	570.2	Soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			3	1 2 2	0.57 B	25						11	0 1 2	0.57 B	25
					4	1 1 2	0.57 B	24		547.7	Medium dense, gray, coarse SAND, little gravel			12	2 5 7	NP	15
					5	0 1 2	0.57 B	17		543.7	Medium dense, gray SANDY GRAVEL						
					6	0 2 2	0.66 B	25		540.9	Very stiff, gray SILTY CLAY to SILTY CLAY LOAM to LOAM, trace to some gravel			13	8 8 9	NP	15
					7	0 1 2	0.57 B	26									
					8	0 2 2	0.66 B	26				40		14	4 7 10	2.46 B	21
		--L _L (%)=35, P _L (%)=15-- --%Gravel=4.3-- --%Sand=15.2-- --%Silt=48.0-- --%Clay=32.4-- --A-6 (15)--															

GENERAL NOTES

Begin Drilling **05-19-2013** Complete Drilling **05-20-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 2055-B-04

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 575.69 ft
 North: 1898363.22 ft
 East: 1171499.16 ft
 Station: 8150+09.25
 Offset: 43.5063 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--%Silt=50.5-- --%Clay=36.1-- --A-6 (16)--															
	513.9									513.9	Hard, gray SILTY CLAY LOAM, trace gravel						
		--L _L (%)=22, P _L (%)=13-- --%Gravel=15.4-- --%Sand=31.5-- --%Silt=41.5-- --%Clay=11.6-- --A-4 (2)--	45	X	15	5 8 10	4.92 B	13				65	X	19	12 21 29	9.89 B	14
			50	X	16	4 6 8	2.62 B	22				70	X	20	23 50/4"	NP	13
			55	X	17	5 8 12	3.36 B	10				75	X	21	36 50/3"	NP	12
	518.9	Medium dense, gray SILT								508.9	Very dense, gray SILT to SILTY LOAM, trace to some gravel						
			60	X	18	4 5 8	NP	25				80	X	22	50/5"	NP	9

GENERAL NOTES

Begin Drilling **05-19-2013** Complete Drilling **05-20-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig _____
 Driller **P&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 20-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 577.12 ft
 North: 1897711.41 ft
 East: 1171734.33 ft
 Station: 1610+87.80
 Offset: 31.0288 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		13.5-inch thick CONCRETE --PAVEMENT--									gravel						
	576.0	4.5-inch thick ASPHALT --PAVEMENT--															
	575.8	Dense, white CRUSHED STONE --BASE COURSE--			1	26 30 11	NP	6						9	0 1 1	0.16 B	25
	573.9	Very soft to soft, gray CLAY to SILTY CLAY, trace gravel			2	2 1 1	0.25 B	27				25		10	0 1 2	0.16 B	26
					3	2 2 1	0.16 B	28						11	1 2 2	0.16 B	26
					4	1 1 2	0.41 B	24						12	2 2 1	0.57 B	27
					5	1 2 1	0.33 B	24									
					6	1 1 2	0.41 B	24						13	1 2 2	0.08 B	26
	561.6	Soft, gray SILTY CLAY LOAM, trace gravel --L _L (%)=31, P _L (%)=16-- --%Gravel=4.8-- --%Sand=16.1-- --%Silt=54.8-- --%Clay=24.3-- --A-6 (10)--			7	2 1 2	0.16 B	18		540.4	Stiff to hard, gray SILTY CLAY to SILTY CLAY LOAM, trace gravel						
	559.1	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace			8	0 1 1	0.16 B	26						14	3 6 10	1.72 B	23

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **10-28-2013** Complete Drilling **11-03-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Tomaras** Checked by **CLM**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **56.00 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 20-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 577.12 ft
 North: 1897711.41 ft
 East: 1171734.33 ft
 Station: 1610+87.80
 Offset: 31.0288 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	520.4	Loose, gray SILT --Saturated--								500.4	Very dense, gray SILTY LOAM, trace gravel						
			45		15	7 8 15	5.74 B	13		515.4	--HARD DRILLING-- --Possible Cobbles-- Very dense, gray, coarse SAND	65		19	48 50/5	NP	11
		--L _L (%)=35, P _L (%)=18-- --%Gravel=1.0-- --%Sand=6.7-- --%Silt=53.8-- --%Clay=38.6-- --A-6 (16)--	50		16	6 9 12	3.94 B	20		510.6	--HARD DRILLING-- --Possible Cobbles-- Hard, gray SILTY CLAY LOAM to SILTY LOAM, trace gravel	70		20	32 45 45	5.41 S	10
			55		17	6 8 9	1.56 B	21				75		21	20 18 35	7.30 S	17
			60		18	3 3 6	1.31 S	29				80		22	39 47 48	NP	15

GENERAL NOTES

Begin Drilling **10-28-2013** Complete Drilling **11-03-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Tomaras** Checked by **CLM**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **56.00 ft**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 20-RWB-01

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 577.12 ft
 North: 1897711.41 ft
 East: 1171734.33 ft
 Station: 1610+87.80
 Offset: 31.0288 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	495.4	--HARD DRILLING-- --Possible Cobbles--															
		Very dense, gray GRAVELLY SAND, some cobbles			23	50/1	NA										
			85														
					24	39 50/5	NP	11									
		--HARD DRILLING-- --Possible Boulders--															
	486.1	--ROLLER BIT REFUSAL-- Boring terminated at 91.00 ft															
			95														
			100														

GENERAL NOTES

Begin Drilling **10-28-2013** Complete Drilling **11-03-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Tomaras** Checked by **CLM**
 Drilling Method **2.25" SSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling ▽ **56.00 ft**
 At Completion of Drilling ▽ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ▽ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 21-RWB-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 596.95 ft
 North: 1897705.23 ft
 East: 1171851.95 ft
 Station: 1611+67.44
 Offset: 53.9743 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	596.0	12-inch thick, brown LOAM, trace gravel --TOPSOIL-- Hard, gray CLAY LOAM, trace gravel --FILL--			1	13 11 11	7.79 S	16						9	1 1 1	< 0.25 P	25
			5		2	5 9 11	5.33 S	13				25		10	0 0 0	0.16 B	22
	591.5	Stiff to medium stiff, gray and brown, SILTY CLAY, trace gravel, slag, brick and wood --FILL--			3	2 2 4	1.23 B	19						11	0 0 0	0.16 B	25
			10		4	2 3 4	1.15 B	19				30		12	0 0 0	0.25 B	25
					5	3 5 5	0.98 B	21									
	584.0	Very stiff, brown and gray SILTY CLAY, trace gravel			6	3 5 7	3.53 B	25						13	0 0 0	< 0.25 P	26
	581.5	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			7	0 2 2	0.66 B	24									
					8	1 1 2	< 0.25 P	29				40		14	0 1 3	0.49 B	25

GENERAL NOTES

Begin Drilling **09-25-2013** Complete Drilling **09-30-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Tomaras** Checked by **L. lordache**
 Drilling Method **2.25" HSA, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 21-RWB-02

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 596.95 ft
 North: 1897705.23 ft
 East: 1171851.95 ft
 Station: 1611+67.44
 Offset: 53.9743 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
			45		15	2 2 2	0.25 P	25				65		19	11 10 16	4.33 N/6	
			50		16	1 2 3	< 0.25 P	25				70		20	10 12 19	4.76 B	19
			55		17	1 3 3	0.66 B	21				75		21	6 10 12	1.80 B	24
	540.2	Stiff to hard, gray SILTY CLAY LOAM, trace gravel															
			60		18	15 17 21	> 4.50 P	15				80		22	6 8 10	3.00 N/6	19

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **09-25-2013** Complete Drilling **09-30-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Tomaras** Checked by **L. lordache**
 Drilling Method **2.25" HSA, boring backfilled upon completion**

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



BORING LOG 21-RWB-02

wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 596.95 ft
 North: 1897705.23 ft
 East: 1171851.95 ft
 Station: 1611+67.44
 Offset: 53.9743 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	
	515.2	Very dense, gray SILTY LOAM, little to some gravel and cobbles									--HARD DRILLING-- --Possible Cobbles--							
				85	23	13 31 41	NP	14			--HARD DRILLING-- --Possible Cobbles--	105	27	50/4	NP	11		
				90	24	18 35 48	9.35 S	10										
				95	25	20 36 50/4	9.10 S	13										
				100	26	50/5	NR											
	490.0										--ROLLER BIT REFUSAL-- Boring terminated at 107.00 ft							

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **09-25-2013** Complete Drilling **09-30-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig _____
 Driller **R&J** Logger **A. Tomaras** Checked by **L. lordache**
 Drilling Method **2.25" HSA, boring backfilled upon completion**

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 21-RWB-03

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 591.97 ft
 North: 1897787.89 ft
 East: 1171858.64 ft
 Station: 1612+32.77
 Offset: 11.8407 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		Very stiff to hard, brown CLAY LOAM, trace brick fragments --FILL--			1	3 4 8	3.50 P	11									
					2	5 5 7	3.12 B	14							0 0 0	0.33 B	23
		--3-inch thick, red, crushed Brick--			3	13 8 6	NP	19							0 1 2	0.45 B	26
					4	5 5 7	6.56 B	15							2 2 2	< 0.25 P	25
	581.5	Stiff, gray SILTY CLAY, trace gravel			5	2 3 4	1.97 B	23									
	579.0	Very soft to medium stiff, gray CLAY, trace gravel			6	2 1 3	0.57 B	25							1 2 2	0.57 B	24
					7	2 1 2	0.49 B	25									
					8	2 2 2	< 0.25 P	28							2 3 3	0.49 B	25

GENERAL NOTES

Begin Drilling **09-23-2013** Complete Drilling **09-23-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Tomaras** Checked by **L. lordache**
 Drilling Method **3.25" HSA, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 21-RWB-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 591.97 ft
 North: 1897787.89 ft
 East: 1171858.64 ft
 Station: 1612+32.77
 Offset: 11.8407 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	540.2	Very stiff to hard, SILTY CLAY to SILTY CLAY LOAM, trace gravel	45		15	2 3 3	< 0.25 P	27		520.2	Dense, gray SILT	65		19	15 17 24	4.10 B	27
	50			16	0 2 2	0.41 B	28		70			20	16 17 20	8.53 B	12		
	55			17	4 5 8	1.48 B	22		75			21	20 26 23	NP	21		
	60			18	14 12 15	3.00 P	16		80			22	19 20 28	8.61 S	14		
	515.2	Hard, gray SILTY CLAY LOAM, trace gravel															

GENERAL NOTES

Begin Drilling **09-23-2013** Complete Drilling **09-23-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Tomaras** Checked by **L. lordache**
 Drilling Method **3.25" HSA, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 22-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 595.62 ft
 North: 1897646.18 ft
 East: 1171875.74 ft
 Station: 1703+67.42
 Offset: 31.6147 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	595.42	42-inch thick CRUSHED STONE Very stiff to hard, brown and gray SILTY CLAY LOAM, trace gravel and brick fragments --FILL--			1	7 10 10	4.50 P	15						9	0 1 2	0.16 B	32
			5		2	4 7 9	4.50 P	13				25		10	0 1 2	0.25 B	27
					3	3 22 12	2.75 P	17						11	1 4 4	0.50 P	19
	587.6	Medium dense, dark brown GRAVELLY LOAM; wet --FILL--	10		4	19 9 10	NP	16				30		12	2 2 2	0.25 B	23
	585.1	Stiff, gray SILTY CLAY, trace gravel			5	3 3 4	1.72 B	26						13	0 1 2	0.33 B	26
			15		6	2 4 6	1.97 B	23				35		14	1 2 2	0.33 B	27
	580.1	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			7	1 2 3	0.66 B	23						14	1 2 2	0.33 B	27
			20		8	1 1 2	0.25 B	25				40		14	1 2 2	0.33 B	27

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **03-13-2014** Complete Drilling **03-16-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 15', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 22-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 595.62 ft
 North: 1897646.18 ft
 East: 1171875.74 ft
 Station: 1703+67.42
 Offset: 31.6147 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
			45		15	0 2 2	0.49 B	24				65		19	10 16 20	8.69 B	12
			50		16	1 3 4	0.25 P	25				70		20	7 14 24	6.07 B	19
			55		17	1 2 2	0.25 B	28				75		21	6 8 12	4.35 B	18
	538.9	Hard, gray SILTY CLAY LOAM, trace gravel								518.9	Medium dense, gray SILT; wet --possible groundwater bearing--						
			60		18	7 17 23	5.74 S	14				80		22	3 5 7	NP	27

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **03-13-2014** Complete Drilling **03-16-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 15', mud rotary thereafter, boring backfilled upon completion**

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 22-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 595.62 ft
 North: 1897646.18 ft
 East: 1171875.74 ft
 Station: 1703+67.42
 Offset: 31.6147 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	513.9	Very dense, gray SILTY LOAM, trace gravel															
			85	X	23	13 25 30	NP	11		491.6	--HARD DRILLING-- --Possible Cobbles--		X	27	60/5	NP	8
										490.6	--WEATHERED BEDROCK--						
			90	X	24	30 45 50/3	NP	15			Strong, light gray, fair rock mass quality, bedded fresh DOLOSTONE, up to 18-inch beds, 10-inch joints spacing, horizontal joints with none to more than 0.2-inch greenish gray argillaceous infilling, hard joint wall, with stylolitic surfaces, and moderately vuggy porosity						
											--Run 1 - RECOVERY=96%-- --RQD=75%-110			1			
			95	X	25	23 50/4	NP	14									
										480.6	Boring terminated at 115.00 ft	115					
	498.9	--HARD DRILLING-- --Possible Cobbles-- Very dense, gray GRAVELLY SANDY LOAM to SILTY LOAM --possible groundwater bearing--	100	X	26	50 50/4	NP	8									

GENERAL NOTES

Begin Drilling **03-13-2014** Complete Drilling **03-16-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **2.25" SSA to 15', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 22-RWB-04

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 586.36 ft
 North: 1898208.77 ft
 East: 1171849.77 ft
 Station: 1212+66.85
 Offset: 28.4715 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	586.13	13-inch thick, brown SILTY LOAM --TOPSOIL-- Hard, brown SILTY CLAY LOAM, trace gravel --FILL--			1	3 4 6	4.10 B	21						9	1 1 2	0.41 B	26
	583.4	Stiff to very stiff, gray SILTY CLAY, trace gravel	5		2	3 4 5	2.87 B	20				25		10	2 2 2	0.49 B	26
					3	2 3 3	1.56 B	22						11	2 1 2	0.41 B	27
	578.4	Soft, gray CLAY, trace gravel	10		4	1 1 2	0.33 B	25				30		12	1 2 3	0.41 B	25
					5	1 1 2	0.33 B	25									
	573.4	Medium stiff, gray SILTY CLAY LOAM, trace gravel	15		6	1 2 4	0.57 B	17				35		13	1 2 3	0.41 B	25
	570.9	Soft, gray CLAY to SILTY CLAY, trace gravel			7	1 2 3	0.41 B	25									
					8	2 2 4	0.41 B	22				40		14	1 2 3	0.25 P	26

GENERAL NOTES

Begin Drilling **08-05-2014** Complete Drilling **08-05-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **M. de los Reyes** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 22-RWB-04

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 586.36 ft
 North: 1898208.77 ft
 East: 1171849.77 ft
 Station: 1212+66.85
 Offset: 28.4715 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	543.9	--HARD DRILLING at 42.5 ft-- --Possible Cobbles--								524.6	Very dense, gray SANDY LOAM, trace gravel						
		Stiff to very stiff, gray SILTY CLAY LOAM, trace gravel	45	X	15	2 4 5	1.50 N/6	18			--Moist--	65	X	19	13 19 35	NP	11
			50	X	16	5 9 12	2.87 B	18									
			55	X	17	9 11 14	2.62 B	14									
	529.6	Very stiff, gray SILTY LOAM to SILTY CLAY LOAM, trace gravel and sand seams	60	X	18	13 19 35	3.69 S	13			Boring terminated at 65.00 ft						

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **08-05-2014** Complete Drilling **08-05-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **M. de los Reyes** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 22-RWB-05

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 594.37 ft
 North: 1898339.83 ft
 East: 1171837.02 ft
 Station: 6332+29.43
 Offset: 43.1182 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	593.2	14-inch thick, dark brown SILTY LOAM --TOPSOIL--															
		Very loose to dense, brown GRAVELLY SAND --FILL--			1	5 7 3	0.50 P	20						9	1 1 2	0.41 B	26
					2	4 4 2	NP	9		571.4	Stiff, gray, SILTY CLAY, trace gravel			10	1 3 3	1.15 B	20
					3	8 1 2	NP	31		568.9	Soft, gray CLAY, trace gravel			11	1 2 4	0.41 B	23
		--Rubble--			4	4 14 33	NP	20						12	1 2 3	0.25 P	24
					5	7 5 3	NP	29									
	581.4	Soft, gray CLAY, trace gravel			6	1 2 2	0.41 B	24						13	1 2 3	0.25 P	27
	578.9	Loose, brown, coarse SAND --MOIST--			7	4 4 3	NP	23									
	576.4	Very soft to soft, gray CLAY to SILTY CLAY, trace gravel			8	1 3 3	< 0.25 P	24						14	1 2 3	0.41 B	25

GENERAL NOTES

Begin Drilling **08-06-2014** Complete Drilling **08-06-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **M. de los Reyes** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling ∇ **5.50 ft**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 22-RWB-05

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 594.37 ft
 North: 1898339.83 ft
 East: 1171837.02 ft
 Station: 6332+29.43
 Offset: 43.1182 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
			45		15	3 3 5	0.49 B	25		529.4		65		19	6 10 15	2.62 B	14
											Boring terminated at 65.00 ft						
			50		16	2 4 5	0.25 P	27				70					
			55		17	1 4 4	0.33 B	31				75					
	537.6	Very stiff, gray SILTY CLAY to SILTY CLAY LOAM, trace gravel															
			60		18	8 13 17	3.69 B	17				80					

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **08-06-2014** Complete Drilling **08-06-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **M. de los Reyes** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

While Drilling ∇ **5.50 ft**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-01

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 575.29 ft
 North: 1898467.55 ft
 East: 1171687.36 ft
 Station: 6334+12.89
 Offset: 30.5965 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		18-inch thick, ASPHALT --FILL--															
	573.8	Loose to medium dense, white CRUSHED STONE --BASE COURSE--			1	5 6 6	NP	6						9	2 2 3	0.25 B	26
			5		2	3 3 3	NP	8				25		10	1 2 2	0.25 B	23
	569.8	Stiff, brown and gray SILTY CLAY LOAM, trace gravel			3	2 3 4	1.17 N/6	19						11	1 2 3	0.25 B	25
	567.3	Very soft to soft, gray CLAY to SILTY CLAY, trace gravel			4	2 2 4	0.49 B	19						12	2 2 3	0.41 B	25
			10		5	1 1 3	0.41 B	23									
			15		6	1 2 2	0.49 B	26						13	2 3 2	0.83 N/6	
					7	3 4 4	0.41 B	25		538.5	Stiff to very stiff, gray SILTY CLAY, trace gravel						
			20		8	2 3 2	0.25 P	27						14	5 7 9	1.64 B	22

GENERAL NOTES

Begin Drilling **07-27-2014** Complete Drilling **07-27-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-02

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 575.96 ft
 North: 1898537.05 ft
 East: 1171661.69 ft
 Station: 6334+85.38
 Offset: 28.1222 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	575.73	73-inch thick ASPHALT --PAVEMENT--															
	575.1	7-inch thick CONCRETE --PAVEMENT--															
		Very dense, grayish white CRUSHED STONE			1	40 37 21	NP	2						9	1 1 2	0.25 B	25
	573.0	--FILL-- Very soft to soft, gray CLAY to SILTY CLAY, trace gravel			2	4 3 2	0.41 B	19				25		10	1 1 2	0.25 B	26
					3	1 2 3	0.49 B	20						11	2 3 4	0.41 B	25
					4	1 2 3	0.41 B	23						12	2 2 3	0.49 B	25
					5	1 2 2	0.41 B	25									
					6	1 2 2	0.41 B	26						13	1 2 3	0.41 B	27
					7	1 2 2	< 0.25 P	27		539.2	Stiff to hard, gray SILTY CLAY to SILTY CLAY LOAM, trace gravel						
					8	1 1 2	0.33 B	26						14	2 4 6	1.31 B	22

GENERAL NOTES

Begin Drilling **08-13-2014** Complete Drilling **08-13-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" HSA, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-03

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 576.57 ft
 North: 1898615.24 ft
 East: 1171637.84 ft
 Station: 6335+65.51
 Offset: 25.2492 LT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	576.34	4-inch thick ASPHALT --PAVEMENT--															
	575.6	8-inch thick CONCRETE --PAVEMENT--															
		Medium dense, gray and white CRUSHED STONE			1	9 9 12	NP	7						9	1 1 2	0.08 B	27
	573.6	--FILL-- Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			2	3 2 3	0.83 N/6					25		10	1 2 2	0.16 B	26
			5		3	1 1 2	0.41 B	22						11	1 2 2	0.16 B	23
					4	1 2 3	0.33 B	23						12	1 2 4	0.33 B	25
			10		5	1 2 3	0.49 B	23									
					6	1 2 3	0.49 B	24						13	1 2 3	0.33 B	26
			15		7	1 2 2	0.49 B	22									
					8	1 2 2	0.25 B	25						14	3 4 8	1.56 B	23
			20														
										539.8	Stiff to very stiff, gray SILTY CLAY to SILTY CLAY LOAM, trace gravel						

--L_L(%)=36, P_L(%)=17--
 --%Gravel=4.9--
 --%Sand=12.1--
 --%Silt=44.7--
 --%Clay=38.4--
 --A-6 (15)--

GENERAL NOTES

Begin Drilling **08-18-2014** Complete Drilling **08-18-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **S. Woods** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-04

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 576.93 ft
 North: 1898688.27 ft
 East: 1171612.80 ft
 Station: 6336+40.47
 Offset: 16.6754 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	575.9	3-inch thick, ASPHALT over 9-inch thick, CONCRETE --PAVEMENT-- Medium dense, gray and white CRUSHED STONE --FILL--			1	13 9 9	NP	3									
	573.2	Medium stiff to very stiff, gray SILTY CLAY LOAM, trace gravel	5		2	5 4 5	2.00 P	14				25		10	2 1 3	0.25 B	26
					3	3 4 4	0.74 B	16						11	1 4 3	0.25 B	26
	568.9	Very soft to medium stiff, gray CLAY, trace gravel	10		4	2 3 4	0.41 B	19				30		12	1 3 4	0.49 B	25
					5	1 2 3	0.57 B	23		545.2	Medium stiff to very stiff, gray SILTY CLAY LOAM, trace gravel						
			15		6	2 2 4	0.74 B	23				35		13	2 4 5	0.90 B	20
					7	0 2 2	0.41 B	25									
			20		8	1 1 2	0.25 B	25				40		14	5 7 11	1.00 P	22

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **07-31-2014** Complete Drilling **07-31-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-04

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 576.93 ft
 North: 1898688.27 ft
 East: 1171612.80 ft
 Station: 6336+40.47
 Offset: 16.6754 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	515.2									515.2	Medium dense, gray SILTY LOAM						
			45	X	15	5 7 11	1.56 B	19				65	X	19	7 9 7	NP	13
										511.9	Boring terminated at 65.00 ft						
			50	X	16	9 11 15	2.13 B	20				70					
	525.2	Hard, gray SILTY CLAY, trace gravel															
			55	X	17	15 15 20	4.02 B	24				75					
	520.2	Medium stiff, gray CLAY, trace gravel															
			60	X	18	3 4 5	0.66 B	40				80					

GENERAL NOTES

Begin Drilling **07-31-2014** Complete Drilling **07-31-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&J** Logger **A. Happel** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-05

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 592.28 ft
 North: 1898793.23 ft
 East: 1171675.68 ft
 Station: 6337+31.20
 Offset: 54.1130 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	591.8	6-inch thick, dark brown SANDY LOAM --TOPSOIL--															
		Loose, brown GRAVELLY SANDY LOAM --FILL--			1	6 3 3	NP	13						9	2 2 4	0.57 B	22
	589.3	Loose to medium dense, brown and gray, fine SAND, trace gravel --FILL--			2	4 4 6	NP	10						10	2 2 3	0.41 B	24
					3	10 5 3	NP	19						11	2 2 3	0.41 B	24
	584.3	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			4	5 2 2	0.80 B	19						12	1 2 2	0.32 B	24
					5	2 2 2	0.33 B	26						13	0 2 3	0.33 B	25
					6	1 1 2	0.16 B	27						14	3 3 3	0.41 B	24
					7	0 2 1	0.33 B	25									
					8	1 2 3	0.41 B	20									

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **08-18-2014** Complete Drilling **08-18-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **H. Bista** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
backfilled upon completion

While Drilling ∇ **5.50 ft**
 At Completion of Drilling ∇ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ∇ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-05

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 592.28 ft
 North: 1898793.23 ft
 East: 1171675.68 ft
 Station: 6337+31.20
 Offset: 54.1130 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	545.5	Medium stiff to stiff, gray SILTY CLAY to SILTY CLAY LOAM, little to some gravel	45	X	15	3 3 5	0.74 B	25									
			50	X	16	4 10 11	0.82 B	25									
			55	X	17	4 6 7	0.90 B	22									
	532.3		60	X	18	10 16 14	1.39 B	19									
Boring terminated at 60.00 ft																	

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **08-18-2014** Complete Drilling **08-18-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **H. Bista** Checked by **C. Marin**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

While Drilling ▽ **5.50 ft**
 At Completion of Drilling ▽ **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water ▽ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG 23-RWB-05HA

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 583.84 ft
 North: 1898780.96 ft
 East: 1171640.86 ft
 Station: 6337+25.29
 Offset: 17.6471 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	582.8	Black SILTY LOAM --TOPSOIL--			1	PUSH	NP	16									
	580.3	Very stiff, gray SILTY CLAY LOAM, trace gravel --FILL--			2	PUSH	2.00 P	16									
		Very stiff, gray SILTY CLAY LOAM, trace gravel	5		3	PUSH	2.50 P	18									
					4	PUSH	2.00 P	18									
	575.8	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel			5	PUSH	0.50 P	19									
			10		6	PUSH	0.75 P	19									
					7	PUSH	0.25 P	21									
			15		8	PUSH	0.25 P	22									
	567.8	Boring terminated at 16.00 ft															

GENERAL NOTES

WATER LEVEL DATA

Begin Drilling **07-28-2014** Complete Drilling **07-28-2014**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **K&K** Logger **F. Bozga** Checked by **C. Marin**
 Drilling Method **1" IDA Pneumatic Geoprobe LB Sampler**

While Drilling **DRY**
 At Completion of Drilling **DRY**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG COMM-HUT-CCTV

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 589.57 ft
 North: 1898191.07 ft
 East: 1171393.69 ft
 Station: 5218+68.15
 Offset: 116.7249 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	589.25	5-inch thick dark brown SILTY LOAM															
		--TOPSOIL--															
		Very stiff to hard, brown CLAY LOAM, trace gravel			1	4 12 17	4.50 P	14						9	1 2 2	0.33 B	26
		--FILL--															
			5		2	5 7 7	3.94 B	14				25		10	1 2 2	0.16 B	24
					3	9 11 10	7.38 B	17						11	1 1 1	0.16 B	26
	581.6	Medium stiff, gray SILTY CLAY, trace gravel															
			10		4	3 4 4	0.82 B	19						12	1 2 2	0.16 B	27
	579.1	Very soft to medium stiff, gray CLAY to SILTY CLAY, trace gravel															
					5	1 2 3	0.49 B	21									
			15		6	1 2 4	0.41 B	22				35		13	1 2 3	0.83 N/6	
					7	2 3 5	0.74 B	25		552.8	Very stiff, gray SILTY CLAY LOAM, some gravel						
					8	1 3 3	0.82 B	19						14	4 6 8	2.00 P	14

GENERAL NOTES

Begin Drilling **11-08-2013** Complete Drilling **11-08-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **D. Kolpacki** Checked by
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **DRY**
 At Completion of Drilling **DRY**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG COMM-HUT-CCTV

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 589.57 ft
 North: 1898191.07 ft
 East: 1171393.69 ft
 Station: 5218+68.15
 Offset: 116.7249 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
	547.8	Soft, gray CLAY, trace gravel	45		15	2 6 8	0.25 P	26									
	542.8	Stiff to hard, gray SILTY CLAY to SILTY CLAY LOAM, trace to little gravel	50		16	4 5 7	1.23 B	24									
			55		17	9 12 15	4.64 B	14									
	529.6	Boring terminated at 60.00 ft	60		18	7 11 19	5.00 N/6	23									

GENERAL NOTES

Begin Drilling **11-08-2013** Complete Drilling **11-08-2013**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **P&N** Logger **D. Kolpacki** Checked by
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling ▽ **DRY**
 At Completion of Drilling ▼ **DRY**
 Time After Drilling **NA**
 Depth to Water ▼ **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG VST-06

WEI Job No.: 1100-04-01

Client: **AECOM**
 Project: **Circle Interchange Reconstruction**
 Location: **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 585.69 ft
 North: 1898109.29 ft
 East: 1171902.18 ft
 Station: 1103+77.81
 Offset: 27.3835 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	
	580.2	Hard, brown SILTY CLAY LOAM, trace gravel --FILL--	5		1	7 6 6	4.50 P	16			--In-Situ Vane Shear, 20.5 feet-- --S _{u undis} = 775.4 psf-- --S _{u remold} = 360.4 psf-- --Sensitivity = 2.2--	5		5				
	576.7	Soft, gray SILTY CLAY LOAM	25		2	1 2 3	0.41 B	23			--In-Situ Vane Shear, 23.0 feet-- --S _{u undis} = 600.6 psf-- --S _{u remold} = 305.8 psf-- --Sensitivity = 2.0--	6		6				
			10								--In-Situ Vane Shear, 25.5 feet-- --S _{u undis} = 578.8 psf-- --S _{u remold} = 316.7 psf-- --Sensitivity = 1.8--	7		7				
			15								--In-Situ Vane Shear, 28.0 feet-- --S _{u undis} = 611.6 psf-- --S _{u remold} = 338.5 psf-- --Sensitivity = 1.8--	8		8				
			20								--In-Situ Vane Shear, 30.5 feet-- --S _{u undis} = 786.3 psf-- --S _{u remold} = 382.2 psf-- --Sensitivity = 2.1--	9		9				
											--In-Situ Vane Shear, 10.5 feet-- --S _{u undis} = 972.0 psf-- --S _{u remold} = 611.6 psf-- --Sensitivity = 1.6--	1		1				
											--In-Situ Vane Shear, 13.0 feet-- --S _{u undis} = 982.9 psf-- --S _{u remold} = 589.7 psf-- --Sensitivity = 1.7--	2		2				
											--In-Situ Vane Shear, 33.0 feet-- --S _{u undis} = 698.9 psf-- --S _{u remold} = 404.1 psf-- --Sensitivity = 1.7--	10		10				
											--In-Situ Vane Shear, 35.5 feet-- --S _{u undis} = 808.1 psf-- --S _{u remold} = 502.4 psf-- --Sensitivity = 1.6--	11		11				
											--In-Situ Vane Shear, 15.5 feet-- --S _{u undis} = 873.7 psf-- --S _{u remold} = 513.3 psf-- --Sensitivity = 1.7--	3		3				
											--In-Situ Vane Shear, 38.0 feet-- --S _{u undis} = 982.9 psf-- --S _{u remold} = 546.0 psf-- --Sensitivity = 1.8--	12		12				
											--In-Situ Vane Shear, 18.0 feet-- --S _{u undis} = 928.3 psf-- --S _{u remold} = 360.4 psf-- --Sensitivity = 2.6--	4		4				

GENERAL NOTES

Begin Drilling **12-09-2015** Complete Drilling **12-14-2015**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **F. Bozga** Checked by **A. Kurnia**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

WANGENGINC 11000401.GPJ WANGENG.GDT 5/15/18



wangeng@wangeng.com
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

BORING LOG VST-06

WEI Job No.: 1100-04-01

Client **AECOM**
 Project **Circle Interchange Reconstruction**
 Location **Section 17, T39N, R14E of 3rd PM**

Datum: NAVD 88
 Elevation: 585.69 ft
 North: 1898109.29 ft
 East: 1171902.18 ft
 Station: 1103+77.81
 Offset: 27.3835 RT

Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)	Profile	Elevation (ft)	SOIL AND ROCK DESCRIPTION	Depth (ft)	Sample Type recovery	Sample No.	SPT Values (blw/6 in)	Qu (tsf)	Moisture Content (%)
		--In-Situ Vane Shear, 40.5 feet-- --S _{u undis} = 906.4 psf-- --S _{u remold} = 524.2 psf-- --Sensitivity = 1.7--			13	VS	0.91										
	542.2	--In-Situ Vane Shear, 43.0 feet-- --S _{u undis} = 677.1 psf-- --S _{u remold} = 393.1 psf-- --Sensitivity = 1.7-- Boring terminated at 43.50 ft			14	VS	0.68										
			45														
			50														
			55														
			60														

GENERAL NOTES


Begin Drilling **12-09-2015** Complete Drilling **12-14-2015**
 Drilling Contractor **Wang Testing Services** Drill Rig
 Driller **R&N** Logger **F. Bozga** Checked by **A. Kurnia**
 Drilling Method **2.25" HSA to 10', mud rotary thereafter, boring**
 **backfilled upon completion**

WATER LEVEL DATA

While Drilling **Rotary wash**
 At Completion of Drilling **mud in the borehole**
 Time After Drilling **NA**
 Depth to Water **NA**

The stratification lines represent the approximate boundary between soil types; the actual transition may be gradual.

APPENDIX B



COBBLES	GRAVEL	SAND		SILT AND CLAY
		coarse	fine	

Specimen Identification	IDH Classification	LL	PL	PI	Cc	Cu
● 1712-B-02#9 21.0 ft	Silty Clay	35	18	17		
☒ 1712-B-02#15 43.5 ft	Silty Loam	27	16	11		
▲ 1712-B-02#17 53.5 ft	Clay	36	19	17		
★ 1712-B-02#20 68.5 ft	Silty Loam	19	14	5	0.92	28.12
◎ 1712-B-02#23 83.5 ft	Silt	NP	NP	NP	1.25	4.36


Specimen Identification	D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay
● 1712-B-02#9 21.0 ft	9.5	0.01	0.002		3.5	14.0	50.3	32.2
☒ 1712-B-02#15 43.5 ft	12.5	0.066	0.007		8.1	26.9	51.7	13.3
▲ 1712-B-02#17 53.5 ft	4.75	0.004			0.1	2.0	49.4	48.5
★ 1712-B-02#20 68.5 ft	19	0.047	0.009	0.002	7.4	21.3	59.7	11.7
◎ 1712-B-02#23 83.5 ft	2	0.015	0.008	0.003	0.0	1.7	91.5	6.8



Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

GRAIN SIZE DISTRIBUTION
 Project: Circle Interchange Reconstruction
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01

WEI GRAIN SIZE IDH 11000401.GPJ US LAB.GDT 5/15/18



COBBLES	GRAVEL	SAND		SILT AND CLAY
		coarse	fine	

Specimen Identification		IDH Classification					LL	PL	PI	Cc	Cu
●	1715-B-03#16 48.5 ft	Silty Clay					36	18	18		
☒	1715-B-03#23 83.5 ft	Silt					NP	NP	NP	1.33	3.11
▲	18-RWB-02#3 6.0 ft	Silty Clay Loam					30	16	14		
★	18-RWB-02#12 28.5 ft	Clay					37	18	19		
⊙	18-RWB-02#15 43.5 ft	Silty Clay					35	17	18		
Specimen Identification		D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay		
●	1715-B-03#16 48.5 ft	4.75	0.005	0.001		0.5	3.1	59.8	36.7		
☒	1715-B-03#23 83.5 ft	4.75	0.011	0.007	0.004	0.1	1.1	92.6	6.3		
▲	18-RWB-02#3 6.0 ft	9.5	0.018	0.003		3.5	15.1	56.3	25.2		
★	18-RWB-02#12 28.5 ft	9.5	0.007	0.001		3.2	10.5	47.4	38.9		
⊙	18-RWB-02#15 43.5 ft	9.5	0.007	0.001		2.2	9.4	51.7	36.7		


WEI GRAIN SIZE IDH 11000401.GPJ US_LAB.GDT 5/15/18



Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

GRAIN SIZE DISTRIBUTION

Project: Circle Interchange Reconstruction
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01



COBBLES	GRAVEL	SAND		SILT AND CLAY
		coarse	fine	

Specimen Identification			IDH Classification					LL	PL	PI	Cc	Cu
●	18-RWB-03#6	13.5 ft	Clay					33	19	14		
■	18-RWB-03#14	38.5 ft	Silty Loam					24	15	9		
▲	19-RWB-01#3	6.0 ft	Clay					31	17	14		
★	19-RWB-01#6	13.5 ft	Silty Clay					31	18	13		
◎	19-RWB-01#8	18.5 ft	Silty Loam					23	16	7	0.59	32.74

Specimen Identification			D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay
●	18-RWB-03#6	13.5 ft	12.5	0.008	0.001		6.1	13.7	44.9	35.3
■	18-RWB-03#14	38.5 ft	9.5	0.049	0.006		8.4	24.5	49.1	18.1
▲	19-RWB-01#3	6.0 ft	4.75	0.011	0.002		2.2	18.3	47.1	32.3
★	19-RWB-01#6	13.5 ft	9.5	0.012	0.002		4.1	13.3	51.6	31.0
◎	19-RWB-01#8	18.5 ft	12.5	0.055	0.007	0.002	6.9	23.7	57.5	11.8


WEI GRAIN SIZE IDH 11000401.GPJ US_LAB.GDT 5/15/18



Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

GRAIN SIZE DISTRIBUTION

Project: Circle Interchange Reconstruction
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01



COBBLES	GRAVEL	SAND		SILT AND CLAY
		coarse	fine	

Specimen Identification			IDH Classification					LL	PL	PI	Cc	Cu
●	19-RWB-01#14	38.5 ft	Silty Clay					34	18	16		
☒	19-RWB-01#17	53.5 ft	Silty Loam					25	16	9		
▲	19-RWB-01#19	63.5 ft	Clay					44	20	24		
★	19-RWB-01#21	73.5 ft	Silty Clay Loam					29	16	13		
◎	2055-B-04#7	16.0 ft	Silty Clay					35	15	20		
Specimen Identification			D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay		
●	19-RWB-01#14	38.5 ft	9.5	0.008	0.001		2.9	13.1	49.6	34.3		
☒	19-RWB-01#17	53.5 ft	9.5	0.056	0.006		6.5	26.5	49.4	17.6		
▲	19-RWB-01#19	63.5 ft	9.5	0.003			1.2	5.0	39.6	54.2		
★	19-RWB-01#21	73.5 ft	9.5	0.014	0.002		3.6	13.5	56.0	26.9		
◎	2055-B-04#7	16.0 ft	9.5	0.01	0.002		4.3	15.2	48.0	32.4		


WEI GRAIN SIZE IDH 11000401.GPJ US LAB.GDT 5/15/18



Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

GRAIN SIZE DISTRIBUTION

Project: Circle Interchange Reconstruction
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01



COBBLES	GRAVEL	SAND		SILT AND CLAY
		coarse	fine	

Specimen Identification			IDH Classification					LL	PL	PI	Cc	Cu
●	2055-B-04#14	38.5 ft	Silty Clay					35	15	20		
☒	2055-B-04#15	43.5 ft	Gravelly Loam					22	13	9	0.43	127.28
▲	21-RWB-02#24	89.0 ft	Silty Loam					22	14	8		
★	22-RWB-03#6	13.5 ft	Silty Clay Loam					32	18	14		
⊙	22-RWB-03#13	33.5 ft	Silty Clay					33	18	15		
Specimen Identification			D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay		
●	2055-B-04#14	38.5 ft	9.5	0.007	0.001		3.6	9.8	50.5	36.1		
☒	2055-B-04#15	43.5 ft	19	0.199	0.012	0.002	15.4	31.5	41.5	11.6		
▲	21-RWB-02#24	89.0 ft	9.5	0.028	0.007		5.0	18.1	63.8	13.1		
★	22-RWB-03#6	13.5 ft	4.75	0.012	0.003		2.5	15.0	57.1	25.4		
⊙	22-RWB-03#13	33.5 ft	9.5	0.01	0.002		2.7	15.7	49.6	32.0		


WEI GRAIN SIZE IDH 11000401.GPJ US LAB.GDT 5/15/18



Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

GRAIN SIZE DISTRIBUTION

Project: Circle Interchange Reconstruction
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01



COBBLES	GRAVEL	SAND		SILT AND CLAY
		coarse	fine	

Specimen Identification	IDH Classification	LL	PL	PI	Cc	Cu
● 22-RWB-03#18 58.5 ft	Silty Clay	35	18	17		
☒ 23-RWB-03#12 28.5 ft	Clay	36	17	19		
▲ 23-RWB-03#15 43.5 ft	Silty Clay Loam	25	16	9		


Specimen Identification	D100	D60	D30	D10	%Gravel	%Sand	%Silt	%Clay
● 22-RWB-03#18 58.5 ft	9.5	0.008	0.002		1.8	10.2	54.1	33.9
☒ 23-RWB-03#12 28.5 ft	9.5	0.007			4.9	12.1	44.7	38.4
▲ 23-RWB-03#15 43.5 ft	9.5	0.043	0.005		6.6	25.6	48.8	19.0



Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

GRAIN SIZE DISTRIBUTION
 Project: Circle Interchange Reconstruction
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01

WEI GRAIN SIZE IDH 11000401.GPJ US_LAB.GDT 5/15/18



Specimen Identification	LL	PL	PI	Fines	IDH Classification
● 1703-B-04#4 8.5 ft	29	16	13	80	Silty Clay Loam
⊠ 1703-B-04#14 38.5 ft	36	18	18	88	Silty Clay
▲ 1703-B-04#16 48.5 ft	27	16	11	74	Silty Clay Loam
★ 1703-B-04#19 63.5 ft	23	16	7	69	Silty Loam
⊙ 1706-B-02#8 18.5 ft	34	17	17	80	Silty Clay
⊕ 1712-B-02#9 21.0 ft	35	18	17	83	Silty Clay
○ 1712-B-02#15 43.5 ft	27	16	11	66	Silty Loam
△ 1712-B-02#17 53.5 ft	36	19	17	98	Clay
⊗ 1712-B-02#20 68.5 ft	19	14	5	72	Silty Loam
⊕ 1712-B-02#23 83.5 ft	NP	NP	NP	99	Silt
□ 1715-B-03#16 48.5 ft	36	18	18	97	Silty Clay
⊕ 1715-B-03#23 83.5 ft	NP	NP	NP	99	Silt
⊕ 18-RWB-02#3 6.0 ft	30	16	14	82	Silty Clay Loam
☆ 18-RWB-02#12 28.5 ft	37	18	19	86	Clay
⊗ 18-RWB-02#15 43.5 ft	35	17	18	88	Silty Clay
■ 18-RWB-03#6 13.5 ft	33	19	14	80	Clay
◆ 18-RWB-03#14 38.5 ft	24	15	9	67	Silty Loam
◇ 19-RWB-01#3 6.0 ft	31	17	14	80	Clay
× 19-RWB-01#6 13.5 ft	31	18	13	83	Silty Clay
⊕ 19-RWB-01#8 18.5 ft	23	16	7	70	Silty Loam

WEI ATTERBERG LIMITS IDH 11000401.GPJ US LAB.GDT 5/15/18




Wang Engineering, Inc.
 1145 North Main Street
 Lombard, IL 60148
 Telephone: 630-953-9928
 Fax: 630-953-9938

ATTERBERG LIMITS' RESULTS

Project: Circle Interchange Reconstruction
 Location: Section 17, T39N, R14E of 3rd PM
 Number: 1100-04-01

APPENDIX C

FILE PATH = p:\617479-P\INT\recomon\line\local\IACOM_D902_MW\Documents\01_Americas\Transportation\60X79_Contract\016879-SHT-Drain-01.dgn





LEGEND

- ⊙ EXISTING MANHOLE
- EXISTING CATCH BASIN
- EXISTING INLET
- ▬ BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
- ⊙ MANHOLE TO BE INSTALLED BY OTHERS
- CATCH BASIN TO BE INSTALLED BY OTHERS
- ▬ INLET TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
- PROPOSED STORM SEWER
- ⊙ PROPOSED MANHOLE
- PROPOSED CATCH BASIN
- ▬ PROPOSED INLET

LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE



D160X79-SHT-Drain-01.dgn
 USER NAME = mkwilson
 PLOT SCALE = 40.0000' / in.
 PLOT DATE = 7/30/2018

DESIGNED - MRC
 DRAWN - MRC
 CHECKED - JMG
 DATE - 7-30-2018

REVISED -
 REVISED -
 REVISED -
 REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 1 OF 10 SHEETS STA. 1600+00 TO STA. 1602+00

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2014-005R&B	COOK	888	262
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				


LEGEND

- EXISTING MANHOLE
- EXISTING CATCH BASIN
- EXISTING INLET
- ▬ BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
- ⊙ MANHOLE TO BE INSTALLED BY OTHERS
- CATCH BASIN TO BE INSTALLED BY OTHERS
- ▬ INLET TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
- PROPOSED STORM SEWER
- PROPOSED MANHOLE
- PROPOSED CATCH BASIN
- ▬ PROPOSED INLET

LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

FILE PATH = p:\61779-P\INT\recomon\line\local\IACOM\DS02_MH\Documents\01_Americas\Transportation\60269938_Circle\Phase_11\000_CAD\006_Roadway\Sheets\60X79_Contract\016879-SHT-Drain-02.dgn



D:\60X79-SHT-Drain-02.dgn
 USER NAME = mkwilson
 PLOT SCALE = 40.0000' / in.
 PLOT DATE = 7/30/2018

DESIGNED - MRC	REVISED -
DRAWN - MRC	REVISED -
CHECKED - JMG	REVISED -
DATE - 7-30-2018	REVISED -



**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 2 OF 10 SHEETS STA. 1602+00 TO STA. 1607+50

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 263
ILLINOIS FED. AID PROJECT			CONTRACT NO. 60X79	

FILE PATH = p:\617479-P\INT\ascom\line\local\IAC\CDM_DS02_MN\Documents\01_Americas\Transportation\60X79-Drain\Phase_11\000_CAD\006_Roadway\Sheets\60X79_Contract\016079-SHT-Drain-03.dgn




LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

LEGEND

- EXISTING MANHOLE
- PROPOSED MANHOLE
- EXISTING CATCH BASIN
- PROPOSED CATCH BASIN
- EXISTING INLET
- PROPOSED INLET
- BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
- MANHOLE TO BE INSTALLED BY OTHERS
- CATCH BASIN TO BE INSTALLED BY OTHERS
- INLET TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
- PROPOSED STORM SEWER



D160X79-SHT-Drain-03.dgn
 USER NAME = mkwilson
 PLOT SCALE = 40.0000' / in.
 PLOT DATE = 7/30/2018

DESIGNED - MRC	REVISED -
DRAWN - MRC	REVISED -
CHECKED - JMG	REVISED -
DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 3 OF 10 SHEETS STA. 1607+50 TO STA. 1613+00

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 264
ILLINOIS FED. AID PROJECT			CONTRACT NO. 60X79	

FILE PATH = p:\161799-P\INT\ascom\line\local\IACOM_D592_WA\Documents\01_Americas\Transportation\60269938_Circle\Phase 1\000_CAD\006_Roadway\Sheets\60X93_Contract\016879-SHT-Drain-04.dgn




LEGEND

	EXISTING MANHOLE		PROPOSED MANHOLE
	EXISTING CATCH BASIN		PROPOSED CATCH BASIN
	EXISTING INLET		PROPOSED INLET
	BRIDGE SCUPPER (SEE STRUCTURAL PLANS)		
	MANHOLE TO BE INSTALLED BY OTHERS		
	CATCH BASIN TO BE INSTALLED BY OTHERS		
	INLET TO BE INSTALLED BY OTHERS		
	STORM SEWER TO BE INSTALLED BY OTHERS		
	STORM SEWER TO BE INSTALLED BY OTHERS (60X93)		
	PROPOSED STORM SEWER		

LEGEND

	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
	STORM SEWER TO BE JACKED IN PLACE
	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE



D168079-SHT-Drain-04.dgn
USER NAME = mkwilson
PLOT SCALE = 40.0017 1/1 in.
PLOT DATE = 7/30/2018

DESIGNED - MRC
DRAWN - MRC
CHECKED - JMG
DATE - 7-30-2018

REVISED -
REVISED -
REVISED -
REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 4 OF 10 SHEETS STA. 1613+00 TO STA. 1618+50

F.A.I. R.E. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 265
ILLINOIS FED. AID PROJECT			CONTRACT NO. 60X79	

LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE




LEGEND

	EXISTING MANHOLE		PROPOSED MANHOLE
	EXISTING CATCH BASIN		PROPOSED CATCH BASIN
	EXISTING INLET		PROPOSED INLET
	BRIDGE SCUPPER (SEE STRUCTURAL PLANS)		
	MANHOLE TO BE INSTALLED BY OTHERS		
	CATCH BASIN TO BE INSTALLED BY OTHERS		
	INLET TO BE INSTALLED BY OTHERS		
	STORM SEWER TO BE INSTALLED BY OTHERS		
	STORM SEWER TO BE INSTALLED BY OTHERS (60X93)		
	PROPOSED STORM SEWER		



BILL OF MATERIAL		
ITEM	UNIT	QUANTITY
DUCTILE IRON FITTING, TYPE 2 WYE 8" PIPE - 6" BRANCH	EACH	1
DUCTILE IRON FITTING 8" 90 DEGREE ELBOW	EACH	1
PIPE CLEANOUT, 8"	EACH	1
STORM SEWERS, TYPE 4, DUCTILE IRON PIPE 8"	FOOT	50
DRAINAGE STRUCTURE	EACH	1
SUBBASE GRANULAR MATERIAL, TYPE B 6"	SQ YD	1
MISCELLANEOUS CONCRETE	CU YD	4.5

NOTE: ALL ITEMS INCLUDED IN THE COST OF DRAINAGE SYSTEM (SPECIAL)



DETAIL A

PR 42" STORM SEWER TO BE INSTALLED BY FUTURE CONTRACT



D:\617479-P\INT\Drawings\0160X79-SHT-Drain-05.dgn
 USER NAME = mkwilson
 PLOT SCALE = 40.0000' / in.
 PLOT DATE = 7/30/2018

DESIGNED - MRC
 DRAWN - MRC
 CHECKED - JMG
 DATE - 7-30-2018

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

PROPOSED DRAINAGE AND UTILITIES PLAN


SCALE: 1"=20' SHEET 5 OF 10 SHEETS STA. 1618+50 TO STA. 1624+00

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2014-005R&B	COOK	888	266
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

FILE PATH = p:\61779-P\INT\secomon\line\local\IACOM_D592_NA\Documents\01_Americas\Transportation\60X79_Contract\016879-SHT-DRAIN-06.dgn

LEGEND


- ⊙ EXISTING MANHOLE
- EXISTING CATCH BASIN
- EXISTING INLET
- ▬ BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
- ⊙ MANHOLE TO BE INSTALLED BY OTHERS
- CATCH BASIN TO BE INSTALLED BY OTHERS
- ▬ INLET TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS
- STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
- PROPOSED STORM SEWER
- ⊙ PROPOSED MANHOLE
- PROPOSED CATCH BASIN
- ▬ PROPOSED INLET



SEE SHEET NO. 264 FOR PROPOSED DRAINAGE

LEGEND

- ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
- YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
- GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
- PURPLE - STORM SEWER TO BE JACKED IN PLACE
- PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
- BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE




D160X79-SHT-DRAIN-06.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PLAN	
SCALE: 1"=20'	SHEET 6 OF 10 SHEETS STA. TO STA.



F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 267
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

FILE PATH = p:\61779-P\INT\p\mnt\p\com\line\local\IAC\CDM\DS02_NA\Documents\01_Americas\Transportation\60X79_Contract\0160X79-SHT-Drain-07.dgn



LEGEND

	ORANGE - STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
	YELLOW - STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
	GREEN - STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
	PURPLE - STORM SEWER TO BE JACKED IN PLACE
	PINK - APPROXIMATE JACKING/ RECEIVING PIT LOCATION
	BLUE - STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE



D160X79-SHT-Drain-07.dgn
 USER NAME = mkwilson
 PLOT SCALE = 40.0000' / in.
 PLOT DATE = 7/30/2018


DESIGNED - MRC	REVISIONS
DRAWN - MRC	REVISIONS
CHECKED - JMG	REVISIONS
DATE - 7-30-2018	REVISIONS

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

PROPOSED DRAINAGE AND UTILITIES PLAN

SCALE: 1"=20' SHEET 7 OF 10 SHEETS STA. 100+00 TO STA. 104+00

F.A.I. R.T.E.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2014-005R&B	COOK	888	268
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				



FILE PATH = p:\61799-P\INT\secomon\line\local\IACOM_D592_MN\Documents\01_Americas\Transportation\60269938_Circle\Phase_11\000_CAD\006_Roadway\Sheets\60X79_Contract\0160X79-Sht-DRAIN-09.dgn

NOTES:
 1. SEE SHEET NO. 264 FOR RAMP EN PLAN DETAILS.

LEGEND	
	EXISTING MANHOLE
	PROPOSED MANHOLE
	EXISTING CATCH BASIN
	PROPOSED CATCH BASIN
	EXISTING INLET
	PROPOSED INLET
	BRIDGE SCUPPER (SEE STRUCTURAL PLANS)
	MANHOLE TO BE INSTALLED BY OTHERS
	CATCH BASIN TO BE INSTALLED BY OTHERS
	INLET TO BE INSTALLED BY OTHERS
	STORM SEWER TO BE INSTALLED BY OTHERS
	STORM SEWER TO BE INSTALLED BY OTHERS (60X93)
	PROPOSED STORM SEWER

LEGEND	
	STRUCTURE ELEMENT INSTALLED BEFORE DRAINAGE
	STRUCTURE ELEMENT INSTALLED AFTER DRAINAGE
	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
	STORM SEWER TO BE JACKED IN PLACE
	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

SEE SHEET NO. 264 FOR RAMP EN PROPOSED DRAINAGE


**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

PROPOSED DRAINAGE AND UTILITIES PLAN
 SCALE: 1"=10' SHEET 9 OF 10 SHEETS STA. TO STA.

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 270
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				




D160X79-Sht-DRAIN-09.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 20.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -



PLAN	SURVEYED	DATE
	PLOTTED	BY
	CHECKED	
	ALIGNED	
	CAD FILE NAME	
	NO.	
	NO.	

PROFILE	SURVEYED	DATE
	GRADES CHECKED	BY
	STRUCTURE	
	NOT AT THIS OFFICE	
	NO.	
	NO.	




EX PCL EL	576.50	576.29	575.99	575.64	575.44	575.72
PR PCL EL						
	1600+00	1600+50	1601+00	1601+50	1602+00	

LEGEND	
ORANGE	- STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
YELLOW	- STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
GREEN	- STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
PURPLE	- STORM SEWER TO BE JACKED IN PLACE
PINK	- APPROXIMATE JACKING/ RECEIVING PIT LOCATION
BLUE	- STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

PLAN	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	ALIGNMENT	
	CADD FILE NAME	
	NO.	

PROFILE	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	STRUCTURE	
	NOT AT THIS OFFICE	
	NO.	



D160X79-SHT-Drain-PRO-02.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE RAMP EN			
SCALE: 1"=20'	SHEET 2	OF 11 SHEETS	STA.1602+00 TO STA.1607+50

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 273
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

PLAN	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	ALIGNED	
	CAD FILE NAME	
	NO.	

PROFILE	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	GRADES	
	STRUCTURE	
	NOT AT THIS OFFICE	
	NO.	



D160X79-SHT-Drain-PRO-03.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE RAMP EN			
SCALE: 1"=20'	SHEET 3	OF 11 SHEETS	STA.1607+50 TO STA.1613+00

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 274
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

PLAN	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	ALIGNED	
	CAD FILE NAME	
	NO.	
	NOTE BOOK	

PROFILE	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	STRUCTURE	
	NOT AT THIS OFFICE	
	NO.	
	NOTE BOOK	



LEGEND	
ORANGE	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
YELLOW	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
GREEN	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
PURPLE	STORM SEWER TO BE JACKED IN PLACE
PINK	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
BLUE	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

D160X79-SHT-Drain-PRO-04.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE RAMP EN			
SCALE: 1"=20'	SHEET 4	OF 11 SHEETS	STA.1613+00 TO STA.3618+50

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 275
ILLINOIS FED. AID PROJECT				CONTRACT NO. 60X79

PLAN	SURVEYED	BY	DATE
	PLOTTED		
	NOTE BOOK		
	NO.		
	CHECKED		
	ALIGNMENT		
	NO.		
	CADD FILE NAME		

PROFILE	SURVEYED	BY	DATE
	PLOTTED		
	NOTE BOOK		
	NO.		
	CHECKED		
	GRADES		
	STRUCTURE		
	NOT AT THIS OFFICE		



FILE PATH = p:\6179-SHT-Drain-PRO-05.dgn

D160X79-SHT-Drain-PRO-05.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE			
RAMP EN			
SCALE: 1"=20'	SHEET 5	OF 11 SHEETS	STA.3618+50 TO STA.3621+00

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2014-005R&B	COOK	888	276
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

PLAN	SURVEYED	BY	DATE
	PLOTTED		
	CHECKED		
	ALIGNMENT		
	NO. _____		
	CADD FILE NAME		

PROFILE	SURVEYED	BY	DATE
	PLOTTED		
	GRADES CHECKED		
	STRUCTURE		
	NOT AT THIS OFFICE		
	NO. _____		



LEGEND	
ORANGE	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
YELLOW	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
GREEN	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
PURPLE	STORM SEWER TO BE JACKED IN PLACE
PINK	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
BLUE	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

DI60X79-SHT-Drain-PRO-09	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE FUTURE NB C-D ROAD			
SCALE: 1"=20'	SHEET 6	OF 11 SHEETS	STA.6320+00 TO STA.6325+70


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2014-005R&B	COOK	888	277
CONTRACT NO. 60X79				ILLINOIS FED. AID PROJECT

FILE PATH = p:\61799-P\INT-recom\line.local\IACOM_0902_MH\Documents\01 America's Transportation\60269938 Circle\Phase 1\2008_CAD\006 Roadway\Sheets\60X79-SHT-Drain-PRO-09

PLAN	SURVEYED	DATE
	PLOTTED	BY
	CHECKED	
	ALIGNMENT	
	NO. CAD FILE NAME	

PROFILE	SURVEYED	DATE
	PLOTTED	BY
	CHECKED	
	GRADES	
	STRUCTURE	
	NOT AT THIS CHKD	

FILE PATH = p:\61799-PRD\Drawings\61799-PRD\61799-PRD-Drain-PRO-10.dgn



LEGEND	
ORANGE	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
YELLOW	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
GREEN	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
PURPLE	STORM SEWER TO BE JACKED IN PLACE
PINK	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
BLUE	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

D160X79-SHT-Drain-PRO-10.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE FUTURE NB C-D ROAD			
SCALE: 1"=20'	SHEET 7	OF 11 SHEETS	STA.6325+70 TO STA.6331+30

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 278
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

PLAN	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	ALIGNMENT	
	NO. CAD FILE NAME	

PROFILE	SURVEYED	DATE
	PLOTTED	
	GRADES CHECKED	
	STRUCTURE	
	NOT AT THIS OFFICE	



LEGEND	
ORANGE	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
YELLOW	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
GREEN	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
PURPLE	STORM SEWER TO BE JACKED IN PLACE
PINK	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
BLUE	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

D:\60X79-SHT-Drain-PRO-11.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE FUTURE NB C-D ROAD			
SCALE: 1"=20'	SHEET 8	OF 11 SHEETS	STA.6325+70 TO STA.6336+90

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 279
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

PLAN	SURVEYED	BY	DATE
	PLOTTED		
	NOTE BOOK		
	NO.		
	CHECKED		
	ALIGNMENT		
	FILE NAME		

PROFILE	SURVEYED	BY	DATE
	PLOTTED		
	GRADES CHECKED		
	STRUCTURE		
	NOT AT THIS OFFICE		



LEGEND	
 	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
 	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
 	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
 	STORM SEWER TO BE JACKED IN PLACE
 	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
 	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

D:\6079-SHT-Drain-PRO-12.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE			
FUTURE NB C-D ROAD			
SCALE: 1"=20'	SHEET 8	OF 11 SHEETS	STA.6336+90 TO STA.6340+00

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2014-005R&B	COOK	888	280
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

PLAN	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	BY	
	NO.	
	FILE NAME	

PROFILE	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	BY	
	NO.	
	FILE NAME	



LEGEND	
ORANGE	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
YELLOW	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
GREEN	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
PURPLE	STORM SEWER TO BE JACKED IN PLACE
PINK	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
BLUE	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE

DI60X79-SHT-Drain-PRO-08	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE			
SB I-9094			
SCALE: 1"=20'	SHEET 10	OF 11 SHEETS	STA. 16+00 TO STA. 21+50

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
90/94/290	2014-005R&B	COOK	888	281
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				

PLAN	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	ALIGNED	
	CAD FILE NAME	
	NO.	
	NOTE BOOK	

PROFILE	SURVEYED	DATE
	PLOTTED	
	CHECKED	
	STRUCTURE	
	NOT AT THIS OFFICE	
	NO.	
	NOTE BOOK	



LEGEND	
ORANGE	STRUCTURAL ELEMENT INSTALLED BEFORE DRAINAGE
YELLOW	STRUCTURAL ELEMENT INSTALLED AFTER DRAINAGE
GREEN	STORM SEWER INSTALLED USING OPEN CUT INSTALLATION
PURPLE	STORM SEWER TO BE JACKED IN PLACE
PINK	APPROXIMATE JACKING/ RECEIVING PIT LOCATION
BLUE	STORM SEWER/ DRAINAGE SYSTEM ATTACHED TO STRUCTURE



D:\60X79-SHT-Drain-PRO-07.dgn	DESIGNED - MRC	REVISED -
USER NAME = mkwilson	DRAWN - MRC	REVISED -
PLOT SCALE = 40.0000' / in.	CHECKED - JMG	REVISED -
PLOT DATE = 7/30/2018	DATE - 7-30-2018	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

DRAINAGE AND UTILITIES PROFILE			
PR 78" MAIN DRAIN			
SCALE: 1"=20'	SHEET 11	OF 11 SHEETS	STA. TO STA.

F.A.I. RTE. 90/94/290	SECTION 2014-005R&B	COUNTY COOK	TOTAL SHEETS 888	SHEET NO. 282
CONTRACT NO. 60X79				
ILLINOIS FED. AID PROJECT				