



ELEVATION  
TYPICAL INTERIOR UNIT  
Even number of panels/interior unit required.




SUPPORT END DETAIL FOR EXTERIOR UNIT




TYPICAL JOINT DETAILS

DETAIL A



ELEVATION  
TYPICAL EXTERIOR UNIT  
Even or odd number of panels/exterior units allowed.



SECTION A-A

- NOTES
- Contractor may alternatively use standard aluminum drive-fit cap to close end. 1/2"  $\phi$  drain hole in end plate/drive-fit cap. (Typ. at ends of all chords)
  - 5 1/2" end dimension may vary by  $\pm 1"$  to provide uniform panel spacing (P).
  - Panel spacing (P) shall be uniform for entire truss and between 4'-0" and 5'-0" for Type I-A or 4'-0" and 5'-6" for Types II-A and III-A.
  - Vertical Diagonals in front and back face shall alternate.
  - Hidden lines show wind bracing alternates direction between planes of top and bottom chords.
  - All diagonals shall be detailed for minimum offset from the panel point based on the following: Offset shall be such as to provide a 3/4" minimum to 1 1/2" maximum clearance between any diagonal and any horizontal or vertical member, and to provide clearance for U-bolt connections of signs or walkway brackets.

OVERHEAD SIGN STRUCTURES  
ALUMINUM TRUSS DETAILS  
FOR TRUSS TYPES I-A, II-A AND III-A

District 2  
Overhead Sign Structure  
Repair & Replacement

DESIGNED -	20
CHECKED -	EXAMINED
DRAWN -	PASSED
CHECKED -	

ENGINEER OF BRIDGE DESIGN

ENGINEER OF BRIDGES AND STRUCTURES

NUMBER	REVISION	DATE