

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	1

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

**PROPOSED
HIGHWAY PLANS**

FAP ROUTE 600 (IL ROUTE 159)
SECTION 1-1BR-1
PROJECT : BHF-0600(059)
SUPERSTRUCTURE REPLACEMENT
ST. CLAIR COUNTY


C-98-130-05

D-98-103-05




LOCATION OF SECTION INDICATED THUS: - [black rectangle] -

FOR INDEX OF SHEETS, SEE SHEET NO. 2




TRIPLE SPAN PPC DECK BEAMS
TO BE REPLACED WITH PPC DECK
BEAMS AT STA. 158+08 (110.17 FT)
OVER RICHLAND CREEK
SN 082-0265
BEGIN STA 157+00
END STA 159+15



LATITUDE 38.52183
LONGITUDE 89.98420

MICROFILMED _____
REEL NUMBER _____
AWARDED _____
RESIDENT ENGINEER _____
AS BUILT CHANGES WERE MADE
ON THE FOLLOWING SHEETS



FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD
ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT
CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS
ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

J.U.L.I.E.
JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION
1-800-892-0123

DESIGN DESIGNATION
NA

FAP ROUTE 600 (IL ROUTE 159)
ADT = 17,200 (2007)
ADT = 21,000 (2027)
SU = 6.2%
MU = 2.4%

GROSS LENGTH = 0.021 MILES
NET LENGTH = 0.021 MILES

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

SUBMITTED August 29, 2006
Mary Janice
DEPUTY DIRECTOR OF HIGHWAYS
REGION FIVE ENGINEER

October 13, 2006
Mike Hine
ENGINEER OF DESIGN AND ENVIRONMENT

October 13, 2006
Milton R. Sees P.E.
DIRECTOR, DIVISION OF HIGHWAYS

**PRINTED BY THE AUTHORITY
OF THE STATE OF ILLINOIS**

PROJECT ENGINEER: PATTI LeBEAU (618) 346-3179
SQUAD CONTACT: ARTHUR MUEHLFELD (618) 346-3209

CONTRACT NO. 76962

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	2
STA.		TO STA.		
FED. ROAD DIST. NO.	ILLINOIS FED. AID PROJECT			

INDEX OF SHEETS

- 1 COVER SHEET
- 2 INDEX OF SHEETS, HIGHWAY STANDARDS, GENERAL NOTES, COMMITMENTS
- 3 SUMMARY OF QUANTITIES
- 4-5 TYPICAL SECTIONS
- 6 TIE POINTS
- 7 SCHEDULE
- 8 PLAN SHEET
- 9-11 STAGE CONSTRUCTION SHEETS
- 12 PAVEMENT MARKING
- 13 WIDE LOAD SIGNING
- 14 TRAIL DETOUR MAP
- 15-29 STRUCTURE PLANS

HIGHWAY STANDARDS

000001-04	701311-02
515001-02	701602-02
606001-02	701801-03
631051-01	702001-06
635011-01	704001-02
701011-01	780001-01
701306-01	781001-02

GENERAL NOTES

1. THE STANDARDS AND REVISIONS NUMBERS SHALL APPLY TO THIS PROJECT.
2. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING MATERIALS.
3. ILLINOIS STATE LAW REQUIRES A 48-HOUR NOTICE BE GIVEN TO ALL UTILITIES WITHIN THE PROJECT AREA BEFORE DIGGING BY CALLING J.U.L.I.E. AND BY NOTIFYING NON-J.U.L.I.E. MEMBERS INDIVIDUALLY. AGENCIES KNOWN TO HAVE FACILITIES WITHIN THE PROJECT AREA ARE AS FOLLOWS:
 - AMERENIP (ELECTRIC & GAS)
 - CITY OF BELLEVILLE (SANITARY SEWER)
 - CHARTER COMMUNICATIONS, INC (CABLE TV)
 - ILLINOIS AMERICAN WATER CO. (WATER)
 - McLEOD USA TELECOMMUNICATIONS, INC. (COMMUNICATIONS)
 - AT&T ILLINOIS (COMMUNICATIONS)
 (MEMBERS OF J.U.L.I.E. (800) 892-0123 ARE INDICATED BY *.
NON-J.U.L.I.E. MEMBERS MUST BE NOTIFIED INDIVIDUALLY.)
4. THE THICKNESS OF BITUMINOUS MIXTURES SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS MAY OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.
5. THE WIDTHS OF BITUMINOUS SURFACE REMOVAL SHOWN ON THE PLANS ARE THE NOMINAL WIDTHS. IRREGULARITIES IN THE SURFACE WIDTH MAY OCCUR THROUGHOUT THE LENGTH OF THE SECTION. BITUMINOUS SURFACE REMOVAL WILL BE PAID FOR IN SQUARE YARDS BASED UPON THE NOMINAL WIDTHS INDICATED.
6. THE VARIOUS THICKNESS OF BITUMINOUS SURFACE REMOVAL SHOWN ON THE PLANS ARE THE AVERAGE THICKNESS BASED UPON CONTROLLING THICKNESS AS INDICATED. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE. BITUMINOUS SURFACE REMOVAL HAS BEEN INCLUDED IN THE PLANS FOR THE PURPOSE OF REMOVING HIGH IRREGULARITIES AND TO ESTABLISH CROSS SLOPE.
7. SAW CUTTING ON ALL EDGES FOR REMOVAL ITEMS SHALL BE INCLUDED IN THE COST OF THE REMOVAL ITEM AS INDICATED AND ACCORDING TO SECTION 440 OF THE STANDARD SPECIFICATIONS.
8. THE CONTRACTOR SHALL FURNISH AND INSTALL WOOD SIGN SUPPORTS IN ACCORDANCE WITH SECTION 730 OF THE STANDARD SPECIFICATIONS, HOWEVER, INSTALLATION BY METHOD "A" (ARTICLE 730.04(A)) SHALL BE THE ONLY METHOD PERMITTED.
9. ROAD CONSTRUCTION AHEAD SIGNS SHALL BE REQUIRED AT INTERSECTING SIDE ROADS THROUGHOUT THE PROJECT. COST TO BE INCLUDED IN BID PRICES FOR TRAFFIC CONTROL AND PROTECTION.
10. A QUANTITY OF 862.5 FEET OF "TEMPORARY PAVEMENT MARKING - LINE 6 INCH" YELLOW AND 112.5 FEET OF "TEMPORARY PAVEMENT MARKING - LINE 6 INCH" WHITE HAS BEEN INCLUDED IN THE PLANS FOR PAINTING THE BOTTOM 6" OF THE TEMPORARY CONCRETE BARRIER.
11. THE CONTRACTOR SHALL BE LIABLE FOR ANY DAMAGES DONE TO THE FENCE, STONE WALL, OR THE CONCRETE UNDER THE STRUCTURE DUE TO CONSTRUCTION ACTIVITIES.
12. THE COST OF ANY SUB-BASE NEEDED UNDER THE RAISED SIDEWALK AND CURB & GUTTER SHALL BE INCLUDED IN THE COST OF "PORTLAND CEMENT CONCRETE SIDEWALK 4 INCH" AND "COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24"; RESPECTIVELY.

EROSION AND SEDIMENT CONTROL GENERAL NOTES

1. ANY AREAS DISTURBED DUE TO CONSTRUCTION ACTIVITIES SHALL BE SEEDED (TEMPORARY AND PERMANENT) AT NO ADDITIONAL COST TO THE DEPARTMENT AND NO OTHER COMPENSATION WILL BE PERMITTED.
2. ALL EROSION CONTROL PRODUCTS FURNISHED SHALL BE SPECIFICALLY RECOMMENDED BY THE MANUFACTURER FOR THE USE SPECIFIED IN THE EROSION CONTROL PLAN. PRIOR TO APPROVAL AND USE OF THE PRODUCT, THE CONTRACTOR SHALL SUBMIT TO THE ENGINEER A NOTARIZED CERTIFICATION BY THE PRODUCER STATING THE INTENDED USE OF THE PRODUCT AND THAT THE PHYSICAL PROPERTIES REQUIRED FOR THIS APPLICATION ARE MET OR EXCEEDED. THE CONTRACTOR SHALL PROVIDE MANUFACTURER RECOMMENDED INSTALLATION PROCEDURES TO FACILITATE THE ENGINEER IN CONSTRUCTION INSPECTION.
3. TEMPORARY SEEDING AND MULCH SHALL BE COMPLETED ON A WEEKLY BASIS ON EXPOSED GROUND AND SHALL BE IN ACCORDANCE WITH SECTION 280 OF THE STANDARD SPECIFICATIONS. TEMPORARY EROSION CONTROL SEEDING SHALL BE APPLIED AT A RATE OF 100 LBS/ACRE.
4. EARTH STOCKPILES SHALL BE TEMPORARILY SEEDED IF THEY ARE TO REMAIN UNUSED FOR MORE THAN FOURTEEN DAYS.
5. FINAL SEEDING SHALL BE PERFORMED AS SOON AS POSSIBLE WITH CLASS 2 SEEDING.

COMMITMENTS

ALL CONSTRUCTION ACTIVITIES SHALL REMAIN OUTSIDE THE WETLAND AREA AND AT NO TIME SHALL THE CONTRACTOR DISTURB THE WETLAND. THIS WET MEADOW IS LOCATED ABOUT 69 FT EAST FROM THE CENTERLINE OF IL RT. 159 AND ALONG THE SOUTH BANK OF RICHLAND CREEK. THIS SITE POSSESSES HYDROPHYTIC VEGETATION, HYDRIC SOIL AND WETLAND HYDROLOGY; THEREFORE, THIS SITE IS A WETLAND.

THE CITY OF BELLEVILLE SHALL BE NOTIFIED TWO WEEKS PRIOR TO THE COMMENCEMENT OF THE RICHLAND CREEK GREENWAY TRAIL DETOUR. AT THAT TIME, THE CITY WILL BE ADVISED AS TO THE TENTATIVE DATES THAT THIS DETOUR WILL BE IN EFFECT.

PLOT DATE = 8/22/2006
 FILE NAME = en:\projects\113305\plan\113305.dgn
 PLOT SCALE = 50.0000' / IN.
 REFERENCE = #REF#

REVISIONS		DATE
NAME		

ILLINOIS DEPARTMENT OF TRANSPORTATION
**INDEX OF SHEETS, HIGHWAY
 STANDARDS, GENERAL NOTES
 & COMMITMENTS**
 FAP ROUTE 600
 SECTION 1-1BR-1
 ST. CLAIR COUNTY

VERT. SCALE: DRAWN BY
 HORIZ. DATE CHECKED BY

SUMMARY OF QUANTITIES

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	3
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		


SUMMARY OF QUANTITIES			URBAN TOTAL QUANTITIES	CONSTRUCTION TYPE CODE	
CODE NO	ITEM	UNIT		X080-2A	SFTY-3N
40600200	BITUMINOUS MATERIALS (PRIME COAT)	TON	0.2	0.2	
40600300	AGGREGATE (PRIME COAT)	TON	1	1	
40600990	TEMPORARY RAMP	SQ YD	179	179	
42400100	PORTLAND CEMENT CONCRETE SIDEWALK 4 INCH	SQ FT	1290	1290	
44000006	BITUMINOUS SURFACE REMOVAL 1 1/2"	SQ YD	547	547	
44000500	COMBINATION CURB AND GUTTER REMOVAL	FOOT	214.5	214.5	
44000600	SIDEWALK REMOVAL	SQ FT	1290	1290	
50101500	REMOVAL OF EXISTING SUPERSTRUCTURES	EACH	1	1	
50102400	CONCRETE REMOVAL	CU YD	7.3	7.3	
50300255	CONCRETE SUPERSTRUCTURE	CU YD	62.3	62.3	
50300260	BRIDGE DECK GROOVING	SQ YD	607	607	
50300300	PROTECTIVE COAT	SQ YD	840	840	
X5030305	CONCRETE WEARING SURFACE, 5"	SQ YD	767	767	
50400305	PRECAST PRESTRESSED CONCRETE DECK BEAMS (17" DEPTH)	SQ FT	6891	6891	
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	17550	17550	
50900905	REMOVING AND RE-ERECTING EXISTING RAILING	FOOT	248	248	
51401600	TEMPORARY BRIDGE RAIL	FOOT	220	220	
51500100	NAME PLATES	EACH	1	1	
60260100	INLETS TO BE ADJUSTED	EACH	2	2	
60605000	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24	FOOT	214.5	214.5	
X63100110	TRAFFIC BARRIER TERMINAL, TYPE 11	EACH	4	4	
63200310	GUARDRAIL REMOVAL	FOOT	42	42	
67000400	ENGINEER'S FIELD OFFICE, TYPE A	CAL MO	14	14	
67100100	MOBILIZATION	L SUM	1	1	
70100460	TRAFFIC CONTROL AND PROTECTION, STANDARD 701306	L SUM	1	1	
70102640	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	L SUM	1	1	
70102672	TRAFFIC CONTROL AND PROTECTION, STANDARD 701602, SPECIAL	L SUM	1	1	
70300100	SHORT-TERM PAVEMENT MARKING	FOOT	60	60	
70300220	TEMPORARY PAVEMENT MARKING - LINE 4"	FOOT	3615	3615	
70300240	TEMPORARY PAVEMENT MARKING - LINE 6"	FOOT	975	975	
70300260	TEMPORARY PAVEMENT MARKING - LINE 12"	FOOT	356	356	
70301000	WORK ZONE PAVEMENT MARKING REMOVAL	SQ FT	1570	1570	

SUMMARY OF QUANTITIES			URBAN TOTAL QUANTITIES	CONSTRUCTION TYPE CODE	
CODE NO	ITEM	UNIT		X080-2A	SFTY-3N
70400500	TEMPORARY CONCRETE BARRIER (STATE OWNED)	FOOT	550	550	
70400600	RELOCATE TEMPORARY CONCRETE BARRIER (STATE OWNED)	FOOT	337.5	337.5	
X78000200	THERMOPLASTIC PAVEMENT MARKING - LINE 4"	FOOT	1042	1042	
X78000600	THERMOPLASTIC PAVEMENT MARKING - LINE 12"	FOOT	229	229	
X78008210	POLYUREA PAVEMENT MARKING TYPE I - LINE 4"	FOOT	545	545	
X78008250	POLYUREA PAVEMENT MARKING TYPE I - LINE 12"	FOOT	127	127	
X78100100	RAISED REFLECTIVE PAVEMENT MARKER	EACH	10	10	
X78100105	RAISED REFLECTIVE PAVEMENT MARKER (BRIDGE)	EACH	11	11	
X78100300	REPLACEMENT REFLECTOR	EACH	16	16	
78300100	PAVEMENT MARKING REMOVAL	SQ FT	574	574	
78300200	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL	EACH	37	37	
X0325305	STRUCTURAL REPAIR OF CONCRETE (DEPTH EQUAL TO OR LESS THAN 5 INCHES)	SQ FT	276	276	
X4066428	BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIX "D", N90	TON	46	46	
X4066775	LEVELING BINDER (MACHINE METHOD), SUPERPAVE N90	TON	33	33	
X7200200	WIDE LOAD SIGNING	L SUM	1	1	
Z0002600	BAR SPLICERS	EACH	234	234	
Z0030240	IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 2	EACH	2	2	
Z0030255	IMPACT ATTENUATORS, TEMPORARY (FULLY REDIRECTIVE, NARROW), TEST LEVEL 2	EACH	1	1	
Z0030320	IMPACT ATTENUATORS, RELOCATE (FULLY REDIRECTIVE), TEST LEVEL 2	EACH	1	1	
Z0030340	IMPACT ATTENUATORS, RELOCATE (NON-REDIRECTIVE), TEST LEVEL 2	EACH	2	2	


PLOT DATE = 8/22/2006
 PLOT NAME = c:\p\projects\76962\plan\p10305.dgn
 PLOT SCALE = 1/4" = 1'-0"
 REFERENCE = REF#

Rev.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	4
STA.		TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		



TYPICAL SECTION
STA. 157+00 TO STA. 157+54



TYPICAL SECTION
STA. 158+63 TO STA. 159+15

LEGEND

- ① EXISTING CONCRETE PAVEMENT
- ② EXISTING RESURFACING 3"
- ③ EXISTING CONCRETE CURB AND GUTTER
- ④ EXISTING CONCRETE SIDEWALK
- ⑤ EXISTING BITUMINOUS CONCRETE BINDER COURSE - 12.5"
- ⑥ EXISTING SUBBASE GRANULAR MATERIAL
- ⑦ PROPOSED BITUMINOUS SURFACE REMOVAL - 1/2"
- ⑧ PROPOSED BITUMINOUS PRIME COAT
- ⑨ PROPOSED AGGREGATE PRIME COAT
- ⑩ PROPOSED LEVELING BINDER, SUPERPAVE - 3 1/2" & VARIES
- ⑪ PROPOSED BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE - 1 1/2"
- ⑫ PROPOSED SIDEWALK REMOVAL
- ⑬ PROPOSED PCC SIDEWALK - 4"
- ⑭ PROPOSED COMBINATION CURB & GUTTER REMOVAL
- ⑮ PROPOSED COMBINATION CURB & GUTTER

PLOT DATE = 8/21/2005
 FILE NAME = c:\pcc\158+63\158+63.dgn
 PLOT SCALE = 5/8" = 1' / IN.
 REFERENCE = REF#

REVISIONS	
NAME	DATE


ILLINOIS DEPARTMENT OF TRANSPORTATION
 EXISTING TYPICAL SECTIONS

FAP ROUTE 600
 SECTION 1-1BR-1
 ST. CLAIR COUNTY


SCALE: VERT.
 HORIZ.
 DATE

DRAWN BY
 CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	5
STA.		TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		



TYPICAL SECTION
STA. 157+00 TO STA. 157+54



TYPICAL SECTION
STA. 158+63 TO STA. 159+15

BITUMINOUS MIXTURE REQUIREMENTS

MIXTURE USE	SURFACE	LEVEL BINDER
AC/PG	PG 64-22	PG 64-22
RAP % (MAX)	10%	10%
DESIGN AIR VOIDS	4.0% @ Ndes=90	4.0% @ Ndes=90
MIX COMPOSITION		
(GRADATION MIXTURE)	IL 9.5	IL 19.0
FRICITION AGG	MIXTURE "D"	MIXTURE "C"

LEGEND



- ① EXISTING CONCRETE PAVEMENT
- ② EXISTING RESURFACING 3"
- ③ EXISTING CONCRETE CURB AND GUTTER
- ④ EXISTING CONCRETE SIDEWALK
- ⑤ EXISTING BITUMINOUS CONCRETE BINDER COURSE - 12.5"
- ⑥ EXISTING SUBBASE GRANULAR MATERIAL
- ⑦ PROPOSED BITUMINOUS SURFACE REMOVAL - 1/2"
- ⑧ PROPOSED BITUMINOUS PRIME COAT
- ⑨ PROPOSED AGGREGATE PRIME COAT
- ⑩ PROPOSED LEVELING BINDER, SUPERPAVE - 3 1/2" & VARIES
- ⑪ PROPOSED BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE - 1 1/2"
- ⑫ PROPOSED SIDEWALK REMOVAL
- ⑬ PROPOSED PCC SIDEWALK - 4"
- ⑭ PROPOSED COMBINATION CURB & GUTTER REMOVAL
- ⑮ PROPOSED COMBINATION CURB & GUTTER

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION PROPOSED TYPICAL SECTIONS
NAME	DATE	
		FAP ROUTE 600 SECTION 1-1BR-1 ST. CLAIR COUNTY


SCALE: VERT. _____
HORIZ. _____
DATE _____ DRAWN BY _____
CHECKED BY _____

PLOT DATE = 8/24/2006
FILE NAME = c:\pcc\projects\aed\02065\plan\plan10305a.dgn
PLOT SCALE = 50.0000 / IN.
REFERENCE = REF#


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	6
STA. 600		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		




TIE POINT
MAG NAIL
STA. 152+01.53




TIE POINT
MAG NAIL
STA. 154+00



TIE POINT
MAG NAIL
STA. 157+87.04



TIE POINT
MAG NAIL
STA. 160+00



TIE POINT
MAG NAIL
STA. 163+90.23

TEMPORARY BENCHMARKS

- TBM-1 - A CHISELED "□" ON SW CORNER OF CONCRETE TRAFFIC SIGNAL CONTROL HANDHOLE ON NE CORNER OF IL 159 & EAST "F" STREET
ELEV = 514.841
- TBM-2 - "X" CUT ON WNW TOP FLANGE BOLT OF FIRE HYDRANT ON E SIDE OF IL 159 APPROX. 90' SOUTH OF SN 082-0265
ELEV = 505.181
- TBM-3 - A CHISELED "□" ON SE CORNER OF CONCRETE FOUNDATION FOR 5' TALL METAL CONTROLLER BOX ON SW CORNER OF INTERSECTION OF RAILROAD TRACKS & IL 159 ACROSS FROM DOUGLAS AVE.
ELEV = 497.974
- TBM-4 - RR SPIKE IN W SIDE OF POWER POLE ON E SIDE OF IL 159 APPROX. 500' S OF BOUL AVENUE APPROX. 125' N OF BUS STOP SHELTER ON N SIDE OF SWANSEA POLICE STATION
ELEV = 508.170
- TBM-5 - A CHISELED "□" ON SW CORNER OF CONCRETE TRAFFIC SIGNAL HANDHOLE BOX ON S SIDE OF IL 161 APPROX. 150' W OF IL 159 CENTERLINE AND IN MIDDLE OF SIDEWALK.
ELEV = 542.267

BENCHMARK

- BM R-114 - A STANDARD DISK SET IN CONCRETE ON THE NW CORNER OF "A" STREET & 1ST STREET IN BELLEVILLE
ELEV = 521.406

NOTE: ALL MEASUREMENTS ARE PULLED DIRECT

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
TIE POINTS & BENCHMARKS

FAP ROUTE 600
SECTION 1-1BR-1
ST. CLAIR COUNTY

SCALE: VERT. _____
HORIZ. _____

DATE _____

DRAWN BY _____
CHECKED BY _____

PLOT DATE = #DATE#
FILE NAME = #FILE#
PLOT SCALE = #SCALE#
REFERENCE = #REF#

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	7
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

PAVEMENT MARKING SCHEDULE

LOCATION	TEMPORARY PAVEMENT MARKING LINE - 4"				TEMPORARY PAVEMENT MARKING LINE - 12"	SHORT-TERM PAVEMENT MARKING	WORK ZONE PAVEMENT MARKING REMOVAL	THERMOPLASTIC PAVEMENT MARKING -4"				THERMOPLASTIC PAVEMENT MARKING -12"		PAVEMENT MARKING REMOVAL					POLYUREA PAVEMENT MARKING TYPE I-LINE 4"	POLYUREA PAVEMENT MARKING TYPE I-LINE 12"			
	STAGE I	STAGE II	STAGE III	FINAL				SOLID LINE	SKIP-DASH LANE LINE	SKIP-DASH LANE LINE	EDGE LINE WHITE	YELLOW	WHITE	SOLID LINE	SKIP-DASH LANE LINE	SKIP-DASH LANE LINE	EDGE LINE	SOLID 12"					
	FOOT	FOOT	FOOT	FOOT				FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT			FOOT	FOOT	
STA 154+02.0 TO STA 156+50.0	248.0		232.0	219.3	62.5		295.8			11.0	2+15.00		62.5				3.3	69.5		62.5			
STA 156+50.0 TO STA 157+00.0	50.0	100.0	118.0	163.3	25.5		169.6	100.0		13.5	50.0		25.5	33.3			4.5	16.7		25.5			
STA 157+00.0 TO STA 157+21.0	21.0	42.0	42.0	69.1	14.4	12	74.2	42.0		6.3	21.0		14.4	14.0			2.2	7.0		14.4			
STA 157+21.0 TO STA 157+53.7		39.0	65.4	106.7	32.0	12	103.9	65.4		9.2	32.7		32.1	21.8			3.1	10.9		32.1			
STA 157+53.7 TO STA 158+62.5			217.6	544.3	127.3	12	382.8											0.5			545.0	127.0	
STA 158+62.5 TO STA 158+85.0			45.0	68.0	26.9	12	66.3	45.0					20.6	7.7	19.2	15.0		6.9	7.7	19.2			
STA 158+85.0 TO STA 159+15.0	30.0		90.0	90.0	39.2	12	110.7	60.0					30.0	13.9	25.5	20.0		10.0	13.9	25.5			
STA 159+15.0 TO STA 160+05.0	141.0		418.0	294.5	28.2		312.9	183.9	20.0		90.0	28.2		61.3	6.7			30.0	28.2				
STA 160+05.0 TO STA 160+33.0	24.0		112.0	25.0			53.9				25.0							8.3					
SUB-TOTAL	514.0	181.0	1340.0	1580.0				496.3	20.0	40.0	485.8	49.8	179.2	165.4	6.7	13.1	159.8	49.8	179.2				
TOTAL		3615			356	60	1570			1042		229				574		545		127			

STAGING SCHEDULE

LOCATION	TRAFFIC BARRIER TERMINAL, TYPE 11	TEMPORARY CONCRETE BARRIER	RELOCATE TEMPORARY CONCRETE BARRIER	TEMPORARY PAVEMENT MARKING LINE 6"	TEMPORARY BRIDGE RAIL	IMPACT ATTENUATOR, TEMPORARY (NON-REDIRECTIVE)	IMPACT ATTENUATOR, RELOCATE (NON-REDIRECTIVE)	IMPACT ATTENUATOR, TEMPORARY (FULLY-REDIRECTIVE)	IMPACT ATTENUATOR, RELOCATE (FULLY-REDIRECTIVE)
	EACH	FOOT	FOOT	FOOT	FOOT	EACH	EACH	EACH	EACH
STAGE I				500		2			
STAGE II	4	550	262.5	475	220		1	1 *	
STAGE III			75				1		1
TOTAL	4	550	337.5	975	220	2	2	1	1

* MAXIMUM WIDTH OF 2'-11" AND A MAXIMUM LENGTH OF 24'.

RESURFACING SCHEDULE

LOCATION	BITUMINOUS MATERIALS (PRIME COAT)	AGGREGATE (PRIME COAT)	BITUMINOUS SURFACE REMOVAL 1 1/2"	BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE	LEVEL BINDER (MACHINE METHOD), SUPERPAVE
STATION TO STATION	TON	TON	SQ YD	TON	TON
STA 157+00.00 TO STA 157+53.70	0.1	0.5	286.8	24.1	17.3
BRIDGE OMISSION					
STA 158+62.80 TO STA 159+15.00	0.1	0.5	260.2	21.9	15.7
TOTAL	0.2	1	547	46	33

RAISED REFLECTIVE PAVEMENT MARKERS SCHEDULE

LOCATION	RAISED REFLECTIVE PAVEMENT MARKER		RAISED REFLECTIVE PAVEMENT MARKER (BRIDGE)	REPLACEMENT REFLECTOR		RAISED REFLECTIVE PAVEMENT MARKER REMOVAL
	2-WAY AMBER	WHITE		2-WAY AMBER	WHITE	
	EACH	EACH		EACH	EACH	
STA 154+02.0 TO STA 156+50.0				1	1	
STA 156+50.0 TO STA 157+00.0				3	1	4
STA 157+00.0 TO STA 157+21.0	1	1				2
STA 157+21.0 TO STA 157+53.7	2					2
STA 157+53.7 TO STA 158+62.5			11			11
STA 158+62.5 TO STA 158+85.0	3					3
STA 158+85.0 TO STA 159+15.0	3					3
STA 159+15.0 TO STA 160+05.0				11		11
STA 160+05.0 TO STA 160+33.0						0
SUB-TOTAL	9	1		14	2	
TOTAL	10		11	16		37

SIDEWALK AND CURB & GUTTER SCHEDULE

LOCATION	SIDEWALK REMOVAL	PCC SIDEWALK 4 IN	COMBINATION CURB & GUTTER REMOVAL	COMBINATION CURB & GUTTER, TYPE B-6.24
STATION TO STATION	SQ FT	SQ FT	FT	FT
NORTHEAST QUADRANT				
STA 157+00.00 TO STA 157+51.00	328.6	328.6	51.0	51.0
NORTHWEST QUADRANT				
STA 157+00.00 TO STA 157+57.70	358.2	358.2	57.8	57.8
BRIDGE OMISSION				
SOUTHEAST QUADRANT				
STA 158+58.80 TO STA 159+15.00	315.4	315.4	56.3	56.3
SOUTHWEST QUADRANT				
STA 158+65.60 TO STA 159+15.00	287.8	287.8	49.4	49.4
TOTAL	1290	1290	214.5	214.5

TEMPORARY RAMP SCHEDULE



LOCATION	WIDTH FOOT	LENGTH FOOT	TEMPORARY RAMP SQ YD
STA 157+00.0	48	5	26.8
STA 159+10.0	41.75	5	23.3
STA 157+41.6	48	12.1	64.7
STA 158+62.8	47.6	12.1	64.2
TOTAL			179

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULES
NAME	DATE	
		FAP ROUTE 600 SECTION 1-1BR-1 ST. CLAIR COUNTY SCALE: VERT. _____ HORIZ. _____ DATE _____

PLOT DATE = #DATE#
 PLOT SCALE = #SCALE#
 PLOT SHEET = #SHEET#
 REFERENCE = #REF#

DRAWN BY _____
 CHECKED BY _____

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	8
STA. 155+00		TO STA. 161+00		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		



PLOT DATE = 8/25/2006
 FILE NAME = c:\projects\rd\10305\plan\10305.dgn
 PLOT SCALE = 28.0000 / IN.
 REFERENCE = #REF#

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
PLAN VIEW
 FAP ROUTE 600
 SECTION 1-1BR-1
 ST. CLAIR COUNTY


SCALE: VERT. _____
 HORIZ. _____
 DATE _____

DRAWN BY _____
 CHECKED BY _____


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	9
STA. 152+00		TO STA. 164+00		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		

LEGEND

- BARRELS OR BARRICADES WITH STEADY BURNING LIGHT
- DIRECTIONAL BARRICADE WITH STEADY BURNING LIGHT
- TEMPORARY CONCRETE BARRIER
- IMPACT ATTENUATOR
- ARROW BOARD
- TYPE III BARRICADE



SAND BARRELL LAYOUT (IF OPTION USED)




SEQUENCE OF CONSTRUCTION:

REMOVE CONFLICTING SKIP-DASH AND SOLID PAVEMENT MARKINGS (SEE SCHEDULES FOR STATIONING).

PLACE 500 FT TEMPORARY CONCRETE BARRIER, DIRECTIONAL BARRICADES, BARRELS, AND 2 EACH IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE).

SEE STANDARD 701602 FOR SIGN LAYOUT.

PERFORM ALL NECESSARY BRIDGE WORK IN STAGE I WORK ZONE, INCLUDING INSTALLATION OF TEMPORARY RAMPS ON BOTH ENDS OF STRUCTURE.



REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

STAGE I CONSTRUCTION

FAP ROUTE 600
SECTION 1-1BR-1
ST. CLAIR COUNTY

SCALE: VERT. _____
HORIZ. _____


DATE _____ DRAWN BY _____
CHECKED BY _____

PLOT DATE = #DATE#
FILE NAME = #FILE#
SCALE = #SCALE#
USER NAME = #USER#

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	10
STA. 152+00		TO STA. 164+00		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

LEGEND

- BARRELS OR BARRICADES WITH STEADY BURNING LIGHT
- DIRECTIONAL BARRICADE WITH STEADY BURNING LIGHT
- TEMPORARY CONCRETE BARRIER
- IMPACT ATTENUATOR
- ARROW BOARD



SAND BARRELL LAYOUT (IF OPTION USED)

TEMPORARY PAVEMENT MARKING, 4" WHITE - 90'

TEMPORARY PAVEMENT MARKING, 4" YELLOW - 92'

TBT, TYPE 11

STAGE II WORK ZONE

RICHLAND CREEK GREENWAY TRAIL

MATCHLINE STA. 158+00



TEMPORARY BRIDGE RAIL

SEQUENCE OF CONSTRUCTION:
 RELOCATE 262.5 FT AND PLACE 37.5 FT TEMPORARY CONCRETE BARRIER.
 PLACE 220 FT OF TEMPORARY BRIDGE RAIL. PLACE 4 EACH TBT, TYPE 11 TO CONNECT BARRIER AND BRIDGE RAIL. PLACE 1 EACH IMPACT ATTENUATOR, TEMPORARY (FULLY RE-DIRECTIVE) AND RELOCATE 1 EACH IMPACT ATTENUATOR (NON-REDIRECTIVE).
 SEE STANDARD 701602 FOR SIGN LAYOUT.
 PERFORM ALL NECESSARY BRIDGE WORK IN STAGE II WORK ZONE, INCLUDING INSTALLATION OF TEMPORARY RAMPS ON BOTH ENDS OF STRUCTURE.

IMPACT ATTENUATOR, TEMPORARY (NON-REDIRECTIVE), TL 2 PLACED IN STAGE I

TEMPORARY CONCRETE BARRIER PLACED IN STAGE I

SEE STANDARD 701602 FOR SIGN LAYOUT



REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
STAGE II CONSTRUCTION
 FAP ROUTE 600
 SECTION 1-1BR-1
 ST. CLAIR COUNTY

SCALE: VERT. _____
 HORIZ. _____
 DATE _____


DRAWN BY _____
 CHECKED BY _____

PLOT DATE =
 DATE =
 PLOT SCALE =
 USER NAME =


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	11
STA. 152+00 TO STA. 164+00				
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT				

LEGEND

- BARRELS OR BARRICADES WITH STEADY BURNING LIGHT
- DIRECTIONAL BARRICADE WITH STEADY BURNING LIGHT
- TEMPORARY CONCRETE BARRIER
- IMPACT ATTENUATOR
- ARROW BOARD




SAND BARRELL LAYOUT (IF OPTION USED)



SEQUENCE OF CONSTRUCTION:

- REMOVE 450 FT AND RELOCATE 75 FT TEMPORARY CONCRETE BARRIER
- REMOVE 110 FT OF TEMPORARY BRIDGE RAIL, 2 EACH TBT, TYPE 11, 1 EACH IMPACT ATTENUATOR, TEMPORARY (NON-REDIRECTIVE) AND RELOCATE 2 EACH IMPACT ATTENUATORS.
- TBT, TYPE 11 REMOVAL SHALL BE PAID FOR AS "GUARDRAIL REMOVAL".
- SEE STANDARD 701602 FOR SIGN LAYOUT.
- PERFORM ALL NECESSARY BRIDGE WORK IN STAGE III WORK ZONE, INCLUDING INSTALLATION OF TEMPORARY RAMPS ON BOTH ENDS OF STRUCTURE.





REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
STAGE III CONSTRUCTION
 FAP ROUTE 600
 SECTION 1-1BR-1
 ST. CLAIR COUNTY



SCALE: VERT. 1" = 20'
 HORIZ. 1" = 40'
 DATE _____ DRAWN BY _____
 CHECKED BY _____

PLOT DATE = 04/15/04
 DATE = 04/15/04
 PLOT SCALE = AS SHOWN
 USER NAME = 4108ER


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	12
STA. TO STA.		FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		



DETAIL 'A'
NOT TO SCALE



DETAIL 'B'



PLOT DATE = 8/23/2006
 PLOT SCALE = 20,000 / IN.
 REFERENCE = #REF#

REVISIONS	
NAME	DATE


ILLINOIS DEPARTMENT OF TRANSPORTATION
PAVEMENT MARKING
 FAP ROUTE 600
 SECTION 1-1BR-1
 ST. CLAIR COUNTY

SCALE: VERT. _____
 HORIZ. _____
 DATE _____ DRAWN BY _____
 CHECKED BY _____

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	13
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

NOTES

- ① ALL SIGNS REQUIRED WILL BE SUPPLIED TO THE CONTRACTOR BY I.D.O.T.
- ② THE CONTRACTOR SHALL FURNISH THE POSTS AND ERECT SIGNS AT THE LOCATIONS SHOWN ON THIS SHEET, AS DIRECTED BY THE R.E./R.T. THE POSTS SHALL REMAIN THE PROPERTY OF THE CONTRACTOR.
- ③ THE CONTRACTOR SHALL GIVE ILLINOIS DEPARTMENT OF TRANSPORTATION, BUREAU OF OPERATIONS TWO WEEKS NOTICE FOR SIGNS. THE CONTRACTOR SHALL PICK UP THE SIGNS AT THE T.M. BUILDING IN FAIRVIEW HGTS., AND RETURN THEM UPON COMPLETION OF THE CONTRACT. CONTACT JEAN SLAPE (618) 346-3289.
- ④ THE ABOVE NOTED WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE, LUMP SUM, FOR "WIDE LOAD SIGNING" AND NO OTHER COMPENSATION WILL BE ALLOWED.
- ⑤ SIGN SPACING WILL BE 400' OR TO FIT FIELD CONDITIONS.
- ⑥ THE HEIGHT AT THE BOTTOM OF THE LOWEST SIGN SHALL NOT BE LESS THAN 7'.



SIGNS REQUIRED

MAX WIDTH 10 FT 6 IN 0.5 MILES AHEAD	(1)	NORTH	(2)
MAX WIDTH 10 FT 6 IN 0.8 MILES AHEAD	(3)	SOUTH	(3)
MAX WIDTH 10 FT 6 IN 1 MILE AHEAD	(1)	ILLINOIS 159	(5)
MAX WIDTH 10 FT 6 IN 1.5 MILES AHEAD	(3)		

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
WIDE LOAD SIGNING
 FAP ROUTE 600
 SECTION 1-1BR-1
 ST. CLAIR COUNTY
 SCALE: VERT. _____
 DATE _____ HORIZ. _____
 DRAWN BY _____
 CHECKED BY _____

PLOT DATE = 8/21/88
 FILE NAME = 81LE1
 PLOT SCALE = 1/8"=1'-0"
 REFERENCE = 81LE1

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	14
STA. TO STA.				
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT				

THE CROSSINGS AT IL 159 AND DOUGLAS AVE ARE SIGNALIZED.


THE PROPOSED TRAIL DETOUR DISTANCES (APPROX.):

- NORTH END PARK TO IL 159 - 355'
- CROSSING DOUGLAS AVENUE - 60'
- CROSSING IL 159 - 70'
- IL 159 TO "Y" INTERSECTION - 690'

THE CONTRACTOR SHALL FURNISH THE POSTS AND ERECT SIGNS AT THE LOCATIONS SHOWN ON THIS SHEET, AS DIRECTED BY THE R.E./R.T. THE POSTS SHALL REMAIN THE PROPERTY OF THE CONTRACTOR.

THE ABOVE NOTED WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE, LUMP SUM, FOR "TRAFFIC CONTROL & PROTECTION 701602 (SPECIAL)" AND NO OTHER COMPENSATION WILL BE ALLOWED.

THE HEIGHT AT THE BOTTOM OF THE LOWEST SIGN SHALL NOT BE LESS THAN 7' UNLESS OTHERWISE DIRECTED BY THE R.E./R.T.



- EXISTING TRAIL
- TEMPORARY TRAIL CLOSURE (APPROX. 930')
- PROPOSED TRAIL DETOUR (APPROX 1185')
- TYPE III BARRICADES

PLAT DATE = 8/23/2006
 FILE NAME = d:\15br\15br14\15br14_14.dwg
 PLOT SCALE = 1/8" = 1'-0"
 REFERENCE = #REF*

SIGNS REQUIRED

1 (1)
 Dimensions: 24" x 12"
 Spacing: 3.9" (left), 9.9" (center), 2.4" (right)
 1.5" Radius, 0.4" Border, 0.4" Indent, Black on Orange;
 [DETOUR VIA] D; [IL 159 TO] D; [DOUGLAS AVE] D;

2 (1)
 Dimensions: 24" x 12"
 Spacing: 3.9" (left), 9.9" (center), 2.4" (right)
 1.5" Radius, 0.4" Border, 0.4" Indent, Black on Orange;
 [DETOUR VIA] D; [DOUGLAS AVE] D; [TO IL 159] D;

3 (2)
 Dimensions: 19.3" x 8.8"
 W1-6 BIKE;
 1.5" Radius, 0.6" Border, 0.4" Indent, Black on Orange;
 Standard Arrow Custom 19.3" X 8.8" 0°;

4 (2)
 Dimensions: 19.3" x 8.8"
 W1-6 BIKE;
 1.5" Radius, 0.6" Border, 0.4" Indent, Black on Orange;
 Standard Arrow Custom 19.3" X 8.8" 180°;

5 (4)
 Dimensions: 18.7" x 12"
 M4-8 MIN & STD;
 1.5" Radius, 0.6" Border, 0.4" Indent, Black on Orange;
 [DETOUR] B 80% spacing;

6 (2)
 Dimensions: 18.0" across sides, 24.2" height
 18.0" across sides 1.5" Radius, 0.6" Border, 0.4" Indent, Black on Orange;
 [TRAIL] C; [CLOSED] C; [AHEAD] C;


7 (3)
 Dimensions: 30" x 48"
 R11-2;
 1.9" Radius, 0.8" Border, 0.5" Indent, Black on White;
 [TRAIL] D 82% spacing; [CLOSED] D 83% spacing;

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION	
NAME	DATE		
		<p align="center">TRAIL DETOUR MAP</p> <p align="center">FAP ROUTE 600 SECTION 1-1BR-1 ST. CLAIR COUNTY</p>	
SCALE:	VERT. DATE	HORIZ.	DRAWN BY
			CHECKED BY

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
FAP 600	1-1BR-1	ST. CLAIR	29	15
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT-		

Contract # 76962



GENERAL NOTES

Plan dimensions and details relative to existing structure have been taken from existing plans and are subject to nominal construction variations. It shall be the Contractor's responsibility to verify such dimensions and details in the field and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in the scope of work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Existing name plate shall be cleaned and relocated adjacent to the new name plate. Cost included with Name Plates.

The cut strands at each beam end shall be given two coats of zinc dust spray or paint meeting the requirements of ASTM A 780. The zinc dust spray or paint shall be applied before corrosion appears and allowed to dry according to the manufacturer's specifications prior to another coat of zinc. A concrete sealer meeting the requirements of Section 587 of the Standard Specifications shall be applied to the exterior face and 9" in on the underside of the fascia beams. The sealer shall be applied after visible crack growth has subsided. This work shall be performed by the producer and included with the cost of the beam.

Repair of the substructure shall be completed prior to placement of the new deck beams.

The contractor is advised that the existing PPC Deck Beams are in a deteriorated condition with reduced load carrying capacity. It is the Contractor's responsibility to account for the condition of the beams when developing construction procedures for removal and replacement of the superstructure.

If the Contractor's procedure for existing beam removal or placement of new beams involves placement of cranes or other heavy equipment on new beams, a detailed procedure shall be submitted to the Engineer for approval. The procedure shall include calculations, prepared and sealed by an Illinois Licensed Structural Engineer, verifying that the equipment and procedure used will not overstress the new beams. To distribute load to multiple beams and protect the concrete, in all cases a double layer mat of heavy timbers shall be used at all times under crane tracks or wheels and any outriggers in down position. If necessary, shims shall be used under the crane mat to ensure uniform contact with the underlying beams. Prior to placement of the timber mats the following shall be done: placement and tightening of transverse tie assemblies, grouting and curing the dowel rods 24 hours minimum and grouting and curing the shear keys. A temporary means of lateral restraint will be required for fascia beams at expansion ends of beams to prevent movement of the beams.

Any damage done to the bridge during beam removal shall be repaired by the Contractor. Cost to be included in the cost of Removal of Existing Superstructures.

The minimum thickness of concrete overlay shall be 5" and varies as required to adjust for the profile grade and camber.

No instream work will be allowed on this project.

All construction joints shall be bonded.

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Removal of Existing Superstructures	Each	1	—	1
Concrete Removal	Cu. Yd.	7.3	—	7.3
Concrete Superstructure	Cu. Yd.	62.3	—	62.3
Bridge Deck Grooving	Sq. Yd.	607	—	607
Protective Coat	Sq. Yd.	840	—	840
Concrete Wearing Surface, 5"	Sq. Yd.	767	—	767
Structural Repair of Concrete (Depth Equal to or Less Than 5")	Sq. Ft.	—	276	276
Precast Prestressed Concrete Deck Beams (17" Depth)	Sq. Ft.	6,891	—	6,891
Reinforcement Bars, Epoxy Coated	Pound	17,700	—	17,700
Temporary Bridge Rail	Foot	220	—	220
Name Plates	Each	1	—	1
Bar Splicers	Each	234	—	234
Removing and Re-Erecting Existing Railing	Foot	248	—	248

LOADING HS20-44
No allowance for future wearing surface.
DESIGN SPECIFICATIONS
2002 AASHTO

FIELD UNITS

$f'_c = 5,000$ psi (Concrete Wearing Surface)
 $f'_c = 3,500$ psi
 $f_y = 60,000$ psi (reinforcement)

DESIGN STRESSES

PRECAST PRESTRESSED UNITS (SPANS 1 & 2)		PRECAST PRESTRESSED UNITS (SPAN 3)	
$f'_c = 5,000$ psi	$f'_c = 6,000$ psi	$f'_c = 5,000$ psi	$f'_c = 270,000$ psi ($1/2$ " low lax. strands)
$f_{ci} = 4,000$ psi	$f_{ci} = 5,000$ psi	$f_s = 270,000$ psi ($1/2$ " low lax. strands)	$f_{si} = 201,960$ psi ($1/2$ " low lax. strands)
$f'_s = 270,000$ psi ($1/2$ " low lax. strands)	$f_{si} = 201,960$ psi ($1/2$ " low lax. strands)		

WATERWAY INFORMATION


Drainage Area = 14.2 Sq. Mi. Low Grade Elev. 495.8 @ Sta. 154+00

Flood	Freq. Yr.	Q C.F.S.	Opening Sq. Ft.		Nat. H.W.E.	Head - Ft.		Headwater El.	
			Exist.	Prop.		Exist.	Prop.	Exist.	Prop.
Design	50	8,020	1,443		497.0	0.6		497.6	
Base	100	9,060	1,878		497.9	0.5		498.4	
Overtopping	30	7,350	1,162		496.1	0.2		496.3	
Max. Calc.	500								

STATION 158+08
BUILT 200 BY
STATE OF ILLINOIS
FAP ROUTE 600 - SEC 1-1BR-1
LOADING HS20
STR. NO. 082-0265

NAME PLATE
See Std. 515001

Plans Prepared By:
Oates Associates, Inc.



Bruce P. Schopp
8/22/06
EXPIRES 11/30/06


GENERAL PLAN & ELEVATION
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-1BR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265

PLOT DATE = #DATE#
FILE NAME = #FILE#
PLOT SCALE = #SCALE#
USER NAME = #USER#


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	SHEET
FAP 600	1-1BR-1	ST. CLAIR	29	16	13 SHEETS
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT			


Contract # 76962




STAGE I REMOVAL
(Looking South)




STAGE I CONSTRUCTION
(Looking South)




STAGE II REMOVAL
(Looking South)




STAGE II CONSTRUCTION
(Looking South)




STAGE III REMOVAL
(Looking South)




STAGE III CONSTRUCTION
(Looking South)



PLAN



CLAMPING PLATE



SECTION

SHEAR KEY CLAMPING DETAILS AT STAGE CONST. JT.

Notes:

- ① For quantity of Temporary Concrete Barrier, see roadway plans.
- ② For details of Temporary Bridge Rail, see sheet 4 of 13.
- ③ For details of Temporary Concrete Barrier, see sheet 3 of 13.
- ④ See Special Provisions for Stage Construction Precast Prestressed Concrete Deck Beams.
- ⑤ Cost of shear key clamps is included with Precast Prestressed Concrete Deck Beams (17" Depth).

STAGE CONSTRUCTION DETAILS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-1BR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265


PLOT DATE = #DATE#
FILE NAME = #FILE#
PLOT SCALE = #SCALE#
USER NAME = #USER#

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
FAP 600	1-IBR-1	ST. CLAIR	29	17
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT		

SHEET
13 SHEETS

Contract # 76962




When "A" is 3'-6" or less, the temporary concrete barrier shall be anchored to the new slab according to Detail I or Detail II. No anchorage is required when "A" is greater than 3'-6".

NOTES


- Detail I - With Bar Splicer or Couplers:
Connect one (1) 1"x7"x10" steel \bar{P} to the top layer of couplers with 2-5/8" ϕ bolts screwed to coupler at approximate ϕ of each barrier panel.
- Detail II - With Extended Reinforcement Bars:
Connect one (1) 1"x7"x10" steel \bar{P} to the concrete slab with 2-5/8" ϕ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate ϕ of each barrier panel.
- Cost of anchorage is included with Temporary Concrete Barrier.

SECTIONS THRU SLAB




DETAIL I

The 1"x7"x10" Plate shall not be removed until Stage II Construction forms and reinforcement bars are in place.



DETAIL II

The 1"x7"x10" Plate shall not be removed until Stage II Construction forms and all reinforcement bars are in place and the concrete is ready to be placed.



\bar{P} 1"x7"x10"

* Required only with Detail II

TEMPORARY CONCRETE BARRIER
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-IBR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265


PLOT DATE = #DATE#
FILE NAME = #FILE#
PLOT SCALE = #SCALE#
USER NAME = #USER#

R-27


10-22-04

Contract # 76962


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION




SECTION A-A




SECTION AT RAIL POST




DETAIL A




SECTION THRU BRACKET




VIEW D-D



VIEW A-A
ROUND HEAD BOLT




SECTION A-A




SECTION AT RAIL POST

ALTERNATE I
(To be used only for Roadway width $\geq 12'$)


2-3/4" ϕ x 6" Round Head Bolts
(With slot or approved recess in head) with locknut & flat hardened washer. 7/8" ϕ holes in hollow structural section may be drilled in the field.




INSERT DETAIL



VIEW C-C




END OF RAIL DETAILS




VIEW E-E

NOTES

Hollow structural sections shall conform to the requirements of ASTM designation A 500 Grade B Structural Steel Tubing.
All other steel shapes and plates shall conform to the requirements of AASHTO M 270 Grade 36 except posts and brackets shall conform to AASHTO M 270, Grade 50.
Bolts, cap screws, and nuts shall conform to the requirements of ASTM designation A 307 except for high strength bolts, threaded studs, nuts and washers noted which shall conform to AASHTO M 270, Grade 50.
The bridge rail shall receive one shop coat of a steel prime paint.
The 1" ϕ high strength bolts or threaded rods used to connect railposts shall be tightened according to Article 505.04(f)(2) of the Standard Specifications.
Temporary Bridge Rail shall be according to Section 514 of the Standard Specifications, except as noted, and will be paid for at contract unit price per foot for Temporary Bridge Rail.
The contact surfaces between post flange, rail and inside face bracket for Alternate I shall be free of all lubricants.
The nut for 5/8" ϕ high strength studs used in Alternate I to connect bracket to post shall be tightened to a snug fit and given an additional half turn.




TEMPORARY BRIDGE RAIL POST SPACING




SECTION B-B

* Drilled holes for existing deck.




P.P.C. DECK BEAMS

* Drill 4-1 1/4" ϕ holes for 1" ϕ threaded rods with hex nut & flat washer. Epoxy grout rods.




ANCHORAGE DETAILS


NEW & EXISTING DECKS



RAIL SPLICE CONNECTION
AT EXPANSION JT.



SECTION AT RAIL SPLICE



PLAN-BOTT. SPLICE PL
TYPICAL

BILL OF MATERIAL

Item	Unit	Quantity
Temporary Bridge Rail	Foot	220

TEMPORARY BRIDGE RAIL
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-1BR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265


DATE: 10/1/88
FILE: 10/1/88
SCALE: 1/8" = 1'-0"
USER: JWB

(10'-9" Maximum Post Spacing)

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


ROUTE NO.	SECTION	COUNTY	SHEET NO.	SHEET
FAP 600	1-1BR-1	ST. CLAIR	29	19
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT-		

Contract #76962




Notes:

- After beams have been erected, holes shall be drilled into substructure and anchor dowels placed. Dowel holes shall be filled with non-shrink grout to top of beam and allowed to cure min. 24 hrs. prior to grouting the shear keys.
- Dowel rods drilled in cap are included in the cost of Precast Prestressed Concrete Deck Beams (17" depth).
- See sheet 7 of 13 for bearing pad details.
- Reinforcement bars designated (E) shall be epoxy coated.
- Concrete wearing surface to be poured after grouting the shear keys.
- 1" Jt. shall be filled with non-shrink grout. 1" dimension may vary to accommodate tolerance in beam lengths.
- Hatched area to be poured after Concrete Wearing Surface is in place. Pour to match overlay cross-slope. See sheet 9 of 13 for details and reinforcing.
- Bars indicated thus 27x4 - #4 etc. indicates 27 lines of bars with 4 lengths per line.
- Temporary Bridge Rail inserts shall be cast into PPC Deck Beams. See sheet 4 of 13 for location of rail anchors.
- Min. lap length #4 - 1'-8"



SECTION THRU ABUTMENT

(Dimensions at right L's to beam ends)




SECTION THRU PIER


(Dimensions at right L's to beam ends)

CROSS SECTION

(Looking South)



REINFORCED CONCRETE WEARING SURFACE PROFILE




BAR c(E)

BAR a1(E)

BAR c1(E)

BAR a1(E)



CONCRETE OVERLAY PARTIAL PLAN

(PPC Deck Beams, Sidewalk, and Parapet not shown for clarity.)

SUPERSTRUCTURE BILL OF MATERIALS

Bar	No.	Size	Length	Shape
a(E)	109	#4	11'-9"	—
a1(E)	218	#4	26'-4"	—
b(E)	268	#4	28'-3"	—
b1(E)	32	#5	32'-3"	—
b2(E)	16	#5	42'-0"	—
c(E)	218	#6	2'-4"	—
c1(E)	218	#6	2'-4"	—
c2(E)	218	#5	5'-8"	—
d(E)	218	#4	3'-9"	L
d1(E)	218	#6	3'-1"	L
d2(E)	52	#4	2'-0"	—
e(E)	48	#4	16'-0"	—
e1(E)	36	#4	13'-9"	—
Concrete Superstructure			Cu. Yd.	53.7
Concrete Wearing Surface			Sq. Yd.	767
Reinforcement Bars, Epoxy Coated			Pound	16,810

SUPERSTRUCTURE DETAILS

IL ROUTE 159 OVER RICHLAND CREEK

F.A.P. ROUTE 600 - SECTION 1-1BR-

ST. CLAIR COUNTY

STA. 158+08


STRUCTURE NO. 082-0265

PLOT DATE = \$DATE\$
FILE NAME = \$FILEL\$
PLOT SCALE = \$SCALE\$
USER NAME = \$USER\$


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	DATE	SHEET
FAP 600	1-IBR-1	ST. CLAIR	29	20
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT-	





Contract # 76962



SIDEWALK AND PARAPET PLAN



SECTION THRU SIDEWALK & PARAPET



PARAPET JOINT DETAIL

- Notes:
- ① Reinforcement bars designated (E) shall be epoxy.
 - ② See sheet 5 of 13 for Bill of Materials.
 - ③ Contractor shall verify existing rail post spacing to placement of rail anchorage.




SIDEWALK & PARAPET DETAILS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-IBR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265

PLOT DATE = *DATE*
FILE NAME = *FILEL*
PLOT SCALE = *SCALE*
USER NAME = *USER*

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
FAP 600	1-IBR-1	ST. CLAIR	29	21
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT-		

Contract # 76962








1/2" ϕ Strands, Each Strand Stressed to 30,900 Lbs.
Spans 1 and 2 - 9-Strands 1 3/4" up, 2-Strands 3 1/4" up
Span 3 - 12-Strands 1 3/4" up, 8-Strands 3 1/4" up, 2-Strands 12" up

*** Transverse Strand Placement Guidelines**

1. Place strands symmetrically about centerline of beam.
2. The minimum distance from center to center of strands in all directions shall be 2".
3. The minimum clearance from strand to dowel hole shall be 1/2".
4. The minimum clearance from strand to void shall be 1/2".

Vertical placement of strands shall not be adjusted to satisfy the above guidelines.



NOTES

Prestressing steel shall be uncoated high strength, low relaxation 7-wire strand, Grade 270. The nominal diameter shall be 1/2" and the nominal cross-sectional area shall be 0.153 sq. in. Lifting loops shall be 2 - 1/2" ϕ -270 ksi strands, as shown. The 1" ϕ rods in the transverse tie assembly shall be tightened to a snug fit and the threads set. Pockets that receive transverse tie bar on outside shall be filled with grout after transverse tie assembly is in place. The bearing seat surfaces shall be adjusted by shimming to assure firm and even bearing. Two 1/8" fabric adjusting shims of the dimensions of the Exterior Bearing Pad shall be provided for each bearing. Keyway surfaces shall be cleaned to remove form oil or other bond breaking material prior to shipment of the beams. Cleaning shall be done by sandblasting the keyway areas between top of the beam and the bottom edge of the key. Corrosion Inhibitor, as covered in the Special Provisions, shall be used in the concrete for precast prestressed concrete deck beams. Required Release Strength, f'cl, shall be 4,000 p.s.i. for Spans 1 & 2 and 5,000 p.s.i. for Span 3.

BILL OF MATERIAL


Item	Unit	Quantity
Precast Prestressed Concrete Deck Beams (17" Depth)	Sq. Ft.	6,85

SUPERSTRUCTURE DETAILS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-IBR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	SHEET
FAP 600	1-IBR-1	ST. CLAIR	29	22	13 SHEETS
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT-			


Contract # 76962




SECTION THRU TOP RAIL



SECTION THRU SPLICE
For Top Rail




RAIL POST CLAMP BAR
For Top Rail




RAIL SPLICE


Notes:
All Posts shall be normal to parapet.
All Aluminum Alloy Extruded Rail shall be supplied in modular lengths of 30 feet, except at the end of bridge or over open joints in bridge where the rail shall be attached to a minimum of 2 posts. If the rail horizontal curve of 2300 foot radius or less, the modular lengths may be reduced but shall be attached to a minimum of 2 posts.
All joints in rail shall be spliced per detail.
Provide 1-1/8" and 2-1/16" Aluminum Shims for 25% of the Posts.
Rail elements shall be parallel to Grade-high spots will be ground and low spots shimmed.
Aluminum alloy rail shall conform to ASTM B 221 alloy 6061-T6 or 6351-T5 with min. yield 35 ksi, min. tensile 38 ksi, and elongation of 10% in 2 inches.
Existing Bridge Handrail shall be removed and re-erected on top of the proposed parapet, and will be paid for at the contract unit price per foot for REMOVING AND RE-ERECTING EXISTING RAILING.



RAIL TERMINAL SECTION




VIEW B-B




SECTION A-A

RAIL POST DETAILS



SEC. THRU ELLIPTICAL RAIL SECTION



SEC. THRU SPLICE

* In lieu of the cast-in-place anchor device shown, the Contractor has the option of drilling and epoxy grouting stainless steel anchor rods of the same diameter and grade as the specified cap screws. Embedment shall be according to the manufacturer's specifications.

Contractor to provide anchorage of existing bridge rail in accordance with this sheet. All other details are shown for information only.

BILL OF MATERIAL

Item	Unit	Quantity
Removing and Re-Erecting Existing Railing	Foot	248


TYPE L ALUMINUM RAILING
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-IBR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265

PLOT DATE = #DATE\$
FILE NAME = #FILEL\$
PLOT SCALE = #SCALE\$
USER NAME = #USER\$

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET
FAP 600	1-1BR-1	ST. CLAIR	29	23
FED. ROAD DIST. NO. 7	ALLIANCE	FED. AID PROJECT		

Contract # 76962



SECTION C-C

(Dimensions at right L's to beam ends)




ABUTMENT ELEVATION

(North abutment shown looking north, South Abutment opposite hand)

BILL OF MATERIAL


(Two Abutments)

Bar	No.	Size	Length	Shape	
e2(E)	24	#4	8'-7"	—	
h(E)	8	#6	15'-9"	—	
h(E)	16	#6	23'-3"	—	
Reinforcement Bars, Epoxy Coated				Pound	890
Concrete Superstructure				Cu. Yd.	8.6
Concrete Removal				Cu. Yd.	7.3




WINGWALL ELEVATION

Showing Dimensions




WINGWALL ELEVATION

Showing Reinforcement



SECTION B-B



VIEW A-A

Notes:



- Existing reinforcement bars shown are to be cleaned and incorporated into new construction.
- Any reinforcement bars that are damaged during construction removal operations shall be repaired or replaced using approved bar splicer or anchorage system. Cost includes Concrete Removal.
- E.F. denotes each face.

ABUTMENT & WINGWALL DETAILS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-1BR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	SHEET
FAP 600	1-IBR-1	ST. CLAIR	29	24	13 SHEETS
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT			

Contract # 76962



BILL OF MATERIAL

Structural Repair of Concrete ($\leq 5"$)	Sq. Ft.	52

Note:
Hatched area indicates approximate area of Structural Repair of Concrete. Exact repair area to be determined by Engineer.


**NORTH & SOUTH ABUTMENT
FORMED CONCRETE REPAIRS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-IBR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265**

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
FAP 600	1-1BR-1	ST. CLAIR	29	25
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT-	

SHEET
13 SHEETS

Contract # 76962



NORTH SIDE PIER 1
(Looking South)



SOUTH SIDE PIER 1
(Looking North)

BILL OF MATERIAL

Structural Repair of Concrete (≤ 5")	Sq. Ft.	99
--------------------------------------	---------	----

Note:
Hatched area indicates approximate area of Structural Repair of Concrete. Exact repair area to be determined by Engineer.

PIER 1 FORMED CONCRETE REPAIRS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-1BR-1
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265


PLOT DATE = #DATE#
FILE NAME = #FILE#
PLOT SCALE = #SCALE#
USER NAME = #USER#

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
FAP 600	1-1BR-1	ST. CLAIR	29	26
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT-	

SHEET 13

Contract # 76962



NORTH SIDE PIER 2
(Looking South)



SOUTH SIDE PIER 2
(Looking North)

BILL OF MATERIAL

Structural Repair of Concrete (≤ 5")	Sq. Ft.	125
--------------------------------------	---------	-----

Note:
Hatched area indicates approximate area of Structural Repair of Concrete. Exact repair area to be determined by Engineer.

PIER 2 FORMED CONCRETE REPAIRS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-1BR-
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265

PLOT DATE = #DATE#
FILE NAME = #FILE#
PLOT SCALE = #SCALE#
USER NAME = #USER#

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
FAP 600	1-1BR-1	ST. CLAIR	29	27
FED. ROAD DIST. NO. 7	ILLINOIS	FED. AID PROJECT-		

SHEET 13 SHEETS

Contract # 76962

NOTES

Bar splicer assemblies shall be of an approved type and shall develop in tension at least 125 percent of the yield strength of the lapped reinforcement bars.

Splicer rods shall be of minimum 60 ksi yield strength, threaded or coiled full length. All reinforcement bars shall be lapped and tied to the splicer rods or dowel bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars.

Other systems of similar design may be submitted to the Engineer for approval. Approval shall be based on certified test results from an approved testing laboratory that the proposed bar splicer assembly satisfies the following requirements:

- ① Minimum Capacity = $1.25 \times f_y \times A_t$
(Tension in kips)
- ② Minimum *Pull-out Strength = $1.25 \times f_{s_{allow}} \times A_t$
(Tension in kips)

Where f_y = Yield strength of lapped reinforcement bars in ksi.
 $f_{s_{allow}}$ = Allowable tensile stress in lapped reinforcement bars in ksi (Service Load)

A_t = Tensile stress area of lapped reinforcement bars.

* = 28 day concrete

Bar Size to be Spliced	Splicer Rod or Dowel Bar Length	Strength Requirements	
		Min. Capacity kips - tension	Min. Pull-Out Strength kips - tension
#4	1'-8"	14.7	5.9
#5	2'-0"	23.0	9.2
#6	2'-7"	33.1	13.3
#7	3'-5"	45.1	18.0
#8	4'-6"	58.9	23.6
#9	5'-9"	75.0	30.0
#10	7'-3"	95.0	38.0
#11	9'-0"	117.4	46.8

Bar splicer assemblies shall be according to Section 508 of the Standard Specifications, except as noted. The furnishing and installation of bar splicer assemblies will be measured and paid for at the contract unit price each for "BAR SPLICERS."

The diameter of this part is the same as the diameter of the bar spliced.


The diameter of this part is equal or larger than the diameter of bar spliced.

ROLLED THREAD DOWEL BAR



**** ONE PIECE**


Wire Connector



WELDED SECTIONS

BAR SPLICER ASSEMBLY ALTERNATIVES

** Heavy Hex Nuts conforming to ASTM A 563, Grade C, D or DH may be used.




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.


"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.




FOR INTEGRAL OR SEMI-INTEGRAL ABUTMENTS

Bar Splicer for #5 bar
Min. Capacity = 23.0 kips - tension
Min. Pull-out Strength = 9.2 kips - tension
No. Required =



FOR PILE BENT ABUTMENTS

Bar Splicer for #5 bar
Min. Capacity = 23.0 kips - tension
Min. Pull-out Strength = 9.2 kips - tension
No. Required =



STANDARD

Bar Size	No. Assemblies Required	Location
#4	218	Conc. Wearing Surface
#6	8	N. Abut.
#6	8	S. Abut.

BAR SPLICER ASSEMBLY DETAILS
IL ROUTE 159 OVER RICHLAND CREEK
F.A.P. ROUTE 600 - SECTION 1-1BR-
ST. CLAIR COUNTY
STA. 158+08
STRUCTURE NO. 082-0265

PLOT DATE = #DATE#
FILE NAME = #FILE#
PLOT SCALE = #SCALE#
USER NAME = #USER#

BSD-1

10-22-04



F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	28
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

B.M.: Bronze plug on E. Ill. Rte. 159 at Sta. 148+24.6
Elev. 500.21
Existing structure: No 082-0069, Sta. 158+11.15, built as N. Illinois street over Richland creek in 1923. The existing 61'-10" simple span with builtup I-beams substructure on stone closed abutments shall be removed utilizing Stage Construction as shown in the Plans.

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

DATE	NO.	BY	CHKD.	APP'D.	SHEET NO. /
11-1-82	1-1BR	ST. CLAIR	17	5	10 SHEETS

No salvage.




CROSS SECTION
Showing Traffic Lanes during Stage Const.
(Looking South)
Dimensions are at RL Ls to E of Rdwy.

GENERAL NOTES

See Proposal for Boring Data.
It shall be the responsibility of the Contractor to verify all dimensions and conditions existing in the field prior to construction & ordering of materials. The top surface of the beams shall be finished in accordance with Art. 505.06 of the Std. Specifications except that the surface shall not be roughened by brooming. The finished surface shall be free of depressions or high spots with sharp corners.
The concrete rail section above the mandatory const. joint at the top of the sidewalk shall be constructed of Class X Concrete, except the aggregates shall conform to the requirements of Handrail Concrete.
Protective coat shall not be applied to surfaces to which Waterproofing Membrane System is applied.
Layout of riprap slope walls may be varied in the field to suit ground conditions as directed by the Engineer.
All reinforcement bars shall conform to the requirements of AASHTO M31 or M53, Grade 60.
The Contractor shall drive one (1) Steel test pile, HPB x 36 of Pier 1 in a permanent location as directed by the Engineer before ordering the remainder of piles.
The contractor will be held responsible for any damages incurred to the 36" combined sewer through his negligence. Damages incurred during normal construction procedures will be paid for in accordance with Section 109 of the Standard Specifications.
① Steel test pile, HPB x 36 of Pier 1 in a permanent location as directed by the Engineer before ordering the remainder of piles.
② Sidewalk Removal is incidental to the cost of the Removal of Existing Structures.
③ See Special Provisions.

TOTAL BILL OF MATERIAL

Item	Quantity	Unit	Total
Waterproofing Membrane System	623	Sq. Yd.	623
PC Mortar Fdring Course	2,049	Lin. Ft.	2,049
Protective Coat	212	Sq. Yd.	212
Class X Concrete	624	Cu. Yd.	3,581
RPC Deck Beams (17")	6,570	Sq. Ft.	23,450
Reinforcement Bars	624	Lbs.	5,851
Structure Excavation	1,950	Sq. Ft.	1,950
Temporary Sheet Piling	63	Tons	63
Bituminous Concrete Surface Course Class I	1	Each	1
Name Plates	1,524	Each	1,524
Stone Rip Rap	248	Lin. Ft.	248
Aluminum Walling Type L	220	Lin. Ft.	220
Removal of Existing Structures	1,660	Cu. Yd.	1,660
Channel Excavation	1,424	Lin. Ft.	1,424
Steel Piles HPB x 36	17	Each	17
Test Piles Steel HPB x 36	43	Each	43
Setting Piles in Rock	166	Sq. Yds.	166
Pavement Replacement	43	Sq. Yds.	43
Pavement Removal	166	Sq. Yds.	166



DESIGNED	DATE
CHECKED	DATE
APPROVED	DATE


STATION 158+08.00
BUILT 197 BY
STATE OF ILLINOIS
F.A. RTE. 600, SEC. 110
F.A. PROJECT # 600(1)
LOADING HS 20
STR. No. 0

NAME PLATE
See Std. E113
① Str. No. to be supplied by the District

WATERWAY INFORMATION
Drainage area 16.33 M.
Existing opening 680 Sq. Ft.
Required opening 270 Sq. Ft.
Proposed opening 1270 Sq. Ft. (below 50 yr. HW2)
High Water El. (50 yr.) = 497.20 = (100 yr.) = 495.70
Q (50) = 3300 CFS = (100 yr.) = 2180 CFS
Created Head = 0.7' - Created Head = 0.99'
All Time H.W. El. = 497.30

FIELD UNITS
F_i = 3500 psi
F_y = 60,000 psi (Reinf.)
F_s = 20,000 psi (Struct.)
LOADING HS 20-44

PRESTRESSED UNITS
F_{ci} = 5000 psi (Spans 112)
F_{ps} = 4000 psi (Spans 142)
F_{ps} = 270,000 psi (RH Strands)
F_{si} = 189,000 psi (RH Strands)
F_{ci} = 6000 psi (Span 3-36 Bms.)
F_{ps} = 5000 psi (Span 3-48 Bms.)
F_{ps} = 4600 psi (Span 3-36 Bms.)
F_{ps} = 4100 psi (Span 3-48 Bms.)
Design Specification: 1977 AASHTO #78 Interims
225 Allow 25% / 54% for future W.S.



GENERAL PLAN & ELEVATION
F.A. RTE. 600 OVER RICHLAND CREEK
F.A. RTE. 600 SECTION 1-1B
ST. CLAIR COUNTY
STA. 158+08.00 @ CHANNEL

FOR INFORMATION ONLY

REVISIONS	NAME	DATE


ILLINOIS DEPARTMENT OF TRANSPORTATION
EXISTING STRUCTURE PLANS

FAP ROUTE 600
SECTION 1-1BR-1
ST. CLAIR COUNTY

SCALE: VERT. DRAWN BY
HORIZ. CHECKED BY
DATE

PLOT DATE = 8/17/2006
PLOT SCALE = 50,000 / 1 IN.
REFERENCE = #REF*

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
600	1-1BR-1	ST. CLAIR	29	29
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		



FOR INFORMATION ONLY

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION EXISTING STRUCTURE PLANS
NAME	DATE	
		FAP ROUTE 600 SECTION 1-1BR-1 ST. CLAIR COUNTY SCALE: VERT. DRAWN BY HORIZ. CHECKED BY DATE

PLOT DATE = 8/17/2005
 FILE NAME = c:\p\projects\ed\0305\plan\p\10305a.dgn
 PLOT SCALE = 50.0000 / IN.
 REFERENCE = BREF#