

INDEX OF SHEETS

SHEET NO	DESCRIPTION
1	COVER SHEET
2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES
3-6	SUMMARY OF QUANTITIES
7	ALIGNMENT, TIES & BENCHMARKS
8	MAINTENANCE OF TRAFFIC PLAN - STAGE I
9	MAINTENANCE OF TRAFFIC PLAN - STAGE II
10	PAVEMENT MARKING PLAN
11	NAVIGATION AND ROADWAY LIGHTING REMOVAL PLAN
12	TEMPORARY LIGHTING SYSTEM
13	NAVIGATION AND ROADWAY LIGHTING CONDUIT PLAN
14	NAVIGATION LIGHTING ONE LINE DIAGRAM
15	ROADWAY LIGHTING ONE LINE DIAGRAM
16-17	NAVIGATION AND ROADWAY LIGHTING DETAILS
18	SERVICE INSTALLATION, TYPE C (SPECIAL) DETAIL
19	TEMPORARY WOOD POLE DETAILS
20	LIGHT POLE FOUNDATION, 40' TO 47 1/2' M.H., 15" BOLT CIRCLE (BE-301)
21	ALUMINUM LIGHT POLE, 40' MOUNTING HEIGHT (BE-401)
22	MISC. ELECTRICAL DETAILS SHEET A (BE-702)
23	TEMPOARY AERIAL CABLE INSTALLATION (BE-801)
24-50	STRUCTURAL SHEETS
51	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS (TC-10)
52	RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT) (TC-11)
53	DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)
54	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) (TC-14)
55	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC-16)
56	ARTERIAL ROAD INFORMATION SIGN (TC-22)
57	DRIVEWAY ENTRANCE SIGNING (TC-26)

STATE STANDARDS

000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
606306-03	CORRUGATED PC CONCRETE MEDIANS
635011-02	REFLECTOR MARKER AND MOUNTING DETAILS
701427	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPER. FOR SPEEDS LESS THAN OR EQUAL TO 40MPH
701606-07	URBAN LANE CLOSURE, MULTILANE 2W WITH MOUNTABLE MEDIAN
701801-04	LANE CLOSURE MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
701901-01	TRAFFIC CONTROL DEVICES
704001-06	TEMPORARY CONCRETE BARRIER
720001-01	SIGN PANEL MOUNTING DETAILS
720011-01	METAL POSTS FOR SIGNS, MARKERS & DELINEATORS
728001-01	TELESCOPING STEEL SIGN SUPPORT
729001-01	APPLICATION OF TYPES A & B METAL POSTS (FOR SIGNS & MARKERS)

COMMITMENTS

- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PROTECT ALL EXISTING TREES WITHIN THE CONSTRUCTION LIMITS UNLESS OTHERWISE NOTED ON THE PLANS.
- THE CONTRACTOR SHALL CONTACT THE US COAST GUARD FOUR WEEKS PRIOR TO STARTING ANY WORK THAT MAY INTERFERE WITH NAVIGATION OPERATIONS IN THE CHANNEL. SEE SPECIAL PROVISIONS FOR DETAILS.
THE CONTACT PERSON IS AS FOLLOWS:

DISTRICT COMMANDER
SCOTT STRIFFLER, BRIDGE PROGRAM MANAGER
UNITED STATES COAST GUARD
NINTH U.S. COAST GUARD DISTRICT
1240 EAST NINTH STREET
CLEVELAND, OH 44199
PHONE: (216) 902-6085

GENERAL NOTES

- WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AS WELL AS ADJOINING RESIDENTIAL AREAS.
- THE CONTRACTOR SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
- THE CONTRACTOR SHALL CONTACT PATRICE HARRIS, THE AREA TRAFFIC FIELD TECHNICIAN, AT (708) 597-9800 TWO (2) WEEKS PRIOR TO THE PLACEMENT OF PERMANENT PAVEMENT MARKINGS.
- ALL DAMAGE TO EXISTING PAVEMENT MARKINGS OUTSIDE THE PROPOSED PAVEMENT MARKING LIMITS SHOWN ON THE PLANS SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE.
- BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING, EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS CHART

OPERATIONS	MIXTURE TYPE	AIR VOIDS @ Ndes
TEMPORARY PAVEMENT	TEMPORARY PAVEMENT, 10" HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50 (IL 9.5 MM), 2" TEMPORARY PAVEMENT (HMA BINDER IL-19 MM), 8"	4% @ 50 GYR 4% @ 50 GYR

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 76-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.

NOTE FOR TEMPORARY PAVEMENT:
PCC TEMPORARY PAVEMENT SHALL CONSIST OF CLASS PV CONCRETE MEETING THE REQUIREMENTS OF ART. 1020 OF THE STANDARD SPECIFICATIONS; TYPICALLY 10" THICK.

\\S:\P202\Public\PROJ\93799.00\Design\Map_Sheets\03799.00 02 Index.dgn