

ITEM 20100110 TREE REMOVAL (6 TO 15 UNITS DIAMETER)				
LOCATION	STATION	OFFSET	UNIT	
US 52/IL 26	389+75.24	75.12 LT	12	
US 52/IL 26	389+93.38	90.74 RT	14	
US 52/IL 26	393+88.45	25.23 LT	6	
US 52/IL 26	394+05.49	22.94 LT	6	
TOTAL			38	

ITEM 20100210 TREE REMOVAL (OVER 15 UNITS DIAMETER)				
LOCATION	STATION	OFFSET	UNIT	
US 52/IL 26	389+41.68	89.48 LT	24	
TOTAL			24	

EARTHWORK SCHEDULE							
LOCATION STATION VOLUME (CU YD)	OFFSET	20200100 EARTH EXCAVATION (CU YD)	EXCAVATION TO BE USED IN EMBANKMENT ADJUSTED FOR SHRINKAGE	EMBANKMENT	EARTHWORK BALANCE WASTE (+) OR SHORTAGE (-) (CU YD)	21101615 TOPSOIL FURNISH AND PLACE, 4" (SQ YD)	
US 52/IL 26							
385+00.00 TO 395+00.00	LT/RT	144	107	191	-84	2395	
387+00.00	LT	19	-	19	-19	59	
387+00.00	RT	11	-	11	-11	35	
387+72.00	LT	3	-	3	-3	8	
388+40.00	LT	24	-	24	-24	76	
388+40.00	RT	24	-	24	-24	75	
TOTAL		225	107	272	-165	2648	

\* PAID FOR AS 20400800 FURNISHED EXCAVATION (CU YD)

ITEM 20800150 TRENCH BACKFILL			
LOCATION STATION TO STATION	STRUCTURE	VOLUME (CU YD)	
US 52/IL 26			
394+65.88 TO 394+43.48	9 TO 13	3	
394+68.81 TO 394+65.88	12 TO 9	1	
TOTAL		4	

STATION	PAVEMENT SQ. YD.	SHOULDER		40600625 LEVELING BINDER (MACHINE METHOD), N50 TON	40603310 HOT-MIX ASPHALT SURF CSE MIX "C", N50 TON	40800050 INCIDENTAL HOT-MIX ASPHALT SURFACING TON	44000157 HOT-MIX ASPHALT SURFACE REMOVAL, 2" SQ YD	48203021 HOT-MIX ASPHALT SHOULDERS, 6" SQ YD
		WIDTH	LT RT					
385+01.84 TO 389+50.00		10	487		55		487	174
385+03.07 TO 389+50.00		10	514		58		514	169
393+93.90 TO 395+00.00	471			62	53			
ACCESS ROAD	265					33		
SHOULDER REPAIR					3			
TOTAL				62	169	33	1001	343

LANDSCAPING												
LOCATION STATION TO STATION	OFFSET	25000210 SEEDING, CLASS 2A (ACRE)	25000310 SEEDING, CLASS 4 (ACRE)	25000750 MOWING (ACRE)	25100115 MULCH, METHOD 2 (ACRE)	25100630 EROSION CONTROL BLANKET (SQ YD)	25100635 HEAVY DUTY EROSION CONTROL BLANKET (SQ YD)	28000250 TEMPORARY EROSION CONTROL SEEDING (POUND)	28000400 PERIMETER EROSION BARRIER (FOOT)	28100105 STONE RIPRAP, CLASS A3 (SQ YD)	28100107 STONE RIPRAP, CLASS A4 (SQ YD)	28200200 FILTER FABRIC (SQ YD)
US 52/IL 26												
385+02 TO 391+10	LT/RT		0.65		0.65		2733	113	1297	398	22	22
392+30 TO 395+00	LT/RT	0.25	0.10	0.25	0.35	139	306	19	625		5	5
TOTAL		0.25	0.75	0.25	1.0	139	3039	132	1922	398	27	27

\* QUANTITY OF MULCH METHOD 2 PROVIDED FOR TEMPORARY USE AS DIRECTED BY THE ENGINEER

ITEM 31100910 SUBBASE GRANULAR MATERIAL, TYPE A 12"	
LOCATION STATION TO STATION	AREA (SQ YD)
US 52/IL 26	
389+50.00 TO 389+70.42	115
393+39.70 TO 393+93.90	277
TOTAL	392

ITEM 31101400 SUBBASE GRANULAR MATERIAL, TYPE B 6"	
LOCATION STATION TO STATION	AREA (SQ YD)
US 52/IL 26	
393+93.90 TO 395+00.00	70
TOTAL	70

ITEM 35102000 AGGREGATE BASE COURSE, TYPE B 8"	
LOCATION STATION TO STATION	AREA (SQ YD)
US 52/IL 26 ACCESS RD UNDER BRIDGE	
391+54.92	265
TOTAL	265

ITEM 42001430 BRIDGE APPROACH PAVEMENT CONNECTOR (FLEXIBLE)	
LOCATION STATION TO STATION	AREA (SQ YD)
US 52/IL 26	
389+50.00 TO 389+70.42	100
393+39.70 TO 393+93.90	265
TOTAL	365

ITEM 44000100 PAVEMENT REMOVAL	
LOCATION STATION TO STATION	AREA (SQ YD)
US 52/IL 26	
389+50.00 TO 389+70.42	100
393+39.70 TO 393+93.90	240
391+54.92 ACCESS ROAD UNDER BRIDGE	265
TOTAL	605

ITEM 44000300 CURB REMOVAL		
LOCATION STATION TO STATION	OFFSET	LENGTH (FOOT)
US 52/IL 26		
385+21.06 TO 389+98.74	LT	478
385+21.52 TO 389+98.86	RT	478
392+91.37 TO 393+08.40	LT	18
392+91.37 TO 393+07.46	RT	17
TOTAL		991

ITEM 44000500 COMBINATION CURB AND GUTTER REMOVAL		
LOCATION STATION TO STATION	OFFSET	LENGTH (FOOT)
US 52/IL 26		
393+08.40 TO 395+00.00	LT	192
393+07.46 TO 395+00.00	RT	193
TOTAL		385

ITEM 60600605 CONCRETE CURB, TYPE B		
LOCATION STATION TO STATION	OFFSET	LENGTH (FOOT)
US 52/IL 26		
385+67.27 TO 389+85.42	LT	419
385+67.27 TO 389+85.42	RT	419
393+24.70 TO 393+39.73	LT	15
392+24.70 TO 393+39.73	RT	15
TOTAL		868

ITEM 60605000 CONCRETE CURB AND GUTTER, TYPE B-6.24		
LOCATION STATION TO STATION	OFFSET	LENGTH (FOOT)
US 52/IL 26		
393+39.73 TO 395+00.00	LT	160
393+39.73 TO 395+00.00	RT	160
TOTAL		320

ITEM 63000003 STEEL PLATE DEAM GUARDRAIL, TYPE A, 9 FOOT POSTS		
LOCATION STATION TO STATION	OFFSET	LENGTH (FOOT)
US 52/IL 26		
385+67.27 TO 389+42.27	LT	375
385+67.27 TO 389+42.27	RT	375
393+67.85 TO 394+42.85	LT	75
393+67.85 TO 394+42.85	RT	75
TOTAL		900