



SOIL BORING LOG

Date 1/18/95

ROUTE FAI-74 DESCRIPTION EB I-74 over UPRR LOGGED BY J. Dudlicek

SECTION (72-6VB) LOCATION Kickapoo Twnsp SE 1/4, SW 1/4, SEC. 24, TWP. 9N, RNG. 7E, 4th PM, Latitude, Longitude

COUNTY Peoria DRILLING METHOD HSA/RW HAMMER TYPE AUTO

STRUCT. NO. 072-0001(EXIST) Station 348+38.61 BORING NO. SB3 (E. Pier) Station 348+79 Offset 18.4 ft RT Ground Surface Elev. 586.75 ft

Table with columns for Depth (ft), Blow Count (blows/ft), and Soil Description. Includes entries for PCC SLOPEWALL, BR GRAVELLY SAND, BR SANDY LOAM, and GR LOAM.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



SOIL BORING LOG

Date 1/18/95

ROUTE FAI-74 DESCRIPTION EB I-74 over UPRR LOGGED BY J. Dudlicek

SECTION (72-6VB) LOCATION Kickapoo Twnsp SE 1/4, SW 1/4, SEC. 24, TWP. 9N, RNG. 7E, 4th PM, Latitude, Longitude

COUNTY Peoria DRILLING METHOD HSA/RW HAMMER TYPE AUTO

STRUCT. NO. 072-0001(EXIST) Station 348+38.61 BORING NO. SB3 (E. Pier) Station 348+79 Offset 18.4 ft RT Ground Surface Elev. 586.75 ft

Table with columns for Depth (ft), Blow Count (blows/ft), and Soil Description. Includes entries for BR GR CLAY LOAM and BR & BR BR GRAVELLY SAND.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



SOIL BORING LOG

Date 1/18/95

ROUTE FAI-74 DESCRIPTION EB I-74 over UPRR LOGGED BY K. Olson

SECTION (72-6VB) LOCATION Kickapoo Twnsp SE 1/4, SW 1/4, SEC. 24, TWP. 9N, RNG. 7E, 4th PM, Latitude, Longitude


COUNTY Peoria DRILLING METHOD HSA HAMMER TYPE AUTO

STRUCT. NO. 072-0001(EXIST) Station 348+38.61 BORING NO. SB4 (E. Abut) Station 349+42 Offset 34.4 ft RT Ground Surface Elev. 602.62 ft

Table with columns for Depth (ft), Blow Count (blows/ft), and Soil Description. Includes entries for SHOULDER MATERIALS, BR & GR BR LOAM, GR LOAM, BR GRAVELLY SAND, and SAND, A-3 SEAM.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-99)



FILE NAME: 30 Borings II.dgn PLOT SCALE: 1:1 PLOT DATE: July 1, 2011

DESIGNED: B. Vegrzyn CHECKED: Coombe-Bloxdorf DRAWN: B. Vegrzyn CHECKED: Coombe-Bloxdorf

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

BORINGS II STRUCTURE NO. 072-0001 & 072-0002 SHEET NO. 30 OF 34 SHEETS

Table with columns: F.A.I. RTE., SECTION, COUNTY, TOTAL SHEETS, SHEET NO., CONTRACT NO. 68874