



TEMPORARY PAVEMENT MARKING LAYOUT

STA	OFFSET	STA	OFFSET
565+68.59	56.00	571+16.87	13.93
565+75	55.99	571+25	13.95
566+00	55.73	571+50	14.23
566+25	55.13	571+75	14.85
566+50	54.19	572+00	15.81
566+75	52.91	572+25	17.12
567+00	51.29	572+50	18.77
567+25	49.32	572+75	20.76
567+50	47.01	573+00	23.09
567+75	44.35	573+25	25.77
568+00	41.35	573+50	28.80
568+25	38.00	573+75	32.18
568+50	34.29	574+00	35.90
568+75	30.24	574+25	39.99
568+99.43	25.93	574+47.72	44.00

LEGEND

- ↑ ARROW BOARD
- ↑ SIGN
- ↑ DIRECTION INDICATOR BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT
- ↑ TYPE II BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT
- DRUM WITH STEADY BURN MONODIRECTIONAL LIGHT
- ↑ VERTICAL PANEL (BACK TO BACK)
- ↑ TYPE III BARRICADE WITH FLASHING LIGHTS
- TEMPORARY CONCRETE BARRIER
- ◁ MONODIRECTIONAL BARRIER MARKER
- ▨ PAVED SHOULDER REMOVAL  
HMA PAVEMENT (FULL DEPTH)
- ▧ APPROACH SLAB REMOVAL
- ▩ PAVEMENT REMOVAL

