



- CONCRETE GUTTER, TYPE B
- (A) STA. 114+60.20, O/S. 34.23' RT "64W55S"
 - (B) STA. 111+43.59, O/S. 58.93' RT "64W"
 - (C) STA. 115+85.81, O/S. 33.98' LT "64W55S"
 - (D) STA. 115+14.34, O/S. 34.31' LT "64W55S"
 - (E) STA. 115+02.54, O/S. 34.20' LT "64W55S"

- PR. EDGE OF SHOULDER LAYOUT POINTS
- (F) STA. 27+56.27, O/S. 11.88' LT "64E"
 - (G) STA. 28+36.99, O/S. 14.72' LT "64E"
 - (H) STA. 28+46.99, O/S. 15.72' LT "64E"
 - (I) STA. 28+93.16, O/S. 17.82' LT "64E"
 - (J) STA. 30+49.97, O/S. 14.41' LT "64E"
 - (K) STA. 31+61.98, O/S. 13.75' LT "64E"
 - (L) STA. 111+22.74, O/S. 14.12' LT "64W"
 - (M) STA. 112+34.74, O/S. 13.46' LT "64W"
 - (N) STA. 113+90.82, O/S. 34.46' LT "64W55S"
 - (O) STA. 114+35.82, O/S. 37.52' LT "64W55S"
 - (P) STA. 114+45.65, O/S. 37.68' LT "64W55S"
 - (Q) STA. 115+02.75, O/S. 39.09' LT "64W55S"
 - (R) STA. 115+67.64, O/S. 34.09' LT "64W55S"

- SPBGR TY A 6FT POSTS
- (1) STA. 117+63.60, O/S. 36.76' LT "64W55S"
 - (2) STA. 114+91.92, O/S. 39.47' LT "64W55S"
- TEMPORARY CONCRETE BARRIER
- (3) STA. 27+89.82, O/S. 14.71' LT "64E"
 - (4) STA. 27+54.83, O/S. 9.25' LT "64E"
 - (5) STA. 24+97.94, O/S. 22.22' LT "55S64E"
 - (6) STA. 110+13.86, O/S. 55.52' RT "64W"
 - (7) STA. 117+08.59, O/S. 41.18' RT "64W55S"
- CONC BAR SP 32
(O/S ARE TO CENTER OF BARRIER)
- (8) STA. 28+46.99, O/S. 16.85' LT "64E"
 - (9) STA. 28+93.19, O/S. 18.95' LT "64E"
 - (10) STA. 30+49.97, O/S. 15.53' LT "64E"
 - (11) STA. 31+61.98, O/S. 14.87' LT "64E"

NOTE:

- TIE PROPOSED CONC BAR SP 32 INTO EXISTING BARRIER
- POINTS ALSO USED IN PR. EDGE OF SHOULDER LAYOUT

