

MATCHLINE STA 59+00 (R 55N)

- TEMP PVT MK LINE 4 (SHEET 2 OF 5)
- (A) STA. 59+00.00, O/S 12.9' RT "55N", BEGIN SOLID YELLOW
 - (B) STA. 62+43.02, O/S 12.8' RT "55N", END SOLID YELLOW
 - (C) STA. 60+82.63, O/S 4.4' LT "55N", BEGIN SOLID WHITE
 - (D) STA. 62+43.02, O/S 12.8' RT "55N"
 - (E) STA. 63+79.30, O/S 12.0' RT "55N", END SOLID WHITE
 - (F) STA. 60+36.24, O/S 18.6' LT "55N", BEGIN SOLID YELLOW
 - (G) STA. 62+24.64, O/S 0.6' LT "55N"
 - (H) STA. 66+48.23, O/S 0.4' LT "55N", END SOLID YELLOW
 - (I) STA. 60+39.93, O/S 0.1' LT "55N64E", BEGIN SOLID WHITE
 - (J) STA. 62+27.18, O/S 4.3' LT "55N64E"
 - (K) STA. 64+52.46, O/S 5.9' LT "55N64E"
 - (L) STA. 65+39.17, O/S 7.4' LT "55N64E"
 - (M) STA. 68+16.37, O/S 8.6' LT "55N64E", END SOLID WHITE
 - (N) STA. 61+43.79, O/S 13.4' LT "55N64E", BEGIN SOLID WHITE
 - (O) STA. 62+27.00, O/S 15.3' LT "55N64E"
 - (P) STA. 64+52.23, O/S 16.9' LT "55N64E"
 - (Q) STA. 64+77.47, O/S 16.3' LT "55N64E", END SOLID WHITE

- LEGEND:**
- CONSTRUCTION WORK ZONE
 - OR TYPE II BARRICADE, DRUM OR VERTICAL BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT AT SPECIFIED SPACING
 - DIRECTION INDICATOR BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT AT SPECIFIED SPACING
 - SIGN LOCATION
 - TYPE III BARRICADES
 - DIRECTION OF TRAFFIC
 - ARROW BOARD

NOTES:

- SIGNS G20-1103(0)-3660 SHOULD BE COORDINATED WITH CONSTRUCTION OF CONTRACT 76C76. CONTRACTOR SHALL IMPLEMENT IF NO OTHER G20-1103(0)-3660 OR SIMILAR SIGNS ARE IN PLACE WITHIN ONE MILE FOLLOWING THE END OF THE CONTRACT 76C51 CONSTRUCTION WORK ZONE.
- THE TERM "DEVICES" USED THROUGHOUT THESE SHEETS REFERS TO TYPE II BARRICADE, DRUM, OR VERTICAL BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT

