

NEW SLAB

## NOTES

Detail I - With Bar Splicer or Couplers:
Connect one (1) I'' x 7' 'x ''W'' steel P to the
top layer of couplers with 2-<sup>5</sup>g'' \$\phi\$ bolts
screwed to coupler at approximate \$\mathbb{C}\$ of
each barrier panel.

Detail II - With Extended Reinforcement Bars:

Connect one (1) 1" x 7" x "W" steel 12 to the concrete slab or concrete wearing surface with 2-58" \$\phi\$ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate \$\mathbb{Q}\$ of each barrier panel.

Cost of anchorage is included with Temporary Concrete Barrier.

The 1" x 7" x "W" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready to be placed.


## SECTIONS THRU SLAB OR DECK BEAM


EXISTING SLAB

\*\*\* Dimension shown is minimum required embedment into concrete.


If hot-mix asphalt wearing surface is present, minimum embedment shall be in addition to wearing surface depth.

\*\*\*\* If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.





EXISTING DECK BEAM



STEEL RETAINER & 1" x 7" x "W"

\* Required only with Detail II

\*\* Wood blocks may be omitted when required to provide minimum stage traffic lane width. When the wood blocks are omitted, the concrete barrier shall be in direct contact with the steel retainer plate.

"W" = Top bars spacing + 4"

R-27

7-1-10

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

TEMPORARY	CONCRETE	BARR	IER F	OR S	TAGE	CONSTRUCTION		
STRUCTURE NO. 097-0076								
	SHEET	NO. 4	0F 26	SHEET	rs		_	

SHEETS N			ILLINOIS	FED. AID	PROJECT		
SHEETS N	_				CONTRAC	T NO.	78161
F.A.P. SECTION COUNTY SHEETS N		328	105B-1		WHITE	54	25
CECTION COUNTY TOTAL SH		F.A.P.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.