

GENERAL NOTES:

- 1 ALL ELEVATIONS SHOWN IN THE PLANS ARE U. S. G. S MEAN SEA LEVEL DATUM
- 2 ANY REFERENCE TO THE STANDARDS THROUGHOUT THE PLANS SHALL BE INTERPRETED TO BE THE LATEST STANDARDS OF THE DEPARTMENT AS INCLUDED IN THE PLANS.
- 3 THE LOCATION OF THOSE BURIED AND ABOVE GROUND UTILITIES SHOWN ARE APPROXIMATE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING UTILITY PROPERTY FROM CONSTRUCTION OPERATIONS AS OUTLINED IN ARTICLE 107.26 OF THE STANDARD SPECIFICATIONS. THE J. U. L. I. E. NUMBER IS (800) 892-0123. A MINIMUM OF 48 HOURS ADVANCE NOTICE IS REQUIRED. SEE SPECIAL PROVISIONS FOR STATUS OF UTILITIES, WITH UTILITY COMPANIES LISTED.
- 4 THE EXISTING ROAD SIGNS THAT INTERFERE WITH CONSTRUCTION SHALL BE RELOCATED AS DIRECTED BY THE ENGINEER. AFTER THE CONSTRUCTION IS COMPLETE, THE CONTRACTOR SHALL REPLACE THE SIGNS AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY, BUT CONSIDERED INCLUDED IN THE CONTRACT UNIT BID PRICES.
- 5 ABANDONED UNDERGROUND UTILITIES THAT CONFLICT WITH THE CONSTRUCTION SHALL BE DISPOSED OF OUTSIDE THE LIMITS OF RIGHT-OF-WAY ACCORDING TO ARTICLE 202.03 OF THE STANDARD SPECIFICATIONS AND AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCLUDED IN THE CONTRACT UNIT BID PRICE FOR EARTH EXCAVATION. NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- 6 THE FOLLOWING APPLICATION RATETS WERE USED FOR QUANTITY CALCULATIONS:

LEVELING BINDER	0.056TON/SQ YD • IN
BIT. CONC. SURF. CSE	0.056TON/SQ YD • IN
AGG. SHLDS./BASE CSE.	2.05 TON/ CU YD
BIT. MATLS. (P.C.)	0.00038 TON/ SQ YD
AGG. (P.C.)	0.001425 TON/SQ YD
AG LIMESTONE	2 TON/ ACRE
NITROGEN	90 LB/ACRE
PHOSPHORUS	90 LB/ACRE
POTASSIUM	90 LB/ACRE
MULCH, METHOD 2	2 TON/ACRE
- 7 ACCESS TO ALL PROPERTIES SHALL BE MAINTAINED DURING CONSTRUCTION ACTIVITIES. WHEN UNAVOIDABLE, REASONABLE PARKING SHALL BE PROVIDED FOR TGOSE PROPERTIES WHICH ARE TEMPORARILY UNACCESSIBLE.
- 8 THE DISTRICT BUREAU OF OPERATIONS SHALL BE NOTIFIED AT LEAST 14 DAYS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS

STANDARDS:

000001-06	701201-04	701901-03
001001-02	701301-04	780001-04
406201-01	701306-03	781001-03
442201-03	701311-03	
482011-03	701501-06	

COMMITMENTS

COMMITMENTS ARE NOT TO BE ALTERED WITHOUT THE WRITTEN APPROVAL OF ALL PARTIES TO WHICH THE COMMENTS WERE MADE.

1. THE RESIDENT ENGINEER SHALL CONTACT STUDIES AND PLANS CONCERNING ANY MAJOR PLAN CHANGES.
2. INFORMATIONAL LETTER TO VIRGINIA

DISTRICT SIX	
EXAMINED <u>10/11</u>	20 <u>12</u>
<i>Bill Boyer</i> OPERATIONS ENGINEER	
EXAMINED <u>OCT 10</u>	20 <u>12</u>
<i>Tommy Ford</i> PROJECT IMPLEMENTATION ENGINEER	
EXAMINED <u>0d.3</u>	20 <u>12</u>
<i>ZRN LJ</i> PROGRAM DEVELOPMENT ENGINEER	

MIXTURE USE (S):	HMA SURFACE	LEVELING BINDER	INCIDENTAL HMA SURFACING	PATCHING
PG	PG 64-22	PG 64-22	PG 64-22	PG 64-22
DESIGN AIR VOIDS	4.0% @ N50	4.0% @ N50	4.0% @ N50	4.0% @ N50
MIXTURE COMPOSITION (GRADATION MIXTURE)	IL 9.5	IL 9.5	IL 9.5 OR 12.5	IL 19.0 OR IL 19.0CB
FRICITION MIXTURE	MIX C	N/A	MIX C	N/A
QUALITY MANAGEMENT	OCP	OCP	•	OC/OA

• INCIDENTAL HMA QUALITY MANAGEMENT IS OC/OA.