

**GENERAL NOTES**

1. Reinforcement bars shall conform to the requirements of ASTM A 706 Gr 60.
2. Reinforcement bars designated (E) shall be epoxy coated.
3. All construction joints shall be bonded..
4. See Special Provisions for Mechanically Stabilized Earth Retaining Wall for design and construction requirements.
5. Limestone Rustication for the Mechanically Stabilized Earth Retaining Wall sections will not be paid for separately, but will be included in the pay item Mechanically Stabilized Earth Retaining Wall.
6. Transition of proposed fence to match existing fence at the beginning and end of retaining wall will be paid for at the contract unit price per foot for chain link fence attached to structure. The 10" diameter, 36" depth concrete footing will not be paid for separate but will be included in the cost of Chain Link Fence attached to structure pay item.
7. Gate fork latch shall be installed at the chain link gate and shall be included in the pay item CHAIN LINK GATES, 4'X6' SINGLE

**TOTAL BILL OF MATERIAL**

Item	Unit	Total
Mechanically Stabilized Earth Retaining Wall	Sq. Ft.	4,210
Reinforcement Bars, Epoxy Coated	Pound	7,621
Structure Excavation	Cu. Yd.	394
Concrete Structure	Cu. Yd.	43
Porous Granular Embankment	Cu. Yd.	13
Form Liner Limestone Surface	Sq. Ft.	2,223
French Drain	Cu. Yd.	36
Pipe Handrail	Foot	24
Chain Link Fence 6' Attached to Structure	Foot	516
Chain Link Gates, 4' x 6' Single	Each	1

**INDEX OF SHEETS**

1. General Plan & Elevation
2. General Notes
3. Wall Facing Section Panel 1 - 12
4. Wall Facing Section Panel 13 - 19
5. - 6. Panel 17 Wall Detail
7. Panel 17 Stair Detail
8. Handrail Detail
9. Fence Detail
10. - 13. Boring Logs