

SCHEDULE OF QUANTITIES

LOCATIONS STA. TO STA.	HMA SURF CSE MIX "D" N50	HMA SURF REM	BIT MAT (PRIME COAT)	LEVELING BINDER (HAND METHOD), N50
	TON	SQ YD	GALLON	TON
283+83.05 - 288+40.55	44	70	48	13
TOTAL	44	70	48	13

LOCATIONS STA. TO STA.	SHORT - TERM PAVEMENT MARKING	WORK ZONE PAVEMENT MARKING REMOVAL	PAINT PAVEMENT MARKING LINE 4"
	FOOT	SQ FT	FOOT
283+83.05 - 288+40.55	1,600	533	2,000
TOTAL	1,600	533	2,000

LOCATIONS STA. TO STA.	CONCRETE REMOVAL	CONCRETE SUPERSTRUCTURE	REINFORCEMENT BARS EPOXY COATED
	CU YD	CU YD	POUND
283+83.05 - 288+40.55	18.7	18.3	1,560
TOTAL	18.7	18.3	1,560

LOCATIONS STA. TO STA.	TEMPORARY CONCRETE BARRIER	RELOCATE TEMP CONC BARRIER
	FOOT	FOOT
283+30.98 - 289+92.62	762.5	762.5
TOTAL	762.5	762.5

LOCATIONS STA. TO STA.	P P CONC DECK BEAM (33' DEPTH)	REM OF EXIST P P CONC DECK BEAMS	ASBESTOS BEARING PAD REMOVAL
	SQ FT	SQ FT	EACH
283+83.05 - 288+40.55	2,469	2,501	11
TOTAL	2,469	2,501	11

LOCATIONS STA. TO STA.	IMPACT ATT TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 3	IMPACT ATT RELOCATE (NON-REDIRECTIVE), TEST LEVEL 3	TEMPORARY RUMBLE STRIP
	EACH	EACH	EACH
283+30.98 - 289+92.62	2	2	6
TOTAL	2	2	6

LOCATIONS STA. TO STA.	WATERPROOFING MEMBRANE SYSTEM
	SQ YD
283+83.05 - 288+40.55	318
TOTAL	318

LOCATIONS STA. TO STA.	POLYMER CONCRETE	SILICONE JOINT SEALER	BARRIER WALL REFLECTOR, TYPE C
	CU FT	FOOT	EACH
283+30.98 - 289+40.55	3.1	30	4
TOTAL	3.1	30	4

LOCATIONS STA. TO STA.	P C MORTAR FAIRING COURSE
	FOOT
283+83.05 - 288+40.55	1,213
TOTAL	1,213

LOCATIONS STA. TO STA.	MOBILIZATION	T C & PROT STANDARD 701321	ENGINEER FIELD OFFICE TYPE A	TEMPORARY BRIDGE TRAFFIC SIGNAL
	L SUM	EACH	CAL. MO.	EACH
283+30.98 - 289+92.62	1	1	2	1
TOTAL	1	1	2	1