



NOTES:
 For General Notes and Design Criteria, see Sheet No. 1.
 Splice material noted as "H.S." shall be Low Alloy High Strength Steel, A.S.T.M. A441-63T. Splice material not noted as "H.S." shall conform to A.S.T.M. A36-62T.
 For the location of various types of girder splices see Sheet Nos. 4, 5, 6 and 7.

IOWA STATE HIGHWAY COMMISSION
 AND ILLINOIS DIVISION OF HIGHWAYS
 INTERSTATE BRIDGE OVER MISSISSIPPI RIVER AT LE CLAIRE, IOWA
 CONTRACT NO. 2 - SUPERSTRUCTURE

BOLTED GIRDER SPLICES

SCALE IN FEET UNLESS NOTED
 MODJESKI & MASTERS, ENGINEERS
 MAY 1964
 SHEET NO. 16 OF 41

Project No: I-80-B(31)310 Design No: 163A Scott County File No: 21704 DR. BARCKBPS

DESIGNED VHV	EXAMINED <i>Timothy A. Daulton</i>	DATE - OCTOBER 12, 2012
CHECKED DAB	ACTING ENGINEER OF STRUCTURAL SERVICES	
DRAWN baliva	PASSED <i>Carl Kruger</i>	
CHECKED VHV DAB	ACTING ENGINEER OF BRIDGES AND STRUCTURES	

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

FOR INFORMATION ONLY
 SN 081-0011

SHEET 13 OF 42 SHEETS

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
80	D2 BRIDGE PAINTING 2012-2	ROCK ISLAND	46	17
CONTRACT NO. 64H81			ILLINOIS FED. AID PROJECT	