



- 62583
- LEGEND**
- HIGH MAST LIGHT TOWER
 - 400 WATT HPS LUMINAIRE (BLACK PHASE-SOLID SYMBOL, RED PHASE-OPEN SYMBOL)
 - HIGH MAST TOWER DESIGNATION
 - LIGHTED SIGN STRUCTURE WITH 170 WATT FLUORESCENT LUMINAIRE, QUANTITY OF LUMINAIRE AS REQUIRED. (BLACK PHASE-SOLID SYMBOL, RED PHASE, OPEN SYMBOL)
 - 3 POLE SAFETY SWITCH
 - UNDERPASS LIGHTING UNIT, 70 WATT HPS LUMINAIRE. (BLACK PHASE-SOLID SYMBOL, RED PHASE- OPEN SYMBOL)
 - LIGHTING CONTROLLER
 - GROUND FIELD
 - ELECTRIC UTILITY SERVICE
 - LUMINAIRE DESIGNATION
 - CONVENTIONAL LIGHTING UNIT, 2-310 WATT HPS LUMINAIRE. (BLACK PHASE-SOLID SYMBOL, RED PHASE-OPEN SYMBOL)
 - CLOSED CIRCUIT TELEVISION CAMERA

LOAD TABLE
LIGHTING CONTROLLER "R1"

CIRCUIT	RED PHASE		BLACK PHASE		
	AMPS	WATTS	AMPS	WATTS	
A	31.4	7,536	B	31.0	7,440
C	24.0	5,760	D	25.1	6,024
E	33.9	8,136	F	32.7	7,848
G	32.5	7,800	H	32.0	7,680
I	-	-	J	-	-
K	-	-	L	-	-
M	-	-	N	-	-
O	-	-	P	-	-
TOTAL	121.8	29,232	TOTAL	120.8	28,992

SINGLE LINE DIAGRAM
LIGHTING CONTROLLER "R1"
NOT TO SCALE