

GENERAL NOTES

GENERAL NOTES

- ① WHERE SECTION OR SUBSECTION MONUMENTS ARE ENCOUNTERED, THE ENGINEER SHALL BE NOTIFIED BEFORE SUCH MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL PROPERTY MARKS AND MONUMENTS UNTIL THE OWNER, AND AUTHORIZED SURVEYOR OR AGENT HAS WITNESSES OR OTHERWISE REFERENCED THEIR LOCATION.
- ② THE NOMINAL THICKNESS FOR BASE AND SURFACE COURSES ARE SHOWN ON THE TYPICAL SECTIONS, STANDARDS, SCHEDULES, OR SPECIAL DETAILS. THE CONSTRUCTED THICKNESS OF THE ABOVE ITEM SHALL NOT BE LESS THAN 90 PERCENT OF THE NOMINAL THICKNESS AT ANY LOCATION.
- ③ THE THICKNESS OF THE HMA MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATION OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HOT-MIX ASPHALT MIXTURE IS PLACED.
- ④ ANY REFERENCE TO A STANDARD IN THE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION, AS INDICATED BY THE SUB-NUMBER LISTED IN THE INDEX OF SHEETS.
- ⑤ THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING UTILITY PROPERTY FROM CONSTRUCTION OPERATIONS AS OUTLINED IN ARTICLE 107.31 OF THE STANDARD SPECIFICATIONS. THE JULIE NUMBER IS 800-892-0123. A MINIMUM OF FORTY-EIGHT HOURS ADVANCED NOTICE IS REQUIRED. ANY DAMAGE TO THE UNDERGROUND FACILITIES CAUSED BY THE CONTRACTOR SHALL BE REPAIRED TO THE SATISFACTION OF THE DEPARTMENT AT THE CONTRACTOR'S EXPENSE, INCLUDING TEMPORARY REPAIRS WHICH MAY BE REQUIRED TO KEEP THE FACILITY OPERATIONAL WHILE MATERIAL IS BEING OBTAINED TO MAKE PERMANENT REPAIRS.
- ⑥ THE LOCATIONS OF THOSE BURIED AND ABOVEGROUND UTILITIES SHOWN ARE APPROXIMATE, ARE SHOWN FOR CONTRACTOR INFORMATIONAL USE ONLY, AND ARE NOT TO BE REFERENCED FOR CONSTRUCTION PURPOSES. THE IMPLIED PRESENCE OR ABSENCE OF UTILITIES IS NOT TO BE CONSTRUED BY THE OWNER, ENGINEER, CONTRACTOR OR SUBCONTRACTORS TO BE AN ACCURATE AND COMPLETE REPRESENTATION OF UTILITIES THAT MAY OR MAY NOT EXIST ON THE CONSTRUCTION SITE. BURIED AND ABOVE GROUND UTILITY LOCATIONS, IDENTIFICATION, AND MARKING ARE THE SOLE RESPONSIBILITY OF THE CONTRACTOR, REROUTING, DISCONNECTION, PROTECTION, ...ETC OF ANY UTILITIES MUST BE COORDINATED BETWEEN CONTRACTOR, UTILITY COMPANY, AND OWNER. SITE SAFETY, INCLUDING THE AVOIDANCE OF HAZARDOUS ASSOCIATED WITH BURIED AND ABOVE GROUND UTILITIES REMAIN THE SOLE RESPONSIBILITY OF THE CONTRACTOR.
- ⑦ THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE:

LOCATION(S):	US 24/IL 96	US 24/IL 96	US 24/IL96	US 24/IL96	US 24/IL 96
MIXTURE USE(S):	HMA CONC SURF CSE	PATCHING	HMA BASE CSE 11"	HMA BASE CSE WID 11"	HMA SHOULDERS 6.5"
AC/PG:	PG 64-22	PG 64-22	PG 64-22	PG 64-22	PG 58-22
DESIGN AIR VOIDS	4.0 @ N design = 70	4.0 @ N design = 70	4.0 @ N design = 70	4.0 @ N design = 70	2.0 @ N design = 30
MIXTURE COMPOSITION (Gradation Mixture)	IL 9.5 OR 12.5	IL 19.0	IL 19.0	IL 19.0	BAM MIX (Other)
FRICTION AGGREGATE	MIX "D"	N/A	N/A	N/A	N/A

US 24/IL 96	Side Rds. & Entr.
LEV BIND	INCIDENTAL HMA SURF
PG 64-22	PG 64-22
4.0 @ N design = 70	4.0 @ N design = 50
IL 9.5	IL 9.5 OR 12.5
N/A	MIX "C"

- ⑧ IN ADDITION TO FIELD AND AERIAL SURVEYS, PLAN DIMENSIONS AND DETAILS RELATIVE TO THE EXISTING FACILITIES HAVE BEEN TAKEN FROM EXISTING PLANS AND ARE SUBJECT TO CONSTRUCTION VARIATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY SUCH DIMENSIONS AND DETAILS IN THE FIELD. SUCH VARIATIONS SHALL NOT BE A CAUSE FOR ADDITIONAL COMPENSATION DUE TO A CHANGE IN THE SCOPE OF WORK. HOWEVER, THE CONTRACTOR WILL BE PAID FOR THE QUANTITY ACTUALLY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.
- ⑨ THE EXACT LOCATIONS AND SIZES OF PAVEMENT PATCHES SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.

RATES OF APPLICATION TABLES

THE FOLLOWING RATES OF APPLICATION HAVE BEEN ASSUMED IN CALCULATING PLAN QUANTITIES.

BITUMINOUS MATERIALS (PRIME COAT): 0.00038 TON / SQ YD (ON PAVEMENT)
 0.001425 TON / SQ YD (ON AGGREGATE)
 AGGREGATE MATERIALS (PRIME COAT): 0.002 TON / SQ YD
 HMA SURFACE MIX D / BINDER (112 LBS): 0.056 TON / SQ YD • In
 AGGREGATE MATERIALS: 2.05 TON / CU YD

COMMITMENTS

THE RESIDENT ENGINEER SHALL CONTACT STUDIES AND PLANS CONCERNING ANY MAJOR PLAN CHANGE. TO MAKE SURE NO PREVIOUS COMMENTS (NOT LISTED) WERE MADE AFFECTING THE DESIGN AND ALLOW AN IMPROVED DESIGN FOR FUTURE PROJECTS.

INDEX OF SHEETS

- 1 COVER SHEET
- 2 INDEX OF SHEETS, LISTS OF STANDARDS, GENERAL NOTES AND COMMITMENTS
- 3 - 13 SUMMARY OF QUANTITIES (11)
- 14 - 38 SCHEDULE OF QUANTITIES (25)
- 39 - 53 TYPICAL SECTIONS (15)
- 54 CROSS-TIES AND BENCH MARKS
- 55 - 83 PLAN AND PROFILE SHEETS (29)
- 84 - 101 STORM WATER AND POLLUTION AND PREVENTION PLAN (18)
- 102 - 107 DRAINAGE DETAILS (6)
- 108 - 119 PAVEMENT ELEVATION DETAILS (12)
- 120 - 133 PAVEMENT MARKING DETAILS (14)
- 134 - 136 TRAFFIC SIGNAL PLANS (3)
- 137 - 138 SUPERELEVATION DETAILS (2)
- 139 - 140 ENTRANCE AND SIDEROAD DETAILS (2)
- 141 CONCRETE COLLAR AND CULVERT EXTENSION DETAILS
- 142 MISCELLANEOUS DETAILS
- 143 - 198 CROSS-SECTION SHEETS (56)

STANDARDS

- | | |
|-----------|---|
| 000001-06 | STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS |
| 280001-07 | TEMPORARY EROSION CONTROL SYSTEMS |
| 442201-03 | CLASS C & D PATCHES |
| 542301-03 | PRECAST REINFORCED CONCRETE FLARED END SECTION |
| 542311-04 | GRATING FOR CONCRETE FLARED END SECTION (FOR 24" THRU 54" PIPE) |
| 602301-03 | INLET - TYPE A |
| 602306-03 | INLET - TYPE B |
| 602401-03 | MANHOLE TYPE A |
| 602601-02 | PRECAST REINFORCED CONCRETE FLAT SLAB TOP |
| 604011-04 | FRAME AND GRATE TYPE 3V |
| 604036-02 | GRATE TYPE B |
| 606001-05 | CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER |
| 606301-04 | PC CONCRETE ISLANDS AND MEDIANS |
| 635011-02 | REFLECTOR MARKER AND MOUNTING DETAIL |
| 701101-03 | OFF ROAD MOVING OPERATIONS MULTILANE 15' TO 24' FROM PAVEMENT EDGE (SHOULDER WORK) |
| 701201-04 | LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS ≥ 45 MPH (INTRSCTN) |
| 701306-03 | LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS ONLY, FOR SPEEDS ≥ 45 MPH (INTRSCTN) |
| 701326-04 | LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS ≥ 45 MPH (WIDENING) |
| 701421-05 | LANE CLOSURE MULTILANE DAY OPERATIONS ONLY, FOR SPEEDS ≥ 45 MPH TO 55 MPH (PATCHING & HMA RESURF) |
| 701422-05 | LANE CLOSURE MULTILANE, FOR SPEEDS ≥ 45 MPH TO 55 MPH (PATCHING & HMA RESURF) |
| 701501-06 | URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED |
| 701701-08 | URBAN LANE CLOSURE MULTILANE INTERSECTION |
| | TRAFFIC CONTROL DEVICES |
| 780001-03 | TYPICAL PAVEMENT MARKING |
| 781001-03 | TYPICAL APPLICATIONS OF RAISED REFLECTIVE PAVEMENT MARKINGS |
| 805001-01 | ELECTRIC SERVICE INSTALLATION DETAILS |
| 814001-02 | HANDHOLES |
| 814006-02 | DOUBLE HANDHOLES |
| 836001-02 | LIGHT POLE FOUNDATION |
| 857001-01 | STANDARD PHASE DESIGNATION DIAGRAMS |
| 862001-01 | UNINTERRUPTIBLE POWER SUPPLY |
| 873001-02 | TRAFFIC SIGNAL GROUNDING AND BOUNDING |
| 877001-05 | STEEL MAST ARM ASSEMBLY AND POLE 16' THROUGH 55' |
| 878001-09 | CONCRETE FOUNDATION DETAILS |
| 880006-01 | TRAFFIC SIGNAL MOUNTING DETAIL |
| 817011-05 | STEEL COMBINATION MAST ARM ASSEMBLY AND POLE 16' THROUGH 55' |

DISTRICT SIX	
EXAMINED <u>12/5</u>	20 <u>12</u>
<i>William M. Brown</i> OPERATIONS ENGINEER	
EXAMINED <u>DEC 10</u>	20 <u>12</u>
<i>Jimmy Z...</i> PROJECT IMPLEMENTATION ENGINEER	
EXAMINED <u>Dec. 14</u>	20 <u>12</u>
<i>ARMU</i> PROGRAM DEVELOPMENT ENGINEER	

⚠ REVISÉD 2-19-13